

## Desoutter



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Desoutter** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Desoutter T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">Pt070-T4000-S13s</a>	Article 2051462304-77 Pneumatic impulse wrench Device is no longer produced, currently 1 piece in stock
<a href="#">Ptf085-T4800-S13s 1/2"</a>	Pneumatic impulse wrench Art nr. 6151720890-77
<a href="#">Ptf060-T6100-S10s 3/8"</a>	**** Alternatif **** Art nr. 6151720880-77 Pneumatic impulse wrench
<a href="#">zum Anziehen von Muttern</a>	ERFORDERLICHE FUNKTIONEN: Projekt; Die Steuereinheit besteht aus einem 90-Grad-Winkelkopf. Elektrisches Anziehen mit Kabel. <input type="checkbox"/> elektrischer Strom wird gesteuert. <input type="checkbox"/> Die Funktionen der Steuereinheit sind wie folgt; - 15 verschiedene Zyklusprogrammspeicher Drehmoment- und Winkelregelung - Abfahrgeschwindigkeit, Endgeschwindigkeit, Drehmoment, Winkel programmierbar - Drehmoment und Winkel k¼nnen am Steuerger¼t digital ¼berwacht werden - Es wird 8 E / A-Ein- und Ausg¼nge haben - Es werden RS232- und Ethernet-Eing¼nge vorhanden sein <input type="checkbox"/> Die elektrischen Anziehen sind wie folgt: - 10-30 Nm Arbeitskapazit¼t - Mindest. Drehzahl 1140 U / min - Gewicht max. 1,7 kg - L¼nge max. 431 mm <input type="checkbox"/> kabel (min.) Es wird 5m sein.
<a href="#">Neu Beschaffung</a>	von unseren Kunden: Derzeit ben¼tigen wir insgesamt 4 Luftmotoren. Anzugsmomente: 3 davon sollten 20 Nm betragen. 1 von ihnen reicht aus, um 15 Nm zu sein. Wenn Motoren mit 20 Nm die Klemmschnalle erreichen, ist der Rotor blockiert und der Stator dreht sich in Klemmrichtung und bewegt den daneben montierten Pneumatikzylinder. Das Signal des Schalters an diesem Zylinder wird als Information an die SPS gesendet, dass das Anzugsmoment erreicht wurde. Das Anzugsmoment ist erreicht. Das Signal wird nicht vom Luftmotor empfangen, der 15 Nm betr¼gt.
<a href="#">ELS6-1000</a>	Cordless screwdriver "E-LIT premium" - Series, adjustable speed, pistol shape, lithium Ion battery technology (70% more energy, 65% longer Battery life, rechargeable at any time - without memory effect), brushless motor, two battery positions, ergonomic Design, direction of rotation reversal at the push of a button, LED display for OK / NOK screw connection, additional acoustic signal after a NOK screw connection, Low battery warning. Torque range 0.8-6 Nm, speed 300 - 1000 Rpm., Output 1/4 "SWF, weight without

battery 0.8 kg Battery and charger are not included and must be to be ordered separately.

[2050504523-D11](#)

[2050536393-C08](#)

[2050536413](#)

[2051474734-D11](#)

[2051478424-C08](#)

[2051479244](#)

[6151652100-D11](#)

[6151654200-D11](#)

[6151656310-D11](#)

[6155703925-368](#)

[6158100460-268](#)

[6158105140-368](#)

[6158116545-D11](#)

[6159175410-168](#)

[6159188005-368](#)

[6159351010-D11](#)

[9433-C08](#)

[CP0214CELEL](#)

[MR25-280-KL air motor](#)

(0.12 HP)(P/N 2051478424)

[PT070-T4000-S13S](#)

[6158107000-77](#)

D53-5 - tool stand with swiveling linear arm, max. torque absorption 5 Nm, max. load 0.8 kg, incl. tool holder D=28.5 to 41 mm, incl. 1 Balancer "5DU"

[M25-1040-TL ATEX](#)

2051478334 The offers compact, lightweight and maintenance-free air motors with Keyed output shaft for a wide range of speeds and torque requirements. They are for installation in Suitable for hand machines or industrial plants. The product line offers clockwise only executions, delivers maximum performance from 1,800 W (2.45 hp), torques from 0.17 Nm to 299 Nm, and Speeds from 35 rpm to 19,500 rpm.

[MOUNTING FLANGE WITH HOLES M25](#)

2050540623 Specification Values (Metric) Family: Accessories for Air Motors Subfamily: mounting flange Energy type: NA

SC2-065-2RM500-S4Q compressed air built-in screwdriver,

<a href="#">2051474364-77</a>	Rod shape, jump start, switching off, right and / Counterclockwise rotation, output: 1/4" SW chuck, idle speed: 470 RPM, torque range: 0.5-6.5 Nm, weight: 0.64 kg, Please compressed air hose with inner diameter min. d=6 Use mm
<a href="#">2051474384-77</a>	*** Alternative *** SC2-045-2RM1000-S4Q Compressed air built-in screwdriver, rod shape, external start, switching off, clockwise and counterclockwise rotation, output: 1/4" SWF chuck, idle speed: 1000 rpm, Torque range: 0.5-4.5 Nm, weight: 0.64 kg, Please compressed air hose with inner diameter min. d=6 Use mm
<a href="#">Clip Rework</a>	DSF0016105
<a href="#">6159172010 POWER CORD C13 EUROPE</a>	
<a href="#">DSF0025111</a>	
<a href="#">DC505</a>	Spring
<a href="#">TRN1612</a>	Feed Hose Inlet Sensor(ITS)
<a href="#">DSF0026146</a>	Cap Nut
<a href="#">FP1049A216</a>	BIT
<a href="#">FP1049A223</a>	Vacuum Bit
<a href="#">DSF0026164</a>	ARM
<a href="#">FP1049A217</a>	Bit Holder
<a href="#">553140</a>	VAF-DB-3/8
<a href="#">FP1080A604</a>	Rear Slide
<a href="#">DSF0026101</a>	Housing
<a href="#">FP1080A603</a>	Front Slide
<a href="#">FP1049A208</a>	Vacuum Tube
<a href="#">6151656910 ERS2-M20</a>	
<a href="#">6159326810 CVIR II</a>	
<a href="#">T046i015msp3</a>	NUTRUNNER 3/8IN
<a href="#">50062</a>	
<a href="#">Tra100-2100</a>	
<a href="#">Dm6-1650t</a>	AIR MOTOR 1650RPM 6.3BAR 0.35HP 260WATT 3NM
<a href="#">1463064</a>	SCREWDRIVER PNEUMATIC SHUT-OFF 1100RPM 18.4CFM
<a href="#">P137707 Ram-Hydraulic Ram-Hydraulic</a>	
<a href="#">P136983 Nadelfuehrung Rund</a>	

<a href="#">Nadelfuehrung Rund</a>	
<a href="#">P106131 Zangendr.Hebel</a> <a href="#">Zangendr.Hebel</a>	
<a href="#">P103028 Plug O Ring Plug O Ring</a>	
<a href="#">10092</a>	
<a href="#">Vp2-X</a>	
<a href="#">P100150 Druckfeder Druckfeder</a>	
<a href="#">P100145 Nadelhalter Nadelhalter</a>	
<a href="#">615-932-677-0</a>	CONTROLLER
<a href="#">6151658830</a>	
<a href="#">P138141 Blank Nutlocking Blank</a> <a href="#">Nutlocking</a>	
<a href="#">P136744 Feder Feder</a>	
<a href="#">P109273 Head Cylinder Head Cylinder</a>	
<a href="#">100443</a>	
<a href="#">Afde410-1200</a>	ELECTRIC DRIVE PNEUMATIC-FEED 1200/1450RPM 50/60HZ
<a href="#">D370-Sx-2000-1379464</a>	
<a href="#">Sd100-Ab820-S4q</a>	SCREW DRIVER PNEUMATIC 820RPM 8.9-88.5IN-LBS
<a href="#">P121598 Einlasskopf Vorm. Einlasskopf</a> <a href="#">Vorm.</a>	
<a href="#">6151653650</a>	
<a href="#">Pt250-T4000-S19s</a>	DESOUTTER SHUT OFF PULSE TOOL
<a href="#">10122</a>	
<a href="#">P106132 Zangendr.Hebel</a> <a href="#">Zangendr.Hebel</a>	
<a href="#">6159-3504-70</a>	NUTRUNNER
<a href="#">P136973 Cylinder -R Cylinder -R</a>	
<a href="#">6159-3261-00d</a>	CONTROLLER
<a href="#">101313</a>	
<a href="#">6151-6523-70</a>	SCREW DRIVER LOW TORQUE
<a href="#">Eral-2-60</a>	TRANSDUCER CONTROLLED TOOL
<a href="#">P140861 Feder Feder</a>	
<a href="#">P136737 Nadelhalter Nadelhalter</a>	

<a href="#">92292</a>	PNEUMATIC D05-HCU PECK KIT 50MM
<a href="#">P109271</a>	<a href="#">Sich.-Mutter Sich.-Mutter</a>
<a href="#">P100964</a>	<a href="#">Gummipuffer Gummipuffer</a>
<a href="#">6159-3264-00</a>	CONTROLLER CVI-II
<a href="#">6158101040</a>	
<a href="#">P113310</a>	<a href="#">Head Blower Cylinder Head Blower Cylinder</a>
<a href="#">P100146</a>	<a href="#">Nadelsatz 3mm (19st) Nadelsatz 3mm (19st)</a>
<a href="#">6151-7005-50</a>	ANGLE GRINDER
<a href="#">P140855</a>	<a href="#">Buchse Buchse</a>
<a href="#">100373</a>	
<a href="#">100792</a>	
<a href="#">6151653910</a>	
<a href="#">102593</a>	
<a href="#">P140042</a>	<a href="#">Blank-Cylinder Blank-Cylinder</a>
<a href="#">Dt-2h410n60</a>	
<a href="#">6151-6534-00</a>	TOOL ELECTRIC FASTENING
<a href="#">P140040</a>	<a href="#">Reservoir Reservoir</a>
<a href="#">P117655</a>	<a href="#">Hebelarm Hebelarm</a>
<a href="#">Slb050-L1000-S4q</a>	
<a href="#">Eca60</a>	NUTRUNNER
<a href="#">50052</a>	
<a href="#">P114616</a>	<a href="#">Piston Piston</a>
<a href="#">P117653</a>	<a href="#">Ventilhebel Ventilhebel</a>
<a href="#">6159-1749-20</a>	CABLE MOTOR 5M
<a href="#">P140857</a>	<a href="#">Coupling Regulator Coupling Regulator</a>
<a href="#">Els12-600-P</a>	
<a href="#">P122967</a>	<a href="#">Stift Stift</a>
<a href="#">615 165 215 0</a>	DRT4 SQ180 TORQUE ROTARY TRANSDUCER
<a href="#">P114036</a>	<a href="#">Wange Wange</a>

<a href="#">2051470394</a>	AIR FEED DRILL
<a href="#">102153</a>	
<a href="#">1388534</a>	
<a href="#">Sbp043-T1100s4q</a>	
<a href="#">P113695 Zylinder Zylinder</a>	
<a href="#">6159360700</a>	
<a href="#">1 2 Filter Bsp</a>	
<a href="#">Afde410-1200-A6-B</a>	ELECTRIC DRIVE PNEUMATIC FEED 1200/1450RPM 50/60HZ
<a href="#">P137708 Plate Retaining Plate Retaining</a>	
<a href="#">101823</a>	
<a href="#">2f89px450</a>	
<a href="#">P139283 Ring-Retaining Ring-Retaining</a>	
<a href="#">P140041 Cap-Inlet Check Cap-Inlet Check</a>	
<a href="#">615 811 924 0</a>	
<a href="#">6159933819</a>	
<a href="#">Mr84700k</a>	MOTOR
<a href="#">Erp10l</a>	ELECTRIC TRANSDUCERIZED NUTRUNNER PISTOL GRIP
<a href="#">Scpt047-A550-S4q</a>	SCREW DRIVER SHUT-OFF PISTOL GRIP TRIGGER START
<a href="#">Eme80-30j</a>	
<a href="#">Afd-40</a>	PNEUMATIC IC SPINDLE DRILL
<a href="#">Cp6031habad</a>	
<a href="#">1414-164</a>	REVERSIBLE AIR MOTOR 290RPM 0.35HP
<a href="#">3/8-L46mm</a>	
<a href="#">102873</a>	
<a href="#">P140860 Screw Screw</a>	
<a href="#">Ecp20s</a>	PISTOL GRIP
<a href="#">50542</a>	
<a href="#">6150040471</a>	NUTRUNNER 3/8IN
<a href="#">P137705 Bushing-Ram Bushing-Ram</a>	

<a href="#">Twin-Cvi-II</a>	CONTROLLER CVI-II
<a href="#">P117633 Screw Nylok Screw Nylok</a>	
<a href="#">0 8 6 Nm</a>	
<a href="#">Cvic-H2</a>	CONTROLLER H-2
<a href="#">Esp1-A</a>	
<a href="#">P137876 Balg Balg</a>	
<a href="#">P136403 Nadelsatz 3mm (19st)</a> <a href="#">Nadelsatz 3mm (19st)</a>	
<a href="#">P113834 Cylinder Cylinder</a>	
<a href="#">6159-3261-90d</a>	CONTROLLER
<a href="#">6159326850</a>	
<a href="#">P137979 Tragekoffer Cp9361 Tragekoffer Cp9361</a>	
<a href="#">2sa8</a>	
<a href="#">10162</a>	
<a href="#">P121581 Ventilfeder Ventilfeder</a>	
<a href="#">6151-6510-30</a>	NUTRUNNER
<a href="#">05 X 80000dv</a>	
<a href="#">P136736 Spindel Spindel</a>	
<a href="#">Vp2-6783-Of</a>	
<a href="#">P106130 Zangendr.Hebel</a> <a href="#">Zangendr.Hebel</a>	
<a href="#">6153-9426-20</a>	MOTOR ASSEMBLY UE4R EME
<a href="#">101282</a>	
<a href="#">Cvicii</a>	CONTROLLER
<a href="#">6151-6520-30</a>	PISTOL GRIP
<a href="#">6158101030</a>	
<a href="#">6151-6520-00</a>	SCREW DRIVER LOW TORQUE
<a href="#">Eral-15-70</a>	TRANSDUCER CONTROLLED TOOL
<a href="#">Cable-Er-5m</a>	CABLE MOTOR 5M
<a href="#">388173</a>	TORQUE ARM 9-31IN RADIUS 21IN STROKE D53-20X
<a href="#">P140862 Feder Feder</a>	

<a href="#">102892</a>	
<a href="#">1462794</a>	PNEUMATIC INLINE TOOL PUSH-TO-START
<a href="#">P106076 Druck-Keilgabel Druck-Keilgabel</a>	
<a href="#">6159326800</a>	ELECTRIC TIGHTENING TOOL CONTROLLER
<a href="#">P104362 Shim Shim</a>	
<a href="#">Cpn/108262</a>	PART
<a href="#">P122208 Kolben Kolben</a>	
<a href="#">Eral2-40</a>	ELECTRIC TRANSDUCERIZED NUTRUNNER ANGLE HEAD
<a href="#">615 917 432 0</a>	TRANSDUCER CABLES DIGITAL 10 PINS
<a href="#">1460634</a>	
<a href="#">Eral2-60</a>	
<a href="#">P106454 Nadelsatz 3mm (19st) Rostfrei Nadelsatz 3mm (19st) Rostfrei</a>	
<a href="#">P140856 Ring Ring</a>	
<a href="#">Alpha-11</a>	NUTRUNNER
<a href="#">P137639 Spacer Spacer</a>	
<a href="#">K160b6</a>	
<a href="#">P136242 Valve-Regulator Valve-Regulator</a>	
<a href="#">P113835 Abdeckkappe Abdeckkappe</a>	
<a href="#">P110745 Drive Spindle Drive Spindle</a>	
<a href="#">6158116710</a>	
<a href="#">6158120975</a>	
<a href="#">P136974 Cylinder -S Cylinder -S</a>	
<a href="#">100172</a>	
<a href="#">6158101020</a>	
<a href="#">P140310 Syringe-Oil Fill Syringe-Oil Fill</a>	
<a href="#">2hh5-550ggmin</a>	
<a href="#">10272</a>	
<a href="#">6159-3261-00</a>	CONTROLLER
<a href="#">100832</a>	



<a href="#">Eap2-65-T1</a>	TOOL FASTENING
<a href="#">P106078 Kolbenst-Gabel Kpl. Kolbenst-Gabel Kpl.</a>	
<a href="#">101273</a>	
<a href="#">6159175420</a>	
<a href="#">P119294 Valve Kit Valve Kit</a>	
<a href="#">P117632 Klemmring Klemmring</a>	
<a href="#">P140854 Tube Throttle Valve Tube Throttle Valve</a>	
<a href="#">P140879 Handgriff Handgriff</a>	
<a href="#">100233</a>	
<a href="#">P100144 Amboss Amboss</a>	
<a href="#">6151-6509-30</a>	NUTRUNNER
<a href="#">H410-N-350</a>	
<a href="#">P105978 6-Kt-Schraube 6-Kt-Schraube</a>	
<a href="#">P106129 Gegenhalter Gegenhalter</a>	
<a href="#">388163</a>	TORQUE ARM 9-30IN RADIUS 10IN STROKE D53-20
<a href="#">Sbp047-T550-S4q</a>	SCREW DRIVER SHUT-OFF PISTOL GRIP
<a href="#">102743</a>	
<a href="#">671094</a>	
<a href="#">P098947 Hammer Spacer Hammer Spacer</a>	
<a href="#">P140863 O-Ring 6.1x1.6 O-Ring 6.1x1.6</a>	
<a href="#">Sd075-Lb1100-S4q</a>	SCREW DRIVER PNEUMATIC 1100RPM 22.1-66.4IN-LBS
<a href="#">P136738 Housing Needles Housing Needles</a>	
<a href="#">102723</a>	
<a href="#">2hm5-550-1309524</a>	
<a href="#">Ecd20</a>	NUTRUNNER
<a href="#">2f89px500</a>	
<a href="#">108262</a>	CONTROL CARD 5OPTION
<a href="#">6151653880</a>	
<a href="#">199-Swf</a>	

<a href="#">P117630 Gehaeuse Gehaeuse</a>	
<a href="#">P137709 Seat-Inlet Check Seat-Inlet Check</a>	
<a href="#">615-165-3630</a>	ELECTRIC TRANSDUCERIZED NUTRUNNER ANGLE HEAD
<a href="#">P140858 Sleeve Regulator Sleeve Regulator</a>	
<a href="#">P122968 Retainer-Collar Pin Retainer-Collar Pin</a>	
<a href="#">P140859 Stift Stift</a>	
<a href="#">1458854</a>	SCREW DRIVER SHUT-OFF PISTOL GRIP TRIGGER START