



Dilatoflex

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Dilatoflex Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Dilatoflex T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
PN 16 DN 150	
PN 16 DN 125	
PN 16 DN 100	
PN 16 DN 80	
PN 16 DN 65	
PN 16 DN 50	
Hibro Art. Nr. 24ar0600ma66	
24sv0050tx	
24ar0600ma0be	
Dn 80 Nps 3 Ln En Mm 130	
Dilatoflex-Hibro-Art-Nr-24sv0100tx-Hinterlegflansche-F3;R-Dilatoflex-Nt-Dn-100-Pn-16-Istanbul-Turkiye	
Nt2 Gz Dn 300 B485 Cl150 12 Holes Of 25.4mm	
S235 Jr A 8540 (80)	
Hibro Art. Nr. 24cc0125kv	

20ar0150f161-3	
Dilatoflex-24sv0300tx-Hinterlegflansche-F3;R-Dilatoflex-Nt-Dn-300-Pn-10pn-16-Istanbul-Turkiye	
Dn350 F Ar 350 Pn10 T6 200	DILATOFLEX® F-type, DN 350, one convolution, length 200 mm., rubber grade ARCN (for abrasive or corrosive products, weak acids and bases, industrial water, sea water, low-temperature water vapour), movements: axial compression 40 mm., axial extension 30 mm., lateral 10 mm., angle 9,5° with loose flanges in hot dip galvanised steel according to PN10; NOTE: please pay attention to the flanges standard, PN16 dimensions: OD 505 mm., drilling pitch 460 mm., 16 holes Ø 22 mm.
Nt / Cc / Dn 250 / Pn-16 (24cc0250t1)	
Dn150	
20	
Nt / Epc / Dn 350 / Pn-10/Pn-16	
Nt1 Gz Dn100 Pn16	
Hibro Art. Nr. 24gz0300kv	
Nt / Epc / Dn 300 / Pn-10/Pn-16	
24ar0032t0	
Hibro Art. Nr. 24gz0250kv	
Nt / Cc / Dn 350 / Pn-10/Pn-16 (24cc0350t1)	
Nt / Cc / Dn 200 / Pn-16 (Hibro Art. Nr. 24cc0200t1bb)	
Dn250 Dilnt1 Cc 250 B405 Pn16 Aex	DILATOFLEX® NT1-type, DN 250, one convolution, length 200 mm., rubber grade CC (Central heating and air conditioning water), movements: axial compression 30 mm., axial extension 30 mm., lateral 15 mm., angle 10° with fixed rubber flanges according to PN16 compatible PN10;
20ar0200f161-3	
24sv0032tx	
Hibro Art. Nr. 24ar0500n0	
24ar0050t1	
250-10 Oem, Replacement Asa 150 Lbs	
S235jr A8540 (60)	
Ami 1162-M10	
Dn200 Dilnt1 Cc 200 B340 Pn16 Aex	DILATOFLEX® NT1-type, DN 200, one convolution, length 150 mm., rubber grade CC (Central heating and air conditioning water), movements: axial compression 30 mm., axial extension 30 mm., lateral 15 mm., angle 10° with fixed rubber flanges according to PN16; NOTE: please pay attention to the flanges standard, PN16 dimensions: OD 340 mm., drilling pitch 295 mm., 12 holes Ø 22 mm.
Hibro Art. Nr. 24gz0100kv	
P.E.D. 97/23/Ce Cat. Iii	
Dilatoflex-24sv0200tx-Hinterlegflansche-F3;R-	

[Dilatoflex Nt-Dn 200 Pn-10 İstanbul-Türkiye](#)
[Asa 150 Lbs](#)

[Nt / Cc / Dn 250 / Pn-10/Pn-16 \(24cc0250t1\)](#)

[Nt / Cc / Dn 150 / Pn-16 \(24cc0150t1\)](#)

[Hibro Art. Nr. 24gz0100t1 Dilatoflex Gummi](#)
[Kompensator](#)

[Nt / Cc / Dn 200 / Pn-10 \(24cc0200t1\)](#)

[T6 In 2 Parts Cb Nt 300 Cli150 T6](#)