

## Direct Logic

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Direct Logic** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Direct Logic Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">305-Opto</a>	Serial CPU Bridge Module
<a href="#">D4-450dc-1</a>	24 VDC
<a href="#">D4-06b-1</a>	6-Slot Local or Expansion Base
<a href="#">F3-04ads</a>	Isolated Analog Input Module
<a href="#">Sr44-242</a>	STELLAR SR44 SERIES FULL FEATURED REDUCED VOLTAGE SOFT STARTER, 242A, 230-460 VAC 3-PHASE, RATED FOR 3 STARTS/HOUR. SINGLE-PHASE 230VAC OR 115VAC CONTROL POWER REQUIRED, IP20 RATING, PANEL-MOUNT. FULL
<a href="#">D0018</a>	FOLDER/SCALE PC BOARD
<a href="#">D0-05dd-D</a>	DLC I/O CPU Module DL05
<a href="#">DI-340</a>	CPU RLL 3.7K WDS ENHANCED 2COMM PORTS
<a href="#">D4-08b-1</a>	8-Slot Local or Expansion Base
<a href="#">D3-10b-1</a>	10 Slot Cardfile W/Power Supply

<a href="#">305-4adc-1x</a>	Isolated Analog Input Module
<a href="#">D3-10bdc</a>	10 Slot Cardfile with 24V Power Supply Unit
<a href="#">Sr400ex</a>	PROGRAMMABLE CONTROLLER
<a href="#">D4-450dc-2</a>	125 VDC
<a href="#">F3-0mux-2</a>	Serial CPU Bridge Module
<a href="#">H2-Ecom</a>	10 Base T Ethernet Port Module ECOM
<a href="#">13050-Hs</a>	Top Hat Rail Mounting Kit
<a href="#">13012-Hs</a>	Top Hat Rail Mounting Kit
<a href="#">F1-130dr</a>	CPU Compact Unit
<a href="#">F2-04thm</a>	Thermocouple Input Module
<a href="#">D4-08nd3s</a>	Digital Input Module
<a href="#">F3-04das</a>	Analog Output Module 5304C1
<a href="#">Svm-210b</a>	SURESERVO AC BRUSHLESS SERVO MOTOR, 1 KW , 230 VAC THREE-PHASE, MEDIUM INERTIA, 2,500 LINE COUNT ENCODER (10,000 COUNTS PER REVOLUTION), WITH INTEGRATED BRAKE.
<a href="#">Lc4b-P13002</a>	MOTOR CONTROL
<a href="#">D4-16tr</a>	Relay Output Module
<a href="#">405-2nim</a>	MODULE NETWORK COMM SLAVE TIWAY 115.2BAUD
<a href="#">D4-08td1</a>	Digital Output Module