

## Dixon

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Dixon** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Dixon T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">13MHM-3P100150</a>	
<a href="#">150E</a>	
<a href="#">200E</a>	
<a href="#">525</a>	
<a href="#">A190032</a>	
<a href="#">A190038</a>	
<a href="#">A190050</a>	
<a href="#">A235012BU</a>	
<a href="#">BBV200FP</a>	
<a href="#">BBV300</a>	
<a href="#">DIXON</a>	
<a href="#">DXHPBV25</a>	

<a href="#">HO22012</a>	
<a href="#">P4F3</a>	
<a href="#">SC13x5SS</a>	
<a href="#">SC25x6SS</a>	
<a href="#">V2F2</a>	
<a href="#">Style 30 3 in. Carbon Steel</a>	V-Ring Swivel Joints w/ 150# Flange Ends - Nitrile Rubber
<a href="#">A430-T2-038</a>	1.5in Dixon Oil S&D Type A430-T2 Hose -40° to +90°, Oil + 100°, 10 bar 40 Metre Coil
<a href="#">A430-T2-050</a>	2" A430 Oil Suction and Delivery Hose ID 51 mm OD 62 mm w. p.: 10 bar, Temperature : +100°C
<a href="#">A430-T2-076</a>	3" A430 Oil Suction and Delivery Hose ID 76 mm w. p.: 10 bar, Temperature : +100°C
<a href="#">DAL200AB</a>	2" Cam & Groove Adaptor Type A 2" BSP female thread, die cast aluminium
<a href="#">DAL300AB</a>	3" Cam & Groove Adaptor Type A 3" BSP female thread, die cast aluminium
<a href="#">DAL400AB</a>	4" Cam & Groove Adaptor Type A 4" BSP female thread, die cast aluminium
<a href="#">DAL200DC</a>	2" Cam & Groove Dust Cap Type DC; die cast aluminium
<a href="#">DAL300DC</a>	3" Cam & Groove Dust Cap Type DC, die cast aluminium
<a href="#">DAL400DC</a>	4" Cam & Groove Dust Cap Type DC; die cast aluminium
<a href="#">FT101-18-ATEX</a>	BAYCO API Optic Sensor Typ FT101 5-Wire, 2in BSPT housing c/w 18in Probe ATEX acc. to 94/9/EC Art. 9
<a href="#">FT100-18-ATEX</a>	BAYCO API Optic Probe Typ FT100, 5-wire +++Probe only++, Length: 18in ATEX acc. to 94/9/EC Art. 9 Ta = -40°C to +70°C
<a href="#">FT304</a>	DIXON-BAYCOSingle Thermistor Socket with Aluminium J-Slot 10 pin and 4 J-Slots (Canada, Europe) Stainless steel hardware and contact pins Modified Version of FT304VI: See quotation 626054 (03/12-14)
<a href="#">FT304VI</a>	Single Optic Socket with Aluminium J-SI API/WOGA, 10 pin and 4 J slots (U.S.) socket with vapour recovery interlock
<a href="#">10366HC-002</a>	FloTech® Replacement Parts Replacement 3-J aluminum socket nose ring
<a href="#">FT391-6</a>	FT390 Dual socket with 4J-10 pin and 4J-6 pin
<a href="#">5204</a>	4" API Bottom Loading/Unloading Valve With fixed handle and sightglass Mat.: Aluminium, Baylast seals

<a href="#">5500BL</a>	4" API Bottom Rack loading Coupler 4" TTMA mounting inlet flange Mat.: Aluminium, Baylast seals Body: 356 T6 aluminum anodized hard-coat Cam: stainless steel Poppet: 356T6 aluminum anodized hard-coat Link, shaft, pin, crank: hardened 17-4PH stainless steel Handle: aluminum
<a href="#">4030-DVR-AL</a>	4" Vapor coupler with probe 3" Female NPT, Aluminium
<a href="#">VRC3000AL</a>	3" Vapor coupler with probe 3" hose shank, Aluminium
<a href="#">4030-CVR-AL</a>	4" Vapor coupler with probe 3" hose shank, Aluminium, Buna-N
<a href="#">4030-DVR-AL</a>	4" Vapor coupler with probe 3" Female NPT, Aluminium
<a href="#">5205</a>	API Dust Cap with Quick Release Lever Mat.: Aluminium, Buna Seal
<a href="#">VR4000</a>	4" Vapor Return Valve x 4" adaptor 4" TTMA Flange Bulb Design Aluminium, Buna Gaskets acrylic sight glasses
<a href="#">VR4100</a>	Vapor Return Valve Material: Aluminum Fuel Compatability: Gasoline and diesel, up to E100 & B20 biofuels
<a href="#">5000AIV</a>	Air Interlock Valve Paddle Plunger Seal: Baylast TM, Mat.: Aluminium
<a href="#">VR4050PL-1200</a>	4" lockable vapour cap for 4" vapour valve, Mat: Nylon, Orange coloured with chain
<a href="#">VR4050PL</a>	4" lockable vapour cap for 4" vapour valve, Mat: Nylon, Orange coloured
<a href="#">VR6030SQ</a>	Sequential Vapor Vent Threaded Gasoline and Diesel up to E100/B100 Aluminium
<a href="#">VR6035SQ</a>	Sequential Vapor Vent TTMA Flange Aluminium, for Gasoline and Diesel up to E100 and B100 Biofuels
<a href="#">4530</a>	3" API Drop Adapter Material Aluminum Seal BaylastT O-ring
<a href="#">4540</a>	4" API Drop Adapter Material Aluminum Seal BaylastT O-ring
<a href="#">FT400</a>	5 conductor cable 100' (30,48 m) (for use w/5 wire optic systems)
<a href="#">FT402E</a>	20 Strain Relief Ftgs M20 x 1.5"
<a href="#">V6M6-B-E</a>	3/4" quick release connector series V External thread NPT 3/4" -not shut-off- Gasket: Buna, material: brass
<a href="#">Qdf75m</a>	
<a href="#">K8f8</a>	
<a href="#">13mhhm-3p100150 (Alternative To K13 1quot;1/2)</a>	
<a href="#">Rn80</a>	8 316SS KING TURNED BACK NIPPLE FOR FLOATING FLANGES, M017-172

<a href="#">03450815</a>	
<a href="#">Am7</a>	
<a href="#">Am3</a>	
<a href="#">Wb1</a>	
<a href="#">Dn25 X 5000 Mm</a>	
<a href="#">A101hp010</a>	
<a href="#">Am8</a>	
<a href="#">Tsk34</a>	
<a href="#">Wb1c</a>	
<a href="#">H360y50uc</a>	6 50 HD YELLOW UNCOUPLED HOSE
<a href="#">Dn25 X 3000 Mm</a>	
<a href="#">Qdhe75m</a>	
<a href="#">Bpn-22</a>	
<a href="#">Ab-8 (Hz-360272p003-13)</a>	
<a href="#">R18-C05r</a>	2 SERIES-1 REGULATOR W/OUT GAUGE
<a href="#">Aksp25</a>	
<a href="#">Dxbn15f</a>	
<a href="#">4nf6</a>	
<a href="#">N4m6-Ls</a>	
<a href="#">A101hp020</a>	
<a href="#">08/013/14/000 ( 1 Box = 350 Pcs)</a>	
<a href="#">08/013/17/000 ( 1 Box = 550 Pcs)</a>	
<a href="#">H450y50sz</a>	5 X 50 HD YELLOW NITRILE HOSE CPLD WITH ALUM STORZ ENDS
<a href="#">1waybv400</a>	4 ALUM 1-WAY FULL FLOW BALL VALVE W/FNPT ENDS, FPM SEALS
<a href="#">08/013/19/000 (1 Box = 450 Pcs)</a>	
<a href="#">Wb-1</a>	
<a href="#">A101hp012</a>	
<a href="#">Am6</a>	
<a href="#">A101hp025</a>	