



## Doseuro S.R.L.

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Doseuro S.R.L.** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Doseuro S.R.L. Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Piston Gasket Set, Pos.3 And 12, For A125n-12/C-32</a>	+ Stuffing box, pos.6, for A125N-12/C-32
<a href="#">D101n-90/B-13 Tn</a>	Diaphragm metering pump 1 x mechanisch angetriebene Membrandosierpumpe mit manueller Hublngenverstellung 0-100% Typ: D101N-90/B-13 Dosiermenge: 0 - 271 l/h max. Betriebsdruck: 5 bar Hubfrequenz: 120 Hbe/min AnschluŐ: 3/4" AuŐengewinde Material: Pumpenkopf: PVC Membran: PTFE beschichtet Ventile: PVC Ventildichtungen: Viton Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55 Gewicht, brutto: ca. 12 kg
<a href="#">A350n-89/B-11, Ss/Nbr</a>	Piston metering pump directly controlled piston metering pump with manual stroke length adjustment 0-100% Type: A350N-89 / B-11 Dosing quantity: 0 - 1,458 l / h Max. Operating pressure: 4 bar Stroke frequency: 112 strokes / min Connection: 1 1/2 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.75kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">A250N-76/B-11, SS/NBR</a>	Piston metering pump 1 x directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A250N-76 / B-11 Dosing quantity: 0 - 766 l / h Max. Operating pressure: 6.5 bar Stroke frequency: 112 strokes / min Connection: 1 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.55kW, 3ph, 230 / 400V, 50Hz, 4 pol., IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 26 kg / 30 kg
<a href="#">D101N-90/B-13</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 5 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.25 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy

	Weight, net / gross: 10 kg / 13kg
<a href="#">Pump head, PVC, ø90mm</a>	Customs tariff number: 84139100 Country of origin: Italy Weight, net / gross: 0.4 kg / 0.6 kg
<a href="#">Valve set, AC13-13, PVC / Viton, for D101N-90 / B-</a>	consisting of suction and pressure valve Customs tariff number: 84139100
<a href="#">Membrane with support plate, ø90mm</a>	Zolltarifnummer: 84139100 Herkunftsland: Italien Gewicht, netto/brutto: 0,15 kg / 0,25 kg
<a href="#">D90 DIAPHRAGM AND PROTECTION POZ.20 + POS.22</a>	
<a href="#">D100N-90/B-13 TN</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">AC5-31</a>	Valve set, AC5-31, PP / Viton consisting of suction and pressure valve
<a href="#">AC13-14</a>	Valve set, AC13-14, PVC / Viton consisting of suction and pressure valve
<a href="#">AB13</a>	Valve set, AB13, SS / Viton consisting of suction and pressure valve
<a href="#">AC8-31</a>	Valve set, AC8-31, PP / Viton consisting of suction and pressure valve
<a href="#">D050N-50/B-13</a>	Diaphragm metering pump D050N-50 / B-13, PVC / Viton, for FeCl3 mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / B-13 Dosing amount: 0 - 49 l / h Max. Operating pressure: 10 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy
<a href="#">D100N-70/B-13</a>	Diaphragm metering pump D100N-70 / B-13, PVC / Viton, for Polyelectrolyte mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-13 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
<a href="#">FM50N-50/B-12 DV</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP

	Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 IT
<a href="#">FM50N-50/D-12 DV</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h Max. Operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">D100N-70/B-11, SS/Viton</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-11 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Membrane: PTFE coated Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 12 kg
<a href="#">B125N-12/C-43 DV</a>	Diaphragm metering pump hydraulically linked diaphragm metering pump with manual stroke length adjustment 0-100% Type: B125N-12 / C-43 DV Dosing amount: 0 - 7.4 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
<a href="#">Diaphragm, ø65 / 50, PTFE, for B125N-12 / C-43</a>	Membrane
<a href="#">FM50N-50/B-12 DV</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy
<a href="#">Diaphragm</a>	Membrane with support plate, ø50mm. for FM50N-50
<a href="#">Membrane with support plate, ø50mm. for FM50N-50</a>	
<a href="#">Valve set, AC5-31, PP / Viton</a>	consisting of suction and pressure valve
<a href="#">Valve set, AC13-13, PVC / Viton</a>	for D100N-90 / B-13
<a href="#">FM50N-50/B-12</a>	mechanically driven diaphragm metering pumps with manual Stroke length adjustment 0-100% Type: FM50N-50 / B-12 Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Weight:

	approx 8 kg Customs tariff number: 84135040 Country of manufacture: Italy
<a href="#">Membrane with support plate, ø30mm.</a>	for D050N-30 / F-12
<a href="#">D100N-90/B-13 TN</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13kg
<a href="#">Piston, ø89, ceramic, for A250</a>	
<a href="#">Piston, ø89, ceramic, for A350</a>	
<a href="#">Gearbox 250</a>	Gearbox A250, without motor, without pump head, with pump holder and motor bell
<a href="#">Gearbox 350</a>	Gearbox A350, without motor, without pump head, with pump holder and motor bell
<a href="#">A125N-11/C-11 DV</a>	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A125N-11 / C-11 DV Dosing amount: 0 - 6 l / h max.operating pressure: 20 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
<a href="#">D100N-90/B-13 TN</a>	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13k
<a href="#">Typ: D100N-70/C-12 DV TN</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
<a href="#">D=100N-90/B-13TN</a>	Q=27-330 litre/hours Pmax= 5 bar Power= 0.18 Kvt
	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A125N-12 / C-77 DV Dosing amount: 0 - 7.2 l / h max.operating pressure: 88 bar Stroke frequency: 96

<a href="#">A125N-12/C-77 DV</a>	strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: ceramic Piston packing: PTFE engg Valves: SS316L Valve seals: PTFE or similar Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
<a href="#">D101N-120/C-11</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-120 / C-11 Dosing amount: 0 - 334 l / h max.operating pressure: 3 bar Stroke frequency: 96 strokes / min Connection: 1 "external thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.37 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">D100N-120/F-13</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-120 / F-11 Dosing quantity: 0 - 219 l / h max.operating pressure: 1.5 bar Stroke frequency: 58 strokes / min Connection: 1 "external thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">D050N-50/C-11 DV</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / C-11 DV Dosing amount: 0 - 39 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">D100N-70/B12 DVTN</a>	
<a href="#">Piston packing set, ø89mm, Viton, for A250N</a>	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering Push rod, item 208, for A250N Spring, for adjustment, item 213, for A250N Scale, item 225, adhesive picture, for A250N Spring, for gear, item 226, for A250N
<a href="#">Piston packing set, ø89mm, Viton, for A350N</a>	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering. Push rod, item 208, for A350N Spring, for adjustment, item 213, for A350N Scale, item 225, sticker, for A350N Spring, for gear, item 226, for A350N
<a href="#">Pos.3 A250NandA350N</a>	Piston packing set, ø89mm, Viton, for A250N and A350N 2 x packing rings Material resistance must be checked by the customer before ordering.
<a href="#">Pos.10 A250NandA350N</a>	Wiper, ø89mm
<a href="#">Push rod, item 208, for A250N</a>	
<a href="#">Spring, for gear, item 226, for A250N</a>	
<a href="#">Push rod, item 208, for A350N</a>	
<a href="#">Spring, for gear, item 226, for A350N</a>	
<a href="#">Adjustment, complete, for A250</a>	Item 210, 211, 212, 213, 221, 222, 225, 263

<a href="#">A350N ADJUSTMENT LEVER</a>	Adjustment, complete, for A350 Item 210, 211, 212, 213, 221, 222, 225, 263,
<a href="#">NN HOSE</a>	Suitable for Ragazzini Psf1 Pump
<a href="#">A175N-38/C-34 Piston metering pump</a>	directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A175N-38 / C-34 Dosing amount: 0 - 115 l / h max.operating pressure: 13 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: SS316L Piston packing: EPDM Valves: SS316L Valve seals: EPDM Motor: 0.25kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">FM50N-50/D-12 DV</a>	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 4.5 kg / 6 kg
<a href="#">Motor - 230V - Hp 0,75</a>	Degree of protect - IP54 Flow rate 102 l/min Tank capacity - 40l Pressure - 1,8bar High circulation pump for descaling, cleaning and power lushing traditional and underfloor heating systems. Ergonomic and easy to handle. Fitted with flow reverser. With cleaning powder.
<a href="#">D100N-90/B-13</a>	
<a href="#">D-100N-90/B-13TN</a>	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">FM50N-50/D-12 DV</a>	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
<a href="#">Piston packing set</a>	Piston packing set, ø76mm, NBR, for A250N, item 3 + 10 2 x packing rings and 1 x wiper
<a href="#">D100N-70/C-12 DV TN</a>	Diaphragm metering pump D100N-70 / C-12 DV TN, PP / Viton mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / C-12 DV TN Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55



<a href="#">D0B07010122N1AA00</a>	Diaphragm dosing pump D-100N-70/B-12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">Valve set, AC13-13</a>	Valve set, AC13-13, PVC / Viton, for D101N-90 / B-13 TN consisting of suction and pressure valve
<a href="#">Diaphragm for D100N-70/B-12 DVTN</a>	Diaphragm with support plate, ø70, for D100N-70/B-12 DVTN
<a href="#">AP A-125N-16/C-82 DV</a>	AP A-125N-16/C-82 DV SPRING RETURN - PLUNGER DOSING PUMP
<a href="#">Diaphragm for D100N-90/B-13 TN</a>	Diaphragm with support plate, ø90, for D100N-90/B-13 TN
<a href="#">D121N-120/B13 - 230400V 50/60Hz - 3phase</a>	
<a href="#">FM50N-50/B12 - 230/400V 50/60Hz - 3pahse</a>	
<a href="#">D100N-70/C12</a>	230/400V 50/60Hz - 3pahse
<a href="#">A250N ADJUSTMENT LEVER-Doseuro to A350n-A250n</a>	
<a href="#">A350N ADJUSTMENT LEVER-Doseuro to A350n-A250n</a>	
<a href="#">OIL LEVEL INDICATOR-Doseuro will be suitable for</a>	A350n-A250n.
<a href="#">27MM*35*MM*7MM PRESSURE SEAL-It will be suitable</a>	for Doseuro A350n-A250n.
<a href="#">OIL FILLING DRAIN PLUG - It Will Be Suitable For</a>	Doseuro A350n-A250n.
<a href="#">D100N-70/F13 DV</a>	Dosing Pump
<a href="#">KIT0MS00700000000</a>	Membran + Schild KIT
<a href="#">KIT0MS01200000000</a>	Membran + Schild KIT
<a href="#">D100N-70/B12</a>	
<a href="#">KIT0MS00900000000</a>	Diaphragm and diaphragm shield (pos. 20+22) for pump D100N, article number KIT0MS00900000000
<a href="#">D100N-70/B12 DV</a>	
<a href="#">AC00000022000M020</a>	DOSEURO SUCTION CHECK VALVE AC-22/20N BODY PVC, BALL SS316, O-RING FPM 1" FOR D121N-120/B 13 PUMP (POLYMER DOSAGE) Set consisting of suction and pressure valve
<a href="#">KIT0MS01200000000.</a>	DOSEURO DIAPHRAGM AND DIAPHRAGM PROTECTION D.120 P. 20 + P. 22, FOR PTFE/NBR D121N-120/B 13 PUMP
<a href="#">A125N-12/C-77 DV.</a>	Model Description : Piston metering pump

<a href="#">A125N-30/B20</a>	Chemical to dose: CHLORINE WATER Cl <sub>2</sub> + H <sub>2</sub> O Max Chem. Temp (°C): 40 Working Pressure (Barg): 2.00 Max Viscosity (Cps): -1.00 Suction Pressure (Barg): N.A. Ambient Temperature: (-20 / +40) °C ΔP (Barg): 2.00 Req. Capacity (Lt/h): 60.00 Model: A125N-30/B-20 Mechanism Type: SPRING RETURN Max Capacity (Lt/h):62 @50Hz Pump Type: Plunger Stroke per minutes: 116 @50Hz Max Pressure (Barg): 14.00 Metal, 10.00 Plastic Stroke length (mm): 12.50 Adjustment: Manual 0 - 100% of stroke length Connection: 1/2" BSPPm Diaphragm Ø (mm): N.A. Valve Type: Double ball Plunger Ø (mm):30 Pump Area: SAFE AREA PUMP HEAD PVC DIAPHRAGM N.A. BALL VALVE* PYREX PLUNGER S.S.316L PLUNGER GASKET NBR VALVE O-RING FPM * for pump with valve size 1 INCHES - ball valve is in PTFE Power Supply:3PH - TRI-PHASE 4 POLES Area: SAFE AREA Protection:IP55 Insulation Class:F Installed Power: 0,18KW Voltage: 400.00 Frequency: 50 HZ Inverter Use: NO
<a href="#">A250N-64/C19</a>	
<a href="#">A175N-38/C19</a>	
<a href="#">FM050N-50B-12</a>	Filtered Level Floater Type: Float with Filter Supply: 24 V DC Signal: 4-20 Ma Model: Axial Inner Coating: Plastic
<a href="#">Dosing pump D100N-70/C12</a>	
<a href="#">FM050N-50/D12</a>	
<a href="#">FM050N-50/F-03</a>	
<a href="#">FM050N-50/F-12</a>	
<a href="#">D100N-105/C-12</a>	
<a href="#">D100N-120/I-23</a>	
<a href="#">SDI-175-12/B-05 DV</a>	E.motor 0,25 KW 3Ph 4 Poli IP 55 Cl. F 400-440V 50-60Hz Size 71 B14 IE2 KIT PRESSURE GAUGE INOX 0-16 BAR
<a href="#">Diaphragm Dosing Pump with Electric Motor SR Serie</a>	SDI-175-12/B-05 DV Type or Name of Liquid: BELGARD EV 2050-100% V/V
<a href="#">Diaphragm Dosing Pump with Electric Motor SR Serie</a>	Model: SDI-175-12/B-05 DV Type or Name of Liquid: BELITE M8-5-7% V/V
<a href="#">D0C09010111N1AA00</a>	type: PUMP D-101N-90/B-11 - - TN 4/3PH-230/400/50/60 SPRING RETURN - MECHANICAL DIAPHRAGM DOSING PUMP required capacity: N.S. l/h max: 271 l/h required pressure: N.S. bar max: 5 bar
<a href="#">AC13/14 Valve</a>	item number AC00000013000M014 (AC 13/14 N (PVC + PYREX + FPM) in ¾" suitable for D100N-90/B13) Both valves are included in the valve set, i.e. suction and pressure side.
<a href="#">CHECK VALVE UNDERSET.</a>	For dosing pump with code d-100n-90/b-13
<a href="#">D100N-70/B12</a>	Diaphragm dosing pump



<a href="#">D 101 N 408 L//sa</a>	
<a href="#">D 100 N 374 L//sa</a>	
<a href="#">D 101 N 408 L//sa</a>	
<a href="#">D 100 N 374 L//sa</a>	
<a href="#">D 100 N 374 L//sa</a>	
<a href="#">D 101 N 408 L//sa</a>	
<a href="#">D 100 N 374 L//sa</a>	
<a href="#">D 101 N 408 L//sa</a>	
<a href="#">D 101 N 408 L//sa</a>	
<a href="#">D 100 N 374 L//sa</a>	
<a href="#">A125N-25/B-20</a>	Execution: 20 PUMP HEAD PVC PLUNGERS S.S.316L PLUNGER GASKET NBR VALVE SEAT PVC VALVE BALL PYREX VALVE GASKET FPM Please check the execution. In the best case, tell us the operating points or the materials.
<a href="#">SUCTION CHECK VALVE AC-13/14N</a>	Art. Nr. AC00000013000M014
<a href="#">SUCTION CHECK VALVE AC-13/14N,</a>	Art. Nr. AC00000013000M014
<a href="#">STAFSJÖ WB DN150 PN10/16 NBR</a>	Manual Knife Valve
<a href="#">Piston dosing pump A125N-25/I-11 with servomotor</a>	4-20 mA
<a href="#">Mechanical dosing pump D-050N-50/C-23 DV</a>	
<a href="#">BTM0D000700081P13</a>	PP pump head
<a href="#">KIT0MS00700000000</a>	Membran
<a href="#">6115145778477</a>	Expansion Tank LR119079046S
<a href="#">FM050N-50/B-11 340/400V 50/60Hz</a>	
<a href="#">KIT0MS00300000000</a>	membrane+membrane shield
<a href="#">A250N-89/C37</a>	piston pump
<a href="#">PRESSURE CHECK VALVE D70/12 AC-8/31N</a>	
<a href="#">SUCTION CHECK VALVE D70/12 AC-8/31N</a>	
<a href="#">ACD0000008000M031</a>	Suction and discharge valve SET AC8/31,
<a href="#">EDI0S006350000G02</a>	Piston Gasket set d64 in FPM
<a href="#">A-125N-11/B13</a>	piston dosing pump

<a href="#">D121N-120/F13</a>	diaphragm dosing pump
<a href="#">RELIEF VALVE VSC-10/43 PVC</a>	VS000000100000043
<a href="#">PISTON GASKETS SET G10-8 P7-8</a>	
<a href="#">S.S.420 PISTON D.14</a>	
<a href="#">PISTON GASKET SET G10-14 P7-14</a>	
<a href="#">CERAMIC PISTON D.8 WITH GRAINS 6X8</a>	
<a href="#">D-121N-120/B-13 - 4/3PH-230/400/50/60</a>	D0I1201013111AA00
<a href="#">Diaphragm dosing pump FM-50N-50/B12 DV, 230/400V</a>	50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 47l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">D-101N-90/B-13</a>	TN 4/3PH-230/400/50/60 D0C09010131N1AA00
<a href="#">FM050N-50/B-12 DV</a>	F0B050301221AA05
<a href="#">D-101N-105/B-13 - - - 4/3PH-230/400/50/60</a>	D0C1051013111AA00
<a href="#">D-101N-70/C-11</a>	TN 4/3PH-230/400/50/60
<a href="#">D-101N-105/B-13</a>	4/3PH-230/400/50/60
<a href="#">A175</a>	Ball check valve part located in the inlet and outlet line of A175 piston dosing pump
<a href="#">KIT0MS01050000000</a>	Membrane with support plate, ø105mm, Pos.20+22
<a href="#">Suction and pressure valve AC13/14 (PVC+PYREX+FPM)</a>	
<a href="#">A125N-8/B-32 DV</a>	
<a href="#">PUMP D-101N-90/B-12 - - TN 4/3PH-230/400/50/60</a>	D0C09010121N1AA00
<a href="#">SUCTION/DELIVERY VALVE SET AC-13/14N G/M</a>	AC00000013000M014
<a href="#">SUCTION/DELIVERY VALVE SET AC-13/31N</a>	AC00000013000M031
<a href="#">SK10MS00+0205</a>	SCL K10MS TMS BPA MOR IE3 M.E. Gr.132 - 11kW - 13kW 660-720/380-415V 50Hz 760-830/440-480V 60HzIE3 - ATEX 3GD - IP65 - CL. F - TROP. PTO - PAINTED - ANOD.+IMPR.+V.INOX II 3GD - Ex h IIC T3 Gc - Ex h IIIC T200°C Dc
<a href="#">PUMP A-250N-89/B-20 - - 4/3PH-230/400/50/60</a>	A0H0891020111AA00
<a href="#">FM050N-50/B-12 DV, 230/400V 50/60Hz</a>	

<a href="#">A0E01620822111110</a>	AP A125N-16/C-82 DV, 1PH SINGLE-PHASE 4 POLES 230V IP55 50 HZ
<a href="#">PUMP AI-350-89/A-13, 400V 50 Hz 1.1 KW, IP55</a>	Eexd II C T4 with ABB Motor Atex Zone 2G T4 IOL08940111110201
<a href="#">DOB09010131N1AA00</a>	Diaphragm metering pump D-100N-90/B-13, 230/400V 50/60Hz in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
<a href="#">D-100N-90/B-13, 230/400V 50/60Hz</a>	D0B09010131N1AA00 in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
<a href="#">B0H0752043111AA00</a>	PUMP B-250N-75/C-43 - -- 4/3PH-230/400/50/60
<a href="#">KIT0R001750000000</a>	GEAR BOX O-RING KIT FOR 175N/D-101N/D-121N Pos 219;220;221;222;235;263
<a href="#">EDR00050150000G02</a>	O-RING GASKET 50 X 1,5 FPM Pos. 7
<a href="#">D0C07010122N1AA00</a>	Membrandosierpumpe D101N-70/B12 DV, 230/400V 50/60Hz, in PP version with 0-100% manual Stroke length adjustment. - max. dosing rate 159 l/h - max. pressure 10 bar - 1/2" BSP male connection
<a href="#">ACD0000008000M031</a>	Ventil-Set AC 8/31N DV (PP+PYREX+FPM)
<a href="#">KIT0MS009000000000</a>	Membrane with support plate, ø90mm, Pos.20+22
<a href="#">KIT0MS012000000000</a>	Membrane with support plate, ø120mm, Pos.20+22
<a href="#">KIT0MS007000000000</a>	Membrane with support plate, ø70mm, Pos.20+22
<a href="#">AC00000013000M014</a>	SUCTION/DELIVERY VALVE SET AC-13/14N G/M
<a href="#">AC00000022000M014</a>	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
<a href="#">AAP00001000000L01</a>	CRANK SHAFT D-100N
<a href="#">ZZZ</a>	ASS000R1010001006 - Push-rod support
<a href="#">ASL00001010000X05</a>	PUSH ROD D-100-101-121N
<a href="#">AMN0C001750000P03 - Adjustment knob (complete)</a>	
<a href="#">AC00000022000M014</a>	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
<a href="#">AC00000022000M014</a>	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
<a href="#">AAP00001210000L01</a>	SHAFT D121N
<a href="#">ASS000R1010001006 - push rod support</a>	
<a href="#">ASL00001010000X05</a>	PUSH ROD D-100-101-121N
<a href="#">ZZZ</a>	AMN0C001750000P03 - Adjustment knob (complete)

<a href="#">BTM0D001200220P01</a>	Pump head in PVC for D-series size 120
<a href="#">ALT0D001200000A05</a>	HEAD LANTERN D.120 FOR D PUMP
<a href="#">ACD0000008000M014</a>	Suction and pressure valve AC-8/14 DV (PVC/PYREX/FPM)
<a href="#">ACD0000008000M014</a>	Suction and pressure valve AC-8/14 DV (PVC/PYREX/FPM)
<a href="#">AAP00001000000L01</a>	CRANK SHAFT D-100N
<a href="#">ASS00001250001A06</a>	PUSH ROD BEARING 125-175N 100N ZAMA
<a href="#">ASL00001010000X05</a>	PUSH ROD D-100-101-121N
<a href="#">AMN0C001700000P03</a>	COMPLET KNOB 50-125-175-101N
<a href="#">BTM0D000700081P01</a>	PVC D.70 PUMP HEAD FOR D PUMP (8holes)
<a href="#">ALT0D000700000P02</a>	HEAD LANTERN D.70 FOR D PUMP
<a href="#">DOB07020122N1AA00</a>	Diaphragm metering pump D100N-70/C12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. metering rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">DOB07020122N1AA00</a>	Membrandosierpumpe D100N-70/C12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">BTM0D001200220P01</a>	Pump head in PVC for D-series size 120
<a href="#">KIT0MS01200000000</a>	Membrane with support plate, ø120mm, Pos.20+22
<a href="#">DOI1201013111AA00</a>	Diaphragm metering pump D121N-120/B13, 230/400V 50/60Hz, in PVC version with 0-100% manual stroke length adjustment. - max. metering rate 570 l/h - max. pressure 5 bar - 1" BSPm connection
<a href="#">DOB07010122N1AA00</a>	Diaphragm metering pump D100N-70/B12 DV, 230/400V 50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. metering rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">DOC09010131N1AA00</a>	PUMP D-101N-90/B-13 - - TN 4/3PH-230/400/50/60
<a href="#">PUMP A-125N-14/F-32 DV</a>	4/3PH-230/400/50/60 A0E0143032211AA00
<a href="#">PUMP D-101N-105/B-13 - - - 4/3PH-230/400/50/60</a>	D0C1051013111AA00
<a href="#">DOA0501012211AA00</a>	Membrandosierpumpe D050N-50/B12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 49 l/h - max. pressure 10 bar - 1/2" BSP male connection
<a href="#">DOA0505012211AA00</a>	Membrandosierpumpe D050N-50/I12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 14 l/h - max. pressure 10 bar - 1/2" BSP male connection

<a href="#">KIT0MS00500000000</a>	Membrane with support plate, ø50mm, Pos.20+22
<a href="#">ACD0000005000M031</a>	Suction and pressure valve AC-5/31 DV (PP/PYREX/FPM) G1/2" male
<a href="#">Suction and pressure valve AC-5/31 DV (PP/PYREX/FPM)</a>	G1/2" male ACD0000005000M031
<a href="#">D-100N-90B-13 TN 271 LT</a>	
<a href="#">PUMP SDI-350-130/B-03 - 230/400V 50/60Hz 2,2 kW</a>	
<a href="#">Pulsation damper PVC with a volume of 6Lt and 1 1/2" connection</a>	
<a href="#">Pulsation damper PVC with a volume of 10Lt and 2" connection</a>	
<a href="#">DCAL0550020001P01</a>	Calibration cylinder CP55 G.2" PVC/TFM/GLASS
<a href="#">WESVS000500000143</a>	pressure control valves VSC 50/43
<a href="#">PUMP SDI-350-120/B-05 - 400V 50Hz 2,2kW</a>	M0L12010051110400
<a href="#">KIT0MS00900000000 - Pos 1</a>	For Pump D-101N-90/B-11
<a href="#">ALT0D000900000P02</a>	Membrane with support plate, ø90mm, Pos.20+22 Pos. 2
<a href="#">EVRG0001750110000</a>	HEAD LANTERN D.90 FOR D PUMP (8 HOLES) Pos. 3
<a href="#">ESM00016240050G01</a>	ENDLESS SCREW/WORM WHEEL GROUP T.1/11,5 175-101N Pos. 4
<a href="#">EVRG0001250120000</a>	For Pump D-100N-70/C-12 DVTN: Pos. 5 ENDLESS SCREW/WORM WHEEL GROUP T.1/12 125N
<a href="#">Diaphragm metering pump D100N-70/B12 DV, 230/400V</a>	50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">Diaphragm metering pump D100N-70/C12 DV, 230/400V</a>	50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">FM-50N-50/B12 DV, 230/400V</a>	diaphragm metering pump 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 47l/h - max. pressure 5 bar - 1/2" BSP male connection
<a href="#">Spring (Pos.226)</a>	
<a href="#">D-100N-70/B-12 DV, 230/400V 50/60Hz</a>	D0B07010122N1AA00 mechanically driven diaphragm dosing pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-12 Dosage: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "external thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55

<a href="#">D101n-90/B13</a>	
<a href="#">A0e25m3011v11aa00</a>	
<a href="#">Metering Pump Doseuro Typ A250n-89/B-19</a>	1 x plunger pump with manual stroke length adjustment 0-100% Type: A250N-89/B-19 Capacity: 0 - 1042 l/h max. pressure: 4,8 bar stroke frequency: 112 strokes/min connection: 1" male thread Material: Pumphead: SS316L Plunger: SS316L Plunger packing: Viton Valves: SS316L Valve gaskets: Viton Motor: 0,55kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
<a href="#">Type : D-101n - 120/B 11</a>	
<a href="#">Push Rod Gasket (Pos.223)</a>	
<a href="#">D101N-70/B12 DV, 230/400V</a>	diaphragm metering pump 50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 159 l/h - max. pressure 10 bar - 1/2" BSP male connection
<a href="#">D- 105/90 Ptfе/ Nbr</a>	Diyafram For this pump (B-175N-40/c)
<a href="#">Set Of Endless Screw (Pos.205) And Worm Wheel (Pos.206), For Model A250</a>	
<a href="#">Metering Pump Doseuro Typ A125n-14/F-33</a>	plunger dosing pump type DOSEURO A125N-14/F-33 with manual stroke length adjustment 0-100% Capacity: 6 l/h Max. operating pressure : 65 bar Strokes frequency : 58 strokes/min Connection: 1/2" BSP male Material : Pumphead: SS316 Plunger: SS420 Plunger packing: PTFE Valves: SS316 Valve gaskets: PTFE Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
<a href="#">206- Worm Wheel</a>	
<a href="#">A-125n-11/C-19</a>	
<a href="#">Flexible Coupling (Pos. 209/1/2/3)</a>	
<a href="#">209/2- Flexible Insert</a>	
<a href="#">Key, 5 X 5 X 20mm (Pos.227)</a>	
<a href="#">Fm50-50/B-12</a>	Metering Pump Doseuro mechanical diaphragm dosing pump with manual stroke length adjustment 0-100% Type: DOSEURO FM50-50/B-12 Capacity: 47 l/h Max. operating pressure : 5 bar Strokes frequency : 116 strokes/min Connection: 1/2" BSP male Material : Pumphead: PP Diaphragm: PTFE coated Valves: PP Valve gaskets: Viton Motor: 0,09kW, 3ph, 230/400V, 50Hz, 4 poles, IP65
<a href="#">209/3- Flexible Coupling (Top)</a>	
<a href="#">Dosing Pump D-101n-70b-11 Tn Membranes</a>	2 MEMBRANES FOR PUMPS THAT DİSTRİBUTE SOLUTION TO FURNACE