

## Driescher

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Driescher** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Driescher T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">2-72264000</a>	H22 SEA 36-630/125 p400 xy775, LI3-064409, 3-pin Load switch fuse combination Type: H22 SEA with release, interior/wall attachment, Ur 36kV, Ir 630/125A, p 400mm, xy 775mm, class M1, with fuse holder 125A attached below for Use of HH fuses with pin release (make Driescher or Siba) according to drawing LI3-064409 item 1, Cu 8.25 kg, Ag 16.78 g, St 77.96 kg,
<a href="#">2-73616014-3</a>	ITr 12-1600-40 p210 3-pol. Innenraum Trennschalter uEsv xy450, 2xG4, 102832-001-01, Type: ITr 12-1600-40, interior/wall attachment, Ur 12kV, Ir 1600A, Ik 40kA, tk 3s, p210mm, xy450mm, class M2, with grounding switch attached below Type: ES 12-31.5 Ik 31.5kA, tk 3s, Ima 50kA, class E1, with mechanical locking, according to drawing 102832-001-01, additionally equipped with: - 4-pin auxiliary switch 013229 on the ITr for position reporting Wiring diagram EQ4A 022A A000 00A, - 4-pin auxiliary switch 013229 on the ES for position reporting Wiring diagram EQ6A 022A A000 00A, Cu 14.83 kg, Ag
	Actuating linkage for DZ Actuating linkage with 1.2m GRP profile according to drawing 131029-012-01, with the

<a href="#">2-77493410</a>	following components: 2 pc. 2-77411600 clamping cranks, 1 pc. 2-45235216 GRP insulating rods 1.2m, with bolts and circlips. Weight St 0.55 kg. Weight approx. 2.62 kg
<a href="#">2-72040129</a>	D-Z drive turn. A left Rotary lever hand drive Type: D-Z drive direction of rotation A, extension left, electro galvanized, use for interior, up to a maximum of 180 Nm, according to drawing AZ3-060473-002-01 Weight 2.8kg. 060473-001-01,
<a href="#">2-72040138-5</a>	D-Z drive direction of rotation A, left. Rotary lever hand drive Type: D-Sterndrive Heavy Duty direction of rotation A, extension left, heavy duty, mounting plate, AZ1-103401/1 electro galvanized, use for interior, up to a maximum of 300 Nm, according to drawing AZ1-103401/1, additionally equipped with: - Mounting plate for side mounting according to drawing 092615, Weight 11.5kg.
<a href="#">2-64168910</a>	Spacer bar for DZ drive For the grounding switch mounted below! Drawing 091644-001-01-F Weight St 0.4 kg.
<a href="#">2-77492500</a>	Drive lever hexagon SW24 Use for interior to DZ drive or drive sleeve, galvanized, lever length 520 mm, Weight St 1.3 kg. c = 520, complete with ball head, drawing AZ4-041399-001-01,
<a href="#">2-77080101</a>	Clamping disc oval for mechanical position reporting to DZ drive or drive sleeve, with locking ring, with off and on sign. HA4-066500-001-01,
<a href="#">SSMD0017</a>	12kV 630A 20kA Air Insulated SYA B:24Vdc, 4NO+4NC, Auxiliary Contact, Sig.Put Contact, Jaw and Pin
<a href="#">Drs04/400-B7</a>	2.4/4.8KV 85X292MM DIN DD
<a href="#">Drs20/250-B8</a>	17/25.8KV 85X442MM DIN-DD
<a href="#">Ftr 38,5-1600-31,5</a>	2-75632508 FTr 38,5-1600-31,5 uEv 2xG8 Zeichnung 106795-002-02 // Freiluft-Trennschalter 90° 3-pole outdoor disconnecter FTr 38.5-1600-31.5, Ur=38.5kV, Ir=2500A, Ik=40kA, tk=3s, BIL 180kV, p=700, xy=1019, class M1, for vertical mounting (90°), insulators cast resign type, creepage distance 830mm, PD3, -- with 8-pole auxiliary switch (4NO/4NC) on disconnecter, according to drawing NU4-013229, according to circuit diagram EQ4A 044A A000 00A, -- with earthing switch Ik=31.5kA, tk=3s, mounted below, mechanical interlocked, with 8-pole auxiliary switch (4NO/4NC) on earthing switch, according to drawing NU4-013229, according to circuit diagram EQ6D 044A A000 00A, according to drawing FT3-106795-002-02. Attention: Auxiliary switch and mechanical interlocking mounted according to drawing 106369-006-02. //weight 165,7 kg
<a href="#">Drs30/200-B9</a>	24/34.5KV 2X85X537MM DIN
<a href="#">Drs30150b9</a>	DIN RAIL
<a href="#">Drs15/250-B8</a>	10/17.5KV 85X442MM DIN DD
<a href="#">Drs20/200-B8</a>	17/25.8KV 85X442MM DIN-DD

<a href="#">Drs07/400-B8</a>	4/7.2KV 2X85X442MM DIN
<a href="#">Drs04/500-B7</a>	2.4/4.8KV 85X292MM DIN DD
<a href="#">Um90 230v Ac Drehsinn B</a>	
<a href="#">Drs15/400-B8</a>	10/17.5KV 85X442MM DIN DD
<a href="#">Drs13/200-B7</a>	10/13.8KV 2X85X292MM DIN
<a href="#">Drs07/500-B8</a>	4/7.2KV 2X85X442MM DIN
<a href="#">Getriebe Um/Uh90</a>	
<a href="#">Drs12/315-B7</a>	7.2/12KV 2X85X292MM DIN
<a href="#">Drs07/500-B4</a>	4/7.2KV 85X442MM DIN
<a href="#">Drs07/400-B4</a>	4/7.2KV 85X442MM DIN
<a href="#">Drs30/125-A9</a>	24/34.5KV 2X66X537MM DIN
<a href="#">Drs20/315-B8</a>	17/25.8KV 85X442MM DIN-DD
<a href="#">Drs04/630-B7</a>	2.4/4.8KV 85X292MM DIN DD
<a href="#">Drs15/315-B8</a>	10/17.5KV 85X442MM DIN DD
<a href="#">Drs07/630-B8</a>	4/7.2KV 2X85X442MM DIN
<a href="#">2-73636996 Itr 38,5-1600-40 OeZl P500</a>	