

Durag

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Durag Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Durag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
D-Lx 100 UI-B1/M3/94ex/Pcg	Old name: D-LX 100 UL / 94 Ex Region code: B; certified for EU, Australia, EAU Code: 1; confirmed for applications up to SIL3 UV compact flame detector # Safety time: 1 sec. # # Analog output: 4-20 mA # - The connected cable variant is shown separately Explosion protection: II 2G Ex d e IIC T6 Gb Ambient temperature Ta -20 ° C = Ta = + 60 ° C (T6)
D-Lx 100 94ex Cbl-S1x-Pcg-00	connection cable - m. Silicone jacket and plastic cable gland, Length 1.5 m - pre-assembly on the flame detector / sensor Customs tariff number: 85444995
D-R 290 M	Measuring head for D-R290 dust measuring system - HxWxD approx. 400x200x400mm, - Purge air flange: bolt circle D = 100mm, air inlet: D40mm - Measuring ranges: 0-0.1 ..1.6 ext / 0-20% ... 100% opacity - suitable for measuring path length 1-8m - Suitable for ambient temperature: -20..50 ° C - with connection cable L = 2m - with sealing sleeve 120x3x20mm Customs tariff number: 90275000
4017379	D-LX 201 UA-C0 / P2 / 0000 / MP3 UV compact flame detector , Direct view version
1117704	D-LX 200 CBL-V1C-MP3-05 Connection cable 5m

4005638	D-HG 400-50-C-230 High energy ignitor , with angled connector
D-R 290 SP R 2	IP65 RS485 4-20mA analog ausgang -40 - +60 grad max. -50 - +20hPa max Betriebs Temp. +250 grad
D-LE 603 UA-P	UV flame sensor Customs tariff number: 85437090 Origin of goods: DE / Hamburg EU AL-No .: N US ECCN: N
D-LE 55 ULD-CG	UV flame sensor for connection to Switching devices for ionization flame monitoring - The connected cable variant is shown separately Customs tariff number: 85437090
D-LE 55 UL CBL-S1X-PCG-10 connection cable	- m. Silicone jacket and plastic cable gland, length 10m - pre-assembled on the flame monitor / sensor Customs tariff number: 85444995
D-LE 103 CBL-V1C-PP1-00	Connection cable - m. PVC jacket, screen and plastic cable socket, length 1.5 m - used f. D-LE 103, D-LE 603/703/701 Customs tariff number: 85444290 Origin of goods: DE / Hamburg
D-LE 55 UL CBL-S1X-PCG-30 connection cable	Alternative item to item 000020 m. Silicone sheath and plastic cable gland, length 30m - pre-assembled on the flame monitor / sensor
D-LX 100 System(e)	8021061 D-LX 100 UL-B1/M3/94Ex/PCG Old name: D-LX 100 UL / 94 Ex Region code: B; certified for EU, Australia, EAU Code: 1; confirmed for applications up to SIL3 UV compact flame monitor # Security time: 1 sec. # * Please confirm when placing the order * # Analog output: 4-20 mA # - The connected cable variant is shown separately Explosion protection: II 2G Ex d e IIC T6 Gb Ambient temperature Ta - 20 ° C = Ta = + 60 ° C (T6) The operating instructions are in the following as an independent Delivery item listed! Customs tariff number: 85371098 Origin of goods: DE / Hamburg
D-LX 100 94EX CBL-V1C-PCG-00	Connection cable - with PVC jacket, screen and plastic cable glands, Length 1.5 m - pre-assembled on the flame monitor / sensor Customs tariff number: 85444995 Origin of goods: DE / Hamburg
D-ZL SP ZSP AL02-NT	1100638 Replacement ignition tip for high-energy ignitors D-HG 400-5x / -80, D-HG 5x0-5x and ignition lances D-ZL 4xx, D-ZL 5xx Normal temperature version (NT) up to 600 ° C Length: 593 mm, including sealing ring (CU) Customs tariff number: 84169000
D-R290 115-230VAC	3129700
FLAMME DETEKTOR	D-LX 201 UA // MARKE: DURAG MODELL: D-LX 201 UA ES WIRD ZUSAMMEN MIT SEINEM 10 METER INTERNEN KABEL UND EINSTELLBARE BEFESTIGUNGSVORRICHTUNG (SCHWENKBEFESTIGUNG //&ack47618.1.txt
	UV compact flame monitor Version for direct view Region code: C for use in EU, AUS Functional safety code: 1 SIL documents available Power supply: 24VDC Housing M5: Al

D-LX 110 UAF-C1/M5/0000/MP7	MP7: Metal connector Spectral range: UV 280-410nm Process connection: Purge air flange G 1 1/4 " Degree of protection (IP / NEMA): IP 65 Ambient temperature: -40 ... +75 ° C
4004545	D-LX 110 CBL-V1C-MP7-00 connection cable - with PVC jacket, screen and metal cable socket, Length 2 m - used f. D-LX 110/710
4021115	D-LX 110_710 MAN-EN Operating instructions in English, printed Customs tariff number: 49011000
D-ZL SP ZSP AL02-HT(P/N:1108430)	
108062	
1100517	
1101520	
1106455	
1106724	
1107644	
1107645	
1113860	
1113984	
1114180	
1114429	
1114759	
1115883	
1115944	
1116329	
1119545	
1119548	
1119549	
1119575	
1119581	
1119630	
1123973	
1125538	
1150116	

1150332	
1156718	
1157527	
1158062	
1163734	
1170408	
1171770	
2001285	
2001289	
4012314	
4012758+1114180	
D-LE 103 UL-P	
Manufacturer Part Number D-LX201UA-C1/M4/84EX/M20	Part name* FLAME SCANNER Ratings 24 Vdc Equipment name* TBA Equipment model number* TBA Equipment serial number TBA Additional information: Spectral sensitivity 190 - 520 nm Ambient temperature #40 °C TO +85 °C Connection, process G 1.1/4 in, FEMALE Connection, purge air G 1/2 in, FEMALE Analogue output (configurable) 4 - 20 mA Classification, hazard areas II 2G Ex db IIC T6/T5 Gb, II 2D Ex tb IIIC T85/100°C Db IP 66, SIL3
D-ZL SP ZSP AL02-HT	Replacement ignition tip for high-energy ignitors D-HG 400-5x/-80, D-HG 5x0-5x and ignition lances D-ZL 4xx, D-ZL 5xx Length: 593 mm, incl. sealing ring (VA)
D-ZL A1-22-90-D1	Ignition lance tube for mounting on D-HG 400-5x, D-HG 500-5x, D-HG 550-5x Diameter: 22mm Total length of ignition lance (LZL), without additional extensions: 1,500 mm Connection thread type: A1 Thread type: D1, flat, suitable for extension ignition lance tube or ignition tip
D-GF 75	
D-GF 150 Automatic Burner Control	
Flame Monitor, Part # D-LX110 UL-C1	
D-LX 201 IG-C0/P2/0000/PCG	4017380 IR compact flame controller Direct view version Region Code: C for use in EU, AUS Functional safety code: 0 SIL documents not available Power supply: 24VDC Housing P2: PA PCG: Plastic cable gland Spectral range: IR 780-1800nm Process connection: purge air flange G 1 1/4" Degree of protection (IP/NEMA): IP 66: Degree of protection (IP/NEMA): IP 68 Ambient temperature: -40 ... +85 °C The connected cable variant is shown separately Customs tariff number: 85371098
D-LX 110 UA-C1/M5/0000/MP7	

D-HG 500-50-C-230	
D-VE 532-11/230AC/NSA 113	
Spare ignition 1108430	
1114746	D-LX 200 CBL-V1C-PCG-10 connection cable - with PVC jacket, screen and plastic cable gland. (metal cable gland for /84Ex), Length 10m - pre-assembly on the flame monitor/sensor, used f. D-LX 200/720/201/721/101/701 and D-LC 101/701 Customs tariff number: 85444995
D-HG 400-50-C-230	High energy ignitor with angled built-in plug Power supply: 230 VAC Ignition energy (J/spark): 4.5 Ignition frequency start phase (sparks/s): 20 Degree of protection: IP 65 Permitted Ambient temperature: -20°C...+60°C Ignition lance connection: Mounted directly on the housing Note: Associated ignition lance components listed below Note: Replaces material number 1151237
1118587	D-HG 400 CBL-S1X-MP4-00 cable - with silicone jacket and metal cable socket, - Length 1.5m
4017092	D-HG 400 MAN-DE Operating instructions German, printed
D-LX 110 UAF-C1/	
D-LX 110 CBL-V1C-	
D-VE 532	
D-H	
D-SK F3-2 (1116957)	D-R 290 Air flow sensor, purge air monitoring - with cable L=2m,
D-FL 100	CONTINUOUS FLOW MEASUREMENT SYSTEM TS EN 14181 QAL 1 CERTIFIED RS485 MODBUS DIGITAL DATA OUTPUT
4009438	D-R 290 SP reflector insert R2 suitable for D-R 290 R2 - 1x reflector insert type II (1.75...12 m) - 3x screws
19-04-12906-1298	Quantity: 40m
4012315	D-LX 201 UA-C1/P2/0000/PCG UV compact flame monitor Direct view version Region code: C for use in EU, AUS Functional safety code: 1 SIL documents available Power supply: 24VDC Housing P2: PA PCG: Plastic cable gland Spectral range: UV-VIS 190-520nm Process connection: viewing tube connection G1 1/4"; purge air connection: G1/2" Protection class (IP/NEMA): IP 66: Protection class (IP/NEMA): IP 68: Protection class (IP/NEMA): NEMA 4X Ambient temperature: -40 ... +85 °C The connected cable variant is shown separately
1114180	D-LX 200 CBL-V1C-PCG-00 connection cable - with PVC jacket, shield and plastic cable gland. (metal cable gland for /84Ex), Length 2m - pre-mont. on the flame monitor/sensor, use. f. D-LX 200/720/201/721/101/701 and D-LC 101/701

4015140	D-LX 201_721 MAN-DE
1101520	D-ZS 033-I Ball adjustment flange Connection on the torch side: 2" welding flange Flame sensor connection: G 1¼" external thread
1108948	D-ZS 117-I Heat insulator Connection on the burner side: G 1¼" internal thread Flame sensor connection: G 1¼" external thread
EVALUATION UNIT D-FL 100-20A IP65	D-FL 100-20A model
4003929	299704 / COMPACT FLAME MONITOR / COMPACT FLAME MONITOR / D-LX 110 UA-C1/M5/0000/MP7, 24 V, 7W, CONTACTS:NO-NC, OUTPUT:0/4...20MA,G1¼ INCH - NPT1¼ INCH , F, G½ INCH -NPT ½ INCH F, (PRODUCT WITH REF. NUMBER DURR 100699050),FOR OVEN SYSTEM
FLAME DEDECTOR D-LE 603 UAF-P	FLAME DEDECTOR.FOR OIL DURAG TYPE:D-LE 603 UAF-P
IGNITION ELECTROD Ø22 MM (DURAG D-HG 400	PART OF IGNITION LANCE. L3 (600 MM) FOR DURAG D-HG400/50S DEVICE. THIS PART WILL BE ACORDING TO ADDED DROWING.
D-LX 201 UA-C0/ P2/0000/MP3	Compact Flame Monitor (with 5m supply cable)
D-HG 400-50-C 230	Electronic Unit 230 Vac, Ignition Voltage 1500V, IP65, Operating Temperature -20/+60 °C
D-LE 703 Flame Sensor Fiber	
D-LX200 UA10	
D-LX 721	
D-R 820F TOZ	MODEL:D-R 820F P L080-DN80-PN6-230-E DUST MEASUREMENT SYSTEM SAMPLING PROBE -D-R 820F SAMPLING PROBE with FRP CABINET -PROBE LENGTH: 820 mm, -MATERIAL HASTELLOY C4 2.4610 -DR800F LASER UNIT -PROCESS CONNECTION:FLANGE DN80, PN6, 1.4571 -POWER SUPPLY: 230 VAC -WORKING TEMPERATURE: -20-50°C - PROTECTION CLASS: IP55
1112303	
D-Le 603 Ua-P (1150332)	
1107281 - Heated Window – 45 Mm	
1103659 (1x10)	
D-ZI A1-22-140-D1	
1112921	
1150425	
Motor 1107147	
Dg-D703	

Db-Hg2600-00-03	
D-Ug660-024d-420	FLAME SCANNER CONTROL UNIT 24VDC 4-20MA OUTPUT
D-Lx 100ul-P	
Zxae11-75e25/00aa0	
1118465	
Dle603uamp	UV SENSOR
D-R 281-21av/No.30	Opacity Meter Transformer Module
D-Zs 117-I	
D-Le703ua-P	
D-Le 130 Man-En Manual	
D-FI 220 Sp	
1104170	
R290re2	
D-Le 103 Cbl-V1c-Pp1-05	
111702	
D-R290-85	
1112988	
D-Le-603 Ui/95ex	
D-Ug 660 115a-020	
D-Gf75-10	
1119589	
Dbfl200lp51	PC BOARD
D-Lx 100 Ua-B1/M3/94ex/Pcg	
D-FI220	
D-Ug660	
1112232	
D-Gf100-10	BURNER CONTROL SYSTEM
Db-Hg2600-00-01	
D-Gf 150-115a 0-20 Ma	
D-Lx 100 Cbl-S1x-Pp2-00.	

1156719	260NM, AXIAL PLUG
D-Ug-660-20	CONTROL UNIT FLAME SAFETY
D-Le 103 Cbl-S1x-Pp1-00.	
D-Lx720ua	
D-Lx100ua-P	
D-Ug-660 D-Ug 660 230a-420	
1163567	
D-R 820f	VERD¼NNERLUFT-EINSTELLVENTIL (Bild im anhang)
Mdimotorpk243	
D-Le 103 Ua-Cg	
D-LI703	
15-L-Tp12-Hd-Spi-L	
D-Le 603 Man-En	
Dbfl200lp5	PC BOARD
Dust Analyzer Wdidioder290	
D-Lx 100 Man - En	
Dle603ua95ex	SCANNER
104107	
D-Ug 660 115a-420	
1 170 408	FLAME MONITOR D-LX 200 UA-10/84EX
D-Lx 100 UI-G1/M2/0000/Pp2 (1150050)	
D-Lx 200 Ua-20/P2/0000/Pcg	
9900871	
4009429	
1114187	
Ad2h5	
17110309	
Dlx100ul94ex	FLAME SCANNER
D-Ug 660 230a-420	
Da-D703	

D-Zs 133-I	
1123403	
D-ZI Zsp-Nt	
D-Le703ig-P	
D-Lx101ua-30	
D-Lx 200 Cbl-V1c-Pcg-00	
D-Gf 150-230a 0-20 Ma	
1118362	
1150513	
1116957	
Reflector=durag D-R 290 Sp R 2	
D-Lx 100 Cbl-V1c-Pp2-00	
D-R300-40	
D-Bt 660	
D-Lx 200	
D-Le103	
D820f	
D-Le 603 Ui 94/Ex	
D-Lx100-UI	
Zx420-K8k50	
1107281	
D-Lx 100 Ua-G1/M2/0000/Pp2	Old designation: D-LX 100 UA-P Region code: G; certified for EU, EAU, USA, CAN Code: 1; confirmed for applications up to SIL3 UV compact flame detector # Security time: 1 sec. # # Analog output: 4-20 mA # Customs tariff no .: 85371098
R290npr	
D-R290	
D-R 280	DR280 Module for Opacity Meter DR280 No 202
D-Ug-660	FLAME SAFETY CONTROL UNIT 115/230VAC 42-60HZ
Dlx100uap	FLAME DETECTOR
D-Gf 150 Man-En	
Heated Window=45mm 1107281	

D-Gf 150-115a 4-20 Ma	
D-Ug 120 024d-420	
D-Le 103 Ig-Cg	
D-Le 603 Man-De	
Zdap-150 M	
Mdiheizsch42mm	
D-R 820f Sp 1124814	1124814 D-R 820F SP MOTORISIERTE VENTIL DICHTUNG
D-Lx 200 720 Man-En	
Old Reference D-Lx 100 UI/94 Ex- New Reference D-Lx 100 UI-B1/M3/94ex/Pcg (1150048)	
D-Lx 100 Cbl-S1x-Pp2-00 Connection Cable	- m. Silicone sheath and plastic cable socket, Length 1.5 m - verw. f. D-LX 100/700 Customs tariff no .: 85444290
D-R280 N01	Durag Module
D-Gf 100-20 , D-Gf 150	
Tk. D-R Sp Set 1124812	1124812 D-R SP SET INJEKTORDICHTUNGS SET
D-Gf 150 - Sold Only To End Users	
D-Lx 100 Ig-Z0/Ek/0000/Pcg	
D-Le 103 Cbl-S1x-Pp1-00 Anschlusskabel	
Dug660115a420	FLAME CONTROL
Dr-290 Spm	
D-Ug 660 230a-020	
D-Hg-400-50/2xr15	
D-Lx 720	
D-Lx100uaf-P	
D-Ug-120	
Dbhg400	MODULE
D-Lx 200 Ua-10/84ex	
1150050	
1118371	
D-R281av-No40	Durag Module
Ug-120	CONTROL UNIT

[D-Zs 033-I](#)

[D-Le 603 Uh-P](#)

[Ug-110](#)

CONTROL UNIT

[Mk2 1122516 D-FI](#)