



Dwyer

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Dwyer Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Dwyer T¼rkiye Distrib¼t¼r¼ veya temsilcisi deŐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Wwdp-2-Lcd	DIFFERENTIAL PRESSURE TRANSMITTER Type: WWDP-2-LCD Measuring ranges: 10, 20, 50,100 psid, selectable With LCD display
13-102931-00	3000MR-1KPA Photohelic 24 VDC range 0-1Kpa
CDT-5D40-CO2	CARBON DIOXIDE TRANSMITTER Range: 0 to 5000 PPM CO2 range Configuration: Duct mount No temperature output, no options
ADPS-03-2-N-C	Adjustable differential pressure switch set point range 0.20 to 2.00" w.c., (50-500Pa) M20 connection. Includes A-481 Installer kit, includes 2 plastic static pressure tips & 7' 2.1 m of PVC tubing
2000-60PA	
2300-120PA	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Zero centre range 60-0-60Pa
V6EPS-S-D-3-S-CSA	Costruction: Exp¼osion proof Body: Stainless steel Circuit (Switch): DPDT Tee Connection Size: 1" Tee Material Stainless steel ***** Option: CSA approved construction with junction box*
2000-500PA	Maghenelic GAuger Range 0-500Pa 90262080 USA
V6EPS-S-S-6-0	FLOW SWITCHES V6 FLOTECT® MINI-SIZE FLOW SWITCHES
A3000-250PA	PHOTOHELIC® PRESSURE SWITCH/GAGE Measuring range: 0 ... 250 Pa (please check, it can also be mm H2O or cm H2O)
0-60 Pascal Magnelic Normaldruck	
SFI-100MP-1-1/4	DWYER MIDWEST SIGHT FLOW INDICATOR Body style: single window, bronze body, ABS impeller Body option: 150 psig maximum pressure option, includes fluoroelastomer gaskets Body size: 1 -1/4 inch connection size Options: none
DWYER MIDWEST SIGHT FLOW	SFI-100MP-3/4 Body style: single window, bronze body, ABS impeller Body option: 150 psig maximum pressure option,

INDICATOR	includes fluoroelastomer gaskets Body size: 3/4 inch connection size Options: none
TEMPERATURE SENSOR,	Ex-Proof, 4-20 mA OUTPUT, 24 V DC SUPPLY, TEMPERATURE MEASUREMENT RANGE: -40/+80, IP>23
CFS2-DNBPN-60	R2-124816-23
A-457	R3-124 816-50 COUNTERWEIGHT
A-459	R3-124 816-52 CABLE HANGER
R6-124812-00	SPPM-24 PRG PANEL MTR
SBLT2-170M-200M	
MPCJR-484	9032896060
DXW-11-153-2	Differential pressure switch brass and fluoroelastomer wetted materials, NEMA 4X, 1/4" NPT connections, SPDT, range 10 to 25 psi.
RMA-25-SSV	Rate-Master® Polycarbonate Flowmeter Measuring range: 10....100 l/min air With stainless steel valve
2320	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGE Measuring range: -10 - 0- 10 Pa
Differential pressure gauge type Photohelic cod.	3000MR-500PA range 0÷500Pa 24 Vcc
2000-60PA-SS	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Measuring range: 0...60 Pa Option: Corrosion resistant brushed stainless steel 304 bezel
2000-100PA-SS	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Measuring range: 0...100 Pa Option: Corrosion resistant brushed stainless steel 304 bezel
MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES	Type: 2300-120PA Type: Zero centre range 60-0-60Pa
MSX-W 22	MAGNESENSE® DIFFERENTIAL PRESSURE TRANSMITTER Replacement for MS2 measuring range 2
Typ: RHP-3E44	HUMIDITY/TEMPERATURE TRANSMITTERS European style wall mount Humidity/Dew Point Output: 4-20 mA/0-5 VDC/0-10 VDC Temperature Output: 4-20 mA/0-5 VDC/0-10 VDC
RHP-3S2B	Humidity Temperature Transmitter 3% Accuracy OSA w/Sintered Filter 0 to 10V 10K @ 25°C Thermistor Type II
L6EPB-B-S-3-B	FLOTECT® LIQUID LEVEL SWITCHES Installation: Brass external float chamber (tee) Float material: Polypropylene spherical Process connection: NPT
170221-00	150-1850 ml/min
	RATE-MASTER® POLYCARBONATE FLOWMETER Measuring range: 0.5...5 l/min air With stainless steel valve

RMA-26-SSV	Temperature limit: 54°C (130°F) Pressure Limit: 100 psi (6.9 bar) Accuracy: 4% Process connection: 1/8" NPT internal thread Weight: 4 oz (113.4 gr.)
SFI-300-1-1/4	Dwyer MIDWEST SIGHT FLOW INDICATOR Double window, bronze body, ABS impeller 1-1/4" connection size
Typ: MSX-W11-PA	Wall mount Unidirectional Range 1: 1 in w.c., 250 Pa, 25 mm w.c. Pressure units: Pascal Accuracy: ±1% FSO. Stability: ±1% FSO/year. Temperature Limits: -4 to 158°F (-20 to 70°C). Pressure Limits: Ranges 2, 3 and 4: 6 psi max operation, 6 psi burst. Power Requirements: 10-36 VDC (2-wire), 17-36 Output Signals: 4-20 mA (2-wire); 0-10V or 0-5 V selectable (3-wire). Response Time: Instantaneous (default) or 3 s (selectable). Zero and Span Adjustments: Digital push-button
674-424	1.00 " wc = 1 inH2O = 249.0889 pascal = 2,490889 mbar
616KD-10	Differential Pressure Transmitter Measuring range: 0...250 Pa Accuracy: 2%
RHPX-3SDA0-00	Humidity and Temperature Transmitter Accuracy: 3 % RH RH Sensor Configuration: Duct mount with plenum plastic probe and hydrophobic filter
RMA-33-TMC	Description : Flowmeter Range: 10 to 110 CC/Min. Water with top mounted valve
Air velocity transmitter,	Type: AVUL-5DA1 Accuracy. ±(0.2 m/s + 5% of reading) @ standard conditions Output: Analog universal (0-5 VDC, 0-10 VDC, 4-20 mA) Options: none
F-44 FLOWMETER	P/N:96171
FLOTECT® MINI-SIZE FLOW SWITCHES	V6EPS-S-S-6-S-MT Body: stainless steel Tee Connection Size: 2 " High temperature option rated 400°F (205°C) (see specifications for ratings)*
Sx-Re/43ca	
1950g-20-B-24	
830-0032 Rma-13-Ssv	
(377a6888p0001)	
M2300-100 (100-0022)	
4010	
616w-0m-Lcd	
Cdt-5d44-Rly	
Act-Da07	
Da-31-153-4	
Series 477av	

475-6-Fm Mk Hand Held Digit Manometer Dual Range 0-30 Psi	
641-12	
Rmb-50d-Ssv	
004-0001 Ms-221	
Rmb-85b-Ssv 02-28.85.Ssv	
Series 4g	
Rmb-52-Ssv	
Rma-42-Ssv	
1626-5	
Series 8b	
Series Hm28	
672-3-A (840-0014) Range: 0-25 In W.C. Output: 4-20 Ma, 2-Wire	
Magnehelic-2000-500pa-Asf	
Dm-1107	
Sgx-D8022n	
Dm-2000	
810-0009	
Dwyer 668b-19-1	
Avu-3-V	
Typ: 15 Vdo	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 15 VDO Mark 1, magnetic coupling Output: Transmitter 1 k Ω Potentiometer 1/2%. 4 to 20 mA. Switch Type: 2 x SPDT, Rated: 10 A @ 125/250 VAC (~), 1/3 PS @ 125/250 VAC (~), 1/2 A @ 125 VDC (), 1/4 A @ 250 VDC (), 4 A at 125 VAC (~) (tungsten). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Rmb-84-Ssv	
Ms2-W102 (840-0014)	
Ms-321	
830-0076 Vfb-67	
Rma-33-Ssv 02-28.33.Ssv	
2000-50mm	

167-12	
Model:H2s-2	
840-0013 Afh2	
Act-Da04	
Series Sppm2	Voll vor Ort konfigurierbares 16-Bit-Farb-Touchscreen-Display
810-0007	
M2000-1.0(Ex 2000-1kpa)	
A-396a	
Act-Da11	
Cct50-202	
1950-0-2f	
Series 8c	
Series Mm	
Dm-1102	
A605c (840-0014)	
Adps-06-2-N	
Series 16c	
Da-7031-153-1	
Series Dm-1000	
Ms-121	
830-00xx Rma-7-Ssv	
Da-31-153-2	
Ms2-D102 (840-0014)	
477-0-Fm , No	
M2000-1.0	
2000-300pa	
004-0001 Adps-03-2-N-C	
Rma-1-Ssv	RMA Rate Master Flowmeter 6837
300u	
Series 2000-Sp	

1823-80	
244	
Series 2500	
Act-Da03	
Series Scd	
Series Ptgd	
Type: 3-5-A-D-0	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 3-5-A-D-0 Mark 3, multiple turns Output: Transmitter 1 k Ω Potentiometer 1/2%. 4 to 20 mA. Switch type: 1 x SPDT, nominal value: 15 A @ 125/250/480 VAC (~); 1/8 hp at 125 VAC (~), 1/4 hp at 250 VAC (~), 1/2 A at 125 VDC (), 1/4 A @ 250 VDC (). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Act-Da13	
682-8	
2001	
Cat. No: Rma 12 Ssv	
Series 16b	
Magnehelic-2000	
43300	
Dm-1112	
1823-10	
Series Pfg2	
M2300-120 Differential Pressure Gauge With Analog Display	
Dr200332	
840-0014/ 2060	
F 195 02-F195	
Rma-34-Ssv	
Modell: Bf-4	
840-0013 A-177 2ã39;X4ã39;	
Series 4000	
1638	
Memb-1950g	

626-00-Ch-P1-E5-S1	
628-00-Ch-P1-E5-S1	
Series 4b	
1910-1-Wp	
Act-Da09	
182310	
Vfa-22	
Wfa-22	
Series At22000	
840-0013 A-178 1ã39;X5ã39;	
Bb-523-3-9s	
Dah-7041-153-24e	
Gfc-1111	CONTROLLER GAS MASS FLOW 0-15LPM 12VDC
Rma-26-Ssv	
Rmb-101-Ssv	
Tmp2000	
672-2-A (840-0014) Range: 0-15 In W.C. Output: 4-20 Ma, 2-Wire	
02-475-00-Fm	
Dm-1109	
Dm-1104	
840-0013 A-179 3ã39;X3ã39;	
Hadp-Uc-06	
1823-2	
Te-Dfg-D0844-00	
Act-Da06	
350 Af Measuring Range 0-4	
Tbx1-Dn100--20/140;c-G1/2	
V6epbbs1b	
Act-Da10	
1823/2a	

Act-Da05	
Act-Da02	
At2ms Pressure Transmitter	
475-X(Xx)-Fm	
M2300-60	
S160-18pm	
1910-00 Spdt Pressure Switch Range 0.07-0.15quot;Wc (17.5-37pa)	
628cr-81-Gh-P1-E1-S1	
840-0013 A190	
Rma-22	
Pg-2010d-10778	
Rhp-3w22	
637-0	SERIES 637 ADJUSTABLE RANGE PRESSURE TRANSMITTER
890-000x 4002	
1626-1	
Da-35-2-2a	PRESSURE SWITCH 5-10AMP AT 120-240VDC
Rf1-01-00-1	TRANSMITTER EXPLOSION PROOF ULTRASONIC LEVEL
Ms 222	
840-0013 Da-7031-153-4	
V10	
BtIm312101	
840-0013 A-174	
Ms-311 / Ms2-W102 (840-0014)	
Typ: 1910 - 00, Art.-Nr.: 02-1910.00	
1950g-20-B-24-Na	
Series 4c	
840-0014 /2500	
Rmb-85d-Ssv	
Series 2000	
Dm-1110	

32-231-0s	CONTROL VALVE 3-15PSI
840-0013 477a-3	
Dm-1108	
M700 Pa 02-700.00.750	
1223 - M400-W/M	
4215-15psi	PRESSURE GAUGE DIFFERENTIAL CAPSUHELIC 0-15PSIG
182300	
250 Af Measuring Range 0-4	
Series Scd-8	
Tpl-03-300	
2000-80cm	
840-0013 A-175	
1950g-20-B-240	
1950 00-2f	
477a-4	
Type: 45 Vdo	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 45 VDO MARK 4, through shaft Output: Transmitter 1 k Ω Potentiometer 1/2%. 4 to 20 mA. Switch Type: 2 x SPDT, Rated: 10 A @ 125/250 VAC (~), 1/3 PS @ 125/250 VAC (~), 1/2 A @ 125 VDC (), 1/4 A @ 250 VDC (), 4 A at 125 VAC (~) (tungsten). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Mda-211	
Afg-2	
Catno1823	
Cdtr-5-W-4-0	
A299 (840-0014)	
840-0013 628-13-Gh-P1-E2-S1	
Series 1500	
A-605	
840-0013 2000-200mm	
1950 10-2f	
1823-1	
Dm-1105	

1227m	
100-0221	
Dm-1111	
628cr-91-Gh-P1-E4-S1	
Rpo04926	
Rma-11-Ssv	
1950 P - 2 - 2f Art.-Nr.: 02-1950.P.2	
Typ: Ms-121	
477a-5	
Model V10 Flotect	
840-0014 /2360	
Hfb-4-35	
Rhrs	
2002vs42231	VALVE 3-15PSI LIN-E-AIRE HI FLOW PNEUMATIC CONTROL
V6eps-S-D-3-S-Csa	
Series 2600	
1950g-20-B-120-Atex	
840-0013 Da-7031-153-5	
Rhp-2s11	
Series 16l	
Sgx-D7122n	
Ms-111-Lcd	
Gfm2-Air-010-A-B-A-N-B-2	
Act-Da14	
840-0013	
Series Vf	
1820-2	
Dmf-41404	DMF-41404 DMF N2 0-100 ML/MIN
Qbmb1-5 50..50pa	
F7-Sb	

Photohelic Serie 3000 Mr
Rma-171 Ssv
2000-500pa
Series 476a
840-0013 Da-7031-153-6
Series 477b
Series 16a
Series 490a
Series 8g
123-153
Rmb-84-Bv , 830-005x / Rmb-84-Ssv!!!
710-0001
Rma-21-Ssv
Series Vfi-300
Air X 100
Rhu-R004
1950-1
01-20.Skala
Dpg-107
Act-Da08
Series 16g
1950p20-B
477-000-Fm , No
100-0030
3000 Mr 02-30.00.500.Mr
1/4 Hp 240v Ac
Tmp 1823-2-Expl
Act-Da01
890-000x 4010
810-0013

Cat. No:1823-40
Series 478a
Rmb-83-Ssv
Vtt-A-N-D2
Series 8600
Series 32dz
Rma-33-Ssv
Series Vdpm
628-13-Gh-P1-E2-S1
Rma-22-Ssv
Series 32a
Dxw-11-153-4
166t(840-0014)
Rmc-107-Ssv
444124-03
840-0013 Da-7031-153-1
Dwyer 668b-08-1
Series 475
Series Sfi-100
M1430 , No
Act-Da12
004-0001 Te-Dfg-E-06-4-4-00
1950p1-B
102.5
840-0013 A-176 1ã39;X4ã39;
Dm-1103
840-0013/ V10 Ss
Aps-350
Series 2-5000
1626-10

Da-21-2-10s
1910-0
Ms2-W101
830-005x / Rmb-84-Ssv
Rma-32-Ssv
Rma-13-Ssv
Rmb-85d-Ssw
V6epb -S-D-3-S-Csa (By V6eps-S-D-3-S-Csa)
Sfi-300mp-3/4quot;