



## Easidew Dew-Point

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Easidew Dew-Point** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Easidew Dew-Point T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Easidew Tx</a>	Basic model: asidew 2-wire dew point transmitter (4-20mA output, 5/8 "UNF process thread, mini-DIN connection). Robust pressure dew point transmitter for continuous measurement in compressed air systems and process gases. + (- 100 / + 20C) Measuring range: -100 to + 20 ° C (-148 to + 68 ° F) dew point measuring range + HD Sensor protection: Standard HDPE filter (protection against fine particles (<10 µm pore size))
<a href="#">SADPmini-Ex-SR-B-4-EU-CC</a>	Intrinsically Safe Portable Dewpoint Hygrometers Sensor Type : Ultra High Capacitance Aluminium Oxide Measuring Range : -110°C to -20°C dewpoint or equivalent Units of Measurement : °C dp, °F dp, ppmv, ppbv, ppmw, g/m3, lb/MMSCF units IS Certification : ATEX II 1G Ex ia IIC T4 (Ta = -20°C to +40°C) ATEX II 1G Ex ia IIC T3 (Ta = -20°C to +50°C) Operating Temperature : -20°C to +50°C Operating Pressure : For use at atmospheric pressure (< 0.3 barg) Integral calculator to display pressure dewpoints Power Supply : Rechargeable Lithium ion battery Mains Plug : EU Type Display : Multi line display with graphics capability Sample Connections : Swagelok stainless steel compression fitting for ¼" OD tube and "fir tree" for 6mm ID sample tube.

Automatic Calibration : "AutoCal" facility for span check and adjustment. Accuracy :  $\pm 2^{\circ}\text{C}$  Dewpoint Included : 2 metres of 6mm ID PTFE. Carrying case with shoulder strap and belt loop. Operating Instruction Manual. Certificate of Test and Calibration, traceable to National/International Humidity Standards.