

Ebara



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Ebara Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ebara T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Psm42-30 Q1-Q1 V G+g	Mechanical Seal
MATRIX 5-6/1.3	
3LSF 65-160/7,5 H132 ATEX T4	
DWO 400	Stainless steel centrifugal pump with open impeller 3 ~ 230/400 V - 50 Hz - 3.0 kW - 3 Ph Mechanical seal K / K / N DNs = 2 1/2 "iG - DNd = 2" iG Housing in VA - impeller in VA open impeller with 19 mm clearance
OFRE-80920-32A-20S	BLOWER FİLTER
Spare parts kit item no. 364 5000 035	
400*250DSCA3-F1302-1480(4)185-5NS	
200DSC3 G1232-1480(4) 132-5NS+QDC	
400*250DSCA3-F1302-1480(4)185-5NS	
200DSC3 G1232-1480(4) 132-5NS+QDC	
2CDX 70/12	2-stage stainless steel centrifugal pump (1.4301) 230/400V - 50Hz - 0.90kW GLRD: K/K/N
6bhe 13-20	
0540 06 CDX 120/20	Stainless steel centrifugal pump (1.4301) 3~ 230/400V - 50Hz - 1.50kW - 3ph GLRD K/K/N DNs = 1 1/4" female - DNd = 1" female Housing in V2A - impeller in V2A
0540 36 CDXL 120/20	Centrifugal pump made of stainless steel (1.4301) 230/400V - 50Hz - 1.50kW GLRD: K/K/N
CDX 200/25	Stainless steel centrifugal pump (1.4301) 230/400V - 50Hz - 1.80kW GLRD: K/K/N
Burner head - Parts for abatement G5-A4	DCT000001, burner, final assy, 4 port

3LM 80-160/11	Stainless steel centrifugal pump EN733 (1.4401) 400/690 V - 50 Hz - 11 kW GLRD: S/S/V
Pos.1 housing	
2CDX 70/12	2-stage stainless steel centrifugal pump (1.4301) 230/400V - 50Hz - 0.90kW GLRD: K/K/N
Pos. 213 vent plug	
Pos. 107 Anello	
Pos.125 Bolt	
Pos 80 Busching	
Pos. 21 impeller	
Pos. 39 key	
K 115V kit	
Pos. 5 Asing Cover	
Pos. 111 comp Mech.Seal	
RAW WATER BOOSTER DEST	FREQUENCY CONTROLLED 1 duty + 1 enduring pump Q: 2x10 m ³ / hour H: 70 mWg WITH EXPANSION TANK AND OTHER ACCESSORIES
Soft WATER BOOSTER DEST	FREQUENCY CONTROLLED 1 task + 1 based nasos Q: 2x10 m ³ / hour H: 90 mWg WITH EXPANSION TANK AND OTHER ACCESSORIES
SUBMERSIBLE DRAIN PUMP	Q : 8m ³ /h H : 12 mWg
3LM 40-160/4,0	Stainless steel centrifugal pump EN733 (1.4401) 230/400 V - 50 Hz - 4,00 kW GLRD: S/S/V
WSP-01-02	Q =1 m ³ /h, Hp = 5 mSS,
Mechanical seal size K/K/N	
Project	
1615109804	B-FRIGEL ENGINE BACK COVER (SMALL)
3M / I 32-160/1,5	Stainless steel centrifugal pump EN733 (1.4301) 3~ 230/400V - 50Hz - 1.50kW - 3ph GLRD K/K/N DNs = 50 - DNd = 32 Casing + impeller in AISI 304
3D 40-160/3.0 Horizontal Shaft Monoblock Casting	Centrifugal Pump Pump nom.motor power: 4.0 Hp - (3.0 kW) Flow rate: 12 m ³ /hr - 42 m ³ /hr Height : 29.4 ms - 18.7 ms Electrical Connection: 230/400V/Three-phase/50Hz Speed : 2 poles (2900 rpm) Body : Cast Iron Shaft : Stainless Steel (AISI 304) Fan : Stainless Steel (AISI 304) Engine Cover: Aluminum Sealing : Mechanical Seal Packing Material : Carbon/Ceramic/NBR Inlet and Outlet Diameter: 65 mm - 40 mm (Flanged)

New Pump	Backwash pump; 2 pieces, Body material: Stainless steel AISI 316 Impeller: Stainless steel AISI 316 (VFD controlled), Working point: approx. 270 m3/h (VFD controlled) Variable Frequency Drive at 1.5 bar Drain pump; 1 piece, Body material: Stainless steel AISI 316 Propeller: Stainless steel AISI 316 (VFD controlled), Working point: approx. 300 m3/h @ 2 bars
Flange	
3LM 50-200/9,2	Stainless steel centrifugal pump EN733 (1.4404) 3~ 400/690V - 50Hz - 9.2kW - 3ph GLRD K/K/N DN = 65 - DNd = 50 Casing + impeller in AISI 304
Type:3M/I 32 - 160/2.2 IE3	Flow rate: 6-20 m3/h H: 35.5 -25m 380V A:8.2/4.7
Matrix spare parts kit	364500134
40M3-/ 3D 50-125/2,2	
3M-S32-200	224 25.1.450850 WHEEL T7042074 Ebara impeller 3M/3P
MECHANIC SEAL EBARA CD 120/07 VITON	
3M-65-160/11	pressure 2.9 kg/cm2, temperature -5+90, productivity up to 138 m3/hour2. EBARA 3M-40-160/4 pump, arbitrary pressure 3.4 kg/cm2, temperature -5+90, capacity up to 34 m3/hour
3LM4/E-80-160/15 pump	pressure 3.5 kg/cm2, temperature -5+90, capacity up to 138 m3/hour
DW VOX M 100A	
CDX / I 120/12	0540 05 Stainless steel centrifugal pump (1.4301) 3~ 230/400 V - 50 Hz - 0,90 kW - 3 Ph GLRD K/K/N DN = 11/4" iG - DNd = 1" iG Housing made of V2A - impeller made of V2A
DW200	3~400V - 50Hz - 1.50kW max. operating temp. 40°C double mechanical seal in oil reserve Includes 10 m power cable DNd = 50 horizontal outlet
Seal carrier	Pos. 4
Impeller	Pos. 2
Spare parts kit	Pos. 11 K
Wear ring item 72-73	Pos. 72-73
shaft seal	Pos.
Housing	Pos.
ball-bearing	Pos.
2CDXHS/I 70/206	220/380-460_60 SCA DWC-V/I 500/3.0 AQ1EGG
	0701 59 High-pressure centrifugal pump in GG/V2A 3~

EVMSG 3-24 F5	230/400V - 50Hz -2.2kW Casing and impeller in V2A Suction + pressure housing in GG DN _s /d = 50 - PN 25 GLRD S/S/EPDM vertical, multistage centrifugal pump with standard motor and hydraulics made of stainless steel 1.4301 Limits of use: Medium temperature: max. 140°C Operating pressure max. 25 bar Q/H range: 1.2 - 4.5 m ³ /h / 169 - 100 m Fl.S H max.: 177 m Comparison operating point: 2.4 m ³ /h - 155 m Fl.S construction Wheel: Shurricane Design Shaft seal: balanced mechanical seal in cartridge design Hydraulics: multi-stage, vertical with INLINE connections Connection dimensions Pressure port: round flange DN 25 Suction nozzle: round flange DN 25 Materials Impeller: stainless steel 1.4301 Step housing: stainless steel 1.4301 Wear ring: stainless steel 1.4301/PPS Housing: gray cast iron Seal carrier: stainless steel 1.4301 Shaft: stainless steel 1.4301 Shaft bearing: tungsten carbide Mechanical seal: SIC(G) / SIC / EPDM O-ring: EPDM Housing jacket: stainless steel 1.4301 Motor lantern: gray cast iron Tie rod: Cr steel Coupling: aluminum Base plate: aluminum Motor data: 3~230V/400V, 50Hz, 2.2 kW, 8.2/4.7 A, 2-pole, Isokl.F, IP55, IE3, with 3 PTC thermistor temperature sensors
EVMG 3 22F5	
CD-X 120/12	
FAN BLADE 3LS/132-200/5.5RK25CABQ1V66BIE3	
CDXL120/12	
Type 2CDX/E 70/10 , AISI 316L	Q (Flow) = 20 - 80 Lt/min H (Height): 38.5 - 27 m Hmax: 41m Hmin: 27 m N (Power): 1.14 / 0.75 Kw n (revolution): 2800 rpm
Type CDX/G 200/25 , AISI 316L	Q (Flow) = 80 - 250 liters/min H (Height): 36.8 - 27.2 m Hmax: 39.4m Hmin: 27.2m N (Power): 2.87 / 1.8 Kw n (revolution): 2800 rpm
EV-SA30-2	DRY PUMP
2CDXL 120/30	2-stage stainless steel centrifugal pump (1.4401) 230/400 V - 50 Hz - 2,20 kW GLRD: K/K/N
3M / I 50-200/11,0	Stainless steel centrifugal pump EN733 (1.4301) 400/690V - 50Hz - 11.0kW GLRD: K/K/N
Normal suction centrifugal pump with open impeller	Serial no. with engine 2.2 kW ; 400V; In: 4.7 A; 50Hz; 2-pole; Efficiency class IE3
DWO 150 M	0531 26 Stainless steel centrifugal pump with open impeller 1~ 230V - 50Hz - 0.55kW - 1 Ph GLRD K/K/N DN _s = 2" iG - DN _d = 2" iG Housing in VA - impeller in VA open impeller with 19 mm ball passage
362710534	No. 9
	0561 05 Stainless steel centrifugal pump EN733 (1.4301) 3~ 230/400 V - 50 Hz - 4.0 kW - 3 Ph GLRD K/K/N DN _s = 50 - DN _d = 32 Housing + impeller in AISI 304 Pump contains the

3M / I 32-200/4,0	following modification Condensate hole Drain plug condensate hole
Matrix 18-5T	230/400 V - 50 Hz - 4,00 kW GLRD: K/K/N Multistage stainless steel centrifugal pump
Pos.94	
0561 10	3M / I 40-160/3,0 Stainless steel centrifugal pump EN733 (1.4301) 230/400 V - 50 Hz - 3,00 kW GLRD: K/K/N
0561 25	3M / I 65-125/7,5 Stainless steel centrifugal pump EN733 (1.4301) 400/690 V - 50 Hz - 7,50 kW GLRD: K/K/N
0561 10	3M / I 40-160/3,0 Stainless steel centrifugal pump EN733 (1.4301) 230/400 V - 50 Hz - 3,00 kW GLRD: K/K/N
DW 150 MA	Submersible motor pump for dirty water/waste water 1~230 V - 50 Hz - 1.10 kW double mechanical seal in oil reservoir incl. 10 m power cable, Schuko plug and float switch
Housing, Pos. 1	
65DVS 51,5	
Mechanical seal for 3LM/I 40-200/7.5 i pump	
Mechanical seal for 3LM/I 40-200/11 pump	
Mechanical seal for EVMSG 15-13 pump	
1615100504e	
3lp80-160/18.5 (Ä1403180104a)	
Cdx/A 70/07	
Cmd 2.00 M	
Dw Vox 200	
Evmu18-3	
Cdxh/A 90/10	
H380v	
3m-160/4.0	
6bhe 20-21	
Evmul45-1	
Cdx/E 90/10	
3 M 40 - 200 / 11	
Dw Vox 300	

Evm.45-5
Best 3 Ma
Cfs21-8213
Cda 400t
Cdx/A 120/20
Ofre-80920-32a-20u
09-117-7
6bhe 20-18
1635250004e Block-Kreiselpumpe- Normalsaugend Baureihe Cdx - Typ Cdx 200/25
08-117-6
80dlfu67.54
Efqu-4
Evmug32
6bhe 20-12
400/Asp Dn80
Kit-3lp80-160/18.5 (#364500036)
6bhe 20-15
Dw Vox M 100 A
6bhe(L) 20-10
1545500063
6bhe 20-17
Matrixhs 3-6t6/2.2
1962020004
2cdxu200/506t2-Bw7
Ofre-80920-32a-20
3m 32-200/3,0
6bhe 20-19
2471040014e
2cdx 120-30 Pump Painting

1330900004e
6bhe 20-20
1635250004e Typ Cdx M 70/05
Dw M 75a
1330910006i
1963030004
1545500064
3lm 50-160/7,5
09-056
Cdx/90/10
1962010004
6bhe 20-16
C-Ga 3301.
C38091/3/3
251450860
1170400004
Ofre-80920-32a-20s
80 DI 51.5
654957
A3ub65
1312550004e
Ofre-80920-32a-20m
Cdm 70/05
Drsv/A80-167-15
6bhe 20-13
3 Lm 32-160/2.2
Evmug32-3-2
Kit-3lp80-160/18.5 (A364500036)
2 Cd X-120
80dl52.2

11-117-8 (Jp3000/29/145) So39
Cdx/A 120/12 Obsolete, Replaced By 1625100004g , Replaced By - 1625100004i
Cdx - Typ Cdx 200/25
230225006
Evmul64
3m 32 - 200/3
Right100
0430610
Efqt2a
09-117-6
0040365-02
Evmu18
2470340014e
Dw Vox 200 Kw
1630080016e
Evmul45
6354-20d-20s
3lp80-160/18.5kit
3lp 80
2cdx 200/40
364500028
Md/A40-200/7,5
09-055, Model: 500x400ksm71, Dwg No: Pr040133809/905, Pos No: 055, Serial Nos: R040133809-1/2
Cmr 0,75 M
6354-32d-10s
Best4
1721100021
6bhe 20-14
Dwo/E 150

[3lp80-160/18.5 \(#1403180104a\)](#)