

Eckardt



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Eckardt Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Eckardt Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Srd991-Bpns7eaany-V07	Weight: 1.900 KG Harmonize number: 9032.89 ECCN: EAR99 Country of Origin: France Lead Time (ARO): 3 Weeks SRD991 FUNCTION: Intelligent Positioner SRD991 certified Ex ia/ Intrinsically Safe or not with advanced diagnostics to operate pneumatic valve actuators. Input Signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION Fieldbus H1 according to FISCO B VERSION: Single Acting P INPUT/COMMUNICATION: PROFIBUS-PA (according to FISCO) N ADDITIONAL INPUTS/OUTPUTS: Prepared for Additional in-/outputs S BUILT-IN LIMIT SWITCH: Without 7 CABLE ENTRY: M20 x 1.5 with one plastic Cable Gland EAA ELECTRICAL CERTIFICATION: II 2 G Ex ia IIC T6 Gb according to ATEX / IECEx N ATTACHMENT KIT: Order as auxiliary Y MANIFOLD: Pneumatic connection 1/4 - 18 NPT made of an additional manifold V07 OPTIONAL MODEL SUFFIX(ES) INCLUDED: LCD w/Menu-Language in English / German / Turkish
21.1206.00 - E1.63-540°/2xZ6/SO	021-10540 Operating pressure: max. 100 bar Torque: 335 Nm at 100 bar Rotation angle: 540 ° + max. 2 ° tolerance Stepless adjustment of the zero position Swallowing volume: 0.762 ccm / 1 ° Output shaft: with a key DIN 6885 Pressure connections: G1 / 4 " Temperature range: -25 ° C to + 70 ° C Additional equipment: - Z6 - 2x switching element, inductive Special: - Proximity switches switch 8.5 ° before the end position - without guide shaft - Radial forces on the output shaft are not permitted Drawing no. / Index: 021120600 Customs tariff no .: 84122989 17.96 kg
21.960.02 - SM4.63-100°(90°)/2xZ6.2/SO	Hydraulic swivel motor Operating pressure: max. 250 bar Torque: 735 Nm at 250 bar Rotation angle: 100 ° ± 0.5 ° set Stepless adjustment of the zero position Swallowing volume: 0.669 ccm / 1 ° Output shaft: with feather keys DIN 6885 Pressure connections: G3 / 8 " Temperature range: -25 ° C to + 70 ° C Additional equipment: - Z6.2 - 2x switching element, prepared Special: - Key position 100 ° before

	normal position - without proximity switch M12x1 Drawing no. / Index: 02196002 Customs tariff no .: 84122989 12.01 kg
SRD991-BDFS6EA4NR-V07	Intelligent Positioner (Intrinsically Safe) Weight: 1.910 KG Harmonize number: 9032.89 ECCN: EAR99 Country of Origin: France PSS Reference: EVE0105E SRD991 FUNCTION: Intelligent Positioner SRD991 certified Ex ia/ Intrinsically Safe or not with advanced diagnostics to operate pneumatic valve actuators. Input Signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION Fieldbus H1 according to FISCO B VERSION: Single Acting D INPUT/COMMUNICATION: Intelligent without Communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position Feedback 4-20 mA and one Binary Output S BUILT-IN LIMIT SWITCH: Without 6 CABLE ENTRY: 1/2-14 NPT (with adapter(s) M20 x 1.5 To 1/2-14 NPT) EA4 ELECTRICAL CERTIFICATION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N ATTACHMENT KIT: Order as auxiliary R MANIFOLD: Pneumatic connection G 1/4 V07 OPTIONAL MODEL SUFFIX(ES) INCLUDED: LCD w/Menu-Language in English / German / Turkish
EW426550063	Electronic SRD991 Digital 4-20mA (ATEX T4) Weight: 0.300 KG Harmonize number: 90330000 Country of Origin: France EW426550063 FUNCTION: Electronic SRD991 Digital 4-20mA (ATEX T4) Electronic SRD991 Digital 4-20mA (ATEX T4) with LCD Rev.3.7.x
INTELLIGENT POSITIONER,	P/N: SRD960-BHQDSN7EDZNG, SUPPLY: max 6/90 bar/psi, Output: 4..20 mA HART, ATEX 2G EEx d IIB/IIC T4/T6
SRD991-BDFT6EA4NY-V07	SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO B DESIGN: single-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position feedback 4-20 mA and a binary output T LIMIT SWITCH BUILT-IN: Inductive Limit Switch - Intrinsic Safe (Standard Version SJ2-N) 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) EA4 EXPLOSION PROTECTION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N MOUNTING KIT: Order as accessory Y CONNECTION STRIP AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection block V07 OPTION(S) INCLUDED IN THE PRICE: LCD menu navigation English / German / Turkish
SRD991-BDNS6EA4NY-V07	SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO B VERSION: single-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) N ADDITIONAL INPUTS/OUTPUTS: Prepared for additional inputs/outputs S LIMIT SWITCH BUILT-IN: without 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) EA4 EXPLOSION PROTECTION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N MOUNTING KIT: Order as accessory Y CONNECTION BLOCK AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection block V07 OPTION(S) INCLUDED IN THE PRICE:

SRD991-CDFV6EA4NY-V07	LCD menu navigation English / German / Turkish SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO C DESIGN: double-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position feedback 4-20 mA and a binary output V LIMIT SWITCH BUILT-IN: Mechanical switches (micro switches) / UL and CS approved 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) ZZZ EXPLOSION PROTECTION: without N MOUNTING KIT: Order as accessory Y CONNECTION STRIP AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection strip V07 OPTION(S) INCLUDED IN THE PRICE: LCD menu navigation English / German / Turkish
SRI986-BIDF7EAANA	
Srd991-Cpns1eaanr-V01	
Membrane Pt700	
Srd991	
Sri 986-Bids2eaana	
Srd991bhfs1ea4ny-1v01	
9926-1001	PNEUMATIC CONTINUOUS-LINE RECORDER
Bpns1zzzny-Iv01	
Srd991-Bdqs7ea4ny-V01	Single; 4-20mA Pozisioner
Pr630b3a1dc3	PNEUMATIC CONTINUOUS LINE RECORDER 24VDC
W-04202	
Srd991-Bdns6faany-V02	PNEUMATIC VALVE POSITIONER SINGLE ACTING 4-20MA
Sri986-Bids7eaana 0/4-20ma	
061039035	Flowserve Positioner With Feedback Card
Lex-G	
Srp981-Bidms1na	
Sri986-Bids7eaana Analog Positioner	
Nsm1-40-180	
Sri 986-Bids7eaana	
Srd991-Bpfs7eaany-V06	
Srd991-Bpfs1eaany-V01	
424-264011	PNEUMATIC POSITIONER

6713	
Srp981bidms1na	
V740dfvna (Ex.6-713-442)	
Srd991- Bdfs7ea4ny-V07 Intelligent Positioner	
Srd991 Bhns7ea4nr	
Augd1e100f	
Ew411406091	
Sri990-Bims7eaa-Y	
Sri986-Bids7eaana	
Ad-A9	
6232-630	PNEUMATIC CONTINUOUS LINE RECORDER
Lexg-Jn	PNEUMATIC POSITIONER