

## Eckardt



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Eckardt** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Eckardt Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Srd991-Bpns7eaany-V07</a>	Weight: 1.900 KG Harmonize number: 9032.89 ECCN: EAR99 Country of Origin: France Lead Time (ARO): 3 Weeks SRD991 FUNCTION: Intelligent Positioner SRD991 certified Ex ia/ Intrinsically Safe or not with advanced diagnostics to operate pneumatic valve actuators. Input Signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION Fieldbus H1 according to FISCO B VERSION: Single Acting P INPUT/COMMUNICATION: PROFIBUS-PA (according to FISCO) N ADDITIONAL INPUTS/OUTPUTS: Prepared for Additional in-/outputs S BUILT-IN LIMIT SWITCH: Without 7 CABLE ENTRY: M20 x 1.5 with one plastic Cable Gland EAA ELECTRICAL CERTIFICATION: II 2 G Ex ia IIC T6 Gb according to ATEX / IECEx N ATTACHMENT KIT: Order as auxiliary Y MANIFOLD: Pneumatic connection 1/4 - 18 NPT made of an additional manifold V07 OPTIONAL MODEL SUFFIX(ES) INCLUDED: LCD w/Menu-Language in English / German / Turkish
<a href="#">21.1206.00 - E1.63-540°/2xZ6/SO</a>	021-10540 Operating pressure: max. 100 bar Torque: 335 Nm at 100 bar Rotation angle: 540 ° + max. 2 ° tolerance Stepless adjustment of the zero position Swallowing volume: 0.762 ccm / 1 ° Output shaft: with a key DIN 6885 Pressure connections: G1 / 4 " Temperature range: -25 ° C to + 70 ° C Additional equipment: - Z6 - 2x switching element, inductive Special: - Proximity switches switch 8.5 ° before the end position - without guide shaft - Radial forces on the output shaft are not permitted Drawing no. / Index: 021120600 Customs tariff no .: 84122989 17.96 kg
<a href="#">21.960.02 - SM4.63-100°(90°)/2xZ6.2/SO</a>	Hydraulic swivel motor Operating pressure: max. 250 bar Torque: 735 Nm at 250 bar Rotation angle: 100 ° ± 0.5 ° set Stepless adjustment of the zero position Swallowing volume: 0.669 ccm / 1 ° Output shaft: with feather keys DIN 6885 Pressure connections: G3 / 8 " Temperature range: -25 ° C to + 70 ° C Additional equipment: - Z6.2 - 2x switching element, prepared Special: - Key position 100 ° before

	normal position - without proximity switch M12x1 Drawing no. / Index: 02196002 Customs tariff no .: 84122989 12.01 kg
<a href="#">SRD991-BDFS6EA4NR-V07</a>	Intelligent Positioner (Intrinsically Safe) Weight: 1.910 KG Harmonize number: 9032.89 ECCN: EAR99 Country of Origin: France PSS Reference: EVE0105E SRD991 FUNCTION: Intelligent Positioner SRD991 certified Ex ia/ Intrinsically Safe or not with advanced diagnostics to operate pneumatic valve actuators. Input Signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION Fieldbus H1 according to FISCO B VERSION: Single Acting D INPUT/COMMUNICATION: Intelligent without Communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position Feedback 4-20 mA and one Binary Output S BUILT-IN LIMIT SWITCH: Without 6 CABLE ENTRY: 1/2-14 NPT (with adapter(s) M20 x 1.5 To 1/2-14 NPT) EA4 ELECTRICAL CERTIFICATION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N ATTACHMENT KIT: Order as auxiliary R MANIFOLD: Pneumatic connection G 1/4 V07 OPTIONAL MODEL SUFFIX(ES) INCLUDED: LCD w/Menu-Language in English / German / Turkish
<a href="#">EW426550063</a>	Electronic SRD991 Digital 4-20mA (ATEX T4) Weight: 0.300 KG Harmonize number: 90330000 Country of Origin: France EW426550063 FUNCTION: Electronic SRD991 Digital 4-20mA (ATEX T4) Electronic SRD991 Digital 4-20mA (ATEX T4) with LCD Rev.3.7.x
<a href="#">INTELLIGENT POSITIONER,</a>	P/N: SRD960-BHQDSN7EDZNG, SUPPLY: max 6/90 bar/psi, Output: 4..20 mA HART, ATEX 2G EEx d IIB/IIC T4/T6
<a href="#">SRD991-BDFT6EA4NY-V07</a>	SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO B DESIGN: single-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position feedback 4-20 mA and a binary output T LIMIT SWITCH BUILT-IN: Inductive Limit Switch - Intrinsic Safe (Standard Version SJ2-N) 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) EA4 EXPLOSION PROTECTION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N MOUNTING KIT: Order as accessory Y CONNECTION STRIP AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection block V07 OPTION(S) INCLUDED IN THE PRICE: LCD menu navigation English / German / Turkish
<a href="#">SRD991-BDNS6EA4NY-V07</a>	SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO B VERSION: single-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) N ADDITIONAL INPUTS/OUTPUTS: Prepared for additional inputs/outputs S LIMIT SWITCH BUILT-IN: without 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) EA4 EXPLOSION PROTECTION: II 2 G Ex ia IIC T4 Gb according to ATEX / IECEx N MOUNTING KIT: Order as accessory Y CONNECTION BLOCK AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection block V07 OPTION(S) INCLUDED IN THE PRICE:

<a href="#">SRD991-CDFV6EA4NY-V07</a>	LCD menu navigation English / German / Turkish SRD991 FUNCTION: Intelligent positioner SRD991 for controlling pneumatic actuators. Input signal 4-20 mA / HART / PROFIBUS-PA / FOUNDATION field bus H1 according to FISCO C DESIGN: double-acting D INPUT/COMMUNICATION: Intelligent without communication (4 - 20 mA) F ADDITIONAL INPUTS/OUTPUTS: Position feedback 4-20 mA and a binary output V LIMIT SWITCH BUILT-IN: Mechanical switches (micro switches) / UL and CS approved 6 CABLE ENTRY: 1/2-14 NPT (with adapter) M20 x 1.5 to 1/2-14 NPT) ZZZ EXPLOSION PROTECTION: without N MOUNTING KIT: Order as accessory Y CONNECTION STRIP AND POWER AMPLIFIER: Pneumatic connection 1/4 - 18 NPT realized by additional connection strip V07 OPTION(S) INCLUDED IN THE PRICE: LCD menu navigation English / German / Turkish
<a href="#">SRI986-BIDF7EAANA</a>	Electro-Pneumatic Positioner SRI986-BIDF7EAANA SRI986 FUNCTION: For Attachment To Final Control Signal For Operation Of Pneumatic Valve Actuators With 0/4 To 20 mA Signal B VERSION: Single Acting I INPUT: Signal Range 0/4 - 20 mA D MODE OF ACTION: Standard Version - Increasing Input Increases Output F BUILT-IN LIMIT SWITCH/POSITION TRANSMITTER: Position Transmitter 4-20 mA 7 CABLE ENTRY: M20x1.5 With One Plastic Cable Gland, Color Gray EAA ELECTRICAL CERTIFICATION: II 2 G EEx ia IIC T6 According To ATEX N ATTACHMENT KIT: Order As Auxiliary A MANIFOLD: Order As Auxiliary
<a href="#">Srd991-Cpns1eaanr-V01</a>	
<a href="#">Membrane Pt700</a>	
<a href="#">Srd991</a>	
<a href="#">Sri_986-Bids2eaana</a>	
<a href="#">Srd991bhfs1ea4ny-1v01</a>	
<a href="#">9926-1001</a>	PNEUMATIC CONTINUOUS-LINE RECORDER
<a href="#">Bpns1zzzny-Iv01</a>	
<a href="#">Srd991-Bdqs7ea4ny-V01</a>	Single; 4-20mA Pozisioner
<a href="#">Pr630b3a1dc3</a>	PNEUMATIC CONTINUOUS LINE RECORDER 24VDC
<a href="#">W-04202</a>	
<a href="#">Srd991-Bdns6faany-V02</a>	PNEUMATIC VALVE POSITIONER SINGLE ACTING 4-20MA
<a href="#">Sri986-Bids7eaana_0/4-20ma</a>	
<a href="#">061039035</a>	Flowserve Positioner With Feedback Card
<a href="#">Lex-G</a>	
<a href="#">Srp981-Bidms1na</a>	
<a href="#">Sri986-Bids7eaana Analog Positioner</a>	

<a href="#">Nsm1-40-180</a>	
<a href="#">Sri_986-Bids7eaana</a>	
<a href="#">Srd991-Bpfs7eaany-V06</a>	
<a href="#">Srd991-Bpfs1eaany-V01</a>	
<a href="#">424-264011</a>	PNEUMATIC POSITIONER
<a href="#">6713</a>	
<a href="#">Srp981bidms1na</a>	
<a href="#">V740dfvna (Ex.6-713-442)</a>	
<a href="#">Srd991- Bdfs7ea4ny-V07 Intelligent Positioner</a>	
<a href="#">Srd991 Bhns7ea4nr</a>	
<a href="#">Augd1e100f</a>	
<a href="#">Ew411406091</a>	
<a href="#">Sri990-Bims7eaa-Y</a>	
<a href="#">Sri986-Bids7eaana</a>	
<a href="#">Ad-A9</a>	
<a href="#">6232-630</a>	PNEUMATIC CONTINUOUS LINE RECORDER
<a href="#">Lexg-Jn</a>	PNEUMATIC POSITIONER