

Econosto



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Econosto Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Econosto Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunulmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
ECON Figur 7249-PN40-DN50	Ball valve, 2-part. Housing, full passage, Flanges according to EN1092-1 form B1 Fire safe according to API 607 6th Ed./ EN-ISO 10497 (2010) Anti-static design, shaft seal TA-Luft 2002 / VDI2440 Housing: cast steel GP240GH (1.0619) Ball: stainless steel 1.4308 Shift shaft: stainless steel 1.4301 Seat rings: PTFE (TFM1600) Shaft sealing: primary O-ring Viton, secondary graphite packing Housing seal: spiral seal SS316 / PTFE / graphite Overall length: EN558-1 row 27 (150 mm) Operation: hand lever made of stainless steel
13278896	ECON Ball valve fig. 7442 stainless steel/RPTFE full bore Class 600 1/2"BSP DN 15 Stainless Steel BSP thread
11815440	Globe valve fig. 251A bronze internal thread BSP 3/4" DN 20 Bronze BSP thread
11815438	Globe valve fig. 251A bronze internal thread BSP 1/2" DN15
13288293	ECON Bellows sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN32 (Econosto item #:-----) DN 32 nodular cast iron/stainless steel Flanged
13288291	ECON Bellows sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN20 (Econosto item #: -----) DN 20 nodular cast iron/stainless steel
13288276	ECON Bellows sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN125 (Econosto item #: -----) DN 125 nodular cast iron/stainless steel
11813012	ECON Wafer check valve fig 2644 stainless steel/metal PN40 DN20 DN 20 Stainless Steel
12712504	ECON Y-filter fig. 1019 cast iron/stainless steel 0,25mm PN16 DN80, Flanged DN 80 nodular cast iron/stainless steel
12712502	ECON Y-filter fig. 1019 cast iron/stainless steel I 0,25mm PN16 DN65, Flanged DN 65 nodular cast iron/stainless steel

13278900	ECON Ball valve fig. 7442 stainless steel/RPTFE full bore Class 600 1 1/2"BSP DN 40 Stainless Steel BSP thread
13278902	ECON Ball valve fig. 7442 stainless steel/RPTFE full bore Class 600 2 1/2"BSP DN 65 Stainless Steel BSP thread
11811978	SPIRAX SARCO Thermodynamic steam trap , Steel , fig1062EType: , horizontal ,Flanged DN20 DN 20 max 32bar T032F nodular cast iron/stainless steel high capacity
082	
084	
09-022 G1/2	
10 12081612 Aandr EL55 IP657	
1002550 DN 20	
1002550 DN 25	
1002550 DN 32	
1032151 OD = 595 -600 MM	
105/420P015ASBT01	
108371-01125	
1096X	
11033218	
11034523	
11110712	
11256343	
11256344	
116212	
11811957	
11815001	
11815003	
1188N	
119799	
12063835	
12103787	
121370	

121376
12256408
12465624
12560465
13278940
13278946
13278950
13383564
13410297
13418669
13494928
135
13517285
13524746
136282
14015950
14031726
1590 FDC H=1440MM
1607 NPT 3/4"
1865
1901
2020-06-29
208908
2480 AISI316L
252147
263LK
272653
286708
3 BTA 20
3 BTA 40
349472

356170
357214 / EC055820080EA0C
4620*
492839(Fig. 573)
522858
522860
613606
640364
643205(Fig.1590FD)
6730
675707
675717
687980/ 1590FD - DN25
71**
726BR
80136604
87S0040
907
908
96240, 410-440 MM
96261 28-34mm
AISI316L
ANSI B 16.5, PCD 11-1/2"
DN 200/ANSI 150
DN 3/4", OR-31
DN100
DN200 PN16 FIGURE 5720 WAFER
DN50
DN80
E6v2

EC001000025HAJ2
EC001000065JAJ2
EC002750025BB13D
EC005240080CF20-WP
EC006752JOEE2B5
EC0119001251000D
EC012700050LO93
EC0160703/4E711E
EC01646CBBCCA21C 364536
EC018500008AF08
EC068210065CBBC
EC073430025SP4D
EC0764403/4RPWD
EC0775203/4LM12G 609350
EC4001D0000BDDB
EC796110000WV0NF
ECO96000150BAHO
EG40
EP05-0AAB11-FiG7901
EP15 - 5CAC11 - FiG.7901
EP30-5DAD61-FiG7901
EP40-5EAE11-FiG7901
EP40-5EAE61-FiG7901
EP60-5GAG61-FiG.7901
FIG 9930
FIG. 1031H 1"
FIG. 1054LA 1/2"
FIG. 822 1/2"
FIG.1191
FIG.8217
FIG.831 - DN 1.1/4"

FIGURE 4620 DN200 PN16	
FIRE FIGHTING 902 - DN50,PN16, 1.5"-50X66MM	
Fig. 275	
fig.7642 (DN50)	
HVBA40A201AF4M600AA1	
Item 3 BTA-20	
JC1"715LITSSK	
JC3"715LITSSK	
JC4"715LITSSK	
K0020NI05	
kat-a1544	
KV6-2	
KV6-5	
REF NO: EC055140060AE10	
REF NO: EC055140076AE10	
REF NO: EC055140088AE10	
S.N8145A Model 125G	
S6-3	
TD42LA	
VH730 NI	
VXS 25 M MS	
VXS 60M VA	
5721LUG/NBR-PN16 DN125	with locking lever Butterfly valve, wafer type, PN16 suitable for mounting between flanges to DIN PN10/16 Body: Nodular cast iron GGG40 Liner: NBR (vulcanised, max 80°C) Disc: Alubronze CuAl10Fe5Ni5-C Shaft: 1.4122 (min. 17% Cr.) Face to face: EN558-1 Series 20 with ratchet lever of cast iron
5721LUG/NBR-PN16 DN150	with locking lever Butterfly valve, wafer type, PN16 suitable for mounting between flanges to DIN PN10/16 Body: Nodular cast iron GGG40 Liner: NBR (vulcanised, max 80°C) Disc: Alubronze CuAl10Fe5Ni5-C Shaft: 1.4122 (min. 17% Cr.) Face to face: EN558-1 Series 20 with ratchet lever of cast iron
	ECON Figure 8937, 4-10 bar, special version for warm applications +20°C ...+200°C * Pressure reducing valve,

8937 1/2"-PN16	spring loaded, with BSPP female threaded ends Piston-controlled, pressure-relieved single piston valve, pressure gauge connection for outlet pressure: G1/4" Maximum inlet pressure: 16 bar outlet pressure range: 4 - 10 bar* Body: stainless steel 1.4408 Seals: PTFE/EPDM/FEPM (+20°C... +200°C)** * also available outlet pressure range: 2-5 bar same price ** other available seal material (same price): PTFE/EPDM (-20°C +150°C) ----- Item 001 - please check the fitting offered, its specification is insufficient
5723LUG/NBR-PN16 DN125	with worm gear ECON Fig. 5723LUG/NBR-PN16 Butterfly valve, wafer type, PN16 suitable for mounting between flanges to DIN PN10/16 Body: Nodular cast iron GGG40 Liner: NBR (vulcanised, max 80°C) Disc: Alubronze CuAl10Fe5Ni5-C Shaft: 1.4122 (min. 17% Cr.) Face to face: EN558-1 Series 20 with gear box of cast iron ECON Figure 4023-AB150N/Handwheel BR125
5723LUG/NBR-PN16 DN150	with worm gear ECON Fig. 5723LUG/NBR-PN16 Butterfly valve, wafer type, PN16 suitable for mounting between flanges to DIN PN10/16 Body: Nodular cast iron GGG40 Liner: NBR (vulcanised, max 80°C) Disc: Alubronze CuAl10Fe5Ni5-C Shaft: 1.4122 (min. 17% Cr.) Face to face: EN558-1 Series 20 with gear box of cast iron ECON Figure 4023-AB150N/Handwheel BR125
8937 1.1/4"-PN16	ECON Figure 8937, 4-10 bar, special version for warm applications +20°C ...+200°C * Pressure reducing valve, spring loaded, with BSPP female threaded ends Piston-controlled, pressure-relieved single piston valve, pressure gauge connection for outlet pressure: G1/4" Maximum inlet pressure: 16 bar outlet pressure range: 4 - 10 bar* Body: stainless steel 1.4408 Seals: PTFE/EPDM/FEPM (+20°C... +200°C)** * also available outlet pressure range: 2-5 bar same price ** other available seal material (same price): PTFE/EPDM (-20°C +150°C) ----- Item 001 - please check the fitting offered, its specification is insufficient
ECON 6831/NBR-PN16-DN125 - EPDM-seatring	suitable for mounting on flanges to DIN PN 10/16 Body: A536-65-45-12 (EN-GJS-400-15) Polyester coated ca. 250 µm Seating: EPDM (vulcanised on support ring,max.) Disc: Stainless steel A351 CF8M (~1.4408) Shaft: AISI 410 (1.4006 - 13%Cr) Face to face: EN558-1 Series 20 Actuator: notched lever of cast iron
Fig. 1908 (8 - 4 bar)	DN50
EC004320080NA23E	Bellows valve FIG 432 DN80 PN16 nodular cast iron Bellows valve DN80 PN16, body/cover: ductile iron ENJS1020, Spindle: 1.4021, bellows: 1.4571, cone: 1.4021, Design as a fixed cone, cover seal: stainless steel/graphite, Actuation: handwheel, connection: flange form B1, overall length 310mm per EN558-1
EC4630D0125LBAC	barrier class Spherical/stainless steel/NBR DpIFI DN125 PN16
EC4630D0100LBAC	barrier class Spherical/stainless steel/NBR DpIFI DN100 PN16
EC4630D0065LBAC	barrier class Spherical/stainless steel/NBR DpIFI DN65 PN16

EC4630D0050LBAC	barrier class Spherical/stainless steel/NBR DpIFI DN50 PN16
ECON Figure 100/248-DN40	Pos. 001 – alternativ zur Ausführung in Stahlguß ECON Figure 100/248-DN40 with mechanical actuated quick closing cylinder Quick closing valve, angle pattern, bellow sealed, with flanges acc. EN1092-1 Facing Form B Body and bonnet: Nodular cast iron GJS-400-18-LT (0.7043) Trim: stainless steel 13% Cr (X15Cr13/1.4024) Stem sealing: O-Ring FPM (Viton) Cylinder: Brass Spring: spring steel Retainer block: Brass Handwheel: steel
DN50 PN40 FIG.7752 SS/SS/PTFE	
EP17-5DAC11-FIG7901	DN25 PN40 TWO PIECE FLANGE STAINLESS BALL VALVE (ECONOSTO BRAND MIN:-10°C MAX: 200°C)
EP25-5DAD11-FIG7901	DN40 PN40 TWO PIECE FLANGE STAINLESS BALL VALVE (ECONOSTO BRAND MIN:-10°C MAX: 200°C)
EC0744201/2RRBDN	Ball valve 7442 stainless steel Class 600 NPS1/2 BSP
ECON@ bellows valve Type: 432 nodular iron/	/stainless steel 13288291 Solid cone Straight PN16 DN20
SPIRAX SARCO Thermodynamic condensate drain	11811976 Fig. 1062 series TD32F stainless steel Max. pressure difference: 32 bar high capacity PN40 DN15
SPIRAX SARCO Thermodynamic condensate drain	11811973 1062 TD32FA series stainless steel max. pressure difference 32 bar high capacity automatic vent PN40 DN15
SPIRAX SARCO Thermodynamic condensate drain	11811974 Fig. 1062 TD32FLC series stainless steel max. pressure difference 32 bar low capacity PN40 DN15
SPIRAX SARCO Thermodynamic condensate drain	1062 TD32FALC series stainless steel max. pressure difference 32 bar low capacity automatic air vent PN40 DN15 11811975
EC026440015RRB6	Including check valve 2644 stainless steel/met. PN40DN15
ECON@ bellows valve Type: 432 nodular iron/stainle	13288290 Solid cone Straight PN16 DN15
SS Ball Valve, 3 inches, Butt Weld	7646
EC0010600004000	
fig 241	
fig 275	
EC009500001AADE	
fig 1607	
fig 2630	
fig 1602	
fig 517	

fig_2630	ECON Bellow sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN50 (Econosto item #: 676157) Cast iron, nodular/SS
Globe valve	
Globe valve	ECON Bellow sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN20 (Econosto item #: 748746) Cast iron, nodular/SS
Globe valve	ECON Bellow sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN20 (Econosto item #: 748746) Cast iron, nodular/SS
Ball Float Steam Traps	SPIRAX SARCO TBall Float Steam Traps , Steel , fig.2933 cast iron , Type:FT43 , horizontal ,Flanged DN32 (Econosto item #: 128311) Cast iron
Non Return Valve	ECON Wafer check valve fig 2644 stainless steel/metal PN40 DN32 (Econosto item #: 127835) Stainless Steel
Globe Valve	ECON Bellow sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN15 Cast iron, nodular/SS Flanged
Globe Valve	ECON Bellow sealed valve fig. 432 nodular cast iron/stainless steel fixed disc PN16 DN20
Steam Trap flowter	SPIRAX SARCO flowter steam trap FT46-14 , horizontal ,Flanged DN15 PN16
Non Return Valve	Wafer type check valve Type: 2644 Stainless steel Wafer PN40
Vana Glob DN100- Fig 268	
Vana Glob DN80- Fig. 268	
VXS25 MVA	
Fig, 7955	
Fig, 79025	
Econ Figure 1607 ? Pn80	
Ec005170100aabb-Wp (1,8 Bar)	
7902-Eda0040-F05-Dsq14	Pneumatic actuator, double acting, 41Nm @ 6 bar Connection F05-double square SQ14
Ec005170100aabb-Wp (2 Bar)	
Bta-20 Power Block Item 3	
Fig. 5723/Nbr Dn80 Pn16	Butterfly valve GGG40/NBR/AIBr Wafer type EC5720D0080ABAB EC040230000AN0N EC4023X0000A0C1
Fig, 268	
Goetze606gf-1ep	

Fig, 201	
Fph-Tb012-F10s/10n-B/Vp/10	
Ec0095003/4aaca	
Eha20-Double Acting Valve(For Cargo Hyd Actuator) Dn150,6quot;	
Fig, 31040	
48,3 Fp	
Dn 1/2quot;, Or-31	
Fig, 21180	
Jis-20k-40	
Fig, 31118	
Fig, 7971	
Article No. Ec0047601/2am35, Order Code: 118378	
7901-Esr1200-S14-F14 / F10-Dsq36	Pneumatic actuator, single acting, spring to close Connection F14 / F10 or F12 with double square SQ36
Epdm 80/16 1 - L=130mm	
Bta-40 Power Block Item 3	
Fig, 276	
Kompaktflansch-Kugelhahnvoller Durchgang Dn32 Pn40 1.4408edelstahl Zwischenflanschwafer Type 60 Mm	
Fig, 418	
Please See Attached Document	
Fig, 31065	
Fig.831 - Dn 1/2quot;	
Ec082170025ac0f	
Figure 1270lm-Lk-Dn50	ECON Figure 1270LM-LK-DN50 DN50-PN16 EC012700050LO93 Globe valve of Aluminium, straight pattern, SDNR-type with loose disc with flanges as per DIN-PN10/16
Econ Fig.907-32x44mm Pn16	
Cl600 102 Bar Econ7442	
Fig. 4622/Nbr Dn250 Pn10	Butterfly valve GGG40/NBR/AIBr Flanged EC4620D0250MCAB EC4002E0000YEJA

119864	
Fig.831 - Dn 1.1/4quot;	
Ec002640040mbh3	
Ec000830040eb3k	
Fig. 861m 1/4" Pn125	Pressure gauge valve with union nut Brass Thread EC0086101/4RABL
Fig, 79015	
Econ Fig. 7901-Sr0080-F07 / F05-Dsq17	Pos. 002 - alternative to EP20-5DAD61-FiG7901-F07 / F05- DSQ17-FIG7901 (EP20 no longer available)
Ec015900715hr0a	
Ec017500002bbync	
Fig, 9130	
Eha-40 Complete Hydraulic Actuator	
Dn 3/4quot;, Or-31	
Basınç D¼Ő¼r¼c¼ Valf - 30 Bar - 7 Bar Und D 16 / 1,5	
Fig, 2577	
Fig, 2876	
Fig, 1271	
Bhg-200	
El-55	24VDC M20 IP65 Amp 1.9 S/N: 320425005 Sea water inlet valve actuator
Fig, 9419	
Deltaflex 3222/Ss Red	
Pn40 Dn150 L:480 1.0619 Gate Valf	
Ec026280024b000	
Eme 215 Ex-Proof	
Fig. 4622/Nbr Dn300 Pn10	Butterfly valve GGG40/NBR/AIBr Flanged EC4620D0300MCAB EC4002E0000YEJA
Fig, 1520	
Fig, 9133	
Fig, 7912	
Fig, 21186	

E6 Fig 9930lug	
Fig. 1010 5/4?	
Ec005170100aagc-Wp (3 Bar)	
Fig. 70 Gy Dn150 Pn16	Check valve cast iron GG25/NBR Flanged EC000700150GN3LD
Econ Figure 1607 - Pn50	
Dn 25	
Fig, 21172	
Rohr Kaplin Dn32 Edelstahl Fp	
Fig, 79612	
Type: 1602	ERIKS item #: 12439121 - Econosto item #: 613606 ECON Ball valve fig. 1602 brass/PTFE PN30 1.1/4"BSP female thread
Fig.292-Dn250 Pn10	
Fig, 3419	
Fig, 1898	
Ec079610000rh0n	
Fig, 31098	
Fig. 1031h 1quot;	
Fig, 277	
Fig, 9131	
Fig, 398	
B00901738	
Fig, 2877	
33,7 Fp	
Bta-40 Roller Item 6	
Econ Globe Valve 241	Please see attached Doc.
Fig, 9530	
Dn25xdn25-Gunmetal	
Fig, 31175	
Econ 518 Safety Valve (0,25 Mpa)	
Fig, 1270	
Fig. 275 Lk Dn40 Pn16	SDNR valve Bronze Flanged EC002750040BL13D

Econ Fig. 7901-Sr0300-F10 / F07-Dsq22	alternative to EP35-5EAE61-FiG7901-F10 / F07-DSQ22 (EP35 no longer available) Pneumatic actuator, single acting, spring to close ECON Fig. 7901-SR0300-F10 / F07-DSQ22 (higher torque, therefore noticeably larger than EP35)
Fig, 21184	
Fig. 1085 5/4quot;	
?48,3 Fp	Muss zertifiziert und feuerfest sein
Eha-20 Complete Hydraulic Actuator	
Fig, 254	
Fig, 1417	
Hydr. Actuator Eha-20 Complete Max Valve Shaft Square 16mm Rotation 90 Working Pressure 100bar Test	
Fig, 21177	
Econ-Hp	
Fig, 2641	
Fig. 1054la 1/2quot;	
Ec009500001aada	
En 1092-1/Pn16;24 Vdc Dn15	
Fig, 524	
Fig, 31080	
Fig, 3417	
Fig, 6417	
Rohr Kaplin Dn25 Edelstahl Fp	
Dn 600 620x675x4,5mm	
Ec002920250gda2	
Econ Figure 925	
Fig, 1272	
Hydr. Actuator Eha-40 Complete Max Valve Shaft Square 24mm Rotation: 90 Working Press. 100bar Test P	
Fig, 523	
Econ Thermostatic Steam Trap 2982	Please see attached Doc.

Rohr Kaplin Dn40 Edelstahl Fp	
Fig.226- Dn 1/4quot;, 6000 Psi	
Fig, 417	
Fig. 1383-Ng63-1,0 /+0,6 Bar	Bourdon tube pressure gauge G1/4" stainless steel Thread EC01382322A5120 +surface mounting bracket
Dn80 Pn16 Glob Valvr	
Econ 518 Safety Valve (0,7 Mpa)	
Kugelhahnvoller Durchgang Dn32 Pn40 1.4408edelstahl Flansche Nach En1092- 1 130 Mm Handhebel	
Eha20-D	
Ec002410080gah3	
Fig, 79611	
Fig, 7972	
Fig. 275 Lk Dn25 Pn16	SDNR valve Bronze Flanged EC002750025BL13D
Ec950 Gg-25 Dn25 Pn10	Please see attached document
Dn200 Pn16 Figure 5720 Wafer	
Fig, 9830	
1.4571	THERMOMETER 250 GRAD
Dn 200/Ansi 150	
7901-Esr1200-S14-F12-Dsq36	Pneumatic actuator, single acting, spring to close Connection F14 / F10 or F12 with double square SQ36
Fig. 1019mesh 1 Mm Dn25 Pn16	Y-straine cast iron GG25 Flanged EC010190025G115
Figure 4620 Dn200 Pn16	
Eha40-D	
Fig, 21182	
Fig. 4622/Nbr Dn200 Pn10	Butterfly valve GGG40/NBR/AIBr Flanged EC4620D0200MCAB EC4002E0000WDGA
Ec018500008bb5b	
Fig, 3041	
Fig, 31075	
Ec005120200aabb-Wp	
Econflex Dn80- Pn 16 L = 130mm	Expansion Joint DN80 Please see attached Photo

Fig, 399	
Dn25xdn25-Bronze	
Fig, 7961	
Fig, 7907	
Fig, 211	
Fig, 2578	
Fig, 269	
Fig 8217f Dn25	
Fig, 2878	
Fig, 1202	
Fig, 3495	
Fig, 31135	
Type:1590	ERIKS item #: 12712185 - Econosto item #: 643148 ECON Sight gauge device fig. 1590 steel/viton/borosilicate reflex body height 1065mm 3/4"BSPP
Fig. 1383-Ng63-1,0 /+5,0 Bar G1/4"	Bourdon tube pressure gauge G1/4" stainless steel Thread EC01383352A
Fig, 248	
Fig.1191 Type A Flange	
Fig, 31115	
Fig, 2576	
Fig, 7902	
Fire Fighting 902 - Dn50,Pn16, 1.5~39;~39;-50x66mm	
Fig.8217	
Eha10-Single Acting Valve(For Balast Hyd Actuator) Dn150,6quot;	
Fig. 822 1/2?	
Fig, 241	
Goetze606gf-1dp	
?33,7 Fp	Muss zertifiziert und feuerfest sein
Fig, 275	

Goetze606gf-1cp (3-10 Bar)	
Econ Fig 70gy-Dn125-Pn16	Max. Differential pressure 4 bar Check valve with flanges to DIN Housing: EN-JL1040 (GG25) Flap: 1.0531 (steel) Seal: NBR Overall length: 170 mm
Fig, 247	
Fig. 4622/Nbr Dn150 Pn16	Butterfly valve GGG40/NBR/AIBr Flanged EC4620D0150LCAB EC4002E0000WDEA
Fig, 9533	
Fig, 242	
Fig, 21170	
Ec005740020cz15r	
Bta-20 Roller Item 6	
Fig.695-3/4quot;	
Egpi-3/8quot;X30	
Fig, 6419	
Fig, 7901	