



EL-O-Matic

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **EL-O-Matic** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız EL-O-Matic T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
21702	ECON electric drive OPEN / CLOSE type 907EXD type ELA80 220-230V AC, connection F07, VK14mm, with manual override, running time 16 sec., IP67, 90 ° angle of rotation, 2 way limit switches as potential-free contacts for feedback, electrical connection 2 x M25 x1.5, Ambient temperature: -20 ° C to + 60 ° C, II 2G Ex db IIB T4 Gb, II 2D Ex tb IIIC T135 ° C Assembly kit, bridge galvanized steel, incl. Assembly and functional test Ebro intermediate flange cap Z011-A DN 100, Housing GG25, disc: 1.4408, sleeve: EPDM black
FD0025.NM00CWALT.NL11SNA.00XX	the EL-O-MATIC F series, ISO F03/F05, double-acting, 90° closing in the Clockwise, square drive 11mm Parallel, with double stroke limitation Adjustment range open position 80° to 95° - closed position 10° to - 5°, Standard temperature version -20°C to +80°C.
FS0350.NU40CWALT.NL27SNA.00XX	drive the EL-O-MATIC F series, (UNC thread), single acting, spring set 40, 90° rotation clockwise / spring closing, Square drive 27mm DIN, Standard temperature version -20°C - 80°C
FS0200.NM40CWALT.0000SNA.00XX	10313 drive the EL-O-MATIC F series, ISO F07/F10, single-acting, spring set 40, 90° closing clockwise / spring closing, prepared for insert, with double Stroke limitation, setting range open Position 80° to 95° - closed position 10° to - 5°, standard temperature version - 20°C to +80°C
14368	Insert for drive size 150/200/350/600, Square 22mm
11041	Centering plate F10, F150/200/350, PCD.102 on PCD.70
13288	FS0012.NM20CWALTN.D09SNA.00XX Drive the EL-O-MATIC F series, ISO F04, single-acting, spring set 20, 90° closing clockwise / spring closing,

	Square mount 9mm diagonal according to DIN, Standard temperature version -20°C to +80°C.
FD0200.NM00CWALL.YD22SNA.00XX Drive	the EL-O-MATIC F series, DIN F10, double-acting, 90° closing in the Clockwise, square drive 22mm diagonal, with double stroke limitation: Adjustment range open position 80° to 95° - closed position 10° to - 5°, Standard temperature version -20°C to +80°C.
FS0200.NM50CWALL.YD22SNA.00XX Drive	the EL-O-MATIC F series, DIN, F10, single-acting, spring set 50, 90° closing clockwise / spring closing, Square mount 22mm diagonal, with double stroke limitation, adjustment range open position 80° to 95° - closed position 10° to - 5°, Standard temperature version -20°C to +80°C.
Wear part set consisting of all	Seals, bearings and guide bands for ED/ES 200, (repair kit) -20°/+80°C, - 4°F/+176°F (VA001-454-31) (902.90.541)
16058	POSIFLEX positioner electro/pneumatic 4-20 mA TYPE F 20 IP 65, M20x1.5, (368.000.164) Position feedback 4-20mA type PTF20 for POSIFLEX positioner 2 microswitches V3, type S 2, for POSIFLEX positioner F 10/20, (368.90.232)
11712	2 pieces micro switch V3, type S2, for POSIFLEX positioner F 10/20, Cable entry M20x1.5, according to data sheet D 6.204, VA368.90.232.
17303	FD0200.NM00CWALTN.L22SNA.00XX actuator of the EL-O-MATIC F series, ISO, F07/F10, double-acting, 90° closing in clockwise direction, square socket 22mm parallel, with double stroke limitation, adjustment range open position 80° to 95° - closed position 10° to - 5°, standard temperature version -20°C - 80°C.
Es0200.U1a04a.22k0	PNEUMATIC ACTUATOR E200 SPRING RETURN SINGLE
Vana 200 Dn / Liner Tire For Vana 200 Dn	
Pd2500.D1b00a.00no	
Ef20/Eex	POSIFLEX F20 EPOXY COATED ALUMINIUM
Ps2500.D0a14a.00n / El-O-Matic - P-Serie / Pneumatische Zahnstangenantriebe	
Es06004	ACTUATOR
Eda100	DOUBLE ACTING