



Elaflex

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Elaflex** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Elaflex T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
ERV-R 800.10 VSRV	Elaflex - Rotring - rubber expansion joints type ERV-R Design according to catalog page 407/408 complete with steel flanges that can be rotated on both sides, galvanized and passivated with a thick layer. Connection dimensions according to DIN PN10, length 250mm. Incl a screwed vacuum support ring made of 1.4571 (VSRV)
HD 38 C LT	30 meters low temperature execution
HD 50 C NEON	20 + 30 meters
HD 63 C NEON	30+30+30+33,5 meters
HD 75 C LT	30+40 meters low temperature execution
KG00062 / CORE COVER VB 80 ALU	
TU00013 / HANDLE TENSIONING RING TWM 50	
ERV-GS 250.16	
ERV-OR 65.25	
Certificate for pressure test	according to EN 10204-3.1 for ERV DN 65 PB 25 bar / TP 40 bar
10281000	Rubber compensator DN 65 ERV-R 65x160 SAE 3 1/2 PN10/16, EPDM, overall length: 160 red ring
ERV-R 200x160.16	

ELAFON Plus ERV-R 65x160 SAE 3 1/2"	5 METERS Elaflex Rotring compensator with SAE flange
Rotring rubber compensator ERV-R 100.16	electrical conductive, length 130 mm flanges galvanized steel, rotatable, Inner rubber: Butyl/EPDM, pressure carrier: PA textile cord, outer rubber: EPDM, ozone-proof, Operating temperature: -40° to +100°C (depending on media), marking: Red ring, ERV DN., PN., date of manufacture, suitable for: Drinking, industrial and cooling water, weak acids and alkalis, Salt solutions, technical, alcohols etc. Approval: DVGW W270, ACS, FDA compliant, For more Information about the operating conditions and more Versions such as PTFE lining, different lengths, support rings and external bracing, please request or inquire about data sheets. Our article number: 1020100100
Rotring rubber compensator ERV-R 50.16	electrical conductive, length 130 mm flanges galvanized steel, rotatable, Inner rubber: Butyl/EPDM, pressure carrier: PA textile cord, outer rubber: EPDM, ozone-proof, Operating temperature: -40° to +100°C (depending on media), marking: Red ring, ERV DN., PN., date of manufacture, suitable for: Drinking, process and cooling water, weak acids and alkalis
93011862	ERV-CR 200.10 Rubber compensator
ERV-CR 80.ASA 150	
ERV-R 65x160.SAE 3½"	
Rubber Compensator	(DN50, PN16, BL150) – ERV-R 50x150.16
PN 16	
ERV-R 500.10 DN500 PN10	14410742
COMPENSATOR DN500 PN10 L=320	TAS
Ew - H 68/75	
Ew - H 52/55	
Vc 63 C	
Spannloc For Item (1) Amp; (2) Above	
Vkx 50.80	
Erv-R 250x175.10	
Vkx 75.80	
Erv-G80.16 Zs	
Tg-21q-Bm-10 Ha	
Ew - H 95/100	
Eg173-6608617	
Vkx 100	
Vk80	
Dn50 – Erv-Gr 50.16 Vsd	
Avkc 38	
Mkc 100.100	
"gelbring" Hd 50 C Hochdruck-Tankwagenschlauch	
14120218	

14120224
Vkx 40.50
X1 Snap Ring, Pn-Eu 231
<!DOCTYPE Html> <html Lang="en"> <head> <!-- Meta --> <meta Charset="utf-8"> <meta Http-
Vkc 75.80 Ss (42301)
Vcx 100.100
14120221
Vcx 38.50
Ew - Sk 5
Ev187-6608617
Dn150 - Erv 150.10/16 Green
Avkx 38
Vkc 80.80
41032
Vk 80 Ai
Dn50 X 130 Nbr(2)
Ef265-6608372
Zva2 1.0
Vkc 75
49999
Avkc 75
Vkc 50.50 Ss (42924)
42293
Spannfix Sx 75
Vcx 38
Erv-G80
Avkc 25
14120215
Vkc 50 Ss
Avkc 32
Zvf40
Tw 100
Rvx 25 Ss
Erv-G80x160.16
Mkx 38

42510 Schauglas
Evr-G125.16
Ef162-6608373
Vkc 38
Erv-G150.16
Mkc 50
41076 / Uts 50 Universalschlauch
Rmc 50 Ss
Ed237-6608377
Eu226-6608378
Ew - Kh 500
Mkx 50.50
X1 Seal, Pn-Eu 226
Vd 20/9,5
Mkx 75 Al
Amkc 25
Vk80-2 1/2
Ew - K 80 St
(Tw 80)
42350 Tw- Mutterkupplung
Vlx 50.50
Zv19.40
Rvc 32 Ss
Vk80 3?
Vlx 63.80
Mkc 75
Mkc 75 Ss
Erv-G100-16
Erv-4 100x150 14126608
Amkc 38
Vk80 2 Å189;?
49999 (Rotex 125.16)
Vlx 32.50
K 200 Din
14410718

X1 Seal_Pn-Ed 237
Vkc 100.100
Mkx 50.80
Mkx 100.100 Ss
Vk80 Tw
Amkx 32
Vhd 63
Vkx 63
Ew - Gh 90/155
Amkc 32
Rmx 50 Ss
Erv-Cr-50.16
Rvc 50 Ss
43573 Zapfschlauch
Rmc 63 Ss
Ew - K 80 Ms
Vkx 50
K 300 Din
Vkc 63
Mkc 75 Al
Vkc 100 Al
Avkc 100
Avkx 100
Ew - H 80/90
Ew - Gh 60/90
Tw 75 1 X 4 Mtr.
K 360 Din
Avkx 50
Erv-G 80.16 Zs
Er127.1
Erv-G100.16gelb
Avkx 63
Mkc 63.80
Zv 204 Pl Mkf
Mkx 38.50
electrically conductive, length 130 mm, flanges galvanized steel,

Yellow ring rubber compensator ERV-G 80.16	rotatable, Inner rubber: NBR (nitrile), pressure carrier: PA textile cord, outer rubber: chloroprene CR, Operating temperature: -20° to +90°C (depending on the media), marking: Yellow ring, ERV DN., PN., Date of manufacture, Suitable for: Mineral oil products, fuel-ethanol mixtures, town and natural gas etc., "no LPG" Approval: DVGW, For further information on the operating conditions and other designs such as PTFE lining, Different lengths, support rings and external bracing please Request or inquire about data sheets. Our article number: 1020110080
Vkc 100.100ss With Clamps	
Avkx 25	
Rvc 38 Ss	
Vkc 63.80	
Dn50 X 130 Nbr	
41075 / Uts 38 Universalschlauch	
Mkc 80.80)	
Mkc 32.50	
Mkx 63.80	
Sms 25-1quot;	
Smc 25-1quot;	
Dn125 - Erv 125.10/16 Green Zs2;	
Mkc 50.80	
Mkx 100 L	
Vkc 75.80	
Evr-G100.16	
Vvx 75 Al	
Eo171-6608370	
Ec231-6608379	
Vvx 75	
Xtw 100	
Vvx 100.100 Ss	
Mkc 100.100 Ss	
Rmx 75 Ss	
"gelbring" Tw 63 Tankwagenschlauch	
Avkx 75	
Dn65 - Erv65.16gr¼n	
Rvx 50 Ss	
Mkc 75.80 Ss (42298)	
Rvx 63 Ss	
Avkc 50	

[Transition Piece Mk 80 \(Brass\) + Barrel Nipple
3 Quot;\(Stainless Steel\) + Coupling Storz B-
3quot; \(Aluminum\)](#)

[Avkx 32](#)

[Vlx 75 Ai](#)

[Vc75-N-3quot; Npt-Ss](#)

[Ew - Kh 1000](#)

[Rvx 38 Ss](#)

[Vlx 50.50 Ss](#)

[Vkc 50](#)

[Svs 32-1½188;Quot;](#)

[Amkx 25](#)

[Ew - H 120/130](#)

[Vkc 75 Al](#)

[Zvf 40.1 1 1/2quot; Ag](#)

[Vkc 100](#)

[Svs 25-1quot;](#)

[Svs 13-Å189;Quot;](#)

[Rmc 75 Ss](#)

[Svc 38-1½189;Quot; Npt](#)

[Mkx 50](#)

[43881 Vaterteil-H¼lsenverschraubung](#)

[Dn200 - Erv 200.10](#)

[Zva 2 Gr 3](#)

[Mkc 50.50](#)

[Svs 19-¥;Quot;](#)

[Mkx 100.100](#)

[Mkc 38.50](#)

[Eo177-6608369](#)

[Vkc 50.50](#)

[Rvc 63 Ss](#)

[Mkx 32.50](#)

[Mkx 75.80](#)

[Smc 32-1½188;Quot;](#)

[Amkx 50](#)

[Vkc 50.80](#)

[Svc 50-2quot; Npt](#)

Mkx 75
Erv-Cr-700.10
4"x150 Coupling
Mkc 38
"orangering" Lpg 32 Tankwagen- Fl¼ssiggasschlauch
Rvc 25 Ss
Mkc 50.50 Ss (42297)
Smc 50-2quot;
Vkx 100 Al
41038 Tw 50
Sms 13-189;Quot;
Erv-Gs 300 X 200 . 16
Zva 25
"gelbring" Hd 63 Hochdruck-Tankwagenschlauch
40122770
Ew - K 100 Ms
Vkc 38.50
Erv-G125.16
Vkx 75.80 Ss
Vkc 75 Ss
Svc 75-3quot; Npt
Rmx 63 Ss
Svc 25-1quot; Npt
Erv-G 80.16
Rvc 75 Ss
Ew - K 50 Ms
Vkx 75 Ss
Sms 32-188;Quot;
Mkx 40.50
Ssb 25
Avkc 63
Ef196-6608617
Mkc 100 L
Vkc 32.50
Erv-Gr¼nring;

Erv-G65.16 Zs
Rvx 75 Ss
Amkx 38
Vkc 100.100 Ss
Eb114+eb115-6608617
Ew - K 50 St
Tw 75
Erv-Gr 80.16; Nominal Width Dn80
Vkx 50 Ss
Eg118-6608617
Sms 19-¥;Quot;
Rvx 32 Ss
Svc 32-1ã188;Quot; Npt
24988/003 Spannloc Clamp