



## Elb Fllstandsgeraete

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Elb Fllstandsgeraete**  
Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Elb Fllstandsgeraete Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">TK-312-B-0001</a>	4102-3-0001 Evaluation device (R / I converter) TK-312 Housing: B / plug-in terminal (screwable) Input: resistance transmitter Output: 4... 20 mA Supply voltage: 24... 230V AC / DC
<a href="#">T-200-F-G2"-PE52-PE-V-0</a>	T-200-F level detector for overfill protection Approval no .: Z-65.11-404 Type: T-200-F-G2 "-PE52-PE-V-0 Measuring principle: magnetic immersion probe Thread: G2 "externally adjustable Float type: 1 x PE52 Connection: polyester can LF: 500 mm Note: We recommend for the respective application a contact protection circuit to be provided.
<a href="#">T-202-VA 1A 60W/VA 250V</a>	113CM
<a href="#">TK30015794B</a>	5410-3-0031 Level sensor TK-300PE Type: TK300-PE-A2"10-870-10-M Connection: PE head 90 mm, red cover included PVDF cable gland Material: pipe and screw connection made of PE Float type: PE52 Electronics: TK-100 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 870 mm Measuring length: 730 mm Resolution: 10mm
<a href="#">T-200-PE</a>	Type: TK308-PE-A1"-11-PO-400-10-M Material: PE Connection: polyester junction box A1" with PE plate AD 150 mm, 15 mm

<a href="#">5410-3-0098</a>	thick, 2x6.5mm hole on bolt circle 130mm, 180 degrees offset with PVDF cable gland Float type: PE78 Electronics: TK-101 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 400 mm Resolution: 10mm Protection class: IP65
<a href="#">5410-3-0099</a>	Type: TK308-PE-A1"-11-PO-700-10-M Material: PE Connection: polyester junction box A1" with PE plate AD 150 mm, 15 mm thick, 2x6.5mm hole on bolt circle 130mm, 180 degrees offset with PVDF cable gland Float type: PE78 Electronics: TK-101 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 700 mm Resolution: 10mm Protection class: IP65
<a href="#">T200PEA2"PE</a>	
<a href="#">Tk-302-Rva-Vva-A 1 1/2"-0-Va44-Po-R = 1,425 Mm-10 Mm Resolution</a>	Statistical commodity number: 90261089 Country of origin: Germany / Hesse