



E.L.B. Fllstandsgeraete

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

E.L.B. Fllstandsgeraete Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız E.L.B. Fllstandsgeraete Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
T202-Va-A11/2"-2x-09-Po	Magnetic immersion probe T202-VA Type: T202-VA-A11 / 2 "- 2x-09-PO Material: stainless steel 1.4571 Connection. G1 1/2 "outside, PO box Float type: 2x VA44 Pipe length: 1,150 mm K1 = 120 mm NC above K2 = lowest point NC below Note: We recommend for the respective application to provide a contact protection circuit.
ER-104-B-2-0-1-6	Electrode relay ER-104 Housing type: B / plug-in terminal (screwable) Output: 2 changeover contacts Sensitivity: 2...30 khm / 2...300 khm Switching delay: 0.5 sec. fixed Supply: 230V AC
ER-104-B-2-0-1-0	Electrode relay ER-104 Housing type: B / plug-in terminal (screwable) Output: 2 changeover contacts Sensitivity: 2...30 khm / 2...300 khm Switching delay: 0.5 sec. fixed Supply: 24VDC
T200f2"v0pe	Leveler T-200-F-G2 "-PE 52-PE-V-0-PE connection housing, LF = 450 mm / "Z-65.11-404" with PVDF cable gland We recommend for the respective application a contact protection
Tk30015794b	Level transmitter TK-300-RPE PU-A2,0 "-PE52-R = 870 mm, active Measuring length 730 mm, resolution 10 mm, PE head black diameter 90 mm, cover red with PVDF cable gland with built-in R / I converter TK-100, output 4..20 mA Connection voltage 11-35 V DC Dimensions see sketch !!