

Elomatic



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Elomatic Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Elomatic T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Fd0065.Nm00cwals.Yd14sna.00	Drive the EL-O-MATIC F series, DIN, F05, double acting, 90 ° clockwise rotation, Square mount 14mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
11629	POSIFLEX positioner electro / pneumatic 4-20 mA TYPE F 20 IP 65, M20x1.5 according to Data sheet D3.301.2 (VA368.00.164), incl. Cable gland.
11708	Position feedback 4-20mA, type PTF20, for POSIFLEX positioner F 10/20, as Plug-in module for F20 circuit board, according to Data sheet D6.202.1
FD0065.NM00CWALS.YD14SNA.00	Drive the EL-O-MATIC F series, DIN, F05, double-acting, 90 ° turn clockwise, Square adapter 14mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
FD0150	
FD0350.NM00CWALL.YD22SNA.00XX	drive the EL-O-MATIC F series, DIN, F10, double acting, 90 ° rotation in Clockwise, square socket 22mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 95 ° - closed position 10 ° to - 5 °,

	standard temperature version - 20 ° C to + 80 ° C.
FD1600.NM00CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, double acting, 90 ° rotation in Clockwise, square socket 46mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 93 ° - closed position 10 ° to - 3 °, standard temperature version - 20 ° C to + 80 ° C
FD2500.NM00CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, double acting, 90 ° rotation in Clockwise, square socket 46mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 93 ° - closed position 10 ° to - 3 °. Standard temperature version - 20 ° C to + 80 ° C
FS0100.NM50CWALL.YD17SNA.00XX	drive the EL-O-MATIC F series, DIN, F07, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 17mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C Country of origin: Malaysia Customs tariff number: 84123900
FS0200.NM50CWALL.YD22SNA.00XX	drive the EL-O-MATIC F series, DIN, F10, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 22mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
FS0600.NM50CWALL.YD27SNA.00XX	drive the EL-O-MATIC F series, DIN, F12, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 27mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C.
FS0950/ 50	
FS0950.NM50CWALL.YD36SNA.00XX	drive the EL-O-MATIC F series, DIN, (drilling pattern F14), single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square socket 36mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C
S1600.NM50CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, (drilling pattern F16), single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 46mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.
FS2500.NM50CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 46mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.

FS4000.NM50CWALL.YQ55SNA.00XX	drive the EL-O-MATIC F series, DIN, drilling pattern F25, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square socket 55mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.
ED 0100-M2A00A	
ED 0200-M2A00A	
ES 0200-M2A04A	
ED 0350-M2A00A	
FS0200.NM40CCALT.NL22SNA.00XX	17354 Drive of the EL-O-MATIC F series, ISO, F10/F07, single acting, spring set 40, 90° rotation counterclockwise / spring opening, Square mount 22mm parallel, with double stroke limitation adjustment range open position 80° to 95° - closed position 10° to - 5°, Standard temperature version - 20°C - 80°C.
POSIFLEX F10 11630	pneumatic positioner POSIFLEX F10, IP65; 0.2 - 1 bar (3-15psi); air connection G1/4", for 90° rotation (368.00.014) country of origin: Germany Customs tariff number: 90328100
FS0200.NM40CCALT.NL22SNA.00XX	18848 Drive of the EL-O-MATIC F series, ISO, F10/F07, single acting, spring set 40, 90° rotation counterclockwise / spring opening, Square mount 22mm parallel, with double stroke limitation: adjustment range open position 80° to 95° - closed position 10° to - 5°, standard temperature version - 20°C - 80°C incl. display
pneumatic positioner POSIFLEX F10	IP65; 0.2 - 1 bar (3-15psi); air connection G1/4", for 90° rotation (368.00.014) incl. PU tubing on bridge (stainless steel) according to VDI / VDE 3845, pitch circle 80 x 30mm, Height 45mm, for pneumatic drives EL-OMATIC, sizes E/F25 to E/F350, incl. mounting screws.
11629	POSIFLEX positioner electro/pneumatic 4-20 mA TYPE F 20 IP 65, M20x1.5 acc Data sheet D3.301.2 (VA368.00.164), incl. cable gland.
13269	Wear parts set consisting of all Seals, bearings and guide bands for ED/ES100, (repair kit) -20°/+80°C, - 4°F/+176°F (VA902.90.531) (VA001-454-25)
992.14.103 B	
750.73.053. 200 Va Transformer	
Pd2500.D1b00a.00n0	
992 14 103b	
Ef-H3bpl-25-Ed25-M	
Fs0600.Nm50cwalt.0000hna.00xx	
Typ: F 20 Ip 65 Art.No. Va368.00.164	

Ed25	
Ed0025m1a00a00n Group-2 Only Actuator	
Fs0350m60cwallt0000sna00	
368 00 164	
Ed0200.D1a00a.22no	
Fs0350.Nm30cwall.Yd22hna.00xx	
Fd0040.Nm00cwals.Yd14sna.00xx	
750 73 053	
Es0024m1a04a00n0 , Fs0025m40cwallyd11sna00	
F 20	
Type:Es0024m1a04a00n0 , Fs0025m40cwallyd11sna00	
Rb2c-190/60	
F20 368.00.164	
EI 1600 380 -415v 50/60 Hz,	
EI-200 380-415v/ 50 Hz	
Typ: Ptf20 Art.No. Va368.92.100	
368.90.011	
Es0200.Mia05a.00n , By Fs0200.Nm50cwall.Yd22sna.00xx	
Va001-454-43	
Va836.00.620	
Es0025.Mia05a.00n0 , By Fs0025.Nm50cwall.Yd11sna.00xx	
11712	2 pieces micro switch V3, type S2, for POSIFLEX positioner F 10/20, Cable entry M20x1.5, according to data sheet D 6.204, VA368.90.232.
Type: Es0025.M1a05a	
Fs0025m50cwallyd11sna00	
750.73.053	
Gasket For Type: Es0025.M1a05a , Fs0025m50cwallyd11sna00	

E350	
Ed1600.H1a00a.00n0	
368.00.014	
79000811	CONTROL CARD
Va368.00.014	
Vaed1600.D1a00a.46n0	
Ed25 A	
9136950003	
Ed0040.M1a00a.00n0 Replaced By Fd0040.Nm00cwals.Yd14sna.00xx	
36928-2 Selector Switch(Local/Off/Remote)	
Ed0040.M1a00a.00n0 267226079 /11	
Ed0200.D1a00a.17no	
El 200	
Fs0350.Nm30ccalt.NI27hna.00xx	
10156 Type Fs0025.Nm50cwall.Yd11sna.00xx	
Fs0600.Nm30ccalt.0000hna.00xx	
Fs0600.Nm30cwall.Yd27hna.00xx	
Ed0950	
368 00 014	
Ec7960x000001d0	
9139170001	
13181 Type Fd0040.Nm00cwals.Yd14sna.00xx	
Doppeltwirkender Pneumatik-Antrieb, Fabrik: El-O-Matic, Typ: Ed 950, Funktion: Code: "a"	
Ed950	
Ed25/A	
E0100	
Fs0350.Nm50cwall.Yd22sna.00xx	

750.73.053.
EI526
EI55
Type: F0100m - Old Name, New Name - Fs0100.Nm50cwall.Yd17sna.00xx
EI 1600
Dc-Ed-15-304 Butterfly Valve 3" With Pneumatic Actuator
Es0350.M1a05a.00n0 / By Fs0350.Nm50cwall.Yd22sna.00xx
Doppeltwirkender Pneumatik-Antrieb, Fabrik: El-O-Matic, Typ: Ed 950, Funktion: Code: Quot;Aquot;
Fs0600.Nm30ccall.Yd27hna.00xx
368.00.110,Obsolete,Replacement By Va368.00.164
Ed100
510/Tspn0237.1
Elf20
Ed0025.D1a00a.11no
Vaps2500.D0d14a.00n0
Es0200.M1a05a.00n0 , Fs0200.Nm50cwall.Yd22sna.00xx
11629 (Typ F 20 Ip 65)
750.73.053 B Transformer
Fs0200.Nm50cwall.Yd22sna.00xx
Ed0100 ACTUATOR
E20100.M1a05a.00no /F8
Fs0350.Nm30ccall.Yd22hna.00xx
368.00.164 Type F20
Es600
Ed 100
530/Ldn Is2
510/Tspn0257

[Es 950](#)

[Elomatic-Ed0100d1a00a017n1-Type-Ed-100-Replaced-By-Fd0100m00cwallyd17sna00-Hochtemperatur-Ausf3;Hrung-20;C--120;C-Istanbul-Turkiye](#)

[368.00.164 Posiflex Positioner, Electro/Pneumatic](#)

[368.92.100](#)

[368.00.164 Typ F 20 Ip 65 D3.301.2](#)

[368.90.232](#)