



## Empaquetaduras Gh

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Empaquetaduras Gh** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Empaquetaduras Gh Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">M-10357</a>	SEAL 290X330X18
<a href="#">M-10358</a>	SEAL FOR ROTARY SHAFT; SPECIAL TYPE; MATERIAL: MILL RIGHT N NITRILE SHAFT DIAMETER: 90 MM; HOUSING DIAMETER: 115 MM; THICKNESS: 13 MM SHORE HARDNESS: 80 A; FLUIDS: ISO HM32 OIL TEMPERATURE RANGE: -30 TO 100°C; MAXIMUM PRESSURE: 0.03 MPA MANUFACTURING STANDARD: ISO 6194 / DIN 3760
<a href="#">M-10377</a>	SEAL FOR ROTARY SHAFT; SPECIAL TYPE; MATERIAL: MILL RIGHT N NITRILE SHAFT DIAMETER: 140 MM; HOUSING DIAMETER: 170 MM; THICKNESS: 14MM; SHORE HARDNESS: 80 A; FLUIDS: ISO HM32 OIL; TEMPERATURE RANGE: 0 TO 80?; MAXIMUM PRESSURE: 0.03 MPA; MANUFACTURING STANDARD: ISO 6194 / DIN 3760; SEAL 140X170X14MM 80A 0.03 MPA
<a href="#">M-10387</a>	SEAL FOR ROTARY SHAFT; SPECIAL TYPE; MATERIAL: MILL RIGHT N NITRILE SHAFT DIAMETER: 240 MM; HOUSING DIAMETER: 280 MM THICKNESS: 19 MM; SHORE HARDNESS: 80 A; FLUIDS: ISO HM32 OIL TEMPERATURE RANGE: -15 TO 170?; MAXIMUM PRESSURE: 0.03 MPA MANUFACTURING STANDARD: ISO 6194 / DIN 3760
<a href="#">O-3393-57 V75 G</a>	O-RING

<a href="#">O-344-31 V90 G</a>	O-RING MODEL G35
<a href="#">O-744-31 V90 G</a>	O-RING MODEL G75
<a href="#">O-944-31 V90 G</a>	O-RING MODEL G95
<a href="#">O-Ring 169.5 Mm</a>	O-RING
<a href="#">O-Ring 294.5 Mm</a>	O-RINGS; INNER DIAMETER: 294.5MM; EXTERIOR DIAMETER: 311.3MM; GROSOR: 8.4MM; MATERIAL: NBR; SHORE HARDNESS: 90
<a href="#">O-Ring 299.3 Mm</a>	O-RING; INTERNAL DIAMETER: 299.3 MM; OUTSIDE DIAMETER: 310.7 MM; THICKNESS: 5.7MM; MATERIAL: NBR; SHORE HARDNESS: 90
<a href="#">O-Ring 359.5 Mm</a>	O-RING; INTERNAL DIAMETER: 359.5 MM; OUTSIDE DIAMETER: 376.3 MM; THICKNESS: 8.4MM; MATERIAL: NBR; SHORE HARDNESS: 90
<a href="#">O-Ring 94.6 Mm</a>	O-RING; INTERNAL DIAMETER: 94.6 MM; OUTSIDE DIAMETER: 106 MM; THICKNESS: 5. 7MM; MATERIAL: NBR; SHORE HARDNESS: 90
<a href="#">R10107-044.644.844</a>	SELLO