



## Erhardt + Leimer

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Erhardt + Leimer** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Erhardt + Leimer T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">STD 018-70</a>	Shielded cable 6 x A 0.14 3 m long, with 1 angle coupling and 1 JST connector IP 40 Net weight approx. 0.200 kg. Country of Origin: Germany (DE) HS 85444993
<a href="#">FX 4200</a>	00363593 Edge sensor ultrasonic, digital, Measuring range +/- 3 mm, according to dimension sheet 158320 with microprocessor, software Dat.Prot. 1.0 + 2.0, LED display scale with membrane keyboard, M16 connector for operating voltage 24 V DC and CAN bus, protection class IP 54, clear width 124 mm, fork depth 52 mm Net weight approx. 0.932 kg. FX 4100 has been replaced by FX 4200. Country of Origin: Germany (DE) HS 90318020
<a href="#">Motor + encoder + gear system is required</a>	
<a href="#">00327361 - VS 3536 -12</a>	
<a href="#">00323892 - RK 4004 controller card</a>	
<a href="#">VG 2021 PIVOTING ROLLER</a>	
<a href="#">00100776-PD 2335</a>	Load cell 1,50kN
<a href="#">FX4631</a>	Software ZC3510-8002F_ZG01 352101
<a href="#">00835595</a>	Load cell 0.15kN 00835595-PD 2525
<a href="#">TYP: SE4051</a>	Typ: DC 5501
<a href="#">00457279-PD 2125</a>	Load cell 0.75kN-00457279 00457279-PD 2125
<a href="#">SWS9573</a>	
<a href="#">type BT0121</a>	Nr.209180 with two shaft output
<a href="#">ultrasonic edge sensor fx 4631</a>	
<a href="#">NR. 229370</a>	

<a href="#">TYP: AG2591</a>	
<a href="#">FX 51010</a>	212048
<a href="#">TYP:AG2595</a>	24V DC I:2.9 A S:+/-75 MM ID NO:710246866 G9192
<a href="#">TYP:AG 2529 226921</a>	AG 2529 NR:226921 24VDC 2,9A S=t/75MT
<a href="#">FR 0901</a>	
<a href="#">PD 2135</a>	
<a href="#">00220906</a>	
<a href="#">Pd 2117</a>	PD 2117 Load cell for bearings D 17 mm Nominal measuring force 0.10 kN, right Special version according to KBS5079-10583691 Plug on the side Net weight about 1,888 kg. Material no. 220829 has been replaced by 489431. Origin: European Union (EN) HS 90318080
<a href="#">Cv 2201</a>	Web force measuring amplifier for DIN rail mounting, Operating voltage 24 V DC, Output 0-10V or 0 / 4-20mA Origin: European Union (DE) HS 85437090
<a href="#">Ch-328284-1</a>	
<a href="#">Ch-349658</a>	
<a href="#">Cv2201-U24vdc-P4w</a>	
<a href="#">Ch-006462</a>	
<a href="#">00043330 Pd 2145</a>	
<a href="#">00302990 Cv 2201</a>	
<a href="#">F 31e</a>	F 31E edge sensor mechanically right, with 2 individually finely adjustable silver contacts for max. 60 V 0.2 A, control bandwidth 0.5 - 30 mm and contact force of the feeler lever adjustable, protection class IP 33, max. 80 degrees C including 2 m connection cable Origin: European Union (DE) HS 90318080
<a href="#">Ag2491</a>	
<a href="#">Dc1340</a>	
<a href="#">9100001</a>	
<a href="#">349658</a>	
<a href="#">Fr6011</a>	
<a href="#">Ag2591</a>	
<a href="#">00230567</a>	
<a href="#">Fm3085t</a>	
<a href="#">00006462</a>	

<a href="#">Rk4004-8403-F-Z101</a>	
<a href="#">Ag 2595</a>	AG 2595 Actuator with DC geared motor 50 W with incremental encoder, Travel +/- 75 mm, positioning speed 25 mm / s, force 1000 N Origin: European Union (EN) HS 85013100
<a href="#">00100783</a>	
<a href="#">Fr 5503</a>	FR 5503 infrared edge sensor for clamping frames according to dimension sheet 10514704 Measuring range +/- 10 mm with microprocessor, LED display scale with membrane keyboard, Plug for operating voltage 24 V and CAN bus, with mechanical scanning and with spring clip. Net weight about 0.625 kg / piece. Origin: European Union (EN) HS 90314990
<a href="#">Va5021</a>	
<a href="#">Ch-323230</a>	
<a href="#">Pd 2535</a>	Light metal force transducers in flange construction, according to dimension sheet M 057626 without ball bearings and circlips for pin diameter 35 mm Version open on one side Nominal measuring force 1.5 kN, protection class IP 54 Country of Origin: Germany (DE) HS 90318080
<a href="#">00320961</a>	
<a href="#">00003235</a>	
<a href="#">FR 5503</a>	"Ident No:1810430279" Infrared edge sensor for clamping frame according to dimension sheet 158289 Measuring range +/- 10 mm with microprocessor, LED display scale with membrane keyboard, Plug for operating voltage 24 V and CAN bus, with mechanical scanning and with spring clip. Net weight approx. 0.625 kg. Country of Origin: Germany (DE) HS 90314990
<a href="#">00302990</a>	
<a href="#">Pd2535 1,5 Kn Loadcell</a>	
<a href="#">Fx 4631</a>	Edge sensor ultrasound, digital, Measuring range +/- 3mm, inside width 30 mm, with 3,000 mm cable and M16 angle plug Origin: European Union (DE) HS 90318020
<a href="#">Fx4060</a>	
<a href="#">00352056</a>	
<a href="#">006462</a>	
<a href="#">Rk 4080 For Kr 6 ...</a>	Spare parts package
<a href="#">Do2000</a>	
<a href="#">Std_018-70</a>	Cable shielded 6 x A 0,14 10 m long, with 1 angle coupling and 1 JST plug IP 40

[00351779](#)

[Dig000](#)