



Etl Pruftechnik

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Etl Pruftechnik Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Etl Pruftechnik T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
UH36	<p>High voltage tester UH36 5 kV AC / 100 mA / 500 VA Parameter: - Test voltage adjustable from 0.1 - 5 kV AC - Tripping current adjustable from 0.5 - 100 mA - Adjustable test time: 1 s - 99 min, infinite - Nominal power of the transformer 500 VA Technology and general: - Tabletop device with dry transformer - Regulated test voltage, electromechanical - Switching on and off at zero voltage - sinusoidal output voltage with 50/60 Hz, depending on from the network - Ramp function and burn function - Monitoring of the test leads for wire breaks - Monitoring of contact with the test object - High voltage outlets on the front - CE compliant, according to EN 50 191, potential-free - Incl. factory calibration certificate, safety circuit plug, key set Operation and interfaces: - Large LED display to show all target and actual values - Optical and acoustic error signaling - Program memory for predefined parameter sets - Sophisticated device peripherals for PLC, RS232, CAN, drivers, Data management program, printer or customized Extensions - PC drivers for customer applications (DLL, Active-X and LabView) optionally available - digital interface for status displays and remote control - Connection for safety circuits and signal lights according to EN 50 191</p>

200209	HV test pistol HTP06C-02 with plug HVP06C 2.0 143.00 286.00 Cable 2 m / two-pole, plug 6 Description: - HV test pistol with automatic starter, application control and Monitoring for cable breaks - HV cable 2-pole, blue (D = 9.6 mm), length 2 m - HV connector HVP06C (D = 6 mm), 2-pin, for insertion in the test device Max. Operating voltages: - 7 kV AC / 10 kV DC, max. 10 A
WK36	Signal light WK36 Signal light red / green according to VDE 0104 / EN 50191
Uh36	
Bt36-Ac-12-0050-Tpt	
Uh28cs-Ac-12-005012kv	AC/50mA/600VAETL PR¼FTECHNIK
Ux36-Ac-12-0050-Ogt	
Ux36-Ac-12-0050-Ogt12kv	AC/50mA/600VAETL PR¼FTECHNIK