



Eurotherm

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Eurotherm Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Eurotherm T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
2408i	MODEL (2408I) display and alarm unit FUNCTION (AL) display and alarm unit DISPLAY SUPPLY VOLTAGE (VH) 85-264Vac mains supply MODULE 2 (G5) 10V transducer supply RELAY OUTPUT 1 (FH) maximum alarm OPERATING INSTRUCTIONS (GER) German SE (F) Linear -100 to + 100mV MINIMUM RANGE 0 MAXIMUM RANGE 1000 DISPLAY UNIT Activate key lock DIGITAL INPUT 2 (J3) Automatic calibration Transd 1 Code: 2408I / XX / GER // EE0632 / F / 0/1000 / X / KL / J3 // // // XX
P104/Cc/Vh/Rrc/R/4cl/Xxxxx	P104 (P104) 1/4 DIN Controller FUNCTION (CC) Controller SUPPLY CONTROLLER (VH) OP2 relay OP3 analog RELAY (R) - Changeover Relay OPTIONS (4CL) RS485 + CT and start at Start up
2404/Cc/Vh/Rd/Fh/D5/Rf/Xx/Ym/Xx/Eng/Xxxxx	
3204	Code: 3204 / CC / VH / DRDX / R / XXX / G / ENG / ENG / XXXXX MODEL (3204) 1/4 controller SUPPLY VOLTAGE (VH) 85-264Vac Mains supply OUTPUTS 1 2 3 (DRDX) 0-: (R) AA -Relay enabled FRONT COLOR (G) Green USER LANGUAGE (ENG) English OPE
Epower	POWER/4PH-100A/600V/XXX/XXX/XXX/XXX/OO/PB/XX/ XX/XX/XXX/XX/XX/XXX/XXX/ (EPOWER) thyristor model RATED CURRENT (4PH-100A) 100A - 4 Ph.station 100 A V SUPPLY (XXX) no fan WARRANTY (XXX) Standard warranty nameplate customer (XX) (XXX) standard OPTION (OO) Options / Quick start code COMMUNICATION (PB) Prof without MODULE 3 (XX) without SOFTWARE OPTION 1 (XXX) without
2500 E/S/Uw Modbus Card	
Code: G108-0001.V1	Limit Alarm, Vdc or mA In, Dual Trip, SPDT Relays
EPACK-1PH NENNSTROM 125A SUPPLY VOLTAGE 500V-85VAC	CONTROL MODE V2-U2 REGELUNG FIELDBUS COMMUNICATION
3216/CP/VL/LRXX/R/XXX/S/FRA/FRA/	3216 MODEL (3216) 1/16 DIN PID controller FUNCTION (CP) 1x8 segments program ac / dc mains supply OUTPUTS 1/2 (LR) 1 logic and 1 relay output AA RELAY (OP4) (S) silver USER LANGUAGE (FRA) French OPERATING INSTRUCTIONS (FRA) French OL
3216/CC/VL/LRXX/R/XXX/S/FRA/FRA	3216 MODEL (3216) 1/16 DIN PID controller FUNCTION (CC) PID controller SUPPLY V supply OUTPUTS 1/2 (LR) 1 logic and 1 relay output AA RELAY (OP4) (R) AA -Relay a LANGUAGE (FRA) French OPERATING INSTRUCTIONS (FRA) French OUTPUT 1 () Not u
2500 E/s/uw/modbus (3.62 versiyon)	
2500M/DI8LOGIC//XXXXX/XXXXXX	2500M MODEL (2500M) module for 2500 I / O MODULE INPUT TYPE (DI8LOGIC) 8-we
2500M/AI4UNIV//XXXXX/XXXXXX	2500M MODEL (2500M) module for 2500 I / O MODULE INPUT TYPE (AI4UNIV) 4-way
2500M/DO4LOGIC//XXXXX/XXXXXX	2500M MODEL (2500M) module for 2500 I / O MODULE INPUT TYPE (DO4LOGIC) 4-w
3216	Alternative to 2216 MODEL (3216) 1/16 DIN PID controller FUNCTION (CC) PID contr mains supply OUTPUTS 1/2 (LR) 1 logic and 1 relay output AA RELAY (OP4) (R) AA r OPERATOR LANGUAGE (ENG) German MANUAL (ENG) German OUTPUT 1 () Not used 3216/CC/VH/LRXX/R/XXX/G/GER/GER/ XXXXX/XXXXX/XXXXX/XXXXX/XXXXXXXX/ // // //
ITOOLS/NONE/USB// // // // // // // //	CONFIGURATION KIT (USB) USB CPI CLIP
EPC3004	MODEL (EPC3004) 1/4 DIN Controller TYPE (CC) Controller Only SUPPLY VOLTAGE (V I/O1 (R2) Relay Output (Supplied with External Snubber) I/O2 (R2) Relay Output (Su Relay Output (Supplied with External Snubber) RS485 COMMUNICATION PROTOCOL (ST) Standard APPLICATION (V) VPU Heat only INPUT 1 SENSOR TYPE (P) PT100 INP 752°F or 273 to 673K UNITS (C) Degrees Celsius (Default) Code: EPC3004/CC/VH/R2 XXXXX/XXXXXX/XX/V/P/3/X/X/X/X/X/X/C/XX/XX/XX/
3216 /CC/V	
P116/CC/VH/RRX/R/XXX	P116 (P116) 1/16 DIN Controller FUCTION (CC) Controller SUPPLY VOLTAGE (VH) 85- Relay RELAY (R) - Changeover Relay QUICK START (O) Quick start at Start up
2404F	MODEL (2404F) 96 x 96 mm Profibus FUNCTION (P4) 4 x 16 Seg Program SUPPLY VO (RF) Fitted Unconfigured COMMS 1 (PB) Profibus Module High Speed RS485 MANUAL Thermocouple MINIMUM RANGE 0 MAXIMUM RANGE 1200 DISPLAY UNITS (C) - Celsius Code:2404F/P4/VH/XX/XX/XX/RF/XX/PB/XX/ENG/XXXXX/ XXXXXX/K/0/1200/C/XX/XX,
3208	MODEL (3208) 1/8 YOUR PID Rules FUNCTION (CC) PID CONTROL SUPPLY VOLTAGE 1 2 3 (RRRX) Relay / Relay / Relay FRONT COLOR (G) Green OPERATING LANGUAGE INSTRUCTIONS (ENG) Code: 3208 / CC / VH / RRRX / X / XXX / G / ENG / ENG / XXX X / X / X / X / X / X / X / X / X / X
Code: ITOOLS/NONE/USB// // // // // // // //	MODEL (ITOOLS) configuration cable

637 KD6R06-7 CAN	
3504	MODEL (3504) 3504 Process controller FUNCTION (CC) PID controller SUPPLY VOLTAGE (VH) 230V SUPPLY CURRENT (I) 40A NUMBER OF CONTROL CIRCUITS (1) 1 control circuit NUMBER OF PROGRAMS (1) 1 program RECIPES (1) 1 recipe FRONT COLOR (S) Silver SLOT 1 EA SLOT (R4) changeover relay dual relay unconfigured USER LANGUAGE (ENG) English OPERATING INSTRUCTIONS (I) Standard Standard guarantee period CONFIGURATION (STD) Standard configuration 504/CC/VH/1/XX/1/1/XXX/S/R4/RR/XX/XX/XX/XX/XX/XX/XX/ENG/ENG/XXXXX/XXXXX/
5114AA	Programmable transmitter 1-channel
5114AB	Programmable transmitter 2-channel
5909	Loop Link Communication interface
EFIT/25A/230V/4MA20/FC/ENG/SELF/XX/NOFUSE/-/	
3504	MODEL (3504) 3504 Process controller FUNCTION (CC) PID controller SUPPLY VOLTAGE (VH) 230V SUPPLY CURRENT (I) 40A NUMBER OF CONTROL CIRCUITS (1) 1 control loop NUMBER OF PROGRAMS (25) 25 programs RECIPES (1) 1 recipe FRONT COLOR (G) Green SLOT 1 IO SLOT (D4) continuous output (D4) continuous output unconfigured SLOT 3 IO SLOT (D6) signal output unconfigured OPERATING INSTRUCTIONS (GER) German WARRANTY (XXXXX) Standard warranty period CONFIGURATION (PP) 2 channel PID controller Thermocouple type K MINIMUM RANGE 0 MAXIMUM RANGE 1200 AA RELAY FUNCTION 1 1HV SLOT FUNCTION 2 1CV SLOT FUNCTION 3 1SA SLOT FUNCTION 4 1SA SLOT FUNCTION 6 XXX Code: 3504/CC/VH/1/XX/25/1/XXX/G/D4/D4/D6/XX/XX/XX/XX/XX/XX/GER/GER/XXXXX/XXXXX/XXXXX/XXXXX/CFG//PP/K/ 0/1200/X/XX/X/XXXXXXXX/1
3504/CC/VH/1/XX/25/1/XXX/G/D4/D4/D6/RR/XX/XX/A2/	XX/XX/ENG/ENG/XXXXX/XXXXX/XXXXX/XXXXX/CFG//PP/ K/0/1200/X/XX/X/XXXXXXXX/1 (3504) 3504 Process controller FUNCTION (CC) PID controller SUPPLY VOLTAGE (VH) 230V SUPPLY CURRENT (I) 40A NUMBER OF CONTROL CIRCUITS (1) 1 control circuit NUMBER OF PROGRAMS (25) 25 programs RECIPES (1) 1 recipe FRONT COLOR (G) Green SLOT 1 EA SLOT (D4) Continuous output unconfigured SLOT 3 EA SLOT (D6) Signal output unconfigured SL unconfigured INTERFACE MANUAL (A2) RS232 Modbus ENGINEERING PLANT English (I) Standard Standard guarantee period CONFIGURATION (CFG) Pre-configuration in the factory channel PID controller SENSOR INPUT CIRCUIT 1 (K) Thermocouple type K MINIMUM RANGE 0 MAXIMUM RANGE 1200 AA RELAY FUNCTION 1 1HV SLOT FUNCTION 2 1CV SLOT FUNCTION 3 1SA SLOT FUNCTION 4 1SA SLOT FUNCTION 6 XXX Code: 3504/CC/VH/1/XX/25/1/XXX/G/D4/D4/D6/XX/XX/XX/XX/XX/XX/GER/GER/XXXXX/XXXXX/XXXXX/XXXXX/CFG//PP/K/ 0/1200/X/XX/X/XXXXXXXX/1
2500 8Loop	
ATV930 Code: ATV930D15N4	frequency converter Frequency converter 3x380 ... 480V, 50 ... 60Hz mains frequency 31.7A (38A for 60s or 1.2 x In), High overload 11kW, 23.5A (35.3A for 60s or 1.5 x In) motors, 0-500Hz motor frequency, Integrated EMC filter according to IEC / EN 61800 according to IEC61000-3-12, max. 44% THDi at 100% load, Integrated dynamic brake display supplied with 24 languages in IP65, 2xEthernet Modbus TCP, Modbus, further device in IP21, WxHxD: 211x546x232mm, 13.6kg, Pv 425W, -15 ... +60 degrees (up Paint. Boards according to IEC / EN 60721 for harsh environments 3C3 / 3S3, CE, UL REACH
TCSMCNAM3M002P	USB / RJ45 cable Programming cable USB / RJ45 with connection cable
L5392 panel	
SUB24	SPARES FOR 24XX MODELS SPARE PART (BEZ2404) 2404 Front Unit Code: SUB24/BE
ATV930D22N4	ATV930D22N4 Frequency converter 3x380...480V, 50...60Hz mains frequency, Standalone or 1.2 x In), High overload 18.5kW, 39.2A (58.8A for 60s or 1.5 x In), For asynchronous motor frequency, Integrated EMC filter according to IEC/EN 61800-3 category C2, Int 3-12, max. 44% THDi at 100% load, Integr. dynamic brake transistor, Pluggable gear in IP65, 2xEthernet Modbus TCP, Modbus, further fieldbuses optional, Wall or built-in 211x546x232mm, 14.3kg, Pv 573W, -15...+60 degrees (up to 50 degrees without de IEC/EN 60721 for harsh environments 3C3/3S3, CE, UL, CSA, EAC, NOM, RCM, DNV, I
EPC3016	MODEL (EPC3016) 1/16 DIN Controller TYPE (CC) Controller only SUPPLY VOLTAGE (V) 24V I/O 1 (L2) Logic I/O 2 (R2) Relay (with snubber) OUTPUT 3 (XX) Form C SERIAL COM (Default) or None ETHERNET, COMMS AND REMOTE SP (CE) Digital Input, Ethernet B APPLICATION (1) Heat only INPUT 1 SENSOR TYPE (P) PT100 INPUT 1 RANGE (F) Full EPC3016/CC/VH/L2/R2/XX/XX/XX/CE/XX/XX
EPACK-1PH/25A/500V/XXX/V2CL/XXX/XXX/TCP/XXX/	XXXXX/XXXXX/GWE/HSP/LC/25A/440V/XX/XX/PA/SP/0V/XX// EPACK-1PH MODEL (E) CURRENT (25A) 25 amps SUPPLY VOLTAGE (500V) 500V max NOT USED (XXX) Not u switching U ² current limit TRANSMISSION OPTION (XXX) COMMUNICATION OPTIONS WARRANTY (XXXXX) Standard Warranty GRAPHIC WIRING (GWE) With graphical edi microswitch CONFIGURATION (LC) Advanced ordering code LOAD CURRENT (25A) 25 volts LOAD TYPE (XX) Resistive load HEATING ELEMENT TYPE (XX) Resistor OPERAT INPUT FUNCTION (SP) Target value ANALOG INPUT TYPE (OV) 0-10 volts
6180A	MODEL (6180A) Graphic recorder CHANNELS (U06) 6 input channels HOUSING OPTIO COLOR (SLV) Silver SUPPLY VOLTAGE (VH) 90-264Vac 45-65Hz 110-370Vdc INTERNA storage. (Flash) STORAGE MEDIUM (CF) CF and Front USB Port NUMBER OF SHUNTS value QTY OF ATTENUATORS BRIDGE SOFTWARE (BLITE) Bridge Lite (Default) GROU 6180A/U06/NONE/PANEL/NOLCK/SLV/VH/XXXX/ XXXXXX/096M/CF/NOMC/NOMS/ORU00/00/00/00/00/4/100/XXXXX/BLITE/XXXXX/NOADT/NOSM/ 06GROUP/MTC00/NOBT0
Serial.No.PL1516000002-PL3	
Serial.No.PL1516000005-PL3	
Serial.No.PL1332000565-PL3	
EFIT/40A/230V/4MA20/FC/ENG/SELE/XX/NOFUSE/-/	MODEL (EFIT) Single Phase Power Controller CURRENT (40A) 40 Amps VOLTAGE (230V) 230V SUPPLY CURRENT (I) 40A NUMBER OF CONTROL CIRCUITS (1) 1 control circuit NUMBER OF PROGRAMS (1) 1 program RECIPES (1) 1 recipe FRONT COLOR (S) Silver SLOT 1 EA SLOT (R4) changeover relay dual relay unconfigured USER LANGUAGE (ENG) English OPERATING INSTRUCTIONS (I) Standard Standard guarantee period CONFIGURATION (STD) Standard configuration 504/CC/VH/1/XX/1/1/XXX/S/R4/RR/XX/XX/XX/XX/XX/XX/ENG/ENG/XXXXX/XXXXX/
	MODEL (EPACK-1PH) MAXIMUM UNIT TEST CURRENT (25A) 25 amps SUPPLY VOLTAGE (500V) 500V max NOT USED (XXX) Not u switching U ² current limit TRANSMISSION OPTION (XXX) COMMUNICATION OPTIONS WARRANTY (XXXXX) Standard Warranty GRAPHIC WIRING (GWE) With graphical edi microswitch CONFIGURATION (LC) Advanced ordering code LOAD CURRENT (25A) 25 volts LOAD TYPE (XX) Resistive load HEATING ELEMENT TYPE (XX) Resistor OPERAT INPUT FUNCTION (SP) Target value ANALOG INPUT TYPE (OV) 0-10 volts

EPACK-1PH/25A/500V/XXX/V2CL/XXX/XXX/TCP/	(V2CL) Auto switching U ² current limit COMMUNICATION OPTIONS (TCP) Modbus TCI With graphical editor Code: EPACK-1PH/25A/500V/XXX/V2CL/XXX/XXX/TCP/ XXX/XXX
P116	
3204	
3504	
3208	
ITOOLS	CONFIGURATION KIT (USB) USB CPI CLIP Code: ITOOLS/NONE/USB/////XXXXX
EPC3016	Code: EPC3016/CC/VH/R2/XX/XX/XX/XX/XX/XX/XXX/ ST/XXXXX/XXXXXX/XX/XX/1/16 DIN Controller TYPE (CC) Controller only SUPPLY VOLTAGE (VH) 100 - 230Vac + (supplied with external snubber) BEZEL (ST) Default
WALL MOUNT F. REGULATOR 2116/2216E 1/16	999-99(400/57)
VERSADAC	MODEL (VERSADAC) Scalable Data Recorder RECORDING TYPE (RXX) Recording Only SLOT MODULE (AI4-TC) 4 Ch Non Isolated TC with CJC SLOT MODULE (AI4-TC) 4 Ch MODULE (AI4-TC) 4 Ch Non Isolated TC with CJC SLOT MODULE (RLY8) 8 Ch Relay C Six Groups VIRTUAL CHANNELS (128VC) 128 Virtual Channels BATCH - Batch enabler Modbus TCP/RTU Master TOOLKIT BLOCKS - Basic Toolkit Blocks OPERATING LANGUAGE Default Code: VERSADAC/RXX/04/AI4-TC/AI4-TC/AI4-TC/RLY8/XX/XX/XX/XX/XX/XXX/XXX/06/128VC/BATCH/NOADT/NOSM/XX/TM/BASIC/ XXXXXX/ENG/XXX/LITE/XXX:
2PH-250A	MODEL (EPOWER) Thyristor Model NENNSTROM (2PH-250A) 250A - 2 Ph. Station 250 LUEFTERVERSORGUNG (230V) 230V AC EPOWER/2PH-250A/600V/230V/XXX/XXX/XX
EPOWER	MODEL (EPOWER) Thyristor Model RATED CURRENT (1PH-100A) 100A - 1 Ph. Station Code: EPOWER/1PH-100A/600V/XXX/ XXX/XXX/XXX/XX/XXXXXXXXXXXXXXXXXXXXXXXXXXXX
EPACK-1PH	MODELL (EPACK-1PH) Maximum device current (100A) 100 amps Auxiliary voltage (5 (PWRL) Power control with current limitation Transfer option (TFR) I2 Transfer Com Graphical wiring (GWE) With graphical editor Fuse (HSP) Super fast fuse without mic PWRL/TFR/XXX/PN/XXX/XXXXX/ XXXXXX/GWE/HSP/XXXXXXXX/XXXXX/
Profibus Card H/W:2500E/S/8LOOPUW	
Profibus Board-9DTYPE	H/W : 2500T/IOC/S
2163-5852 Package Size: 3= 1/32nd DIN Panel	Legacy Model Primary Function: C = PID Controller with Universal Input Power Supply points Output 1 and 2: EJ - Out1 = Mech Relay 5A, SPDT : Out2 = Mech Relay 5A, SPDT Auxiliary Control Functions: A = None Output 3 and 4: AA - Out3 = None : Out4 = None PID Version Custom Options: WP = Logo Face Plate Model Number: PM3C2EJ-BAAAN
A105104806	
T800	
Epower/2ph-100a/600v/XXX/XXX/XXX/XXX/Oo/XX/XX/XX/XX/XXX/XX/XX/XXX/XXX/XXX/XX/XXXXXXXXXXXXXXXXXXXX	
Te10a/50a/100v/4ma20/Pa/Eng/230v/CI/Nofuse/-/-/00./	
Efit/50a/100v/4ma20/Pa/Eng/230v/CI/Nofuse/-/	
Dc021449	
902/Is/Hre/Cre//Vh/Xn//Le/Tr/Hav/////0/300/C/70	
Epower/Drv-XXX/XXX/XXX/XXX/XXX/XXX/Oo/Et/XX/XX/XX/Plm/XX/XX/XXX/XXX/XX/XXXXXXXXXXXXXXXXXXXX	
Tc2000/02/250/440v/220v/4ma20/Fra/-/Fuse/-/Non?	
C25631-001-001-09-98	
T2550/L60/F32/Mb-Tcpm/Serial/None/XXXXX/XXXXX	
Ssd 6253 Vers:1.3	
S/N:Us32071-1-1-D-3711-PI3 I5	
425a/40a/440v/220v240/0v10/Pa/Frau/CI/-/Fuse/00	
EPC3016	The type 2216E regulator you requested is no longer included in our scope of deliver replacement device as follows: MODEL (EPC3016) 1/16 DIN Controller TYPE (CC) Cor - 230Vac +/-15% (48 to 62Hz) I/O 1 (L2) Logic SERIAL COMMS PROTOCOL (XX) Mod Standard APPLICATION (1) Heat only INPUT 1 SENSOR TYPE (P) PT100 INPUT 1 RAN to 473K UNITS (C) °Celsius Code: EPC3016/CC/VH/L2/XX/XX/XX/XX/XX/XX/XXX/ST/XXXXX/XXXXXX/XX/1/P/2/X/X/X/X/X/C/X/
8396p0180	
2208e/Cc/Vh/XX/Rc/XX/XX/2xx/Eng	
Rvda-6v25/A02 , Ssrdcds30a1 Or Ssrpcds90a3+ssrah1	
Tc2000/02/75a/440v//Lgc/000/Ger/-/Nofuse/-/None/-/-/00	
590p-53270020	
Hp25a/280/D	
Efit/25a/240v/4ma20/Pa/Eng/Self/XX/Nofuse/-/	MODEL (EFIT) Single Phase Power Controller CURRENT (25A) 25 Amps VOLTAGE (240 FIRING (PA) Phase Angle BEDIENUNGSANLEITUNG (ENG) Englisch SUPPLY (SELF) Sel

Limit FUSE (NOFUSE) Without Fuse SPC (-) Standard Code: EFIT/25A/240V/4MA20/P

[Sub818/Spare/Bezel](#)

[10a Phase Angle 25a 115w 4 20ma](#)

[8396p0182](#)

[Rvaa6v25](#)

[590p-53235010-P00-U4wp](#)

[Q408-0c00/0c04](#)

[Tcsmcnam3m002p](#)

Programming cable USB / RJ45 with connecting cable Code: TCSMCNAM3002P

[T2550](#)

[Altivar 71](#)

[T630 / Mains / Explo / - / - / T730/- 133678 / 001 / 1 / 3697 / F5 By 2704](#)

[3208](#)

Temperature / Process Controllers Analogue IP/OP In: 2 Out: 3 Combinational Logic IP/OP In: 3 Out: 4 Maths Equation none PC Configuration Wizard Safety Approvals E Text messaging

[590p-53235010-P00-U0v0](#)

[Epack-3ph](#)

Code: EPACK-3PH/125A/500V/XXX/PWRCL/TFR/XXX/TCP/XXX/ XXXXX/XXXXXX/GWE/AK/XXX MODEL (EPACK-3PH) MAXIMUM CURRENT (125A) 125 Amps AUXILIARY POW CONTROL OPTION (PWRCL) Power Control with Current Limit TRANSFER OPTIONS (T Modbus TCP WARRANTY (XXXXX) Standard LABEL (XXXXX) Standard Eurotherm Label Wiring Edition FUSE (HSP) High Speed Fuse without microswitch CONFIGURATION (L Ampere LOAD VOLTAGE (400V) LOAD CONFIGURATION (3S) Star without neutral LO/ (XX) Resistive FIRING MODE (PA) Phase Angle ANALOG INPUT FUNCTION (SP) Setp Volt DIGITAL INPUT 2 FUNCTION (AK) Alarm Acknowledgement

[955+8n0300-D4.](#)

[590p-53270020-P00-](#)

[I/O Modul- Eingangstyp \(Do424v\) 4fach Digitalausgang 24v](#)

[Digital I/O A-L Mod High Req](#)

[Vw3a4702](#)

EMC filter to reduce EMC interference Rated current 15A Category C2 up to 150 m Mc up to 300 m Motor cable length geschrimt Dimensions WxHxD 75x240x140mm Weigl Code: VW 3A4702

[2ph 100a](#)

[Epack-1ph](#)

MODELL (EPACK-1PH) MAXIMUM DEVICE CURRENT (125A) 125 amp auxiliary voltage UNUSED CONTROL OPTIONS (V2CL) Automatic switchover U² current limit TRANSFER COMMUNICATION OPTIONS (TCP) Modbus TCP (standard) WARRANTY (XXXXX) Stanc (GWE) With graphic editor SECURITY (HSP) Super quick Fuse without microswitch CC code LAST CURRENT (125A) 125 Amp mA DIGITAL INPUT 2 FUNCTION (AK) Alarm cc Code: EPACK-1PH / 125A / 500V / XXX / V2CL / TFR / XXX / TCP / XXX / XXXXX / XX XX / XX / PA / SP / 4A / AK //

[Rek41/09](#)

[2204e](#)

[Fks/Fks6113a00er00](#)

[Tc3001/150a/440v/2/20vâ;Yeni Model Typ Epower](#)

[2500m](#)

[Atv630u55n4](#)

Frequency converter 3x380 ... 480V, 50 ... 60Hz Mains frequency, standard overload High overload 4kW, 9.3A (14A for 60s or 1.5 x In), For Asynchronous and synchronous Integr. EMC filter according to IEC / EN 61800-3 Category C2, Integr. Choke accordin 100% load, pluggable graphics display supplied with 24 languages in IP65, Ethernet fieldbuses optional, wall or recessed version in IP21, WxHxD: 144x350x203mm, 4.7 to 50 degrees without declassification), varnish. Boards according to IEC / EN 60721 UL, CSA, EAC, NOM, RCM, DNV, GL, TUV, REACH Code: ATV630U55N4

[2132](#)

[Hp25a 280 D](#)

[Te10a Te10a/25a/240v/0v10/Pa/Ger/-/-/Nofuse/-/-/00](#)

[Epack 2ph - 80a](#)

[3216](#)

3216 / CC / VH / DRXX / R / XXX / G / ENG / ENG / XXXXX MODEL (3216) 1/16 DIN P controller SUPPLY VOLTAGE (VH) 85-264Vac Mains supply OUTPUTS 1/2 (DR) 1x 0 / (OP4) (R) AA -Relay enabled FRONT COLOR (G) Green USER LANGUAGE (ENG) Englis OUTPUT 1 () Not used Special Features Recipes, Text messaging

[Epack 2ph - 100a](#)

[Te10a 16a/230v/4ma20/Pa/Eng/-/Cl/Nofuse/-/-/00](#)

3216 MODEL (3216) 1/16 DIN PID Controller FUNCTION (CC) PID Controller SUPPLY

216/Cc/Vh/Drxx/R/Xxx/G/Eng/Eng/	OUTPUT 1/2 (DR) 1x 0 / 4-20mA / 1x Relay Output AA RELAY (OP4) (R) AA Relay en
2408/Vc/Rm/Xx/Xx/Hf/Fm/Xx/Ita	LANGUAGE (ENG) English OPERATING MANUAL (ENG) English
Epower/4ph-400a/600v/230v/Xxx/Xxx/Xxx/Oo/Et/ Xx/Xx/Xx/Plm/Xx/Xx/Xxx/Xxx/Xxx/Xx/XXXXXXXXXXXX	
Ah025075u002 V.9 Rs485 Comms 24-26-27-35	
Er-PI1152q	
Dc955+8r0040	
Tc2000/02/250a/440v/220v/ 4ma20/000/Fra/-/Fuse/-/None/-/00	
6180a	
Eurotherm Te10a 25a/230v/Ov10/Pa/Ger/-/Nofuse/-/00	
Epower/2ph-160a/600v/230v/Xxx/Xxx/Xxx/ Oo/Xx/Xx/Xx/Xx/Xxx/Xx/Xxx/Xxx/Xxx/Xx/XXXXXXXXXXXX	
Efit/16a/230v/4ma20/Fc/Eng/Self/Xx/Nofuse/-/	
2500m Di8contact	
2408	
1ph-160a/600v/230v	
815/818	
2216l	
Tc Pc2500m/Ai2/Univ/-/-/Eng2500t/Ai2/Tc/-/-/None/Eng	
3504	We need the 1600 degree control instead of 1200 degree control Wir brauchen statt Kontrolle
650.075.400.F	
590p-53270020-P00-U4wp	
2208e/Cc/Vh/Rh/Rc/Xx/Xx/2xx/Eng	
2116/Al/Vh/Emng/Ac/Fh/2/0/400/C/Xx/Xx	
Pa068033	
Rvaa6v40	
2500m/Di8contact//Xxxxx/Xxxxx	
3ph160a600v	
T2550b	
Rq01476b	
818 S Td Cnome	
2500e S 8loop Profibus	
Back Led Light Link 2 L5392	
E+plc400	
Fks/Fks6113000000	
21081/Al/Gn/Vh/Rf/Rf/Engf/04172	
942s/1v/Hdv/Adr/Ssr//Vh/Xm/Le/271/Ih/Tac/Abb//Xa0,0/39.6/Mv/0/10000/Psi/0	
Epower 3ph	
Tc2000/02/60a/440v//Lgc/000/Ger/-/Nofuse/-/None/-/00	
2208e/Cc/Vh/Rh/Xx/Xx/Xx/2xx/Eng	
Ah242919	
Ah026222u002 V.6a Profibus Comms 24-26-27-35	
Auxillary Supply Fan 115vac(For 690pf/0750/400/0011/Us)	
Rsda-660/75/1e , By Epack-1ph	
La243101	
G448-0002	
2500p 2as	
Svda/3v25/A02	
808/R1/R1/0/0/0/QIs(Ejhc130)	

Hue-800s
Rsda-660100-1e0
Tc/Mvpc2500m/Ai4/Univ/-/-/Eng2500t/Ai4/Tc/-/-/None/Eng
Atv630u40n4
Frequency converter 3x380 ... 480V, 50 ... 60Hz mains frequency, standard overload (In), High overload 3kW, 7.2A (10.8A for 60s or 1.5 x In) , For asynchronous and sync frequency, Integr. EMC filter according to IEC / EN 61800-3 Category C2, Integr. Cho 44% THDi at 100% load, pluggable graphics display supplied with 24 languages in I additional fieldbus optional, wall or recessed version in IP21, WxHxD: 144x350x203mm degrees (up to 50 degrees without declassification), varnish. Boards according to IEC 3C3 / 3S3, CE, UL, CSA, EAC, NOM, RCM, DNV, GL, TUV, REACH Code: ATV630U40N4
Te10a Te10a/25a/240v/0v10/Fc/Ger/-/-/Nofuse/-/-/00
2208e
Rvda-6v40/A02
Epower/3ph-100a/600v/Xxx/Xxx/Xxx/Xxx/Oo/Y2/ Xxx/Xx/Xx/Xxx/Xx/Xx/Xxx/Xxx/Xxx/Xxx/XXXXXXXXXXXXXXXXXXXX
92730+92731
La244790
590p
Te 10 A/240v/4ma20
Ah025246u002 V.5 Dual Relay 2-Fin 24-26-27-35
Regulateur Chaud (2 Boucles) 2604
Eycon-10
T 640
Rsda/75a/500v/Ldc/Eng (48/500 Vac)
3508
Epower/Pwr-400a/600v/230v/Xxx/Xxx/ Xxx/Xx/XXXXXXXXXXXXXXXXXXXX
Te10a (16a 0-10v)
Rsda-660/50/1e
Sub26 Ersatzteil Serie 2600 Ersatzteil (Ms) 24v Transmitter Psu Code: Sub26/Ms//Xx/Xx//Xxx
2408/Vc/Vm/Pm/Xx/Xx/Fh/Fm/Xx/Ita
Do4 24 V Version 2 S/N: Hk29169-002-001 Date: 01-08 Coc:Sn005 Custref 3793 Custpart 250089119
Pa075318
942s/Iv/Pdv//Adr/Ssr//Vh/Xm/Le//271/Ih/Pac//Aab///Xa/0.0/39.6/Mv/0/10000/Psi/00
Subepwr/Profibus
2500e
Blue Ink,6 Pcs/Pack (For Type No:392 Recorder/ 1235995-1,02-02-V3-10 D13)
Te10a 160a/400v/0v10/Pa/Ger/-/-/Nofuse/-/00
Rack-L5300
C3s300v4f10i10t10m00
Afs6113a00er00
Epack-2ph
2216e
Ssd 590 Vers:8.9
E+plc100
Epower/3ph-160a/600v/230v
21081
Ssd 690 Vers:8.9
Apc Smart-Upsxl Modular3000va
Code: Nanodac/Vh/C/P/Lrr/Xx/Es/Sv/Basiceng/Xxx/ Xxxxx/XXXXXX/05/