

Ewon



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Ewon** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ewon Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
WEC61330 Ewon COSY 131 VPN/Ethernet	4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 108.8 x 98.3 x 43.6 mm (H x D x W) Operating temperature: -25 ° C to 60 ° C
Ewon Cosy 131 - 3G	
Ewon Cosy 131 - WiFi	
WEC61330	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
	Ewon COSY 131 VPN/Ethernet/WLAN 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN

WEC6133C	connection via LAN + WLAN 802.11 b / g / n Output power 19dBm WiFi antenna included Note: When using accessory antennas, observe the permissible transmission power SD card slot for configuration / device update, 2x DI and 1x DO, Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
WEC6133G	Ewon COSY 131 VPN/Ethernet/LTE-Modem Europa 4x RJ45 LAN/WAN 10/100 Base (integrierter 4-fach Switch konfigurierbar) 1x USB-Port WAN-Anbindung ¼ber LAN und GSM/GPRS/EDGE/UMTS/HSUPA/LTE mit bis zu 150 Mbit, Frequenzb¼nder f¼r Europa (1, 3, 7, 8, 20) SD-Kartenlaufwerk zum Konfigurieren/Ger¼te-Update Integriertes Webinterface f¼r Konfiguration OpenVPN f¼r sichere Internet-Verbindung mit Talk2M Gr¼Btm¼glichster Schutz durch Zugriffskontrolle Spannungsversorgung: 12-24 VDC Abmessungen: 106 x 99 x 40 mm (H x T x B) Betriebstemperatur: -25°C bis 70°C
Router eWon 2005CD	
WEC61330	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
FLEXY201	Ewon Flexy 201 M2M and remote maintenance router 4x RJ45 LAN 10/100 Base (integrated switch) 1x SD card slot for configuration / device update 2x digital input 1x digital output 4x slot for expansion cards Integrated web interface for configuration Routing function for remote maintenance access Ethernet / serial Communication protocols to controls (e.g. Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and email BASIC editor for free programming Integration of your own HTML pages with eWON tags OpenVPN for a secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 80 x 89 x 134 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C
FLB3204	Ewon Flexy expansion card for cellular LTE Europe Frequency bands for Europe (1, 3, 7, 8, 20) GSM / GPRS / EDGE / UMTS / HSUPA / LTE with up to 150 Mbit 1x SMA socket For use in the basic modules Weight: <300 g Operating temperature: -25 ° C to 70 ° C
Cosy 131	
WEC6133D	Ewon COSY 131 VPN/Ethernet/3G+-Modem 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN and GSM / GPRS / EDGE / UMTS / HSPA + modem, SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions:

	106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
131 EC 61330 00MA/S	
FLEXY205	Ewon Flexy 205 remote maintenance router 4x RJ45 LAN / WAN 10/100 Base (integrated switch configurable) 1x SD card slot for configuration / device update 2x digital input 1x digital output 2x slot for expansion cards Integrated web interface for configuration Communication protocols to controls (e.g. Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and email BASIC IDE / JAVA for free programming Integration of your own HTML pages with eWON tags OpenVPN for a secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 133 x 122 x 55 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C
WEC61330	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN/WAN 10/100 Base (integrierter 3-fach Switch konfigurierbar) 1x USB-Port WAN-Anbindung über LAN SD-Kartenlaufwerk zum Konfigurieren/Geräte-Update Integriertes Webinterface für Konfiguration OpenVPN für sichere Internet-Verbindung mit Talk2M Größtmöglicher Schutz durch Zugriffskontrolle Spannungsversorgung: 12-24 VDC Abmessungen: 106 x 99 x 40 mm (H x T x B) Betriebstemperatur: -25°C bis 70°C
WEC61330	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
WEC61330	Ewon COSY 131 VPN/Ethernet Switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
EC61330 Cosy 131	Industrial Internet Router 001616325-81
Nur Bilder	haben leider keine model/Artikel nr.
EC6133C	001616327-81 Cosy 131 WIFI Industrial Inet Router
Ec51460	COSY 141MPI INDUSTRIAL VPN ROUTER
S7-300	CPU 314C-2 PTP Kompakt-CPU with M
EC61330	Cosy 131 Industrial Internet Router
VC61330-00MA/S COSY131LAN	
Cosy 131 Industrial Internet Router	

777555	Special procurement item
VPN Router eWON 2005 CD/ETHERNET EW26201-00	
EC61330-00-Q1 Communication Module IP Router, VPN,	4 x 10/100Mb Ethernet, 2DI, 1DO, USB eWON Cozy BRAND
Ewon Flexy 205 Starter Kit STK205	
Ewon Flexy 205 Starter Kit	777555-81 STK205#Ewon Flb 204 = cannot be obtained
Flb 204	
EC61330	
ewon flexy 205	
EC71330_00MA	EAN: 2050007680710 COSY+ EtherNet 2621279-81
Cosy 131 WIFI Industrial Inet Router	Manufacturer's part number: EC6133C
EC61330	eWon Cosy 131 , 4xRJ45 (1x WAN port ve 3 x LAN port)
FLX3101_00	Single ethernet extension board for Ewon Flexy Indus. Internet Router
EC 61330 COSY 131 ETHERNET ROUTER	
2179520004 REMOTE GATEWAY 131 EC61330	
Wec6133d	
Ec6133c Ewon Cosy 131	eWON COSY 131 VPN/Ethernet/WLAN 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN + WLAN 802.11 b / g / n Output power 19dBm Wi-Fi Austeckantenne included Note: When using accessory antennas, observe permissible transmission power SD card slot for configuring / device update, 2x DI and 1x DO, Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Ew05201	ETHERNET GATEWAY MODULE 300MA 12-24VDC 5W
Wec61330 Ewon Cosy 131 Vpn/Ethernet	4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Ew26201-00	REMOTE CONNECTIVITY GATEWAY
Ewon-2001/Gprs	ETHERNET GATEWAY MODULE 300MA 12-24VDC GPRS
E3w Flb3202	

Wew33204	
Wew26204	
Wew40902f (Replacement For Wew40902b)	
Ewon2005cd Vpn/Ethernet/Mpi	
Wec61330 - Ewon Cosy 131 Vpn/Ethernet	4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Wew2626b	
Flexy10100_00ma	
Flb3271	
Ew26204	MODEM
E3w Ec61330	
Ec51460	COSY 141MPI INDUSTRIAL VPN ROUTER
E3w Ew26201	
Wew40902b	
Wec61330	Ewon COZY 131 VPN / Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Cosy 131 , Wec6133d	
Ewon2005cd Vpn/Ethernet/Seriell/Pstn	
Cosy 141 Wec51410	
Cosy 141 Wec51460	
Wew2620b	
Ewon Cosy 141 Vpn/Ethernet/Seriell	
Ec6133c	ROUTER
Wec51460	
Wew46261	
Wew3326b	
Wew40912b	

Flexy20300	
E3w Flexy20100	
Wew2620a	
Ew21205-00-16	ETHERNET GATEWAY MODULE 300MA 12-24VDC GPRS
Ew26264	
Ewon Cosy 141 Vpn/Ethernet/Mpi	
Wew26261	
Wew26201	
Flx3101	
Wew40902f	
Wec6133d Ewon Cosy 131 Vpn/Ethernet/3g+-Modem	4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN and GSM / GPRS / EDGE / UMTS / HSPA + modem, SD card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
E3w Flb3271	
Ewon 2005cd	
Ewon Cosy 131 Vpn/Ethernet	WEC61330 4x RJ45 LAN / WAN 10/100 base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Flexy205	Ewon Flexy 205 remote maintenance router 4x RJ45 LAN / WAN 10/100 Base (integrated switch configurable) 1x SD card slot for configuring / device update 2x digital input 1x digital output 2x slot for expansion cards Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and Email BASIC IDE / JAVA for free programming Integration of own HTML pages with eWON tags OpenVPN for secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 133 x 122 x 55 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C
Fla3301	Ewon Flexy expansion card serial 1x RS232 / 422/485 1x RS232 Usable as IO or VCOM interface For use in the base modules Weight: <300 g Operating temperature: -25 ° C to 70 ° C
Ewon 4005 Cd	

Ec61330	Ewon cosy 131 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
Wec51410	
E3w Flx3101	
1422 – 0075 – 21 / Flexy20100_00ma/S	
Ewon2101cd Vpn/Mpi/Gprs Qb	