

## Exair

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Exair** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Exair T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">110012</a>	
<a href="#">110012-.005</a>	
<a href="#">110018</a>	
<a href="#">110024</a>	
<a href="#">1102</a>	
<a href="#">110900</a>	
<a href="#">1109SS</a>	
<a href="#">1109SS-NPT</a>	
<a href="#">150150 1-1/2"</a>	
<a href="#">2048</a>	
<a href="#">3215</a>	
<a href="#">3240</a>	

<a href="#">4040</a>	
<a href="#">4315-ETC240</a>	
<a href="#">6081 1 IN. ALUM. LINE VAC</a>	
<a href="#">6085 2-1/2"</a>	
<a href="#">6295</a>	
<a href="#">6932-20</a>	
<a href="#">900569</a>	
<a href="#">9009</a>	
<a href="#">BP110003</a>	
<a href="#">BP110030</a>	
<a href="#">BP150125</a>	
<a href="#">BP3725</a>	
<a href="#">BP3825J</a>	
<a href="#">BP5215J</a>	
<a href="#">BP6196</a>	
<a href="#">MODEL</a>	
<a href="#">Model No. 6067</a>	
<a href="#">MODEL:6083</a>	
<a href="#">NEMA 12</a>	
<a href="#">W 5215 invalid/check 5215</a>	
<a href="#">BP6296</a>	Drum Vac Reversible System Deluxe, reversibel, passend für jede Eurotonne 205 Liter, OHNE FASS, mit Fassroller best.aus: BP6196+6901+9041+900097+901176: 1xBP6091 Pumpe Edelstahl mit 1/4"Gewinde 1x9012 Kugelhahn 1/4-1/4"-Gewinde 1x6711 Rohr aus Kunststoff 2"NPT Adapter 1x6708 Adapter Kunststoff 1 1/2"-Gewinde 1x6707 Bogen 90° mit Spannexz.u.Schlauchanschl. 1x6569 Schlauch flexibel 3000mm lang 1x6812 abgeschrägtes Aluminium Saug-Rohr = BP6196 zuzüglich nachfolgender Teile: 1x6901 Absaug-Set (1x6586 einteiliger ABS-Stab 1372mm+1x6587 Doppelgummischrubber) 1x900097 Satz Saugwerkzeuge (1x6565 Fugenbürste + 1x6566 Flachdüse + 2x6568 Verlängerungsrohr)
<a href="#">BP120028</a>	Super Air Amplifier, 203mm, 8", aluminum, 3/4" E.G with handle, standard shim thickness 0.23 mm .009" Air consumption at 5.5 bar 3396 l/min
<a href="#">28101486 Pneumatic, Flow Controller,</a>	(PISTON AIR INLET ADJUSTABLE EXHAUST)

<a href="#">1/8" x 8mm</a>	
<a href="#">BP110054</a>	Super Air Knife Aluminum, 1372 mm 54" Air consumption at 5.5 bar 4428 l/min
<a href="#">BP9077</a>	Alternative position Compressed air supply set for Super Air Knives 48"+54" long consisting of flex hose 1/2" in nitrile/PVC, various brass fittings, pressure gauges; max. temp. 55°C
<a href="#">900517</a>	Alternative position Universal mounting kit in stainless steel 303/304, too all Air Knives consisting of: Mounting bracket (900503) and screws, nuts, Discs=like 9060 but without Rods/extension arms or swivel clamp, like 9060.
<a href="#">BP4015</a>	Cabinet Cooler NEMA 12=IP54, power 290 watts Consumption 425 l/min. at 6.9 bar, Kcal./h 252, 1/4" connection NEMA 12=dust and oil resistant
<a href="#">BP4025</a>	Alternative position Cabinet Cooler NEMA 12=IP54, power 495 watts Consumption at 6.9 bar 708 l/min., Kcal./h 428, 1/4" connection NEMA 12=dust and oil resistant
<a href="#">BP4030</a>	Alternative position Cabinet Cooler NEMA 12=IP54, power 585 watts Consumption at 6.9 bar 850 l/min., Kcal./h. 504, 1/4"BSP connection NEMA 12=dust and oil resistant
<a href="#">BP4040</a>	Alternative position Cabinet Cooler NEMA 12=IP54, power 820 watts 706 kcal/h, consumption 1,132 l/min. at 6.9 bar, 1/4" connection NEMA 12=dust and oil resistant
<a href="#">4904</a>	Hose kit large - DIM 12/1.5 = 12 x 15 consisting of: 1 m air hose, DIM 12/1.5 = 12 x 15 3 x9522 eyelets 1 x9525 angle hose nozzle 1 x9526 end caps (necessary for control cabinet cooler)
<a href="#">4014413</a>	3/2 solenoid valve 24 V GS, with temperature control 0-120°, with LED Thermostat control consisting of: 1xZI-4014411 directional control valve V61B413A.A213L3/2, 24 V GS (aluminium), G 1/4" IT, flow 1300 l/min., 1xCO-4017101 temperature controller in the range 0-120°, switching difference 3+/-1.5°C, 250 V/AC, 50/60 Hz, 20A 1xZI-4014403 device socket 0664811 with LED
<a href="#">BP4630</a>	Cabinet Cooler NEMA 4=IP66, power 585 watts including straight hose nozzle, brass elbow, silencer Consumption 850 l/min., Kcal./h. 504, 1/4" connection, at 6.9 bar, NEMA 4 = splash-proof
<a href="#">4904</a>	Alternative position Hose kit large - DIM 12/1.5 = 12 x 15 consisting of: 1 m air hose, DIM 12/1.5 = 12 x 15 3 x9522 eyelets 1 x9525 angle hose nozzle 1 x9526 end caps (necessary for control cabinet cooler)
<a href="#">4014416</a>	Alternative position 3/2 solenoid valve 220...240 V with Thermostat control with LED Thermostat control consisting of: 4014412=V61B413A-A219L =3/2 way valve 220 V (aluminium), 1/4", flow 1,300 l/min at 2-8 bar, and temperature controller 4017001= ALRE-ZN112525 (switching difference 0.5 K/0.5°C)(successor model for PTR.01.082-24)

	Customs fee number. 9032.10.80 Country of origin Germany incl. 4014404=0664812 device socket with LED
<a href="#">4012655</a>	Alternative position Maintenance unit WKF 1/4" connection, size 1 Series W 75, (successor set WH 4012622: 17960505/333) 1500 l/min flow (=9027 EXAIR), best. out of: 4012656=17910505 Filter combination device WKF-K1-1/4-8-A-M, pore size 5µ size 1 series W 75, automatic condensate drain, 1/4" connection, 2000 l/min flow (=9004 EXAIR incl. Manometer) 4012657=17910333 Deoiler submicrofilter WKF-SMF-1/4 size 1 series W 75, < 0.01mg/cbm Residual oil content; flow recommended 350 NI/min 4012658=17910704 Filter insert WKF-ET-5µ-1 4012659=17910401 Clutch kit WKF-ZUB-KUP-1 PL16959 several individual devices, Maintenance devices size 1 series W 75,
<a href="#">4907</a>	Alternative position Connection set VA to the side. Mounting the NEMA 4/4X except 4608 + 4608SS; made of stainless steel 303
<a href="#">BP4015</a>	Cabinet Cooler NEMA 12=IP54, power 290 watts Consumption 425 l/min. at 6.9 bar, Kcal./h 252, 1/4" connection NEMA 12=dust and oil resistant
<a href="#">BP3208</a>	Vortex Tube, 1/8", 227 l/min/160 watts cooling capacity at 6.9 bar
<a href="#">3905</a>	Alternative position Cold Muffler for Vortex Tube BP3202-BP3208 + BP3402-BP3408
<a href="#">3903</a>	Alternative position Hot muffler for Vortex Tube BP3202-BP3240 + BP3402-BP3440
<a href="#">3909</a>	Alternative position Generator set (all C+R) including brass covers for Vortex Tube BP3202-3208: small 1x each 2 C+R, 4 C+R, 8 C+R, with 1x each brass covers 2 + 4 + 8
<a href="#">BP4030</a>	Cabinet Cooler NEMA 12=IP54, power 585Watt Consumption at 6.9 bar 850 l/min., Kcal./h. 504, 1/4"BSP connection NEMA 12=dust and oil resistant
<a href="#">4904</a>	Alternative position Hose kit large - DIM 12/1.5 = 12 x 15 consisting of: 1 m air hose, DIM 12/1.5 = 12 x 15 3 x9522 retaining eyelets 1 x9525 angled hose nozzle 1 x9526 end caps (required for control cabinet cooler)
<a href="#">4014413</a>	Alternative position 3/2 solenoid valve 24 V GS, with temperature control 0-120°, with LED Thermostat control consisting of: 1xZI-4014411 directional valve V61B413A.A213L3/2, 24 V GS (aluminum), G 1/4" IG, flow rate 1300 l/min., 1xCO-4017101 temperature controller in the range 0-120°, switching difference 3+/-1.5°C, 250 V/AC, 50/60 Hz, 20 A 1xZI-4014403 device socket 0664811 with LED
	Alternative position Maintenance unit WKF 1/4" connection, size 1 Series W 75, (successor set WH 4012622: 17960505/333) 1500 l/min flow (=9027 EXAIR), consisting of: 4012656=17910505 Filter combination device WKF-K1-1/4-8-

<a href="#">4012655</a>	A-M, pore size 1 Series W75, automatic condensate drain, 1/4" connection, 2000 l/min flow (=9004 EXAIR incl. pressure gauge) Customs tariff number: 84811005 Country of origin: Germany 4012657=17910333 Deoiler submicrofilter WKF-SMF-1/4 size 1 Series W75, < 0.01mg/cbm Residual oil content; recommended flow rate 350 NI/min Customs tariff number: 84213925 Country of origin: Germany 4012658=17910704 Filter insert WKF-ET-5µ-1 Customs tariff number: 84219990 Country of origin: Germany 4012659=17910401 Coupling kit WKF-ZUB-KUP-1 PL16959 of several individual devices, Maintenance devices size 1 series W75,
<a href="#">Bp6196 Reversible Drum Vac System With Bp Threads</a>	
<a href="#">6067</a>	
<a href="#">1104</a>	
<a href="#">6066</a>	
<a href="#">Shim Set For Exair Model 110012-.005</a>	
<a href="#">Modelã 6086</a>	
<a href="#">110003</a>	
<a href="#">6087</a>	
<a href="#">6193-30</a>	
<a href="#">1010ss</a>	
<a href="#">6064</a>	
<a href="#">9096</a>	
<a href="#">110024ss</a>	
<a href="#">110042</a>	
<a href="#">110012ss</a>	KNIFE
<a href="#">1122</a>	
<a href="#">5215</a>	
<a href="#">Model : 6r23</a>	
<a href="#">7941</a>	
<a href="#">6393-30</a>	
<a href="#">9097</a>	
<a href="#">120021</a>	
<a href="#">Bp110006</a>	

<a href="#">1-800-903-0247</a>	
<a href="#">Model 6060</a>	
<a href="#">6293-30</a>	
<a href="#">9092-M3-Dat</a>	
<a href="#">5330</a>	
<a href="#">4725ss</a>	
<a href="#">2436</a>	
<a href="#">2454</a>	
<a href="#">1103ss</a>	
<a href="#">110006</a>	
<a href="#">6196</a>	
<a href="#">Shim Set For Exair Model 110060-.005</a>	
<a href="#">7907</a>	
<a href="#">6041</a>	
<a href="#">Bp6190</a>	
<a href="#">6081 1 In. Alum. Line Vac</a>	
<a href="#">110003ss</a>	
<a href="#">110009</a>	
<a href="#">9095</a>	
<a href="#">110048</a>	AIR KNIFE 48IN 1/4 INLETX5 0.002 AIR SLOT
<a href="#">4830ss</a>	CABINET COOLER SS NEMA4X W/THERMOSTAT 2000BTU/HR
<a href="#">4330</a>	
<a href="#">120020</a>	
<a href="#">6085</a>	