

Felm

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Felm Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Felm Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Motor Hydraulic System	RATING : 30 Y2-200L-4 Y/D=31.6A/54.7A Y/D=690V/400V RPM:1480
Motor Recirculation Pump	RATING:4 MA112M-4 Y/D=8.42A/14.68A Y/D=380-400V/220-230V. RPM:1480
Re Cirulation Motor (Flange)	Rating:7.5Kw MA132M-4 14.8 400 RPM:1440
Hydraulic Motor	rating:55kw Y2 250 M4 98 400V RPM:1480
F3r 225s-4	1 Stck 37 kW, 4P, 400/690V/50Hz, IP55/IC411, F/B, IM B3, CI, IE3 Motor. In BG F3R 225S-4. Motor Gewicht: 314 kg. KK on the right side as seen from the AS (Terminal Box on right side as seen from DE). 3xPTC in the windings. Temperature: 40 degrees C. Max. Installation height: below 1000 m above sea level. Relative humidity: 90%. Felm IE3 motor brochure in the system. You will find engine data in the brochure. Engine drawing and data sheet later.
F3-222 M-4	KW45 RPM1480 HZ50 volt 380-400 Vakum Motor
F3-160 M -2	KW11 RPM 2940 HZ50 volt 380-400 Vakum Motor

132S-2
17
66034-1
BG F2 160M1-2
BG F2 160M2-2
BG F3 160L-2
BG F3 160M-2
F 132S-4/8
F2 315 s4
F3 160L-4
F3 160L-6
F3 160M1-2
F3 160M-4
F3 180L-4
F3 180L-6
F3 200L
F3 200L 30 4 V1 40 0-690/50
F3 225M-4
F3 315LX
F3 315LX 200 4 B3B 5 400-690/50
F3-225S4
FA3 100L1-4
FA3 100L2-4
FA3 100LB-4
FA3 112 M2
FA3 132M-4
FA3 90L-4
FA3-100L-6
FA3-100LA-4
FA3-100LA-4XXX
IP55/IC411

MA 80A-4
MA100L1-4
PT100
Y2 200 L1-2 30/2950
Y2 250 M4 55/1475
Y2-225M-6
Y2280S-6 B3
FIP ALFA BLOC 125-16,2
-Y2 315m-4, Mtg B3
F2 315m4, Power (Kw) 132, Poles 4, Mtg B3, Voltage 400v 50hz
Y2 200 L1-2 30/2950 Imv1 Obsolete, Alternative Ie3 - F3 200I1-2
F2-160m-2
Y2 250 M4 55/1475 Imv1 Obsolete, Alternative Ie3 - F3 250m
Type: Ma80b-2 - Obsolete Replaced By Bg Fa2 80b-2
Pt100 Electric Motor
F2. 160 L4 Elektromotor 15 Kw
Ma 100I1-4 Motor
Fa2-80b-2
Type: F2-355m-4
30kw 1440rpm 400/690v 200I-4 B3 33kW 1468 D/DK 400/690V Y2 200 L4
Y2-280s- 2
Fa2-808-4
Fa2 90I-4 Motor
33982209001
Ma 71a-2
F2 225m-6
Felm -Hv355-4
Fan, Part No. 17

Ma 100I1-4
FelM F2 180 L4 Elektromotor 27kw1470 U/Min
2,2 Kw, 2p, 230/400v/50hz, Ip55/Ic411, F/B, Im B35, Al, Ie2
Fa2-99I4 Cnc Tailstock Motor For Cncã3
Fa3 100I-2 Motor
Fa3 132m-4 7,5 Kw, 4p, 400/690v/50hz, Ip55/Ic411, F/B, Im B3, Al, Ie3 Motor. In Bg Fa3 132m-4.
Type: Y2-225m-6 Obsolete, Replaced By F2 225m-6. Motor
Ie3 - F3 200I1-2
F2 225m-6 Motor
Ie3 - F3 250m
Fa3 100I-2
FelM-Y2 315m-4, Mtg B5 / V1 / B35
Bg Fa2 80b-2
-Hv355-4
F2r 200I-4
Ta-17-1167
2014100294 - Obsolete, Replaced By - 2,2 Kw, 2p, 230/400v/50hz, Ip55/Ic411, F/B, Im B35, Al, Ie2
Ma 80a-4 0,55 Kw, 4p, 230/400v/50hz, Ip55/Ic411, F/B, Im B14, Al, Ie1 Motor. In Bg Ma 80a-4
Fa3-132m Asynchronous Three-Phase Motor Fa3-132m Kw7.5 P4 B3 V400/690/50hz FelM
Type: Y2-225m-6 Obsolete, Replaced By F2 225m-6.
F3 180m-2 Motor
Ma100I1-4 Cnc Lubrication Motor
Fa2-99I4
Fa3 112 M2 Motor

Fa2 80l-4	
F2 315 M-4	
Fa2-808-4 Cnc Tailstock Hydraulic Unit Motor	
F2 355m-4	
A3-100lb Asynchronous Three-Phase Motor A3-100lb Kw3 P4 B35 V230/400/50hz Felm	
Ma 90l-4	
Ie3 - F3 200l1-2 Electric Motor	
-Y2 315m-4, Mtg B5 / V1 / B35	
F2r 200l-4 Motor	
F2-225m-2	
Fa2 80l-4 Motor	
Bg F3 355l3-2	355 kW, 2P, 400 / 690V / 50Hz, IP55 / IC411, F / B, IM B3, GG, IE3 motor. In BG F3 355L3-2. Engine weight: 1740 kg. - Temperature: 40 degrees C Max. Altitude: 1000 m above sea level (MSL). -Position a) is an updated version (upgrade - higher efficiency) of the original engine. Offered engine is identical in construction for assembly. -I hereby send motor drawing FELM IE3 motor catalog for your info. Engine data are in the catalog. -KK Above (Top Terminal Box). 3xPTC in the windings. Roller bearings on the AS (on DE).
Felm-Y2 315m-4, Mtg B3	
F3-160m Asynchronous Three-Phase Motor F3-160m Kw11 P2 B5 V400/690/50hz + Tcd Pump 40-250/2-R/Gs	
Teil 17	
Y2280s-6 B3 Motor	
Ie3 - F3 250m Electric Motor	
Y2 250 M4 55/1475 Imv1 Obsolete, Alternative Ie3 - F3 250m Electric Motor	
Electric Motor	22kw 2951 RPM 400V Y2 180 M2
Fa2-90l-4 Elektromotor Fa2-90l-4 1.5 Kw 1400r/Min	
Y2 200 L1-2 30/2950 Imv1 Obsolete, Alternative Ie3 - F3 200l1-2 Electric Motor	
E2-225m-2	

F3 250m-4	55 kW, 4P, 400/690V/50Hz, IP55/IC411, F/B, IM B3, GG, IE3 Motor. In BG F3 250M-4. Motor Gewicht: 473 kg. KK Above (Top Terminal Box). 3xPTC in the windings. Temperature: 40 degrees C Max. Altitude: 1000 m above sea level (MSL). The offered engine is updated version with high (IE3) efficiency. The motor is identical for assembly. I am sending you the motor drawing and FELM IE3 motor catalog.
F2-225m-4	
F2-180m-2	
Felm-L3;Fter-Teil-17--Istanbul-Turkiye	
Fa2 90I-4	
Fa2-99I4 Cnc Tailstock Motor For Cnc#3	