

Ffe

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ffe Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ffe T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
FFE vibration switch with manual reset	Model: 8000 - 000 Set level range: 0.5 ... 9 g (Factory setting: 3 g) Microswitch: SPDT / silver contacts Switching capacity: 5 A at 250 Vac or 30Vdc Ambient temperature: - 45...+85 °C Housing: Die-cast zinc alloy Mazak III with powder coat finishing electrical connection: M20 x 1,5 Protection: IP 66/67 to. BS EN 60529
Model: 8001 - 000	FFE vibration switch with manual reset Set level range: 0.5 ... 9 g (Factory setting: 3 g) Microswitch: DPCO / silver contacts Switching capacity: 5 A at 250 Vac or 30Vdc Ambient temperature: - 45 ... + 85 ° C Housing: Die-cast zinc alloy Mazak III with powder coat finishing electrical connection: M20 x 1,5 Protection: IP 66/67 to. BS EN 60529
VIPRATION SWITCH TYPE 3171	
Modell 8001 - 00	FFE vibration monitor with manual reset Adjustment range: 0.5...9 g (factory setting: 3 g) Microswitch: double pole changeover / silver contacts Switching capacity: 5 A at 250 Vac or 30 Vdc Ambient temperature: - 45...+85°C Housing: Die-cast with polyester paint Cable entry: M20 x 1.5 Degree of protection: IP 66 / 67 according to BS EN 60529

8001 - 000	FFE vibration monitor with manual reset Adjustment range: 0.5...9 g (factory setting: 3 g) Microswitch: double pole changeover / silver contacts Switching capacity: 5 A at 250 Vac or 30 Vdc Ambient temperature: - 45...+85°C Housing: Die-cast with polyester paint Cable entry: M20 x 1.5 Degree of protection: IP 66 / 67 according to BS EN 60529
3171MR & S	
Fire Fighting Type 3171	
FFE-3171WPMR-1-S	FFE vibration monitor with manual reset Model: 8000 - 000 Setting range: 0.5...9 g (factory setting: 3 g) Microswitch: single-pole changeover / silver contacts Switching capacity: 5 A at 250 Vac or 30 Vdc Ambient temperature: - 45...+85°C Housing: die-cast with polyester coating Cable entry: M20 x 1.5 Protection class: IP 66 / 67 in accordance with BS EN 60529
Cable Gland	
8001-030	
8101 - 000	
Modell: 8001-010 (24 Vdc)	
Ffe-Ffe-Vibrationswõ;Chter-Modell-3171-Ex-Mit-Handr3;Ckstellung-Istanbul-Turkiye	
Modell: 8001-030 (240 Vac)	
8001-010	
Fireray 50r	
Modell 8100 - 000	
8000 - 000	
Modell: 8001-020 (110 Vac)	
8000 - 000 (3171)	
8100 - 000	
3171 Ex D E	
Modell 8000-000	
8001-020	
Ffe 8000 - 000	
Ffe-3171mr-1-S Obsolete, Replaced By Ffe 8000 - 000	
3171 Ex	

[8001 - 000](#)

[Type:3171for Cooling Tower Replaced](#)
[By 8001 - 000](#)