

Fiama

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Fiama Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Fiama T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
PF-700-10K-2	Draw wire encoder, standard version Measuring length 700mm Resistance value 10k Cable connection (m) 2
10731	
1083	
11170	
1121	
11634	
1190	
12092	
12094	
12405	
12426	

[1271](#)

[1361](#)

[13656](#)

[1405701](#)

[1524](#)

[16004](#)

[16033](#)

[16034](#)

[1661](#)

[1663](#)

[2239](#)

[25931](#)

[27210](#)

[28100](#)

[28642](#)

[30491](#)

[30620](#)

[31948](#)

[31994](#)

[32166](#)

[32168](#)

[32169](#)

[32171](#)

[3644](#)

[4510](#)

[5074](#)

[5159](#)

[5297](#)

[75-DX-F14-R-P6](#)

[8418](#)

[8799](#)

9602103	
I60-10-DX-2Z-0-10	
OP3-A-2,0-DX-F14-R-P6	
OP3-A-4,0-DX-F14-R-P6	
OP3-B-1.0-DX-F14-G-P6	
OP3-C-2,0-DX-F14-R-P6	
OP3-D-5,0-SX-RB12-G-P6	
OP6-A-2.0-DX-F20-G	
OP6-A-2.5 DX-F20-R	
OP7F25-B-2,0-SX-F25-R	
OP9-A-8,0-DX-F30-R	
PA50-2K-S	
PF-1000-10K-2	
PF-200-10K-2	
PR-20-1-3W-10K-2	
PR-20-24-1W-10K-2	
PR20C	
PR-20C-30-10W-10K	
SEM150/220	
SEP-160-24VDS	
TC80 R1M DX	
TC80-R1/1-C-1-B/0-300	
DIST. BLOCK OP7 A/B F25 1449521 FIAMA(1449521)	
OP6-A-2.0-SX-F20-R	
PR-20C-24-10W-10K-C1	gear potentiometer Connector version with mating connector 20C / hollow shaft 20mm connector design 24 / translation 24 10W / Pot. 10 spirals 10K / resistance value C1 / mating connector straight
IN80-0.5/714-SX-0-10	29183 Position display digital/analogue 5/714 / display 0005/714 rev. SX /Zdirection ascending to the left 0-10 / scale 0-10 SX
20M58R-D10	

Digital position display	Type: OP6-D-2.0-DX-F20-G ----- ----- D / reading position, horizontal fronts. 2.0 / display/rev.(mm) DX / counting direction right. F20 / hollow shaft 20 mm G / Housing color black
23228	OP7-C-3,0-DX-F20-R Digital position display C / Reading position front bottom 3.0 / Display/rev. (mm) DX / Counting direction right-hand F20 / Hollow shaft 20 mm R / Housing color orange
MSCZ5A	
PR-20C-1-10W-C1	20 / hollow shaft 20 mm C / connector version 1 / ratio 1.1 10W / Pot. 10 coil designed for 10 revolutions C1 / connector version, 4-pin.
9500107c Encoder	
Pf-300-10k-2	
Pf-1000-10-2	
Ef700	
Op6a80dxf20r	
Sem-150-230vac	
4424	
9500105c Encoder	
Ef 700-2	
3439	
Pr20c Rotary Potentiometers	
Op3-A-4,0-Sx-Rb12-R-P6	
1405701 Mechanical Counter90291090	
9512100	
Faw-1.	
27210 Seilzuggeber, Potentiometrisch Pf-2000-T-I-2	
6186	
Pf-300-5k-5	
1399	
Op6-A-3.0-Dx-F20-R	
28743	
Sep 160f/220	

Pf-700-10k-2
Op6-B-2,5-Dx-F20r Digitale Positionsanzeige
F2x2t
Pf300 10 Kohm
16034 Getriebepotentiometerpr-20c-24- 10w-0.5k
Pfa-5000-10k-T-Pg7
8016 Sep-160-24vdc
Sep-160-24vac
Ep20-A-G-20-1 Batterie Betrieben Art Nr. 5900
Op6-A-6,0-Sx-F20-R
Op6a40sxf20r R-K
Pr20c-R72/1-10 Rotations-Potentiometer (Sensor)
V2x34ac Relay 24vdc
Op6-A-2.0-Dx-F20-R
Op6-A-8.0-Dx-F20-R
Op7-A-1,5-Dx-F20-R-Zf
Ts501894g
Des:Vr-1 Alin:Ver.Rullo 4,5 Vdc Dod: 9051000
4613
Atex150/24vcc Flag Levelfiama Se Atex150/24vccsupply 24vcc 3vacode 9691150 Ex
Pa50k 9520150 (Pa50-2k-S)
Pr10.
Op7f25-A-10,0-Sx-F25-R(Ex.Op7 A 100 Sx F.22 R 5rn)
Op3-D-5,0-Sx-Rb12-G-P6 Digitale Positionsanzeige
Fgb-1
Im60-I-60-2

F1x52	
6349	
Im60-V2-60-5	
Op6a80sxf20r	
En20- F20-500-Pp-5	
In90f Indicators With Gravity And Fixed Reaction, With Counter I90f 100:1	
24527	
Ep20-A-G-20-1 Art Nr. 5900 Elektronische Positionsanzeige	
Pr-20-24-10w-10k-2 Art-Nr. 6354 Getriebepotentiometer	
Op3-C1,2/5-Dx-F14-R-P6	
F2x-3-2t	
P200p Handwheel Under The Shaft Diameter Of 16 Mm, With Handle Mg-80	
Se.Atex150/24vcc Sensor Rotations- Grenzschalter	
Fke6-20-A/B	
2987	
3439 Sep-160-F-230vac	
Pr-20c-24-10w-10k	
1107	
3359	
Op3-B-1,5-Dx-F14-R-P6	
Pa50-2k-S 9520150	
Pf700-10k-2 1430	
F20-1,0	
9105012	
Ef700-2	700 / measuring length 700mm 2 / cable connection (m) Resolution: 256 pulses 1024 steps: 102mm (0.1mm) Exit: Push Pull, AB
27297	
Op9t-B-10,0-Sx-F20-R	

Pr20-20-4-1w-10k-5	
9054182	
Pf1000	
6197	
1900/450 Sx66.56= 450 81310500	
Op 7 Op7f25	
Sep-160-24vdc	Level control for solids 160 / rod 160 mm 24VDC / operating voltage VCC