


Finder



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Finder** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Finder T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
56.32.9.024.0000	Power relay, 24V/DC, 2 change-over contact, Umax=250V/AC, AC1=3000VA, AC15=500VA, DC1=12A/30V, 0.25A/110V, 0.12A/220V, coil: 24V/DC +10-15%
99.01.9.024.99	Addition module for 6-24V/DC relays, free-wheeling diode and LED, for plug 96.72 and 96.74 (series 56)
56.34.9.024.0000	Power relay, 24V/DC, 4 change-over cont., Umax=250V/AC, AC1=3000VA, AC15=500VA, DC1=12A/30V, 0.25A/110V, 0.12A/220V, coil: 24V/DC +10-15%
96.72	Plug for relays, 2-pole, blue, for relay standard 56.32
96.74	Plug for relays, 4-pole, blue, for relay standard 56.34
65.31.9.024.4300	
MEX125OR	
NA 3-20	Bare shaft pump in cast iron with simple seal (Sic/Sic/NBR).
SHAFT SLEEVE POS.71	
SHAFT POS.24	
BEARING HOUSING POS.21	
IMPELLER POS.3	
7T.81.0.000.2303	

HC100-250	seri:103939-2 NU2210-3310 2-Cover 1st¼ck 21-Bearing zusammen mit 22. und 22.1 zusamnne 1 st¼ck
55.34.9.220.0040	4 Pole (4CO 4PDT) 7A / 15A max.250V AC Nennleistung AC1: 1750VA Nennlast AC15 230V AC: 350VA Schaltverm¼gen DC1: 30/110 / 220V = 7 / 0,25 / 0,12A Standardkontaktmaterial = AgNi (Hilfsrelais werden mit 15-teiligen 9404SMA-Buchsen geliefert.)
87.02.0240.0001	Time setting from 0.05 seconds to 60 hours: Contact Configuration: 2Pole (2CO (DPDT) 8 / 30A 250 / 400V AC 2000VA 400VA breaking capacity DC1: 30/110 / 220V: 8 / 0.5 / 0.2A Switching load: 300MW (10V / 5mA) AgCdO
34.51.7.012.0010 / 12V 6A	
95.75	Relay socket PL21 + 095.71 Retaining bracket
HC40-200N/DOT	
Relay Socket [95.05	
Relay Socket [94.74	Type:RAIL,RELAY BASE
TYPE:MEX 10/TB 0.37 KW	
9505SMA	
40.52.8.230.0000	
40.52.9.024.0000	
TLA-F50-0-0606-0411-C1-D-M24	API Tank Level Alarm TLA™ TLA Electronic Part Process Connection Flange DN 50 PN 10-40 Product Pressure Standard 1st Switch Point 0606 Length of 1st rod in mm L1 (specify length in mm 4 digits) 2nd Switch Point 0411 Length of 2nd rod in mm L2 (specify length in mm 4 digits) Output Signal C1 - Current 14 mA ("dry")/ 7 mA ("wet") Certification Det Norske Veritas og Germanischer Lloyd (DNVGL) Cable Inlet Cable inlet M24x1.5 inner thread
SINGLE CONTACT FINDER RELAY, Type: 24V 12A,	, 40.51.7.024.0000
HC40-20CN/DOT	
46.61.8.230.0054	
46.61.8.230.0054 -SOCKET	
14*16 HPP206	THROAT BUSHING, PART NO.: 217004, PARTS FOR "FINDER" CENTRIFUGAL PUMP
60.13.4.011.0040	Current relay 0,085....0,15A with coil AC/DC series 60 ; 3Pole
60.13.4.021.0040	Current relay 0,17....0,25A with coil AC/DC series 60 ; 3Pole
71.51.8.230.1021	10A ; Programmable Universal Current Monitoring Relay ; SPDT-CO ; 250VAC
55.34	
553390245090	
D8435 A276gr420	
553490240040	
465282300040	
70.61.8.400	

Ac150-250e/Agt
9403sma
Made
553480245050
38.5170240050
553480480054
553480240050
405270240000
Hc65-250
553382305050
553480245054
94.04.0
439404
553382300010
405290240000
403170240000
553390242090
44.52.8.024
9980902499
553292200040
553480065050
9472
Ba286573
97.02spa
601282300040
44.52.8
9021sma
553390600090
553480120050
553380120010
4340619024
405290120000
553480480050
553391250010
95.75
120_03g0.75

553480240030
34.51.7.012.0010 - R¼le
810102300000
Fin406180240000
553481100054
4340317024
D8436 A276gr420
3451
4340528230
553482300050
553292205040
40.31.9.018.0000
601381100040
553392205010
4380010240
553480480030
405281100000
9482
Led 9901.9024.99
95853spa
553282300040
553390120090
553381100010
553390240080
095913
553391100010
439021
553380240050
553382300030
9404sma
9404
553480245040
553480245001
553391250090
34.51.7.024.0010
Hc65-250 9564

406190240000
553390120070
286573
553480242050
43601390240040
40.52.8.230
30227012, 0000
Fror74g2,5m
553380480010
553390240010
553390245000
551390240000bob-24vdc
55.34.8.110.0054
553480425040
405190240000
40318110
9505sma
553382300000
43553480240054
553290240040
Fror74g1,5m
553382400010
120 04g0.75
40319024
26.01.8.230.0000
80.01.0.240.0000
553380060000
5534823000040
553480485030
553292205020
553390120010
553480240000
553480125040
553480060040
553390242000

55.32.9.024.0094
40.8/10/16a
99.02.0.230.09
553480420050
D31019 Rev1 A276gr420
553390240090
553480242040
38.81.7.024.9024
553480120040
40.52.8.024
553390245010
72a100001000
948430
553390060010
Czooolo
553381200010
601380240040
553390602000
553392200010
43553490240040
439505
6013
Hc65-250 D6672 A351cf8m
553291250090
439403
26-01
553381150010
553390600010
601281100040
553382302030
553480240040
D6059 8as40
55.34.8.024.0040
553382400030
D38969 A576ty1045
553490240020

553390240000bob-12vdc
9901902499
44-95.75
9473
553480240054
553380240010
553382300050
44.52.9.024
55.32.8.110.0054
55.34.9.024.0040
553480420040
40.61.7.024.0000
553390245070
553480120054
553390245001
601390240040
55.34.9.024.0094
44.52
553380245010
741453
553390240060
44-95.05
5533
553280240040
553390240070
553480125050