

Finetek



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Finetek Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Finetek Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
EFB-1420	Float Type EFB-1420 1. Housing material:P.P. (IP67) 2. Switch Component:Reed Switch 3. Switch Form: SPDT Hold type 4. Contact Rating:1A/30W 240Vac/200Vdc 5. Operate Temp.: -20~140°C (tank inside temp.) 6. Cable Length: 2M (PVC Cable)
Rotary Paddle Level Switch	Order code: SEX20000-BAEAAA703H00713000T02 Model: SE3810ECRH3000+TB Customer No: SE3810ECRH3000S Supply voltage: 24Vdc Housing: Aluminum, IP65 Applicable S.G.: 0.3~1 g/cm3 Paddle shapes: Scimitar Connection:3/4"PF Screw Lead wire:3000mm cable Display status: Green (Stopped), Red (Working)
15DC37576	
651071157	
AB1010	
AB1032	
AB3010	
AC1060S	
AE510	
AX10000-FBASB103RMB331000	
BAH-30	
BAH60	
BAH-80	
BAH-80 = AA2080	
BVK-10	
BVK-13	

BVK-13 (AB1013)
BVK-20
BVK-25
BVK-25 (AB1025)
BVP-30C (AC1030C)
BVP-30S (AC1030S)
BVP-40S (AC1040S)
BVR-065
BVT 08 (AB3008)
BVT 10 (AB3010)
BVT 20 (AB3020)
BVT-08
BVT-25 (AB3025)
BVT-36
CWY-BO 810800-50-03-01-01
EB4300-DR00500
EB43113A20500
EB5301-FQ5000
EBB-0612
EDX40000-0CR
EGS152-AF1010-105
EGS152-AF1010-115
EPR10CBA00ADF4
EPR10FBA00ADF4
EPR10CBA00ADF4
FA-CC05
FAMC03
FAPW03
FASA05
FC PV1 3DA 20P

FC-1RFP210200A
FCCFN6F441500A(1400)
FCH11QDD05P
FCH11QDD05X
FCH21PDA05X
FCH21PDD05
FCH21PDD15X
FCH23FDD05D
FCH33FDD25X
FCH61PDA
FCM10000-H1181DD230005
FCV11QFD05P
FCV21QDA05X
FCV21QDA05X
FCV33FDA
FCV33FDA05X
FD3061DA05P
FD5001DD05X
FD5062DA05X
FD7NDRAS140500A
FDBEM3S210200
FDBEM3S220235
FDM30000-30MBVDA291005
FDMH50-BR
FDMRN50COB
FDNDVAS140500C
FGABFQ4S31500 (1050)
FGCCFR4S30600
FGDBHN7S53000
FGDCFQ5P31500
for SEB-0261-B

FTEPR10CBA00ADF4
FTFCH21PDD05X
FTFCH23FDD05X
FTFDMH50BR05X
FTSC2100RODQ0500
FTSP2000BRN2
FTSP200LBQA2
LR-1011
PT-7320-S4000-0
PT-7620-S101-00
PT-7620-S111-10
PT7620-S441-00
PT-7620T1010-0
PT8320-SO-1111
RP80DCRG3000 >>> NEW NR. SE280DCRG3000
SA128A
SA130BEN0500
SC2110R6DQ500
SC2110R6ET0300L
SC24100-DDR+TB
SC28000-DCQ
SC281L0DCQ
SD20 4 AR NO-10m
SD20GM2N1
SDX2003A-AAA401 MAAPAAA2000
SE110BDRA0105
SE110CEUA0500
SE110EDRA
SE111ADMF
SE120EGMA0500(200)

SE130EGMA1500
SE280B
SE284DCR10150/5000
SE3800ACRG3000
SE3800BCRI
SE3800BCRI0300
SE3800DCRG1000
SE3800ECRI0300
SE3802DCRG3000
SE3805BCRFS
SE3810ACRG3000
SE3810BCRG3000
SE3810ECRH5000
SE3815DCRI5000TA
SE3815ECRI0150
SE3815ECRI0150/5000S
SE3815ECRI5000
SE3820BCRG3000
SE3820BCRI0300
SE3820DCRG1000
SE3820DCRG3000
SE3824BCRI
SE3825BCRI
SEB-0261-B
SER255ECRH3000
SEXBA1X-0008
SF 1710
SF1800
SFX10000-A1EAAA801MAX
SP200-6-BU-P2

SP202 0 2U A 0 0050	
SP20202UA-0-0050+TA	
SP202-0-2U-A-2-0050+TA	
SPX10000-AACA507MAB0040	
VP-30S	
VR 100 (AB2100)	
VT20	
SC1740R	SCX1001C-AABCAAA801MA000105 Tuning Fork Level Switch Type: Standard Certification: ATEX-Ex d Construction: Standard Power supply: 20~250Vac/Vdc 50/60Hz; Relay O/P- Euro terminal Connection: 1" PT Probe Material: SUS 304 Length: 105MM Weight: about 2.5 kg / per pcs
SE141BGMB0300	High-temp model with shaft protective tube type Voltage: 220Vac Connection: 2-1/2" x 5kg/cm2 (Standard thin flange) Paddle shapes: 65*80 (W x H) Length: 300mm
Model # SD204BRP1-A	Order Code# SDX1003A-AAA517MAAPBA0000 Model # SD204BRP1-A Housing Material: SUS304 Connection Thread:1/2"G Output:PNP Transmitter Material:PES Power Supply:10~28 VDC Contact:Normal Open (NO:actuate into water) Outlet Type:M12 Operating Temp:-10~125C Qty: 50 pcs (MOQ)
SEX20000-AAEAAA703H00713000	ROTARY PADDLE LEVEL SWITCH Model: SE3800ECRH3000 HOUSING: ALUMINUM COVER SUPPLY VOLTAGE: 24VDC CONNECTION: 3/4" PF PADDLE: PC SCIMITAR(120 x 98) CABLE LENTH: 3000MM Weight: approx. 1.90 / per unit
SE290BERH050	Rotary Paddle Level Switch(Mini Type) Order Code# SEX40000-CABAAB103H0500 Model: SE290BERH0500 Ambient temperature :-20°C ~ 80°C Power supply: AC220V Connection: JIS, 1-1/2", PF male Paddle model: PC; Scimitar type 120x98(WxH) Length: 500mm
SA111A	FineTek-Capacitance Level Switch Order code: SAX10000- BDAAA801RMA330250 Standard Model (12.7 Standard Type) Power supply: AC100V~240Vac (Rotary knob) Connection: Thread, 1"PT Output signal: Relay Probe material: SUS304 Insulated material: UPE Probe length: 250mm
Order Code# FCM10000- V2181DD230002	Model: FCV21QDD02P Mounting: Top or bottom mounting Type: Type 2 Material of Wetted parts: PP(Foam float), PP(Floating pole) Switching Capacity Max: 50W 240VAC/200VDC SPST Contact Model: Normal Closed Reversible Material of Lead wire: PVC (80BC AWG22) Lead wire length: 200 mm
Order Code# FCM10000-V2181DE230002	Model: FCV21QDE02P Mounting: Top or bottom mounting Type: Type 2 Material of Wetted parts: PP(Foam float), PP(Floating pole) Switching Capacity Max: 50W 240VAC/200VDC SPST Contact Model: Normal Open

	Reversible Material of Lead wire: PVC (80BC AWG22) Lead wire length: 200 mm
Rotary Paddle Level Switch	Order Code# SEX50000-AAEAAB103G0300T Model: SE110EERF0300 Customer label: SE255EERF Housing: Aluminum cover Power supply: DC 24V Connection: ANSI/ASTM, 1-1/2" PF Paddle model: 132 x 100 Length:300mm
SPX10000-AACA507MBB0040	Model: SP200-6-BU-P-2 Standard Construction: Compact type Connection: ANSI, 1/2", NPT male Material: SUS316 Output signal: PNP Length: 40 mm Cable Length: 2m
Tuning Fork Level Switch	Order Code# SCX1007C-CABCACB107MA000300 Model: SC1741R0EU0300 Standard Certification: NEPSI-Ex d Construction: Ultra extension type Power Supply: C :20~250Vac/Vdc, 50/60Hz ; Relay O/P - Euro terminal Connection: ANSI, 1-1/2", NPT male. Probe Material: SUS304 Probe Length: 300 mm
Rotary Paddle Level Switch	Order Code: SEX20000-AAEAAB103S00710300T01 Model: SE3800EERF General Type Housing cover: Aluminum cover Operation temperature: -40'C~85'C Supply voltage: 24Vdc Contact capacity: 5A/250Vac, 5A/30Vdc Connection: 1-1/2"PF Paddle shape: Scimitar
SD204BRP1-A	
SEX20000	
SE290BERH0500	Rotary Paddle Level Switch (Mini Type) Order Code# SEX40000-CABAAB103H0500 Ambient temperature :-20°C ~ 80°C Power supply: AC220V Connection: JIS, 1-1/2", PF male Paddle model: PC; Scimitar type 120x98(WxH) Length: 500mm
Bvr-65 (Ab2065)	
Ff20bhm	
Sdb-B0	
Se284ccrk	
Sc2210x	
Fch23fdd05x Grenzscharter	
Se146 A/B/C/D/E	
Bvt 10 (Ab3010) Pneumatischer Vibrator Turbinenartig Vt-10	
0420433 Sensor Fd-1s110065	
Bvk 20 (Ab1020)	
Se3800eerf	Rotary Paddle Level Switch AL cover Power: 24Vdc Thread connection 1-1/2" PF(G) Stainless steel scimitar paddle

Edsd_11
Se141adnd0500
Se180dcrg3000 Yerine Se280dcrg3000
Se3800eclr
Pb_1471_T02_4120
Fgdbhn7s53000 Magnetic Float Level Indicator
Sc1410x
Sa160 A/B/C
Fch21pdd05x Schwimmersensor
Fdmrn5b0b
Sc1600x
Pt7620-S11100
Sc2300x
Se111adm
Fd7 D Hm 7 S6 4
Sp200-6-Bq-A-2
Sc1740x
Sc1700x
Se174
Sb1710
Fdmrn5a0b
Sa376 Sa377 Sa378
Sc381
Sd204arp1
Facc05
Ff30a3q
Fd E Dq 1 S1 3
Sc1420x
Ff15heq
Fcv33fda05

Ff62dfm
Fd Mh50c/56c
Bah-40
Fc H21pd
Fd B Fm 4 S3 4
Sb1712
Se173
Sb2500
Cse110edrs Dn.No:10hb19680
Fd 50 1
Ff12heq
Sc352
Sf 1800 Durchflussschalter 1 Zoll
Fdmm5a0b Marine Level Switch
Se130agma (1000)
Fd 35 1
Sc2200x
Sc2110
Fdmm8c
Ff12dfq
Fch23fdd05x Schwimmersensor
Ab2050 Bvr-50
Bvp-60s (Ac1060s)
S/M 1015 47 Flow Sensor Sp-200-6-Bu-P-2
Sc281
Fdmm5d
Fd 45 1
Ff45dfm
Fd7 D Hq 7 S6 4
Fdmm5d0b

Vp-30s Vibrator
Bvk-16(Ab1016)
Fd K Hq 7 S6 4
Srt
Fch35gd
Fdmh50-Br(05x)
Ff50dfm
Se250eerf
Bvp 30s
Fd E Eq 3 S2 3
Fc-Pv1-3-D-A-20-P Niveauschalter
Se3825bcrl
Sc2510
Fd3501de05x Mini Float Level Switch
Sc1540x
Fd K Hm 7 S6 4
Sa110 Sa111 A/B/C
Fd3501de+tc
??1025 (Vk-25) Vibrator
Bvr-100 (Ab2100)
Sd20
Please see attached Photo
Fd B Eq 3 S2 4
Se190berf 230v/Ac
Ff12bhm
Fd B Hq 7 S6 4
Ff73glo
Fdmh60-Bq Fuel Level Sensor Horizontal Stainless Steel. 50vt240vac
Fgccfr4s30600 Magnetic Float Level Indicator Fgccfr4s30600
Fdmh50abq05x

Sb2120
Fd7 D Fq 4 S4 4
Bvr-065(Ab2065)
Sc1701
Fd7 N Hq 7 S6 4
0420433
Sc1420
Fd Mh60/66
Se177
Fapw-05
Efb-1420,Au15120111 Level Meter
Fch21pda05x Schwimmersensor
Ff20clo
Sa276 Sa277
Fc C Fq 5 P3 4
Efb-1250
Sb1711
Ff75dfm
Fd3501de05x
Fch11qd
Sa130 Sa132 A/B/C
Ac1040s Piston Vibrator (Vp-40s)size Range Of Rubber Mixers 270-20
Fd4001de05
Tx100r
Se3800bcmg1500
Se130ddmf1000
Ff10clo
Ff70/71dfm
Sc2500
Sb17 20 28 50 60

Fapw03 Schwimmer-Grenzschalter
Fd 30 2
Fdsf 11
Sc2120
Pneumovibrator Bvk-10
Fch23fdd50x
Fdmh66-Bq03x
Sc351
Fc Pv2
Fdmrn5a
Fd4001de05x
Ah-80
Bvr-065 Pneumatic Vibrator
Ff90clo
Ff12dfm
Bvk-20 Pneumatic Vibrator
Ff10dfq
Fc C Fq 6 F4 4
Se140 A/B/C/D
Fdsa 21
Fdsa 22
Sensor Sp200-6-Bu-P-2
Bvt-10 Vibrator
Fd Mh50br
Efb-1420 Level Gauge Sensor
Rp80dcrq3000 Gt;Gt;Gt; New Nr. Se280dcrq3000
Famc03 Float Sensors
Pb-1471-T02-4121
Ff10dfm
Ff70/71cfm

Sb17 10 11 12
Sa 150 Bdq 1000
Bah-40 Pneumatikhammer
Pb-2471-T11-4101
Sb2200
Sc380
Sdx 20000-Aaa401maapaaa2000 Optical Level Switch
Fdsa 11
Efb 1250
Facc03
Sb2600
Sa180 Sa181
Se110b
Bvp-30s
Se3824bcric
Pb-2471-T11-4100
Sc350
Fch33fd
Fdmrn8c0b
Ff20dfq
Fdmrn8d0b
150 Bdq 4000
Sa140 A/B/C
Sc2100r
Sb 2 10 11 12 20
Sc2800
Sd21
Vt-25
Ff12ceo
Ff10heq

Sc1400
Fd 30 1
Pb-1471-T02-4120
Fd5003g
Ff12ceq
Ff12clo
Pb-2471-T11-0000 Obsolete/ Replaced By Pb-1471-T01-0000
Fdmrn5c0b
Fcv21qda05p
Fch23fd
Fdmrn8b0b
Fd 40 2
Se255eeref
Fdmh60-Bu05x
Faccx6
Fd 50 2
Sa120 Sa128 A/B/C
Se140a3uf
Sez55eeref
Fd Mh60a/66a
Sc2100r0dq0500
Sc1710x
Fd E 3m 1 S1 3
Fc C Fn 5 P3 4
Bvr-50 (Ab2050)
Ff20cem
Fd-30-0-2-D-D-05x
Se111eqmf
150 Bdq 1500
Sa372 Sa375 Sa374

Cse110edrs
Efb-1400
Sc2400
Fd Mh60c/66c
Sc1741
Se3 20 24 22 25
Se110edra Sensor Rp101 (Se110 E 24vdc) Bestellnummer Se110edra
Fapw05 Schwimmer-Grenzschalter
Ff20dfm
Fd3061da05x
Fd-1s110065
Se172
Se141 A/B/C/D
Sc1740r0fw0105
Ff20dlo
Fd E Ej 4 S4 1
Fdmh50br
Bvp-60s
Fc H31pd
Bvk 13 (Ab1013)
Sc1400x
Ff70/71bhm
Sa370 Sa371 Sa373
Ff10ceq
Fd E Ek 3 S2 1
Sc24
Bvk-16 (Ab1016)
Se3 0 2 3 5
Fd B Fq 4 S4 4
Vibrator Bvp-60s

Sp202 0 2u A 0 0050 Sensor Duct
Sc1741x
Sd22
Fdsc 11
Fdmrn5b
Level Sensor For Se250
Ff55dfm
Sa278 Sa279
Fd3062da05x
Fd7 D Fm 4 S4 4
Bvp-30s Bvp-30s
Sd 220
Sc2100x
Se284bcric0300 Sensor
Sb1760
Se120
Fdmh66 Bq03x
Fch21pdd (Hexagon)
Fc Pv1
Sc2811
Se110 120 130
Facc20
Fdmrn5cob
Ff10cem
Fc H51pd
Sc35
Fc C Fn 6 F4 4
Fd Mh50/56
Sb1750
Fch21pd
Ec1300fx1100

Sc2110x
Ff80efm
Bvr-80 (Ab2080)
Ff40dfm
Se3800dcrq3000
Eb52a0-Dq1000
Bvk 32 (Ab1032)
Bvk-25 (Ab1025) Pneumatischer Vibrator
Se130egma1200
Sb2110
Fdsa 12
Ae 510
Fdsb 11
Facc10
Vt20 Pneumatik Vibrator Vt20
Sc1110 = New Article Sc2100r0dq0500
Pb2471-T118000
Sa270 Sa271 Sa273
Bah Pneumatic Vibrator
Sb1728
Ff20ceo
Se130
Fch23fdd05x
Fdm10000-06maca501291005
Se255ecrh3000(By Se3800ecrh3000)
Fas 75 Sus 304 Schwimmender Kabel- Level-Sensor
Fd E Em 3 S2 3
Se111admf Rotary Paddle Level Switch110vac, 5a/250vac, Flange: 1"x5k
Fd B Fq 4 S3 4

Se290bcrg0300
Sc241x
Bvt-08 Turbine Pneumatic Vibrator
Sc1740
Fdmrn8a0b
Se3820bcric0300
Se171
Ff10bhm
Sdx 20000-Aaa401maapaaa2000 Niveauschalter Optisch
Se111
Se280dcrg3000
Sc28
Sb1720
Ff12cem
Tx101f
Fg Tab-2100
Fdmrn5c
Se170
Sc1410r6eu0300
Se141bssb0500
Fd7503g
Se176
Circled In Red Parts For Flowmeter Sp-200
150 Bdq 3000
Famc05
SD204BRP1-A Optical Level Switch 1. Material: SUS304 2. Protection: IP67 3. Operation Temperature: -10~125 °C 4. Ambient Temperature: -10~80 °C 5. Operation Pressure: Max.40kg/cm² 6. Load Current: Max. Load 100mA 7. Overload Current Protection: 100mA 8. Power: 10~28 Vdc 9. Connection Thread:1/2"G(PF) 10. Lead Wire: 2m CABLE(dia. 3.8) 3C PVC 23 AWG (optional) 11.Output:PNP , Wet In Liquid NO Weight:560g

Se3800bcri0300	
Fd B Fm 4 S4 4	
Sc240x	
Fd 75 1	
Fd B Fm 7 S6 4	
Ff81e	
Fc Pv3	
Fd7 N Hm 7 S6 4	
Fcv33fda05 Sensor Schwimmerschalter	
Fch25gd	
Se3 7 8	
Se160 A/B/C/D/E	
Se3800ecri0300	
Sb2280	
Sa150 A/B/C	
Se280	
Se140 160	
Eb5301-Eu2000	
Fdsc 61 1 Da 10 F	
Fcsbt8f251020a + Ta	
Efb-1420	Float Type EFB-1420 1. Housing material:P.P. (IP67) 2. Switch Component:Reed Switch 3. Switch Form: SPDT Hold type 4. Contact Rating:1A/30W 220Vac/200Vdc 5. Operate Temp.: -20~140°C (tank inside temp.) 6. Cable Length: 2M (PVC Cable)
Fdmh50br05x Float Liquid Level Sensor	
Sd20gm2n1-A Optical Level Switch	
Se175	
Eb4300-Dr00500 Niveausensor	
Sc1701x	
Bah-40 Pneumatische Hammer Ah-40	
Fdmh50br05x	

Sc1700	
Fd K Fm 4 S4 4	
Fcsbt8f251020a+ta	
Fch31pd	
Efb 1420	Float Type EFB-1420 1. Housing material:P.P. (IP67) 2. Switch Component:Reed Switch 3. Switch Form: SPDT Hold type 4. Contact Rating:1A/30W 220Vac/200Vdc 5. Operate Temp.: -20~140°C (tank inside temp.) 6. Cable Length: 2M (PVC Cable)
Sp200-6-Bu-P2-0031	
Sc1540	
Edx40000-0cr Speed Monitormodel	
Ff20ceg	
Eb5300eq9000+ta	
Fdmh50cbr	
Fh Dm 4 S3 1	
Fd 40 1	
Bvk 10 (Ab1010)	
Fch23fdd05d Schwimmersensor	
Sa128	
Fdse 11	
Ec1210em	
Eb4301du01000	
Sc280	
Fd K Fq 4 S4 4	
Fd4503d	
Fd 45 2	
Sc1710	
Fcv33fda05p	
Bah-80 Bah-80 (Aa-2080)	
Fd3061da05p Magnetischer Niveauschalter	
20000-Aaa401maapaaa2000 Optical Level Switch	

Sa272 Sa275 Sa274	
Fgabfq4s31050	
Sc1410	
Se111egmf	
Eb4301-Da20500	
Fdmrn5c Hochwassersensor	
Fdmh50cbr Horizontal Mini Float Level Switch Insus304	
Sc1600	
Sb 2 28 50 60	
Sp2000brp2(0031)	
Sb2100	
Fm Fm 4 S3 1	
Fd B Em 3 S2 4	
Sc2300	
Sc382	
Bvt-25 (Ab3025) Pneumatischer Vibrator Turbinenartig Vt-25	
Ff10ceo	
Se3815dcric0150	Rotary Paddle Level Switch SE3815DCRI0150/5000 general Type Hausing: Aluminum cover with LED Lamp Model: High temperature shaft protective tube 1. Voltage: 24Vac, 50/60Hz 2. Mounting: 3/4"PF 3. Paddle: Stainless steel 100 x 30mm (W x H) 4. Length: 150mm 5. Contact capacity: 3A/250 Vac 6. Protection/material: IP65 Temperature: - 20~70°C
Fc H41pd	
Sp200-0-Br-B-5	
Fd3501de	
Fch21pdd05x	
Sc2500x	
Fd Mh50a/56a	
Se110	
Fdmh60-Bq	

[Se110berf0500](#)

[Sc2100](#)

[Sc38](#)