



## Finish Thompson Inc

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Finish Thompson Inc** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Finish Thompson Inc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">DPFV012</a>	PFV40 pumping station, pipe length: 102 cm Pipe diameter: 2 inches (5.1 cm) Material: PVDF; Shaft: Alloy 625, FKM O-rings, impeller: PVDF Hose connection: 1 inch (DN25)
<a href="#">106658</a>	Drum pump motor M5V Voltage: 1 x 230V / 50Hz Power: 650 watts Speed: 3,500 to 10,000 rpm Degree of protection: IP24 Viscosity: maximum 500 mPa s Connection cable: 3.5 m with Schuko plug Extras: quick release
<a href="#">DB11P1009</a>	Pumpe DB11P-B-6-94
<a href="#">DB15V1240</a>	Pump DB15V-B-7-10P-24
<a href="#">M6X</a>	drum pump motor A101125 Drive: compressed air Connection: 5.5 - 6.9 bar at 25 - 54 m <sup>3</sup> /h Power: 600 watts output power Speed: 300-6,000 rpm - adjustable Viscosity: maximum 330 mPa s
<a href="#">DB5.5P1012</a>	Pump DB5.5P-B-64
<a href="#">DB15 MAGNETIC COUPLING PP BODY</a>	Flow rate: 20 m <sup>3</sup> /h Pressure : 21 mSS Pump body : Polypropylene Bearings: Teflon O-Rings : Viton Input / Output: 2" F-BSP / 1 1/2" M-BSP Engine : 2.2 kW 2 FINISH THOMPSON, DB15 MAGNETIC DRIVE CENTRIFUGAL PUMP Flow rate: 20 m <sup>3</sup> /h Pressure : 21 mSS Pump body : PVDF Bearings: Teflon O-Rings : Viton Input / Output: 2" F-BSP / 1 1/2" M-BSP Engine : 2.2 kW
<a href="#">DB15V1240</a>	Pump DB15V-B-7-10P-24
<a href="#">MG112344K3</a>	e-mot. 3 x 400/690V, IEC 112, IMB 34, 4.0 kW, 2-pin. IE3 3xPTC
<a href="#">DB22P1549</a>	Pumpe DB22P-T-B-2-24
<a href="#">DEFV004</a>	Pumping station EFV48 Tube length: 122 cm Tube diameter: 33 mm Material: PVDF; Shaft: Alloy 625, FKM O-rings, Impeller: ETFE Hose connection: 3/4 inch (DN20)

<a href="#">107324-2</a>	Barrel pump motor S2 Voltage: 1 x 230V / 50-60Hz Power: 110 watts output power Speed: 8,000 / 14,000 rpm - switchable Degree of protection: IP24 Viscosity: maximum 300 mPa s Connecting cable: 3.5 m with Schuko plug
<a href="#">DEFV003</a>	Pump station EFV40 Tube length: 102 cm Tube diameter: 33 mm Material: PVDF; Shaft: Alloy 625, FKM O-rings, impeller: ETFE Hose connection: 3/4 inch (DN20)
<a href="#">DSFVV003</a>	Pumpwerk SFVV 40
<a href="#">DPPFM003</a>	Pump station PFM48, pipe length: 122 cm Pipe diameter: 2 inches (5.1 cm) Material: Polypropylene, PTFE, ETFE ; Shaft: stainless steel 316, FKM O-rings, impeller: PVDF Hose connection: 1 inch (DN25)
<a href="#">106658</a>	Barrel pump motor M5V Voltage: 1 x 230V/50Hz Power: 650 watts Speed: 3,500 to 10,000 1/min Protection class: IP24 Viscosity: maximum 500 mPa s Connection cable: 3.5 m with Schuko plug Extras: quick release
<a href="#">DB11V1227</a>	Pumpe DB11V-T-B-6-94
<a href="#">MK309 ATEX EEx II3 G2 D22 - 2900RPM 0.18KW</a>	
<a href="#">DB5.5 PERFORMANCE 3450 RPM</a>	
<a href="#">BARRIER SHAFT CERAMIC DB-SP22</a>	pos5
<a href="#">DB22 Sealless</a>	5.5 kw Exproof Electric Motor PVDF Body Magnetic Driven (Without Seal) Pump Connection: BSP (Threaded) Bearings: Carbon O-Rings: Viton Inlet Diameter: 2" FBSP Outlet Diameter: 2" MBSP Fan Diameter: 7.00" (17.78 cm) Non-sparking ring (for ex-proof motor) ATEX
<a href="#">DEFP003</a>	Pump station EFP40 Tube length: 102 cm Tube diameter: 32 mm Material: Polypropylene; Shaft: stainless steel 316, FKM O-rings, impeller: PP Hose connection: 3/4 inch (DN20)
<a href="#">DEFP003</a>	Pump tube EFP40 Pipe length: 102 cm Pipe diameter: 32 mm Material: polypropylene; shaft: stainless steel 316, FKM O-rings, impeller: PP Hose connection: 3/4 inch (DN20)
<a href="#">107324-2</a>	Barrel pump motor S2 Voltage: 1 x 230V / 50-60Hz Power: 110 watts output Speed: 8,000 / 14,000 rpm - switchable Protection class: IP24 Viscosity: maximum 300 mPa s Connection cable: 3.5 m with Schuko plug
<a href="#">DEFV004</a>	Pump station EFV48 Pipe length: 122 cm Pipe diameter: 33 mm Material: PVDF; Shaft: Alloy 625, FKM O-rings, impeller: ETFE Hose connection: 3/4 inch (DN20)
<a href="#">107324-2</a>	Barrel pump motor S2 Voltage: 1 x 230V / 50-60Hz Power: 110 watts output Speed: 8,000 / 14,000 rpm - switchable Protection class: IP24 Viscosity: maximum 300 mPa s Connection cable: 3.5 m with Schuko plug
<a href="#">Db15v - Ff - 6 - 10p - 24</a>	

[Db 15v-B-7-10p-24 Asit Pompasi](#)

[Db22p-B-3c-35](#)