

Fluid O Tech



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Fluid O Tech Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Fluid O Tech Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
110238.17	
1108aaam3e0000	24 V 50/60 Hz 45W SELENOİD PUMP
Tmss101n	Rotary vane pump magnetic coupling Stainless steel bypass. with 1 spacer pin
Tmc7-N	Drive 90W 1AC230V50 / 60Hz IP20 0.82 / 0.95A 5mF n = 2900/3500 with fan CO15509, thermal protection, attachments-N
Pa_801g	"HIFLOW" rotary vane pump, brass with bypass, G = 1/2 ", NSF
Type: 110238.17	
Po_811vg	"HIFLOW" rotary vane pump. Stainless steel. Seal: (Viton), G 1/2 "
Pa_304g	"ROTOFLOW" rotary vane pump, brass Bypass relieved, G3 / 8 ", NSF
Messinggehuse Der Serie Po 70-400	
Pa_301 X - Brass Rotary Vane Pump	
P00301agcne0000 Wps	
FG309XPS24T	"Integral pump" assembly, consisting of: MINI gear pump 316 / PEEK, without bypass, connections 1/8 "NPT in line, O-rings PTFE, DC motor 24V, brushless, control voltage 0.3-5V for 300-5000 RPM
PA_401G	"ROTOFLOW" rotary vane pump, brass, Bypass, NSF, G 3/8 "
	"Integral pump" assembly, consisting of: MINI gear pump PPS

FG313RPS24V	/ PEEK, without bypass, connections 1/8 "NPT in line, O-rings FKM, DC motor 24V, brushless, control voltage 0.3-5V for 300-5000 RPM Usage: Replacement for identical pump with article no. FG313RD0PV10000
PO_611VG	Rotary vane pump. Stainless steel, bypass, O-rings: Viton. G1 / 2 " + PO-22347 Lantern BG71 (PLAST) "Rotoflow" + PO-22350 Coupling BG 71 'Rotoflow' Brass / rubber + MOFU-0.37 / 1500-PEL Three-phase motor 230/400 V, 50 Hz, 0.37 kW at 1350 rpm with integrated frequency converter, EMC class C2 according to EN61800-3, Supply voltage 1x230V, 50Hz, output frequency continuously adjustable from 10-100Hz, optionally by hand via potentiometer or via analogue signal 0-5V, 0-10V, 0-20mA. Protection class IP55, cable 1.5m + Schuko plug, programmable analog Inputs, potentiometer, on / off / right / left switch ----- Use: Monethylene Glycol 50%, T = 60 ° C Desired performance: Approx. 10LPM against 4bar differential pressure Available power: According to the M-M characteristic, moreover, continuously adjustable via a frequency converter. Motor power sufficient for differential pressures up to 6bar
Elektropump Type 110380.20	
PA 401G	"ROTOFLOW" rotary vane pump, brass, Bypass, NSF, G 3/8 " Usage: replacement for rotary vane pump PA3601
(nur die NFS	11038-0.20 1400 rpm
MG209XTB17 + D256K34-55U	1 MG209XTB17 MINI gear pump 316 / PTFE Bypass. Connections in line 2 MGB03 Lantern for BG56 with MGA09 3 D256K34-55U Motor 90W 3AC230 / 400V50Hz IP55 WKL "F" n = 2800 K21-56K2U unventilated
PO-E483X55	Sondermotor 640W 1AC230V50Hz(16) IP55 n=1250 4.6A CLF TS #110238.17
MGK317XPS07T+MGCK11S-24	MGK317XPS07T MINI gear pump 316 / PEEK / PTFE, without bypass Connections in line. O-rings PTFE + MGCK11S-24 Motor + attachments, consisting of: Motor 24VDC, 50W, n = 3300, lantern, magnet "rare earth
PO-E483X55 110238.17	
TMCF01S	
TMCF07S	
MGCF03S	
MGCF07S	All: Flow rate: 10-15 LPM Pressure : 4-5 bar Voltage: 220V Pumps should operate at an average pressure of 4-5 bar between 10-15 LPM flow rate. Average values are provided in the working graphs of the models I have mentioned above. For this reason, I ask you to pay attention to this criterion in the other options you will offer.
	unser Kunde sucht eine geeignete Pumpe: Es sollte für den Dauereinsatz von Chemikalien wie Heizöl, AdBlue etc. geeignet sein. Durchfluss (Druckbereich etc.) Kennlinien und

Pumpe für den AdBlue	Grafiken (Pumpenkurven) des jeweiligen Modells können sie uns wenn verfügbar Model vorschlagen mit Datenblatt.
110238,17 / 230 v / 630 W / 1250 RPM	motor und komplett
MGK313XPS07T	MINI gear pump 316/PEEK/PVDF, without bypass connections in line. O-rings PTFE Corresponds to the item code on the pump MK313XE0PT00000 + additional Conversion of the pump to elastomer silicone
PA 601G	"HIFLOW" rotary vane pump, brass Bypass. Seal:Nitrile, NSF, G=1/2", 1 spacer pin PTFE
PO-E483W55*	Special motor 550W 1AC230V50Hz(14)IP55 n=1360 4.2A CLF TS #110827.02 with two cable glands PG9
PO230AV	
FG404XPS24T	"Integral pump" assembly, consisting of: MINI gear pump 316/PEEK, without bypass, connections 1/8"NPT in line, Ceramic shafts+wear plates, PTFE O-rings, DC motor 24V, brushless, Control voltage 0.5-5V for 500-5000RPM Use: pump identical to item no. FG404XDOCT10000
CD119	
MG209XTS17	MINI gear pump 316/PTFE connections in line
MG304XPS17T	MINI gear pump 316/PEEK/PTFE Connections 1/8" in line MGC11 Drive 24 VDC n=3100 consisting of: MG-GM42x30I, MGA05, MG-60380-R1
PA 801G	"HIFLOW" rotary vane pump, brass with bypass, G=1/2", NSF
FROB 50 D 3/8 L 35 (17/15	
PA 401G	"ROTOFLOW" rotary vane pump, brass, By-pass, NSF, G 3/8"
PA 401G	ROTOFLOW" rotary vane pump, brass, By-pass, NSF, G 3/8"
PA 801	S/N: 2L6FS
PO-E483X55	Special motor 640W 1AC230V50Hz(16) IP55 n=1250 4.6A CLF TS #110238.17
110238.17	
TSFRSS300	Rotary vane pump stainless steel Integral motor+control 1AC230V50/60Hz
EVO 00888 90-76-04/82040011	
PA 401G	"ROTOFLOW" rotary vane pump, brass, By-pass, NSF, G 3/8"
PO-E483X55	640W 1AC230V50Hz(16) IP55 n=1250 4.6A CLF TS #110238.17 Application: Replacement for identical motor with designation 110238.17
110238.17	

PO-E483X55	Sondermotor 640W 1AC230V50Hz(16) IP55 n=1250 4.6A CLF TS #110238.17
MGKP409T	Repair kit for MG/FG409 ceramic/ceramic PEEK/PTFE consisting of: set of shafts+gears(9), set of bearing bushes(6), set of housing seals(4,10) Use: spare parts for pump marked FG409XDOCT10000
PA401	Connection : 3/8" , TechPA401 rotoflow high pressure pump
Motor suitable for pump	373 W, 1400RPM , 3,5A , 230V-50HZ Rotoflow pump motor
13 K05100	
Pa074	Pumphead PA074 FLUID-O-TECH L 82mm 70l / h connection 3/8 "gas with bypass Brass
13 K09151	
Fg309xps24t	Assembly "integral pump", consisting of: MINI gear pump 316 / PEEK, without bypass, connections 1/8 "NPT in line, O-rings PTFE, DC motor 24V, brushless, control voltage 0.3-5V for 300-5000UPM
Po4060	Rotary vane pump 1600l / h connection G 1 " Stainless steel 303. without bypass DIVERS INCLUDED
Pr 3 Ase Series	Type : 110380.20 PR 3 ASE Series Pump
1108aaam3n	
1106pakm1n	
17wf3	Pump unit - 17WF3
Pa1001g	"HIFLOW" rotary vane pump brass Bypass, G = 1/2, Seal: Nitrile. NSF
90-76-01/82040001	
Mkcs11s	
1206dadlm1n 240v Hz50 W70	
400 L H Pump	
Pa 601g	"HIFLOW" Drehschieberpumpe, Messing
3.040.3.260.01.00	
90-76-04-/82040011	
110380- 20 373w 1400rpm - Pompa Parçası	
1208ndaaooo12	
M36x30	