

Fluitex

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Fluitex Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Fluitex T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
40CM.FLUİTEX E 350-5	
45 CM.FLUİTEX E 350-5	
50CM.FLUİTEX E 350-5	
60CM.FLUİTEX E 350-5	
65CM.FLUİTEX E 350-5	
70CM.FLUİTEX E 350-5	
75CM.FLUİTEX E 350-5	
2022103059900	
2071108049900	
208000031 E 800/4 BREITE 1000MM	
208003041 (AD 800/5 LANGE 50M; BREITE 570MM; DICKE 5MM)	

E 800/5 260x7x250x4	
E 800/5.	
E.800	
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:450 mm used for All air slides FLUITEX® E 350/4
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:600 mm used for All air slides FLUITEX® E 350/4
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:800 mm used for All air slides 250METERS
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:1800 mm used for All air slides FLUITEX® E 350/5
FLUITEX E 350/5	thickness:5mm width:450mm Material: Polyester Thickness DIN 53855:5mm +/-0 3mm 1 250 Meters Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:600mm thickness:5mm Material: Polyester 2 250 Meters Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:800mm thickness:5mm Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:1800mm thickness:5mm Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
Fluitex E 800/4 Rollenware	2011108049900
2012103459900	Fluitex AD 350 roll goods 20,14 m²
An 350	Thickness: 5 mm-1000x1000 mm
E800/5 R1	
269996040 (Ad 800/5 7200 Mm X 550 Mm)	
208000031 E 800/4 Breite 1000mm	
208000031 E 800/4 Breite 800mm	
269991040 600 X 400 Mm	

208003041 (Ad 800/5 Lã196;Nge 50m; Breite 570mm; Dicke 5mm)
3
Ad 800/5 (2111331500000)
41507
208000041 (E 800/5 Lã196;Nge 750m Breite 100mm Dicke 5mm)
An350/5
269996040 (Ad 800/5 1200 Mm X 1200 Mm)
269991040 1990 X 1060 Mm
Ad350/5 (41507)
269991040 2450 X 1060 Mm
20800041 E 800/5
E 800/5
Ad 800/5 (2111331300000)
203000041 E 350/5
269996040 (Ad 800/5 1610 Mm X 1610 Mm)
269991040 2410 X 1060 Mm
269996040 (Ad 800/5 750 Mm X 750 Mm)
30755
Ad350/5 (30755)
20800004 Fluitex E 800/5 Pneumatikgewebe
Fluitex An 350/5
Ad 800/5 (2411338800003)
1
E 1600/5 (241358800000)