

## FLUX GERTE

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**FLUX GERTE** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız FLUX GERTE Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">10-457 01 003</a>	Collector motor F 457EL 230V / 50Hz, 800W , IP24, USS With electronic speed setting, with undervoltage release, double insulated, protection class II, with overcurrent protection switch, 5 m cable and safety plug
<a href="#">10-41600100</a>	470W/6bar with actuation valve (detectable), with silencer, with hose nozzle DN 10 for compressed air hose Ex marking: II 2G Ex h IIC T6 Gb HS Code: 8412 39 00 Origin: DE Weight/unit: 1.3790 kg
<a href="#">10-42422007</a>	Drum pump FP 424Ex S-43/38-700, FKM With zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution: sealless in the liquid area Material: stainless steel (1.4571) Material shaft: stainless steel (1.4571) Shaft bearing: PTFE/carbon Material rotor: ETFE Seal material: FKM Immersion depth / outer Ø: 700 / 43 mm Pressure port: G 1 1/4 A Rotor: axial rotor without hose connection Driven by commutator motor, brushless Motor or air motor possible. *** (Alternative / optional position)***
	Drum pump FP 424Ex S-43/38-1000, FKM with zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution:

## FLUX GERTE

YURSAT yedek para tedariki yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribtr yada temsilcisi deĐildir.

[10-42422010](#)

sealless in the liquid area Material: stainless steel (1.4571)  
Material shaft: stainless steel (1.4571) Shaft bearing:  
PTFE/carbon Material rotor: ETFE Seal material: FKM  
Immersion depth / outer Ø: 1000 / 43 mm Pressure port: G 1  
1/4 A Rotor: axial rotor without hose connection Driven by  
commutator motor, brushless Motor or air motor possible

[10-42422012](#)

Drum pump FP 424Ex S-43/38-1200, FKM With zone  
separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution:  
sealless in the liquid area Material: stainless steel (1.4571)  
Material shaft: stainless steel (1.4571) Shaft bearing:  
PTFE/carbon Material rotor: ETFE Seal material: FKM  
Immersion depth / outer Ø: 1200 / 43 mm Pressure port: G 1  
1/4 A Rotor: axial rotor without hose connection Driven by  
commutator motor, brushless Motor or air motor possible.  
\*\*\* (Alternative / optional position) \*\*\*