

FLUX GERTE

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
FLUX GERTE Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız FLUX GERTE Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
10-457 01 003	Collector motor F 457EL 230V / 50Hz, 800W , IP24, USS With electronic speed setting, with undervoltage release, double insulated, protection class II, with overcurrent protection switch, 5 m cable and safety plug
10-41600100	470W/6bar with actuation valve (detectable), with silencer, with hose nozzle DN 10 for compressed air hose Ex marking: II 2G Ex h IIC T6 Gb HS Code: 8412 39 00 Origin: DE Weight/unit: 1.3790 kg
10-42422007	Drum pump FP 424Ex S-43/38-700, FKM With zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution: sealless in the liquid area Material: stainless steel (1.4571) Material shaft: stainless steel (1.4571) Shaft bearing: PTFE/carbon Material rotor: ETFE Seal material: FKM Immersion depth / outer Ø: 700 / 43 mm Pressure port: G 1 1/4 A Rotor: axial rotor without hose connection Driven by commutator motor, brushless Motor or air motor possible. *** (Alternative / optional position)***
	Drum pump FP 424Ex S-43/38-1000, FKM with zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution:

FLUX GERTE

YURSAT yedek para tedariki yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribtr yada temsilcisi deĐildir.

[10-42422010](#)

sealless in the liquid area Material: stainless steel (1.4571)
Material shaft: stainless steel (1.4571) Shaft bearing:
PTFE/carbon Material rotor: ETFE Seal material: FKM
Immersion depth / outer Ø: 1000 / 43 mm Pressure port: G 1
1/4 A Rotor: axial rotor without hose connection Driven by
commutator motor, brushless Motor or air motor possible

[10-42422012](#)

Drum pump FP 424Ex S-43/38-1200, FKM With zone
separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution:
sealless in the liquid area Material: stainless steel (1.4571)
Material shaft: stainless steel (1.4571) Shaft bearing:
PTFE/carbon Material rotor: ETFE Seal material: FKM
Immersion depth / outer Ø: 1200 / 43 mm Pressure port: G 1
1/4 A Rotor: axial rotor without hose connection Driven by
commutator motor, brushless Motor or air motor possible.
*** (Alternative / optional position) ***