

Flux Pump

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Flux Pump Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Flux Pump T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
10-424 60 212	Drum pump F424 PVDF-50 / 38-1200 made of PVDF ETFE rotor sealless design Hastelloy C shaft Pressure connection: G 1 1/4 A Outside Ø: 50 mm Immersion depth: 1200 mm without hose connection without drive motor
10-424 40 212	Drum pump F424 PP-50 / 38-1200 made of polypropylene (PP) ETFE rotor sealless design Hastelloy C shaft Pressure connection: G 1 1/4 A Outside Ø: 50 mm Immersion depth: 1200 mm without hose connection without drive motor
10-410 14 028	Coupling star (PA)
10-424 41 232	Coupling cage (PA)
10-908 83 019	Spacer sleeve
10-424 41 726	Inner tube F424 pre-assembled PP-50 /.- 1200
10-424 61 726	Inner tube F424 pre-assembled PVDF-50 / 38-1200
10-424 41 036	T-piece (PP)
	Brushless motor FBM 4000 Ex 230V, 50-60Hz, USS & 5m

10-40001000	cable Connection voltage: 230 V Rated power: 0.6 kW Frequency: 50-60Hz Cable length: 5 m Type plug: CEE 7/7 plug Undervoltage protection: yes+no Motor protection switch: no Speed control: yes Protection class: IP 55 Ex marking: II 2 G Ex db eb IIC T5 Gb Cooling: externally ventilated -15.00% HS Code: 8501 40 20 Origin: DE Weight/unit: 6.0770 kg
F430 1000mm	Barrel pump F430 PP-40/33-1000, EPDM Made of polypropylene (PP) Rotor made of ETFE Inner tube made of steel coated with PP, This ensures reliable function of the mechanical seal made of oxide ceramic, PTFE/carbon, O-rings made of EPDM, shaft in the liquid area from Hastelloy C, Pressure port: G 1 1/4 A Outer Ø: 40 mm Immersion depth: 1000 mm without hose connection without drive motor - 15.00% HS code: 8413 70 81 Origin: DE Weight/Unit: 1.3900 kg
F430 1200mm	Alternative Barrel pump F430 PP-40/33-1200, EPDM Made of polypropylene (PP) Rotor made of ETFE Inner tube made of steel coated with PP, This ensures reliable function of the mechanical seal made of oxide ceramic, PTFE/carbon, O-rings made of EPDM, Shaft in the liquid area made of Hastelloy C, Pressure port: G 1 1/4 A Outer Ø: 40 mm Immersion depth: 1200 mm without hose connection without drive motor
10-K0004000	Configuration hose line 10-95904052 (1 piece) hose connection cpl. PP DN 25, G 1 1/4 Made of polypropylene with union nut G 1 1/4 suitable for hoses made of PVC or NBR without thermoplastic inliner 10-95913243 (1 piece) 1-ear clamp, stainless steel Ø=31.8-35.0 mm Stainless steel DIN 1.4301 10-00110041 (2m) PVC hose with wire coil DN 25, AD=34, 5 bar, FOOD For neutral and aggressive non-flammable liquids max. operating pressure at 20°C: 5 bar Temperature: max. 60°C Nominal width: DN 25 Outer Diameter: 34mm approved by regulation EC 1935/2004 10-95913243 (1 piece) 1-ear clamp, stainless steel Ø=31.8-35.0 mm Stainless steel DIN 1.4301 10-00112510 (1 piece) Fuel nozzle PP, DN 25, EPDM Housing polypropylene, seals EPDM, with rotating hose connection and protective bracket Operating pressure max. 3 bar at 20°C Medium temperature max. 50°C Weight/unit: 0.2870 kg
10-00114054	Barrel screw connection PP conductive Thread R2, Ø-40/41 Electrically conductive Ø 40/41 mm with external thread R2 for secure attachment of pumps with Ø 40/41 mm inside Bunghole of a barrel. HS code: 8413 91 00 Origin: DE Weight/unit: 0.0670 kg
10-00114063 Alternative	Screw cap made of PE DN 150 for attaching the barrel pump TPE seal with internal thread G2"
10-00114064 Alternative	Screw cap made of PE DN 225 for attaching the barrel pump EPDM seal
	Collector motor F 460-1 Ex 230V/50Hz Connection voltage: 230 V Rated power: 0.7 kW Frequency: 50Hz Cable length: 5 m Plug type: CEE 7/7 plug Undervoltage protection: yes Motor protection switch: yes Speed control: no Protection

10-46001028	class: IP 55 Ex marking: II 2 G Ex db eb IIC T6 Gb Cooling: externally ventilated Attention: Protective contact plugs must not be used in Ex areas! Explosion-proof plugs (CEAG or STEEL) are available separately from us Mounted upon request for an additional charge.
10-43069112	Barrel pump F430 PVDF-40/33-1200, FFKM Made of PVDF(PVDF) Rotor made of ETFE Inner tube made of steel coated with PVDF, This ensures reliable function of the mechanical seal made of oxide ceramic, PTFE/carbon, O-rings made of FFKM (perfluoro rubber), shaft in the liquid area Hastelloy C, Pressure port: G 1 1/4 A Outer Ø: 40 mm Immersion depth: 1200 mm Driven by collector motor, brushless motor or compressed air motor
F430PP (EPDM)/ FBM4000EX	PUMP SET F 430PP (EPDM)/ FBM4000EX
10-40001000	Brushless motor FBM 4000 Ex 230V, 50-60Hz, USS & 5m cable Connection voltage: 230 V Rated power: 0.6 kW Frequency: 50-60Hz Cable length: 5 m Plug type: CEE 7/7 plug Undervoltage protection: yes+no Motor protection switch: no Speed control: yes Protection class: IP 55 Ex marking: II 2 G Ex db eb IIC T5 Gb Cooling: externally ventilated
10-43048110	Barrel pump F430 PP-40/33-1000, EPDM Made of polypropylene (PP) Rotor made of ETFE Inner tube made of steel coated with PP, This ensures reliable function of the mechanical seal made of oxide ceramic, PTFE/carbon, O-rings made of EPDM, shaft in the liquid area from Hastelloy C, Pressure port: G 1 1/4 A Outer Ø: 40 mm Immersion depth: 1000 mm without hose connection without drive motor
10-43048112	Barrel pump F430 PP-40/33-1200, EPDM Made of polypropylene (PP) Rotor made of ETFE Inner tube made of steel coated with PP, This ensures reliable function of the mechanical seal made of oxide ceramic, PTFE/carbon, O-rings made of EPDM, Shaft in the liquid area made of Hastelloy C, Pressure port: G 1 1/4 A Outer Ø: 40 mm Immersion depth: 1200 mm without hose connection without drive motor
10-K0004000	Configuration hose line -15.00% 10-95904052 (1 piece) Hose connection complete PP DN 25, G 1 1/4 Made of polypropylene with union nut G 1 1/4 suitable for hoses made of PVC or NBR without thermoplastic inliner 10-95913243 (1 piece) 1-ear clamp, stainless steel Ø=31.8-35.0 mm Stainless steel DIN 1.4301 10-00110041 (2m) PVC hose with wire coil DN 25, AD=34, 5 bar, FOOD For neutral and aggressive not easily flammable liquids max. operating pressure at 20°C: 5 bar Temperature: max. 60°C Nominal diameter: DN 25 Outer diameter: 34mm approved by regulation EC 1935/2004 10-95913243 (1 piece) 1-ear clamp, stainless steel Ø=31.8-35.0 mm Stainless steel DIN 1.4301 10-00112510 (1 piece) Fuel nozzle PP, DN 25, EPDM Housing polypropylene, seals EPDM, with rotating hose connection and protective bracket Operating pressure max. 3 bar at 20°C Medium temperature max. 50°C
	Barrel screw connection PP conductive Thread R2, Ø-40/41

10-00114054	Electrically conductive Ø 40/41 mm with external thread R2 for secure attachment of pumps with Ø 40/41 mm Bunghole of a barrel.
10-00114063	Screw cap made of PE DN 150 for attaching the barrel pump TPE seal with internal thread G2
10-00114064	Screw cap made of PE DN 225 for attaching the barrel pump EPDM seal
PUMP SET F 430PP (EPDM)/ FBM4000EX	F430PP (EPDM)/ FBM4000EX
10-45860010	Pump set F430 PVDF-40/33-1000 & Motor F458 Concentrated acids consisting of: Collector motor F458, 230 V, 50 Hz, 460 watts, IP 55, 5 m cable with plug Barrel pump F430 PVDF-40/33-1000, FKM Chemical hose DN 19, 2 m long, with hose sockets made of PVDF PVDF fuel nozzle Barrel screw connection PP prepared for immediate commissioning
10-45860012	Pump set F430 PVDF-40/33-1200 & Motor F458 Concentrated acids consisting of: Collector motor F458, 230 V, 50 Hz, 460 watts, IP 55, 5 m cable with plug Barrel pump F430 PVDF-40/33-1200, FKM Chemical hose DN 19, 2 m long, with hose sockets made of PVDF PVDF fuel nozzle Barrel screw connection PP prepared for immediate commissioning
10-410 14 028	Coupling star
10-420 51 275	Coupling star
10-922 40 005	Grooved ball bearing
10-925 10 001	Shaft seal (NBR)
10-920 51 013	Slide bearing
10-430 41 312	Upper shaft Immersion length 1200 mm
10-430 41 331	Lower shaft
10-925 65 028	O-Ring Ø 32,2 x 3 (FFKM)
10-920 51 010	Support bearing 11 Immersion leng.1200mm
10-925 13 004	O-ring Ø 9 x 2,25 (NBR)
10-920 51 014	Slide bearing
10-925 11 001	Shaft seal (FKM)
10-958 25 092	Mechanical seal (FFKM)
10-908 06 011	Comp. washer Ø 6,5 x Ø 15,5 x 0,5
10-908 06 012	Comp. washer Ø 6,5 x Ø 15,5 x 1
10-430 41 300	Impeller
10-918 80 002	Circlip

10-952 00 012	grease for shaft seals & inner tube
10-925 64 003	Flat seal
10-959 05 084	Hose connector DN 19
10-959 05 085	Hose connector DN 25
Spare Parts	
10-41014028	clutch star (PA)
10-42051275	clutch cage (PA)
10-92240005	deep groove ball bearing D=9/24x7
10-92510001	shaft seal D=6/16x7(NBR)
10-92051013	Plain bearing D=6.05/15x10 (impregnated with sintered metal)
10-43041312	Upper shaft D=6, ET=1200 F430PP/PVDF
10-43041331	Lower shaft D=6.0x90 (HC)
10-92565028	O-ring D=32.2x3 (FFKM)
10-92051010	support bearing cpl.
10-92513004	O-Ring Ø 9x2,25 (NBR)
10-92051014	Plain bearing D=6.05/13x10 (impregnated with sintered metal)
10-92511001	shaft seal D=6/16x7 (FKM)
10-95825092	Mechanical seal Oxide ceramic/PTFE-carbon, FFKM For F430, F425, F426, O-rings made of FFKM
10-90806011	shim D=6.5/15.5x0.5 (1.4571)
10-90806012	shim D=6.5/15.5x1.0 (1.4571)
10-43041300	Rotor D=33 (ETFE)
10-91880002	Retaining ring, S for F4../F550/F570
10-95200012	Food grade grease (Paraliq GA 3400)
10-92564003	Flat gasket, PTFE Ø 31/39x1.5
10-95905084	Hose connector PVDF DN 19 for connection thread G 1 1/4
10-95905085	Hose connector PVDF DN 25 for connection thread G 1 1/4
10-90790026	toggle union nut G 1 1/4 (PVDF)
10-43090063	Inner tube complete F430 PVDF-40/33-1200
10-43090162	Outer pipe complete F430 PVDF-40/33-1200 With union nut

[10-43090039](#)

Inner tube F430 pre-assembled PVDF-40/..-1200