

Fowler

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Fowler** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Fowler T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
03000400	Inclinometer CLINOTRONIC PLUS Measuring range $\pm 45^\circ$, increments 0.02 mm/m, Error limit 1 arcmin(for measurements up to 10°), Housing aluminum, dimensions 100 x 75x30mm Measuring bases flat, without magnets and M3 thread Nomenclature number: 9031 8020 Switzerland
83798700	DAkKS calibration clinometer digital ... optional ... according to ISO 17025
40013901	Electronic dial indicator Basic measuring range 25 mm, error limit 10 μm , digit increment 0.01 mm, Degree of protection IP51, data output ... see catalog page 439 in the appendix
86400K07 (Calibration)	ISO calibration dial gauges with numerical display
45140209	depth gauge bridge bearing surface 120 x 20 mm, Bearing surface hardened, ground and lapped, Flatness tolerance according to DIN 874, body burnished, for holding devices with clamping shank $\varnothing 8 \text{ h6}$... see catalog page 556 in the appendix
84210K07 (Calibration)	ISO calibration measuring bridges
41154T39	Measuring insert T 11/4, D = 1 mm Connection thread M 2.5 x 5
41155T49	Measuring insert extension MV5, L = 100 mm cyl. Shaft $\varnothing 5 \text{ mm}$, connecting thread M 2.5 x 5
41155T44	Measuring insert extension MV5, L = 50 mm cyl. Shaft $\varnothing 5 \text{ mm}$, connecting thread M 2.5 x 5

54-422-450-1	
54-770-014	PROBE HOLDER BODY LED 14MM SWIVEL SHANK
2d Coaxial Set – Metric 52-710-030-0	
52-088-024	CALIPER ULTRA-ALUMINUM VERNIER 24IN/600MM
Sylvac50	INTERFACE
03000400 - Clinotronic Plus (Without Magnets And M3 Thread)	Inclinometer CLINOTRONIC PLUS Measuring range $\pm 45^\circ$, numbering 0.02 mm / m, Error limit 1 arcmin (for measurements up to 10°), Housing aluminum, dimension 100 x 75 x 30 mm, Measuring bases flat, without magnets and M3 thread ... according to enclosed catalog pages 32-33 Statistical commodity code: 9031 8020 UKZ: Switzerland / Switzerland
03000440 - Clinotronic Plus (Magnets On All 4 Sides)	Inclinometer CLINOTRONIC PLUS Measuring range $\pm 45^\circ$, numbering 0.02 mm / m, Error limit 1 arcmin (for measurements up to 10°), Housing aluminum, dimension 100 x 75 x 30 mm, Measuring bases flat, magnets on all 4 sides ... according to enclosed catalog pages 32-33 Statistical commodity code: 9031 8020 UKZ: Switzerland / Switzerland
52-760-000-0	
Sylvac25	INTERFACE
54-530-155-0	INDICATOR ELECTRONIC ULTRA-DIGIT MARK V 1IN
54618148	DIGITAL DISPLA
Wyler Calibration Clinotronic	