

## Frigel

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Frigel** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Frigel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Rcd 40/12 Sp</a>	
<a href="#">3HL 1450 HT TC</a>	
<a href="#">PMR6G</a>	
<a href="#">Ecodrygel 3DK 102P EC</a>	
<a href="#">KFC1200</a>	
<a href="#">(RCD60/12SP - RCD80/12SP)</a>	
<a href="#">Zeichnung</a>	
<a href="#">RTK22002F</a>	ESA TOUCH SCREEN RETROFIT KIT FOR RC40 60 80 WITH ESA CODE EW 107BD4SP000FR
<a href="#">RTK22003F</a>	ESA TOUCH SCREEN RETROFIT KIT FOR RC100 130 170L WITH ESA CODE EW 107BD4SP000FR
<a href="#">A3G800-AB01-03</a>	
	NRCD3501H0S Microgel = RCD Digital Model: RCD 350/48 SP

<a href="#">RCD 350/48 SP</a>	Power supply: 400V / 50Hz ±10% Compact high-performance refrigeration machine with two temperature zones Water condensed with temperature control function Operating temperature: -5/+90°C (glycol required below 9°C) High performance process pump Highly efficient scroll compressor Motor-driven proportional valve on the process side
<a href="#">NRCZKSD030</a>	Optional Microgel = accessories Model: Tool Drain Kit RCD 300/350/450 Not usable with pressurized systems
<a href="#">FOR 3DK32D MODEL COOLING UNIT; . EDK CELLULOSIC FI</a>	
<a href="#">FOR EDK31D MODEL COOLING UNIT; . EDK CELLULOSIC FI</a>	
<a href="#">2FCP40003</a>	SANYIO-PANASONIC SCROLL COMPRESSOR C-SCN753 H8H/K 380/415V-50Hz 440/460V-60Hz
<a href="#">Nrbm210nh0</a>	Turbogel = RBM Model: RBM 210/0 HP Power supply: 400V / 50Hz ± 10% Temperature control unit with a temperature zone Heating power: 0 kW / without heating element Motor-driven proportional valve for temperature control Direct cooling
<a href="#">Nzziskclp4</a>	INTERFACE IS-CL (CURRENT LOOP) WITH 4 CABLES EQUIPMENT
<a href="#">Kfc1200</a>	3 Way Valve
<a href="#">3hl 1150 Ht Tc</a>	Industrial Chiller
<a href="#">3gh950 Tm</a>	Pump Station
<a href="#">Art Nr. 2tva80088</a>	PRE ASSEMBLED EBM EC AXIAL FAN HYBRID BLADES A3G8000AY2701 (TILTED BLADES) + GRILL G080048-02-01 +WALLRING 800/7813A FEZN15/10 POL9006/1L COD.EBM 106AW0587
<a href="#">Pmr6g Modbus</a>	Control panel
<a href="#">Nrbd130rs0</a>	