

Gemco Electric

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Gemco Electric Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Gemco Electric T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
955sv71620e	955S BRIK™ LDT, 5 TO -5 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01380	955S BRIK™ LDT, 0 TO 10 VDC, 138 INCH STROKE LENGTH, NO OPTION
955sv71740	955S BRIK™ LDT, 5 TO -5 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv71080e	955S BRIK™ LDT, 5 TO -5 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60900e	955S BRIK™ LDT, -5 TO 5 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv40840	955S BRIK™ LDT, 0 TO 5 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv41680e	955S BRIK™ LDT, 0 TO 5 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv30780	955S BRIK™ LDT, 10 TO -10 VDC, 78 INCH STROKE LENGTH, NO OPTION

956s-V4-0240-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 5 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv00720e	955S BRIK™ LDT, 0 TO 10 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac40300a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 30 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv30660e	955S BRIK™ LDT, 10 TO -10 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01740	955S BRIK™ LDT, 0 TO 10 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv11200e	955S BRIK™ LDT, 10 TO 0 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61080	955S BRIK™ LDT, -5 TO 5 VDC, 108 INCH STROKE LENGTH, NO OPTION
955sv01380e	955S BRIK™ LDT, 0 TO 10 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11620	955S BRIK™ LDT, 10 TO 0 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv01260	955S BRIK™ LDT, 0 TO 10 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sc21800e	955S BRIK™ LDT, 20 TO 4MA, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60960	955S BRIK™ LDT, -5 TO 5 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sv61740	955S BRIK™ LDT, -5 TO 5 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv41260	955S BRIK™ LDT, 0 TO 5 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv71500e	955S BRIK™ LDT, 5 TO -5 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11080e	955S BRIK™ LDT, 10 TO 0 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av10300a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 30 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv00780e	955S BRIK™ LDT, 0 TO 10 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41020e	955S BRIK™ LDT, 0 TO 5 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

955sv71560e	955S BRIK™ LDT, 5 TO -5 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01080e	955S BRIK™ LDT, 0 TO 10 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Vp-0300-I-001-A	VARIABLE PULSE, 30 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, TAPPED FEMALE PISTON ROD
956a-V1-0360-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956sv20360x	MALE PISTON 1/4" -28 THREADS
956dcp0300x	28 THREADS
956s-V1-0300-E	956S BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv51560e	955S BRIK™ LDT, 5 TO 0 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51260	955S BRIK™ LDT, 5 TO 0 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv41800e	955S BRIK™ LDT, 0 TO 5 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71080	955S BRIK™ LDT, 5 TO -5 VDC, 108 INCH STROKE LENGTH, NO OPTION
956sv40360x	MALE PISTON 1/4" -28 THREADS
955sc41680e	955S BRIK™ LDT, 4 TO 20MA, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60780	955S BRIK™ LDT, -5 TO 5 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv11800e	955S BRIK™ LDT, 10 TO 0 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc40900	955S BRIK™ LDT, 4 TO 20MA, 90 INCH STROKE LENGTH, NO OPTION
955sv61200e	955S BRIK™ LDT, -5 TO 5 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01560e	955S BRIK™ LDT, 0 TO 10 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31200e	955S BRIK™ LDT, 10 TO -10 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01680e	955S BRIK™ LDT, 0 TO 10 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

955sc41380	955S BRIK™ LDT, 4 TO 20MA, 138 INCH STROKE LENGTH, NO OPTION
956d-Vp-0300-I-001-X	MALE PISTON
956a-V0-0300-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv31500e	955S BRIK™ LDT, 10 TO -10 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41620	955S BRIK™ LDT, 4 TO 20MA, 162 INCH STROKE LENGTH, NO OPTION
956s-C2-0240-E	956S BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv11500e	955S BRIK™ LDT, 10 TO 0 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21200e	955S BRIK™ LDT, -10 TO 10 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11440	955S BRIK™ LDT, 10 TO 0 VDC, 144 INCH STROKE LENGTH, NO OPTION
955sv50780e	955S BRIK™ LDT, 5 TO 0 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60780e	955S BRIK™ LDT, -5 TO 5 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Vp-0360-I-001-A	VARIABLE PULSE, 36 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, TAPPED FEMALE PISTON ROD
956s-V0-0300-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc41560e	955S BRIK™ LDT, 4 TO 20MA, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11380e	955S BRIK™ LDT, 10 TO 0 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41200e	955S BRIK™ LDT, 0 TO 5 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11260	955S BRIK™ LDT, 10 TO 0 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv21020e	955S BRIK™ LDT, -10 TO 10 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sv10360a	956S BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28

955sv60960e	955S BRIK™ LDT, -5 TO 5 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41320e	955S BRIK™ LDT, 4 TO 20MA, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sv50360x	MALE PISTON 1/4" -28 THREADS
955sv71800	955S BRIK™ LDT, 5 TO -5 VDC, 180 INCH STROKE LENGTH, NO OPTION
955sc40780e	955S BRIK™ LDT, 4 TO 20MA, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61680	955S BRIK™ LDT, -5 TO 5 VDC, 168 INCH STROKE LENGTH, NO OPTION
955sc21440e	955S BRIK™ LDT, 20 TO 4MA, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956dcp0360a	CONTROL PULSE, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv70660e	955S BRIK™ LDT, 5 TO -5 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv10900	955S BRIK™ LDT, 10 TO 0 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sc40720e	955S BRIK™ LDT, 4 TO 20MA, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av10360a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv21260	955S BRIK™ LDT, -10 TO 10 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv40840e	955S BRIK™ LDT, 0 TO 5 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sc40360a	956S BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
956sc20360x	MALE PISTON 1/4" -28 THREADS
955sv61260e	955S BRIK™ LDT, -5 TO 5 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21740	955S BRIK™ LDT, -10 TO 10 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv30840	955S BRIK™ LDT, 10 TO -10 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv21260e	955S BRIK™ LDT, -10 TO 10 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41440e	955S BRIK™ LDT, 0 TO 5 VDC, 144 INCH STROKE LENGTH,

956sv70360x	WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING. MALE PISTON 1/4" -28 THREADS
955sv41740	955S BRIK™ LDT, 0 TO 5 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sc41560	955S BRIK™ LDT, 4 TO 20MA, 156 INCH STROKE LENGTH, NO OPTION
955sv20840	955S BRIK™ LDT, -10 TO 10 VDC, 84 INCH STROKE LENGTH, NO OPTION
956dcp0360x	28 THREADS
956sv10360x	MALE PISTON 1/4" -28 THREADS
955sv41020	955S BRIK™ LDT, 0 TO 5 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv21080e	955S BRIK™ LDT, -10 TO 10 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51620e	955S BRIK™ LDT, 5 TO 0 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv10660e	955S BRIK™ LDT, 10 TO 0 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70900e	955S BRIK™ LDT, 5 TO -5 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71380	955S BRIK™ LDT, 5 TO -5 VDC, 138 INCH STROKE LENGTH, NO OPTION
956a-V0-0240-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv71320	955S BRIK™ LDT, 5 TO -5 VDC, 132 INCH STROKE LENGTH, NO OPTION
956s-C2-0360-E	956S BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv51200e	955S BRIK™ LDT, 5 TO 0 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41800e	955S BRIK™ LDT, 4 TO 20MA, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21560e	955S BRIK™ LDT, 20 TO 4MA, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V5-0300-E	956S BLOK™ LDT ANALOG VERSION, 5 TO 0 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv71440	955S BRIK™ LDT, 5 TO -5 VDC, 144 INCH STROKE LENGTH, NO OPTION

955sv61620	955S BRIK™ LDT, -5 TO 5 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sc41140e	955S BRIK™ LDT, 4 TO 20MA, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11740e	955S BRIK™ LDT, 10 TO 0 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01800	955S BRIK™ LDT, 0 TO 10 VDC, 180 INCH STROKE LENGTH, NO OPTION
956s-V1-0360-E	956S BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
19804126t	LIMIT SWITCH ROTATING CAM
955sv31440	955S BRIK™ LDT, 10 TO -10 VDC, 144 INCH STROKE LENGTH, NO OPTION
955sc41800	955S BRIK™ LDT, 4 TO 20MA, 180 INCH STROKE LENGTH, NO OPTION
955sv40900	955S BRIK™ LDT, 0 TO 5 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv10900e	955S BRIK™ LDT, 10 TO 0 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41680	955S BRIK™ LDT, 4 TO 20MA, 168 INCH STROKE LENGTH, NO OPTION
955sc21320e	955S BRIK™ LDT, 20 TO 4MA, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv10960	955S BRIK™ LDT, 10 TO 0 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sv20960e	955S BRIK™ LDT, -10 TO 10 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv00900	955S BRIK™ LDT, 0 TO 10 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv51680	955S BRIK™ LDT, 5 TO 0 VDC, 168 INCH STROKE LENGTH, NO OPTION
956s-V5-0240-E	956S BLOK™ LDT ANALOG VERSION, 5 TO 0 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956s-C4-0300-E	956S BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv51440	955S BRIK™ LDT, 5 TO 0 VDC, 144 INCH STROKE LENGTH, NO OPTION

955sv50900	955S BRIK™ LDT, 5 TO 0 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv31200	955S BRIK™ LDT, 10 TO -10 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv41140	955S BRIK™ LDT, 0 TO 5 VDC, 114 INCH STROKE LENGTH, NO OPTION
955sv11440e	955S BRIK™ LDT, 10 TO 0 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sv30360a	956S BLOK™ LDT ANALOG VERSION, 10 TO -10 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
955sv51560	955S BRIK™ LDT, 5 TO 0 VDC, 156 INCH STROKE LENGTH, NO OPTION
955sv21140	955S BRIK™ LDT, -10 TO 10 VDC, 114 INCH STROKE LENGTH, NO OPTION
956ac20360x	MALE PISTON 1/4"- 28 THREADS.
955sv70960e	955S BRIK™ LDT, 5 TO -5 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41260	955S BRIK™ LDT, 4 TO 20MA, 126 INCH STROKE LENGTH, NO OPTION
955sv51380e	955S BRIK™ LDT, 5 TO 0 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv50840	955S BRIK™ LDT, 5 TO 0 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv51740	955S BRIK™ LDT, 5 TO 0 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv71380e	955S BRIK™ LDT, 5 TO -5 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21500e	955S BRIK™ LDT, 20 TO 4MA, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Vp-0180-I-001-E	VARIABLE PULSE, 18 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, WET ENVIRONMENT. ELECTRON
955sv61200	955S BRIK™ LDT, -5 TO 5 VDC, 120 INCH STROKE LENGTH, NO OPTION
956av00240x	MALE PISTON 1/4"- 28 THREADS.
955sv21500e	955S BRIK™ LDT, -10 TO 10 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01320e	955S BRIK™ LDT, 0 TO 10 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
	955S BRIK™ LDT, 20 TO 4MA, 132 INCH STROKE LENGTH, NO

955sc21320	OPTION
955sv31560e	955S BRIK™ LDT, 10 TO -10 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac20300a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 30 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv61320	955S BRIK™ LDT, -5 TO 5 VDC, 132 INCH STROKE LENGTH, NO OPTION
956s-V2-0240-E	956S BLOK™ LDT ANALOG VERSION, -10 TO 10 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv71020e	955S BRIK™ LDT, 5 TO -5 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv20720e	955S BRIK™ LDT, -10 TO 10 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv00900e	955S BRIK™ LDT, 0 TO 10 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V7-0360-E	956S BLOK™ LDT ANALOG VERSION, 5 TO -5 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc40840	955S BRIK™ LDT, 4 TO 20MA, 84 INCH STROKE LENGTH, NO OPTION
955sv41680	955S BRIK™ LDT, 0 TO 5 VDC, 168 INCH STROKE LENGTH, NO OPTION
955sv51260e	955S BRIK™ LDT, 5 TO 0 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51080e	955S BRIK™ LDT, 5 TO 0 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41380	955S BRIK™ LDT, 0 TO 5 VDC, 138 INCH STROKE LENGTH, NO OPTION
956s-V7-0300-E	956S BLOK™ LDT ANALOG VERSION, 5 TO -5 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956s-V1-0240-E	956S BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc21740e	955S BRIK™ LDT, 20 TO 4MA, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70780e	955S BRIK™ LDT, 5 TO -5 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11680e	955S BRIK™ LDT, 10 TO 0 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

956a-V1-0300-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc41500	955S BRIK™ LDT, 4 TO 20MA, 150 INCH STROKE LENGTH, NO OPTION
956a-V1-0180-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 18 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv41620	955S BRIK™ LDT, 0 TO 5 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv51440e	955S BRIK™ LDT, 5 TO 0 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956a-V1-0240-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv00780	955S BRIK™ LDT, 0 TO 10 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv41080	955S BRIK™ LDT, 0 TO 5 VDC, 108 INCH STROKE LENGTH, NO OPTION
956s-V0-0360-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956s-V2-0300-E	956S BLOK™ LDT ANALOG VERSION, -10 TO 10 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc21620e	955S BRIK™ LDT, 20 TO 4MA, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac40300x	MALE PISTON 1/4"- 28 THREADS.
955sv01200e	955S BRIK™ LDT, 0 TO 10 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51320e	955S BRIK™ LDT, 5 TO 0 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21620e	955S BRIK™ LDT, -10 TO 10 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av10300x	MALE PISTON 1/4"- 28 THREADS.
956a-V0-0180-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 18 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv21200	955S BRIK™ LDT, -10 TO 10 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv11680	955S BRIK™ LDT, 10 TO 0 VDC, 168 INCH STROKE LENGTH, NO OPTION

955sv61440e	955S BRIK™ LDT, -5 TO 5 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21080	955S BRIK™ LDT, -10 TO 10 VDC, 108 INCH STROKE LENGTH, NO OPTION
955sv61320e	955S BRIK™ LDT, -5 TO 5 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc40840e	955S BRIK™ LDT, 4 TO 20MA, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01020e	955S BRIK™ LDT, 0 TO 10 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11500	955S BRIK™ LDT, 10 TO 0 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv41080e	955S BRIK™ LDT, 0 TO 5 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sv70360a	956S BLOK™ LDT ANALOG VERSION, 5 TO -5 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
956av00240a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 24 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
1989-Ca-16-R-12-S-E-B-E	CONTROLLER QUICKSET 3
955sv51200	955S BRIK™ LDT, 5 TO 0 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv31800e	955S BRIK™ LDT, 10 TO -10 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41380e	955S BRIK™ LDT, 0 TO 5 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V3-0300-E	956S BLOK™ LDT ANALOG VERSION, 10 TO -10 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv01800e	955S BRIK™ LDT, 0 TO 10 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc40780	955S BRIK™ LDT, 4 TO 20MA, 78 INCH STROKE LENGTH, NO OPTION
955sv61800	955S BRIK™ LDT, -5 TO 5 VDC, 180 INCH STROKE LENGTH, NO OPTION
955sv31680e	955S BRIK™ LDT, 10 TO -10 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11020e	955S BRIK™ LDT, 10 TO 0 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

955sv40960e	955S BRIK™ LDT, 0 TO 5 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71500	955S BRIK™ LDT, 5 TO -5 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sc41200e	955S BRIK™ LDT, 4 TO 20MA, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av10360x	MALE PISTON 1/4"- 28 THREADS.
955sv20780e	955S BRIK™ LDT, -10 TO 10 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61020	955S BRIK™ LDT, -5 TO 5 VDC, 102 INCH STROKE LENGTH, NO OPTION
1986-I1gr24sx	RESOLVER MODULE
955sv11140	955S BRIK™ LDT, 10 TO 0 VDC, 114 INCH STROKE LENGTH, NO OPTION
956ac40360a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sc41620e	955S BRIK™ LDT, 4 TO 20MA, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V6-0360-E	956S BLOK™ LDT ANALOG VERSION, -5 TO 5 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956d-Vp-0300-I-001-E	VARIABLE PULSE, 30 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, WET ENVIRONMENT. ELECTRON
955sv71620	955S BRIK™ LDT, 5 TO -5 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv01740e	955S BRIK™ LDT, 0 TO 10 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61740e	955S BRIK™ LDT, -5 TO 5 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv40660e	955S BRIK™ LDT, 0 TO 5 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac20300x	MALE PISTON 1/4"- 28 THREADS.
955sv70900	955S BRIK™ LDT, 5 TO -5 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv10720e	955S BRIK™ LDT, 10 TO 0 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V4-0300-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 5 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.

955sv41440	955S BRIK™ LDT, 0 TO 5 VDC, 144 INCH STROKE LENGTH, NO OPTION
956s-V3-0360-E	956S BLOK™ LDT ANALOG VERSION, 10 TO -10 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc41740	955S BRIK™ LDT, 4 TO 20MA, 174 INCH STROKE LENGTH, NO OPTION
955sv50960e	955S BRIK™ LDT, 5 TO 0 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01680	955S BRIK™ LDT, 0 TO 10 VDC, 168 INCH STROKE LENGTH, NO OPTION
955sv61140e	955S BRIK™ LDT, -5 TO 5 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61440	955S BRIK™ LDT, -5 TO 5 VDC, 144 INCH STROKE LENGTH, NO OPTION
955sv21740e	955S BRIK™ LDT, -10 TO 10 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av00360x	MALE PISTON 1/4"- 28 THREADS.
955sc21500	955S BRIK™ LDT, 20 TO 4MA, 150 INCH STROKE LENGTH, NO OPTION
955sv51500e	955S BRIK™ LDT, 5 TO 0 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51800e	955S BRIK™ LDT, 5 TO 0 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21020	955S BRIK™ LDT, -10 TO 10 VDC, 102 INCH STROKE LENGTH, NO OPTION
1996crsa12	1996 RAM-SET SHUT HEIGHT CONTROLLER, RS485 COMMUNICATION, NEMA 12 ENCLOSURE
955sv21440	955S BRIK™ LDT, -10 TO 10 VDC, 144 INCH STROKE LENGTH, NO OPTION
955sc21380e	955S BRIK™ LDT, 20 TO 4MA, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv40960	955S BRIK™ LDT, 0 TO 5 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sc40960	955S BRIK™ LDT, 4 TO 20MA, 96 INCH STROKE LENGTH, NO OPTION
956a-C4-0180-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 18 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv41260e	955S BRIK™ LDT, 0 TO 5 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

955sc21800	955S BRIK™ LDT, 20 TO 4MA, 180 INCH STROKE LENGTH, NO OPTION
955sv11260e	955S BRIK™ LDT, 10 TO 0 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V6-0300-E	956S BLOK™ LDT ANALOG VERSION, -5 TO 5 VDC, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv50780	955S BRIK™ LDT, 5 TO 0 VDC, 78 INCH STROKE LENGTH, NO OPTION
956a-V0-0360-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv51380	955S BRIK™ LDT, 5 TO 0 VDC, 138 INCH STROKE LENGTH, NO OPTION
1090a1	MULTIBUS 1 HIGH SPEED PLS
955sv01500e	955S BRIK™ LDT, 0 TO 10 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41620e	955S BRIK™ LDT, 0 TO 5 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41560	955S BRIK™ LDT, 0 TO 5 VDC, 156 INCH STROKE LENGTH, NO OPTION
956sc40360x	MALE PISTON 1/4" -28 THREADS
955sv61500e	955S BRIK™ LDT, -5 TO 5 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv50840e	955S BRIK™ LDT, 5 TO 0 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956dcp0300a	CONTROL PULSE, 30 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sc41740e	955S BRIK™ LDT, 4 TO 20MA, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av00360a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv51620	955S BRIK™ LDT, 5 TO 0 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv01320	955S BRIK™ LDT, 0 TO 10 VDC, 132 INCH STROKE LENGTH, NO OPTION
956d-Vp-0240-I-001-E	VARIABLE PULSE, 24 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, WET ENVIRONMENT. ELECTRON

956sv00360x	MALE PISTON 1/4" -28 THREADS
956sv00360a	956S BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
955sv00840e	955S BRIK™ LDT, 0 TO 10 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv30900e	955S BRIK™ LDT, 10 TO -10 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-C4-0360-E	956S BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv61560e	955S BRIK™ LDT, -5 TO 5 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V5-0360-E	956S BLOK™ LDT ANALOG VERSION, 5 TO 0 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv21380	955S BRIK™ LDT, -10 TO 10 VDC, 138 INCH STROKE LENGTH, NO OPTION
955sv21140e	955S BRIK™ LDT, -10 TO 10 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70780	955S BRIK™ LDT, 5 TO -5 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv11140e	955S BRIK™ LDT, 10 TO 0 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11320	955S BRIK™ LDT, 10 TO 0 VDC, 132 INCH STROKE LENGTH, NO OPTION
955sv21380e	955S BRIK™ LDT, -10 TO 10 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51080	955S BRIK™ LDT, 5 TO 0 VDC, 108 INCH STROKE LENGTH, NO OPTION
955sv31140	955S BRIK™ LDT, 10 TO -10 VDC, 114 INCH STROKE LENGTH, NO OPTION
955sv20900e	955S BRIK™ LDT, -10 TO 10 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956sv60360x	MALE PISTON 1/4" -28 THREADS
955sv11020	955S BRIK™ LDT, 10 TO 0 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv31380	955S BRIK™ LDT, 10 TO -10 VDC, 138 INCH STROKE LENGTH, NO OPTION
956ac40240x	MALE PISTON 1/4"- 28 THREADS.
	955S BRIK™ LDT, 0 TO 10 VDC, 84 INCH STROKE LENGTH,

955sv00840	NO OPTION
955sc21680e	955S BRIK™ LDT, 20 TO 4MA, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
1980-404x-Sprx-S-28-L	CAM LIMIT SWITCH SPDT 28:1
955sv10840	955S BRIK™ LDT, 10 TO 0 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv50660e	955S BRIK™ LDT, 5 TO 0 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60840	955S BRIK™ LDT, -5 TO 5 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv61020e	955S BRIK™ LDT, -5 TO 5 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31320e	955S BRIK™ LDT, 10 TO -10 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V6-0240-E	956S BLOK™ LDT ANALOG VERSION, -5 TO 5 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv31560	955S BRIK™ LDT, 10 TO -10 VDC, 156 INCH STROKE LENGTH, NO OPTION
955sv31500	955S BRIK™ LDT, 10 TO -10 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv30960e	955S BRIK™ LDT, 10 TO -10 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41800	955S BRIK™ LDT, 0 TO 5 VDC, 180 INCH STROKE LENGTH, NO OPTION
956sv60360a	956S BLOK™ LDT ANALOG VERSION, -5 TO 5 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
955sv71260	955S BRIK™ LDT, 5 TO -5 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv11800	955S BRIK™ LDT, 10 TO 0 VDC, 180 INCH STROKE LENGTH, NO OPTION
955sv71200	955S BRIK™ LDT, 5 TO -5 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv71140e	955S BRIK™ LDT, 5 TO -5 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31680	955S BRIK™ LDT, 10 TO -10 VDC, 168 INCH STROKE LENGTH, NO OPTION
1989-A-16-R-14-S-C-X	PROGRAMMABLE LIMIT SWITCH CPU/KEYPAD 16OUT ANALOG
955sv11380	955S BRIK™ LDT, 10 TO 0 VDC, 138 INCH STROKE LENGTH, NO OPTION

955sc21380	955S BRIK™ LDT, 20 TO 4MA, 138 INCH STROKE LENGTH, NO OPTION
955sv61560	955S BRIK™ LDT, -5 TO 5 VDC, 156 INCH STROKE LENGTH, NO OPTION
956sv20360a	956S BLOK™ LDT ANALOG VERSION, -10 TO 10 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
956av10240x	MALE PISTON 1/4" - 28 THREADS.
955sv60840e	955S BRIK™ LDT, -5 TO 5 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70960	955S BRIK™ LDT, 5 TO -5 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sv31140e	955S BRIK™ LDT, 10 TO -10 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31380e	955S BRIK™ LDT, 10 TO -10 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70840	955S BRIK™ LDT, 5 TO -5 VDC, 84 INCH STROKE LENGTH, NO OPTION
955sv10840e	955S BRIK™ LDT, 10 TO 0 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61680e	955S BRIK™ LDT, -5 TO 5 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11620e	955S BRIK™ LDT, 10 TO 0 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac20360a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sc21560	955S BRIK™ LDT, 20 TO 4MA, 156 INCH STROKE LENGTH, NO OPTION
955sc41200	955S BRIK™ LDT, 4 TO 20MA, 120 INCH STROKE LENGTH, NO OPTION
955sv61800e	955S BRIK™ LDT, -5 TO 5 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv30960	955S BRIK™ LDT, 10 TO -10 VDC, 96 INCH STROKE LENGTH, NO OPTION
956d-Vp-0360-I-001-X	MALE PISTON
956s-C4-0240-E	956S BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956s-V4-0360-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 5 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.

955sv01620	955S BRIK™ LDT, 0 TO 10 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv40900e	955S BRIK™ LDT, 0 TO 5 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21800e	955S BRIK™ LDT, -10 TO 10 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41080e	955S BRIK™ LDT, 4 TO 20MA, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01140	955S BRIK™ LDT, 0 TO 10 VDC, 114 INCH STROKE LENGTH, NO OPTION
955sv51020	955S BRIK™ LDT, 5 TO 0 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv61380	955S BRIK™ LDT, -5 TO 5 VDC, 138 INCH STROKE LENGTH, NO OPTION
955sv51740e	955S BRIK™ LDT, 5 TO 0 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31440e	955S BRIK™ LDT, 10 TO -10 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21260	955S BRIK™ LDT, 20 TO 4MA, 126 INCH STROKE LENGTH, NO OPTION
955sv01620e	955S BRIK™ LDT, 0 TO 10 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51020e	955S BRIK™ LDT, 5 TO 0 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956av00300a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 30 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv21560e	955S BRIK™ LDT, -10 TO 10 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956a-C2-0240-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv40780e	955S BRIK™ LDT, 0 TO 5 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41080	955S BRIK™ LDT, 4 TO 20MA, 108 INCH STROKE LENGTH, NO OPTION
956a-C2-0300-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv30720e	955S BRIK™ LDT, 10 TO -10 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.

955sv31620e	955S BRIK™ LDT, 10 TO -10 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac40240a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 24 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv31800	955S BRIK™ LDT, 10 TO -10 VDC, 180 INCH STROKE LENGTH, NO OPTION
955sv20780	955S BRIK™ LDT, -10 TO 10 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv71020	955S BRIK™ LDT, 5 TO -5 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv30900	955S BRIK™ LDT, 10 TO -10 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv31320	955S BRIK™ LDT, 10 TO -10 VDC, 132 INCH STROKE LENGTH, NO OPTION
955sc40900e	955S BRIK™ LDT, 4 TO 20MA, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71140	955S BRIK™ LDT, 5 TO -5 VDC, 114 INCH STROKE LENGTH, NO OPTION
955sv31020	955S BRIK™ LDT, 10 TO -10 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv51500	955S BRIK™ LDT, 5 TO 0 VDC, 150 INCH STROKE LENGTH, NO OPTION
956sv50360a	956S BLOK™ LDT ANALOG VERSION, 5 TO 0 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
956s-C2-0300-E	956S BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956d-Cp-0360-E	CONTROL PULSE, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING
955sv21560	955S BRIK™ LDT, -10 TO 10 VDC, 156 INCH STROKE LENGTH, NO OPTION
955sv71800e	955S BRIK™ LDT, 5 TO -5 VDC, 180 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01260e	955S BRIK™ LDT, 0 TO 10 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21680	955S BRIK™ LDT, -10 TO 10 VDC, 168 INCH STROKE LENGTH, NO OPTION
955sv01440e	955S BRIK™ LDT, 0 TO 10 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21680	955S BRIK™ LDT, 20 TO 4MA, 168 INCH STROKE LENGTH, NO OPTION

955sv20660e	955S BRIK™ LDT, -10 TO 10 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956ac20240x	MALE PISTON 1/4"- 28 THREADS.
955sv20960	955S BRIK™ LDT, -10 TO 10 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sv50720e	955S BRIK™ LDT, 5 TO 0 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61260	955S BRIK™ LDT, -5 TO 5 VDC, 126 INCH STROKE LENGTH, NO OPTION
955sv01140e	955S BRIK™ LDT, 0 TO 10 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
1989-Ca-1530a	PROGRAMMABLE LIMIT SWITCH HIGH SPEED
955sv71440e	955S BRIK™ LDT, 5 TO -5 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21620	955S BRIK™ LDT, -10 TO 10 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv61500	955S BRIK™ LDT, -5 TO 5 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv31260	955S BRIK™ LDT, 10 TO -10 VDC, 126 INCH STROKE LENGTH, NO OPTION
956a-C4-0360-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
956s-V0-0240-E	956S BLOK™ LDT ANALOG VERSION, 0 TO 10 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv11320e	955S BRIK™ LDT, 10 TO 0 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
1991-A-1-16-R-12-E-X	1991 QUIK-SET IV HIGH SPEED PLS, COMPLETE SYSTEM CPU AND KEYPAD, 110 VAC 50/60 HZ, 16 OUTPUT CIRCUITS, RESOLVER INPUT, 4096 POSITIONS, 12 BIT RESOLUTI
955sv01200	955S BRIK™ LDT, 0 TO 10 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv61140	955S BRIK™ LDT, -5 TO 5 VDC, 114 INCH STROKE LENGTH, NO OPTION
956sv40360a	956S BLOK™ LDT ANALOG VERSION, 0 TO 5 VDC, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28
956a-C4-0240-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.

955sv41320	955S BRIK™ LDT, 0 TO 5 VDC, 132 INCH STROKE LENGTH, NO OPTION
956ac40360x	MALE PISTON 1/4"- 28 THREADS.
955sv60900	955S BRIK™ LDT, -5 TO 5 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sv51140	955S BRIK™ LDT, 5 TO 0 VDC, 114 INCH STROKE LENGTH, NO OPTION
955sv00660e	955S BRIK™ LDT, 0 TO 10 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21320e	955S BRIK™ LDT, -10 TO 10 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv10960e	955S BRIK™ LDT, 10 TO 0 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Cp-0180-E	CONTROL PULSE, 18 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING
955sv01500	955S BRIK™ LDT, 0 TO 10 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv31620	955S BRIK™ LDT, 10 TO -10 VDC, 162 INCH STROKE LENGTH, NO OPTION
955sv30840e	955S BRIK™ LDT, 10 TO -10 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41500	955S BRIK™ LDT, 0 TO 5 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv41200	955S BRIK™ LDT, 0 TO 5 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sc41500e	955S BRIK™ LDT, 4 TO 20MA, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71260e	955S BRIK™ LDT, 5 TO -5 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61620e	955S BRIK™ LDT, -5 TO 5 VDC, 162 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41560e	955S BRIK™ LDT, 0 TO 5 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51320	955S BRIK™ LDT, 5 TO 0 VDC, 132 INCH STROKE LENGTH, NO OPTION
955sv40720e	955S BRIK™ LDT, 0 TO 5 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956a-C4-0300-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 4 TO 20MA, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.

955sv61380e	955S BRIK™ LDT, -5 TO 5 VDC, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11740	955S BRIK™ LDT, 10 TO 0 VDC, 174 INCH STROKE LENGTH, NO OPTION
955sv41140e	955S BRIK™ LDT, 0 TO 5 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv50900e	955S BRIK™ LDT, 5 TO 0 VDC, 90 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv20900	955S BRIK™ LDT, -10 TO 10 VDC, 90 INCH STROKE LENGTH, NO OPTION
955sc41260e	955S BRIK™ LDT, 4 TO 20MA, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Vp-0360-I-001-E	VARIABLE PULSE, 36 INCH STROKE LENGTH, INTERNAL INTERROGATION, 1 RECIRCULATION, WET ENVIRONMENT. ELECTRON
955sv21440e	955S BRIK™ LDT, -10 TO 10 VDC, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11560e	955S BRIK™ LDT, 10 TO 0 VDC, 156 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv30780e	955S BRIK™ LDT, 10 TO -10 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21260e	955S BRIK™ LDT, 20 TO 4MA, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv61080e	955S BRIK™ LDT, -5 TO 5 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc41020e	955S BRIK™ LDT, 4 TO 20MA, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv50960	955S BRIK™ LDT, 5 TO 0 VDC, 96 INCH STROKE LENGTH, NO OPTION
956d-Cp-0240-E	CONTROL PULSE, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING
956sv30360x	MALE PISTON 1/4" -28 THREADS
1090b1	MULTIBUS HIGH SPEED PLS
955sc41020	955S BRIK™ LDT, 4 TO 20MA, 102 INCH STROKE LENGTH, NO OPTION
955sv71560	955S BRIK™ LDT, 5 TO -5 VDC, 156 INCH STROKE LENGTH, NO OPTION
956sc20360a	956S BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 36 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD1/4" -28

955sc41140	955S BRIK™ LDT, 4 TO 20MA, 114 INCH STROKE LENGTH, NO OPTION
955sv71680e	955S BRIK™ LDT, 5 TO -5 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv20840e	955S BRIK™ LDT, -10 TO 10 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21320	955S BRIK™ LDT, -10 TO 10 VDC, 132 INCH STROKE LENGTH, NO OPTION
955sc41380e	955S BRIK™ LDT, 4 TO 20MA, 138 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31740	955S BRIK™ LDT, 10 TO -10 VDC, 174 INCH STROKE LENGTH, NO OPTION
956av10240a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 10 TO 0 VDC, 24 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv10780e	955S BRIK™ LDT, 10 TO 0 VDC, 78 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc40960e	955S BRIK™ LDT, 4 TO 20MA, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01080	955S BRIK™ LDT, 0 TO 10 VDC, 108 INCH STROKE LENGTH, NO OPTION
955sc41440e	955S BRIK™ LDT, 4 TO 20MA, 144 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41500e	955S BRIK™ LDT, 0 TO 5 VDC, 150 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51140e	955S BRIK™ LDT, 5 TO 0 VDC, 114 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv31080	955S BRIK™ LDT, 10 TO -10 VDC, 108 INCH STROKE LENGTH, NO OPTION
955sv41740e	955S BRIK™ LDT, 0 TO 5 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv60660e	955S BRIK™ LDT, -5 TO 5 VDC, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv51680e	955S BRIK™ LDT, 5 TO 0 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv71740e	955S BRIK™ LDT, 5 TO -5 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv21680e	955S BRIK™ LDT, -10 TO 10 VDC, 168 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11080	955S BRIK™ LDT, 10 TO 0 VDC, 108 INCH STROKE LENGTH, NO OPTION

1995-A-6m-X	PROGRAMMABLE LIMIT SWITCH BRAKING SYSTEM MICRO SET
955sv31260e	955S BRIK™ LDT, 10 TO -10 VDC, 126 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956d-Cp-0300-E	CONTROL PULSE, 30 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING
1771-PIs-B1	LIMIT SWITCH PROGRAMMABLE HIGH-SPEED 16OUT DIRECT
956ac20240a	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 24 INCH STROKE LENGTH, TAPPED FEMALE PISTON ROD 1/4" -28
955sv60720e	955S BRIK™ LDT, -5 TO 5 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv41320e	955S BRIK™ LDT, 0 TO 5 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V3-0240-E	956S BLOK™ LDT ANALOG VERSION, 10 TO -10 VDC, 24 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sc41320	955S BRIK™ LDT, 4 TO 20MA, 132 INCH STROKE LENGTH, NO OPTION
955sv40780	955S BRIK™ LDT, 0 TO 5 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv01440	955S BRIK™ LDT, 0 TO 10 VDC, 144 INCH STROKE LENGTH, NO OPTION
955sv31020e	955S BRIK™ LDT, 10 TO -10 VDC, 102 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv01020	955S BRIK™ LDT, 0 TO 10 VDC, 102 INCH STROKE LENGTH, NO OPTION
955sv31740e	955S BRIK™ LDT, 10 TO -10 VDC, 174 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv00960e	955S BRIK™ LDT, 0 TO 10 VDC, 96 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956s-V2-0360-E	956S BLOK™ LDT ANALOG VERSION, -10 TO 10 VDC, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv51800	955S BRIK™ LDT, 5 TO 0 VDC, 180 INCH STROKE LENGTH, NO OPTION
956av00300x	MALE PISTON 1/4"- 28 THREADS.
955sc40660e	955S BRIK™ LDT, 4 TO 20MA, 66 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
956a-C2-0180-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 18 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.

955sc41440	955S BRIK™ LDT, 4 TO 20MA, 144 INCH STROKE LENGTH, NO OPTION
955sv70720e	955S BRIK™ LDT, 5 TO -5 VDC, 72 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv00960	955S BRIK™ LDT, 0 TO 10 VDC, 96 INCH STROKE LENGTH, NO OPTION
955sc21740	955S BRIK™ LDT, 20 TO 4MA, 174 INCH STROKE LENGTH, NO OPTION
955sv71200e	955S BRIK™ LDT, 5 TO -5 VDC, 120 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sc21440	955S BRIK™ LDT, 20 TO 4MA, 144 INCH STROKE LENGTH, NO OPTION
956a-C2-0360-E	956A/956D-CP BLOK™ LDT ANALOG VERSION, 20 TO 4MA, 36 INCH STROKE LENGTH, WET ENVIRONMENT. ELECTRONICS SEALED TO IP 68 RATING.
955sv71320e	955S BRIK™ LDT, 5 TO -5 VDC, 132 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv70840e	955S BRIK™ LDT, 5 TO -5 VDC, 84 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
955sv11560	955S BRIK™ LDT, 10 TO 0 VDC, 156 INCH STROKE LENGTH, NO OPTION
955sv01560	955S BRIK™ LDT, 0 TO 10 VDC, 156 INCH STROKE LENGTH, NO OPTION
955sv10780	955S BRIK™ LDT, 10 TO 0 VDC, 78 INCH STROKE LENGTH, NO OPTION
955sv11200	955S BRIK™ LDT, 10 TO 0 VDC, 120 INCH STROKE LENGTH, NO OPTION
955sv21800	955S BRIK™ LDT, -10 TO 10 VDC, 180 INCH STROKE LENGTH, NO OPTION
955sv21500	955S BRIK™ LDT, -10 TO 10 VDC, 150 INCH STROKE LENGTH, NO OPTION
955sv31080e	955S BRIK™ LDT, 10 TO -10 VDC, 108 INCH STROKE LENGTH, WET ENVIRONMENT.ELECTRONICS SEALED TO IP68 RATING.
1989-O-115-M-S	1989LAS QUIK-SET III PLS, OUTPUT MODULE ASSEMBLY, 115 VAC 50-60 HZ, MECHANICAL RELAY SPDT 10 AMP, STANDARD PANEL MOUNT
955sv71680	955S BRIK™ LDT, 5 TO -5 VDC, 168 INCH STROKE LENGTH, NO OPTION
955sc21620	955S BRIK™ LDT, 20 TO 4MA, 162 INCH STROKE LENGTH, NO OPTION