



Gems Sensor

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Gems Sensor Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Gems Sensor Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
6700-B-G-C16-A0-M-3-030-B	Pressure transducer 6700 B 4 - 20mA G Gauge C16 0-160 bar A0 G1 / 4 "external M IP68 Immersible cable 3 CE 030 30 meters cable B 0.15% / 0.5%
Typ: 3100-B-0010g-05-B-000	Pressure transducer B 4 - 20mA 0010G 0 - 10barG 05 G1 / 4 External Soft Seal B Industrial DIN 9.4mm 0 No Restrictor 00 No Cable Customs tariff number: 9026 2020 GB 0.208kg
3300b01b0a01b00v	
Typ: 3100-B-0016g-05-B-000	Pressure transducer B 4 - 20mA 0016G 0-16 barG 05 G 1/4 External Soft Seal B Industrial DIN 9.4mm (mating connector not supplied) 0 No Restrictor 00 No Cable Customs tariff number: 9026 2020 Country of origin: GB
FS925	flow switch
2600BGA1019M3GA005	Measuring range: 0-10mWG Pressure transducer
Rotor Flow	
2200AGG5008A2UA	
W977953	LS-800-4-SS-BN-SPDT-020-GR4-3 Level Switch
1200HGG3002A3UA	
3500-B-0001G-05-B-000	Pressure transducer Serie 3500 B 4...20 mA 0001G 1barG 05 G1/4 External Soft Seal B Industrial DIN 9.4mm 000 No Cable
6700-B-G-C16-A0-M-3-030-B	Pressure transducer 6700 B 4 - 20mA G Gauge C16 0-160 bar A0 G1 / 4 "external dıŐ uzunluĐu 11,40mm olmalıdır M IP68 Immersible cable 3 CE 030 30 meters cable B 0.15% / 0.5%
Seri: F119799	

B2010-LCO2-LB-24VDC	Orifice 3/64 (Body) MOPD: 900 psi Cv 0.045 (Body) Body port configuration: 1/4-18 NPT female thread (in-line porting only) Voltage: 24V DC
B2012-LCO2-LB-24VDC	Orifice 5/64 (body) MOPD: 270 psi Cv 0.105 (body) Body port configuration: 1 / 4-18 NPT female thread (in-line porting only) Voltage: 24V DC Minimum order quantity: 50 pieces
BG2007-01-LB-V-G1-204	
BG2005-01-LB-V-G1-204	
Art.-Nr.: 156268	RotorFlow RFS 2500 flow monitor Working range: 15.0 ... 75.0 l / min Connection thread: 1/2 "NPT Input: 24 VDC Housing: brass
LS-7 Type	Float switch Stainless / Stainless (Ext mount, 1/2 "NPT) Leads Item no .: 164870 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.495 kg
PS71	
CAP-300	Capacitive Level Sensor 1/4 "-18NPTM INTEGRAL 3- PIN GERMAN WET SINK Item no .: 240640
227202	ELS-1150XP Optic 1/2" NPT 5-28VDC FM Dry Sink NO Nickel Plated Steel
RFO-2500	Flow monitor RFO-2500 Brass 1/4" NPT (0.4 - 4) 2 - 20 L/min Item No.: 156261 Customs tariff number: 9026 1021 Country of origin: US Net position weight: 0.500 kg
3300B02B5G01E000	
06062	
DATE KOD:601	AGFA CORPORATION 094085-0109 REV B
PN 229206	
Model: LS-1700	Part No: 016-0026 Supply Voltage: 250 V AC-DC Current: 0.5 A, 50 VA
PN 2934 FS-3 Flow Switch	
LS-270	float switch 50VA, N.C. Type: LS-270 Item No.: 43982
VALVE,SOLENOID:3050,24VDC,1W,053/17,50PSI	
VALVE,SOLENOID:3050,24VDC,1W,358/16,50PSI	
Flow switch Gems Sensors FS-100E-A	
0-30 BAR 3100 GEMS(MET.8)	
GH3312-S20	

flow switch	45518 Brass, Lead Wires, 1/4" NPT female connection SPST, N.O. , 0.25GPM Type: FS-927 Item no: 70821
3101H150PG01E000	SUPPLY : 8 - 30 V.DC. CONNECTION: G 1/4" EXTERNAL RANGE: 0 - 150 PSIG OUTPUT:1 - 5 V. M12X1P(4-PIN) TEMP OUTPUT RANGE -40 °C to 125 °C
FS-927	flow switch Brass, Lead Wires, 1/4" NPT female connection SPST, N.O. , 0.25GPM Type: FS-927 Item no: 70821
10PG08E000	SERIAL XT41202TP-063-12-0210
3100T300PG0290000F 0-300PSI	
223060 REV C	
3100B300PG0290	
3100B0100S05B000	0-100 bar
Coupling	Yellow Water coupling
3200-B-0100S-05-G-0-00	Pressure sensor B - 4-20mA 0100S - 0...100barS 05 - G1/4 External Soft Seal G - Electrical Connection : EN 175301-803(ex DIN 43650A) 0 - No Restrictor 00 - No cable
3100	
3300BB060G18G000	4-20 ma pressure transmitter
310-1-H-150PG-01-E-000	
Art-Nr: 155421	Flow monitor type RFO-2500 Working range: 2-20 l / min Connection thread: 1/4 "NPT Input: 4.5-24 V DC Output: 4.5-24 V, pulse 25-225 Hz Art-Nr: 155421 Weight / St .: approx. 0.15 kg 1 pc 128,200 128,20 AL: N ECCN: Customs tariff number: 9026 1029 Country of origin: US Net position weight: 0.150 kg
Stu 009886 - 312 - 07 - 0030	
223060 Rev C	120 VAC HYPERTHERM FLOWMETER Please look at the attachment
020-3499	
Ls-1700 Tfe (174200)	float switch Material: PTFE Switch: SPST, 20 VA, N.C. Item No. : 174200 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.750 kg
Dm-133475	
Fs-6 0,4l/Min	
2200 B G B10 01 A 3 Ua	

3100b0016g05b00004	
Ls-800e-Pvc-K12-1-O-Dual	
Fs-550-E	
Ls-1700 Tfe (174100)	float switch Material: PTFE Switch: SPST, 20 VA, N.O. Item No .: 174100 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.750 kg
020-3497	
Ls800e-Pvc-O-K12-Dual	
3100-B-0400s-02-B-0-000	
3100-B-0400s-05-B-000	Pressure transducer B - 4-20mA 0400S - 0-400 barS 05 - G1 / 4 "Soft Seal B - Industrial Din 0 - No Restrictor 00 - No cable
Ls800e-No0101275	
Ls800e-Pvc-O-K12-1-Dual	
3300b06b0g18g000	
P/M-133475	
3300-B-300pg-02-9-0000f	
20va/T0241	
2200 B G A25 01 A 3 Ua	
Ls-2050-E	
Ls800e-O-Bcc-C-K6-2-0161610	
Wif-1250 / Water In Fuel Single Point Level Sensor	
145149	
020-3495	
Ls800e-O-Tm-N-S-4	
20va/T0242	
Xm800-3-Ss-Ss-3-50-1800-1.62g(Ex1.62dia)	
Ls800-2a-Br-Bn Spdt-20-Gr4-3	
Ls 1700	
Ls800-Pvc-Tpvc-K12-Gr1	
Gems Ls-400e-O-Tc-C-K6-3	DIP: 200 mm MONTAGEART: 33mm / G1 MINIMUM SIGNAL OUTPUT wird verwendet. KONTAKTZUFUHR: 220VDC ÖLTEMPERATUR: 0 ... 100°C KABELEINGANG:

	PG13,5 RACK Edelstahl
3100b0010g05g000	Please look at the attachment
Ps82	
20va/T0240	
Fs-926e-0.05-M-X-S-Ge169	
Fls3	