

General Instruments

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
General Instruments Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız General Instruments Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Sfbspg-V-10-S6-S-S-6-15-Ntm-(0 To 100)-B	GAUGE,PRESSURE:56.1BARG,1/2IN,NPT,100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 100)-B-A-BB-X-SN ,MFR:GENERAL INSTRUMENT
Sfbspg-V-10-S6-S-S-6-15-Ntm	GAUGE,PRESSURE:4.7BARG,1/2IN,NPT,100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 10)-B-A-BB-X-SN-SY,MFR:GENERAL INSTRUMENT
Sfbspg-Y-10-S6-S-S-6-15-Ntm-(0 To 10)-B	GAUGE,PRESSURE:4.85BARG,1/2IN,NPT,100MM,-45-205DEG,SFBSPG,SFBSPG-Y-10- S6-S-S-6-15-NTM-(0 to 10)-B-BB-X-SDT-S4-S6-S6-15-NTM,MFR:GENERAL INSTRUMENT
Sfbspg-V-10-S6-S-S-6-15-Ntm-(0 To 10)-B	GAUGE,PRESSURE:6.5BARG,1/2IN,NPT,100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 10)-B-A-BB-X-SY,MFR:GENERAL INSTRUMENT
Bdt-E-10-S4-A-460-S6-15ntm-(0 To 60	THERMOMETER,BIMETALLIC:0-60DEG,100MM,STEM LENGTH 460MM,SS316,1-1/2IN,BDT-E-10-S4-A-460-S6-15NTM-(0 to 60)-C-A,MFR:GENERAL INSTRUMENT
	Dial Size : 4" (100mm), Aluminium, white background with Black markings Case & Bezel : SS316, bayonet type bezel, weatherproof to IP-68 as per IS:13947 Window : Shatterproof

Sfbspg-Y Bottom Entry, 2" Pipe Mounting, Solid Front Case	Glass Bourdon : SS316 Socket : SS316 Movement : SS316 Connection : 1/2" NPT(M) Range : 0 to 10 Bar Accuracy : ± 1% FSD Over Range : 130% FSD Zero Reset : Micrometer Pointer Blow out Disc : Provided (Neoprene) on Back of case Diaphragm Seal Unit for the above Gauge: Model : CSU-SDT... Sandwich Diaphragm Seal (Threaded) Top Chamber : SS304 Diaphragm (Wetted Part) : SS316 Bottom Flange : SS316 Connection : 1/2" NPT(M) Filling Fluid : Silicon Oil
Bdt-E ... Rigid Stem, Every Angle Construction, Local Mounting	Dial Size : 4" (100mm), Aluminium, white background with black markings Case & Bezel : SS304, bayonet type bezel, weatherproof to IP-67 as per IS:13947 Window : Shatterproof Glass Stem : 6mm OD in SS316 Stem Length : 460mm below connection Connection : 1/2" NPT(M) Adjustable compression fitting in SS316 Range : 0 to 60 Deg. C Accuracy : ± 1% FSD Over Range : 125% FSD Zero Reset : Micrometer Pointer
Sfbspg-V Bottom Entry, Local Mounting, Solid Front Case	Dial Size : 4" (100mm), Aluminium, white background with Black markings Case & Bezel : SS316, bayonet type bezel, weatherproof to IP-68 as per IS:13947 Window : Shatterproof Glass Bourdon : SS316 Socket : SS316 Movement : SS316 Connection : 1/2" NPT(M) Range : As shown in below Table Accuracy : ± 1% FSD Over Range : 130% FSD Zero Reset : Micrometer Pointer Blow out Disc : Provided (Neoprene) on Back of case Accessories : 1] Snubber in SS316 Connection: 1/2" NPT(F) x 1/2" NPT(M) 2] Syphon in SS316 Body: Sch. 80 Instrument Connection: 1/2" NPT(F) Process Connection: 1/4" NPT(F) 1. 0 to 100Bar Snubber :Yes Syphon:No Qty.3 2. 0 to 10Bar Snubber :Yes Syphon:Yes Qty.3 3. 0 to 10Bar Snubber :No Syphon:Yes Qty.3