

GENKİNGER

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
GENKİNGER Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız GENKİNGER T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
EFY 3504 REMOTO CONTROL JOYSTICK LIFTING	980692
Typ EGS 70 AC	Genkinger-bAKA Electric tug Conditions of use Load transport trolley * single-axle with support legs * we ask for pictures or drawings to be sent (please note) Load dimensions (L x W x H)... x... x... mm (please specify) Wheel diameter / material ... mm / ... (please specify) Load suspension by means of a ball head on the ball socket * * Ball socket must be created by the customer and attached to the load. A corresponding (please note) overhang or coordination with the chassis of the tractor must be taken into account! Ground conditions good, level concrete floor No inclines / slopes Deployment profile 1-shift operation Operating hours <1000 per year Ambient temperature 5 - 30 ° C Lifting device load capacity 4000 kg Trailer load 7000 kg Tensile force 3500 N Ball head □ 45 mm (please check) Device length 1500 mm Device width 890 mm Device height 1465 mm Stroke range of the ball head 200 - 360 mm (please check) Trailer hitch with 2 support heights 415-575 / 500-660 mm Landing gear: Clear width between the chassis 160 mm Outer width above the running gear 620 mm (please check) 2 twin polyurethane

rollers □ 200 mm Center drive with polyurethane drive wheel
Ø 320 x 100 mm as well as two spring-loaded elastic support
rollers □ 125 mm Three-phase drive motor 1.8 kW Travel
speed with / without load 4.5 / 6.0 km / h

[WH73RN2](#)