

Georgin



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Georgin** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Georgin Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Model: TXC100LA	Case 100mm SS with bottom connection and wall mounting bracket Case oil filled Range: 0-120°C Capillary: 12 metres SS with PVC cover Connection: 1/2" BSP type CS3 Stem: 90mm x 14mm Double magnetic contact: M11 Optional SS capillary with SS armor, where the SS armor is PVC covered Surcharge: 85, - Euro net / piece
Ref. BXNP13000-B0	Potentiometer convertor Input: orig: 0-> 30% ext: 70->100% Output: generator 4/20 mA Option: without, clamp terminals Input power supply: 230 Vac Rail DIN mounting interface ATEX information: EC type examination certificate LCIE 02 ATEX 6104X [Ex ia] IIC (-20 °C < Ta < 60 °C) Group II (surface) - category (1) G/D Installation in safe zone barrier for equipment installed in zone 0,1,2 gas or zone 20,21,22 dust See leaflet for a safe use customs code: 8504 3180 FR
FP6KX	Ref. FP6KX Pressure switch F series protection : IP66 housing : mazak, epoxy painted, st. st. screws range : -1 to 5 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2" GM switch : 1 tropicalized SPDT adjust. deadband : <0,205 to 1 bar current rating : 10A/240VAC - 0.5A/110VDC cable gland : polyamid M16 (Ø5-10) PED information: material complies with PED 2014/68/EU article reference: 0FP06BKS0000 customs code: 9032 2000 country of origin: France / U.E. Gewicht ca. 1,2 kg / Stck
FP-54-P	
FP-6-K	
303020	
30359 REGXPR03	

30392	
30903 XPC180PS0C000	
30994	
401011	
41181	
CPANFQ	
EPPX3FPHX0000	
FD16MX	
FDH34GX	
FKCT33V52KCBYAU	
FKCT33V5-2XCBY-AU	
FKCT35V52KCBYAU	
FP62RX	
GR5000S00	
IFC6DBPSAA6J0	
IFC6DBRSAA6J0	
IFC6DNPSAA3J0	
OFP06BPSY03A0 (FP6PX)	
PB30DLX	
SETPOINT 80 BAR INCREASING (?)	
SR5302A	
PDC-1.1.I.0	Pressure switch for non-aggressive liquids and gases Switching differential: Switching differential not adjustable Switching range: 1 to 10 bar Option: none
PDC-1.1.D.0	Switching differential: Switching differential not adjustable Switching range: 0.04 to 0.25 bar Option: none
PDC-1.1.E.0	Switching differential: Switching differential not adjustable Switching range: 0.1 to 0.6 bar Option: none
PDC-1.1.A.0	Switching differential: Switching differential not adjustable Switching range: 1 to 16 mbar Option: none
PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none
PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none

PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none
30980	Ref. C6PX Capillary temperature switch P series protection : IP66 housing : mazak, epoxy painted, st. st. screws range : 25 to 95 °C max. temperature : 105 °C sensing element : 3m capillary-bulb Ø14x150mm material : 316L st. st. capillary protection : st. st. armor switch : 1 SPDT, dry contact adjust. deadband :(low/high of range)4-25°C/2-9°C current rating : 5A/240VAC - 0.5A/110VDC cable gland : polyamid M20 (Ø7.5-13) features: st. st. tag plate PED information: material complies with PED 2014/68/EU Category IV article reference: 0PC06BPSYB0A0 customs code: 9032 1080 country of origin: France / U.E. Gewicht ca. 2,2 kg / Stück *****PLEASE CHECK THE TECHNICAL DETAILS!*****
GR3000A00	Ref. GR3000A00 (0 / 10 bar) Gauge pressure transmitter...GR/GA series housing : stainless steel / protection : IP65 range : 0 - 10 bar max. pressure : 30 bar sensor : ceramic cell on viton gasket process connection : 1/2" BSPM - st.st. 316L electrical connector : DIN43650 power supply : 10...30 Vdc output signal : 4...20 mA max. global error : <0.5% FS article reference: GR3000A00
GRD000S00	30702 Pressure transmitter 0 - 6 bar ATEX GR series pressure transmitter Case: stainless steel Degree of protection: IP65 Measuring range: 0 - 6 bar Maximum pressure: 15 bar Sensor: Ceramic cell, Viton seal Process connection: 1/2" BSPM Material: St. St. 316L electrical connector: DIN 43650 Supply voltage: 10 - 30 VDC Output: 4-20mA, 2-wire max error rate: <0.5% FS ATEX information: certificate LCIE 01 ATEX 6137X Ex ia IIC T6 or T5 Ga (-30<Ta<55 or 70°C) Ex ia IIIC T80°C or T95°C Da (-30<Ta<55°C or 70°C) Groupe II - category 1 GD - Zones 0-1-2 or 20-21-22 Ex ia I - Group I (Mines) - Category M1 Production Notification LCIE 02 ATEX Q 8023 Customs tariff number: 9026 2020 Country of origin: France / EU
RDN210000	30164 Intrinsically safe relay Input: 2x switch or proximity sensor Output: 1 x transistor per channel Option: without, clamp terminals Power supply: 230Vac Rail DIN mounting interface ATEX information: EC type examination certificate LCIE 02 ATEX 6104X [Ex ia] IIC (-20 °C < Ta < 60 °C) Group II (surface) - category (1) G/D Installation in safe zone barrier for equipment installed in zone 0,1,2 gas or zone 20,21,22 dust See leaflet for a safe use
0FP34PPAY03A0	FPA34PX pressure switch 0.5 - 10 bar F-Series Pressure Switches Degree of protection: IP66 Housing: Mazak, epoxy resin coated, stainless steel screws Measuring range: 0.5 - 10 bar maximum pressure: 80 bar Sensor element: BunaN membrane Material: BunaN - 316L stainless steel flange Process connection: 1/2" NPTM 2 simultaneous tropicalized SPDT contacts adjustable hysteresis: <0.52 - 2 bar Current: 10A/240VAC - 0.5A/110VDC electrical connection: M20x150 Special feature: stainless steel type plate Item code: 0FP34PPAY03A0 Customs tariff number: 9032 2000 Country of origin: France / EU Ref.FPA34PX Pressure switch F series protection : IP66 housing : mazak, epoxy painted-st. St.

	screws range : 0.5 to 10 bar
30367	REGFR12 Setting [2 SPDT (FP-FML)] Limit setting + sealing + test report Switching point: 3.5 bar *** please specify whether "rising" or "falling" should be set REGFR12 Setting [2 SPDT (FP-FML)] presetting/sealing/ test report set point at 3.5 bar ***direction "increasing" or "decreasing" to be confirmed*** TAG n° MLDP02 CP003
306154	M5000 pressure gauge D: 150 mm 0 - 10 bar M5000 series pressure gauge D: 150 mm - 304 st.st. - 4mm Safety glass Measuring range: 0 - 10 bar (Class 1) Connection: 1/2" NPTM below 316L st. st. Bourdon tube and Process connection 1 x SPDT contact (type 821-3) + filled with silicone oil Item code: M5000ED3P1F00 Customs tariff number: 9026 2040 Country of origin: France / EU Ref. M5000 (Ø150 0/10 bar) pressure gauge M5000 series case: Ø150 - 304 st.st. -safety glass 4mm range: 0...10 bar (class 1) connection : 1/2"NPTM bottom 316L st.st. bourdon tube and process connection 1 x SPDT contact (Type 821-3) + silicon oil filled article reference: M5000ED3P1F00
303003	ACCM5020 stainless steel tag plate ACCM5020 Stainless Steel tag plate material: AISI 304 SS
303007	Calibration certificate 5 points (M5000) 5 points: 0 - 25 - 50 - 75 - 100 % article reference: ACCM5000
40425	FKPT02V62ACBYLL pressure sensor 0.3125 - 5 bar FKP series pressure sensor min./max. Sapnne: 0.3125 - 5 bar max. pressure (overload limit): 15 bar Calibration range: *** please specify if desired*** Accuracy: +/- 0.1% of calibrated span Measuring membrane: 316L st.st. Bride: INOX 316L filled with silicone oil Process connection: 1/2" - 14 NPTI Power supply 10.5 - 45 VDC Electrical connection: 1/2" - 14 NPT Output signal: 4 - 20 mA (2-wire technology) + HART RFI protection according to IEC 801-3 Housing: die-cast aluminum alloy, Polyester coated Digital display (customized scaling) additionally: stainless steel nameplate equipped with Stainless steel fastening clamp for 2 inch pipe assembly Item reference: FKPT02V62ACBYLL
401158	Ref. P30KX Pressure switch P series protection : IP66 housing : mazak, epoxy painted-st. st. screws range : -1 to 3.5 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 2 simultaneous SPDT - tight deadband fixed deadband current rating : 5A/240VAC - 0.5A/130VDC cable gland : polyamid M20 (Ø7.5-13) article reference: OPP30BKS0000 include; 30398 REGPR12 presetting+ sealing+ test report set point: 1 bar decreasing
40098	Pressure switch Georgin 0.5-10 bar, type FP62PX Ref. FP62PX Pressure switch F series protection : IP66 / ATEX increased safety housing : mazak, epoxy painted, st. st. screws range : 0.5 to 10 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 1 SPDT Ex d IIC T6 adjust. deadband : <0,45 to 2 bar current rating : 5A/240VAC - 0.4A/250VDC cable gland :

	brass M16 (Ø4.5-10)-Ex e features: Ex de st. st. tag plate ATEX information: Certificate LCIE 02 ATEX 6161X Ex de IIC T6 (-20°C<Ta<60°C) Ex tD A21 IP66 T80°C Group II (Surface) - Category 2GD Zones 1-2 or zones 21-22 Production Notification LCIE 02 ATEX Q 8023 See leaflet for a safe use article reference: EFP62FPSY0000
FP62FX pressure switch 0...250 mbar ATEX	Ref. FP62FX Pressure switch F series protection : IP66 / ATEX increased safety housing : mazak, epoxy painted, st. st. screws range : 0 to 250 mbar max. pressure : 2 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 1 SPDT Ex d IIC T6 adjust. deadband : <34 to 250 mbar current rating : 5A/240VAC - 0.4A/250VDC cable gland : brass M16 (Ø4.5-10)-Ex e features: Ex de st. st. tag plate ATEX information: Certificate LCIE 02 ATEX 6161X Ex de IIC T6 (-20°C<Ta<60°C) Ex tD A21 IP66 T80°C Group II (Surface) - Category 2GD Zones 1-2 or zones 21-22 Production Notification LCIE 02 ATEX Q 8023 See leaflet for a safe use article reference: EFP62FFSY0000
30335	REGFR01 Setting [1 SPDT (FP-FML)] presetting/sealing/ test report set point at 100 mbar decreasing TAG n: 5YAX04 38 PSL ???
0fp06bpsx0300	
0fc06bpsxa0a0 Ref. Fc6px	
Tre000s000	
P96kx40bcs1	
Fc6tx	
0fp06bpsy0000	
Gf7013011b	
Article Code : 0pd54bksy0000	Ref. DPB54PX22 Diff.pressure switch P series protection : IP66 housing : mazak, epoxy painted-st.st. screws range : 0.15 to 4 bar min/max static pressure : -1 / 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 2 separate SPDT, dry contact adjust. from : <0,26 to 1 bar current rating : 5A/240VAC - 0.5A/110VDC cable gland : polyamid M20 (Ø7.5-13) PED information: material complies with PED 2014/68/EU Category IV Article code : OPD54BKSY0000 customs code: 9032 2000 country of origin: France / U.E.
Hdrhfdhf	
Art.-Code: T7100dd0p1jnr00	Ref. T7100 (100mm 0/100°C) inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...100 °C (class 1) stem : bottom connection bulb Ø10 x S= 300mm - 316L st.st. connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DD0P1JNR00 customs code: 9025 1980 country of origin: France / U.E.

Rdn 110000	
Fkpt02v52acby0y	
17a2e4	
Article Code : T7100dazr1knr00	inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...120 °C (class 1) sensing element : bottom connection - back flange capillary 8m - bulb Ø12 x S= 110mm - 316L st.st. capillary protection : no connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DAZR1KNR00 customs code: 9025 1980 country of origin: France / U.E.
Eppx4fpsx0000	
Fkpt02v52kcby0y	
Fp6px	
Bzg788+	
Gr5000s00 (0/50 Bar)	
Bxne ** 000e	
Gf7013010b	
Fp4k, Art. N: 0fp04bks00000	
Eppx4fps00000	
Fkct22v52acbyau	
Sealing Device - F Series	
Gre000s00	
Mpb10e	
0fp54bqsx0300 Ref. Fp54qx	
Fp6nx 95kpa Range0.1-2bar Max8bar	
P62px	
Fkpt03v52acba0y	
4do Fb621x	
Setpoint 80 Bar Increasing (?)	
S771	
Sr5002a00	
Gr7000s00	
Fkpt02v52acba0y	
Fc 54t	

Fp6sx	
Dpb54px22 0,15/4 Bar	
Article Code : T7100dazr1knr00 (12m)	Ref. T7100 (100mm 0/120 °C) inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...120 °C (class 1) sensing element : bottom connection - back flange capillary 12m - bulb Ø12 x S= 130mm 316L st.st. capillary protection : no connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DAZR1KNR00 customs code: 9025 1980 country of origin: France / U.E.
Fp6k+s680	
Phb96tx	
0fp06brsx0300 Ref. Fp6rx	
C6yx	
0pc06bysy0000	
Fc6gxrtpf	
Phb10rx	
P16ax40a6	
Hm451u3331211	
Fp62p	
199041294	
Grk000s00	
C96pxutox	
Art.-Code: T7100dazr1knr00	T7100 Industrial Inert gas pressure thermometer Industrial inert gas pressure thermometer the T7100 series suitable for heavy environments and corrosive media Housing: d: 100 mm, 304 st.st., 4 mm clear glass Measuring range: 0 - 120 ° C (class 1) Sensor element: bulb, d: 12 mm x S: 110 mm Material: 316L st.st., 8 m capillary Connection radially at the bottom - fastening at the rear Capillary tube protection: no Process connection: 1/2 "GM rotatable magnetic contact 821-11 + filled with dielectric oil Art.-Code: T7100DAZR1KNR00 Customs tariff number: 9025 1980 Country of origin: France / EU
Fp6nx 15kpa Range0-250mbar Max2bar	
Rdn110000	
	Ref. FP6K Pressure switch F series protection : IP66 housing : mazak, epoxy painted-st.st. screws range : -1 to 5 bar max. pressure : 13 bar sensing element : bellows material : bronze process connection : 1/2"GM switch : 1 tropicalized

Article Code : 0fp06bksa0000	SPDT adjust. deadband : <0,165 to 1 bar current rating : 10A/240VAC - 0.5A/110VDC cable gland : polyamid M16 (Ø5-10) Article code : 0FP06BKSA0000 customs code: 9032 2000 country of origin: France / U.E.
Tschg 100 Q 100 'C X 300 Mm.X Q 12 M11	
Bzg796	
M5000 Dd0w1g00	
Fkct22v52kcbyau	
Phb34sx	
Bvns0b00-00-00	
Fkpt01v52acby0y	
Fkct35v52acbyau	
Bxnp	
Ofp06bpsx0300	
Ofp06bpsyo3a0	
Pa36k	
Regpr13	Setting [2 SPDT (PL-DIFF)] presetting/sealing/ test report set point at ***to be confirmed***
Pressure Switch=2.5/25 Gerorgin Max30bar	PRESSURE SWITCH=2.5/25 GERORGIN MAX30BAR
Fp54qx	
0fp06bpsx0000	
Ertetert	
0fc06btx0000	
Fc6pxrtpf	
0fd06bmjx0200 Ref. Dfms6mx	
Regfr01	Setting [1 SPDT (FP-FML)] presetting/sealing/ test report set point at 0,5 bar decreasing Zolltarifnummer: 9026 8099 Ursprungsland: Frankreich / EU
0fp06bvlx0300 Ref. Fpl6vx	
Fkpt03v52acby0y	
Fp-6-K -1/5 Bar	
Fp6nx 8kpa Range0-250mbar Max2bar	

Dfsdgdgfd
Fb621x
Fkpt03v52kcb0y
0pd06bcb00200 Ref. Dmpb6m11
Txc100la-0/120'C-8m Kss+pvc-A-Cs3-1/2"Bsp 90x14mm-M11
0fc06btsx0000
Fp4drx
P162px
Fkct33v52acbyau
0fp04bksa00a0 Ref. Fp4k
Rdn211
0fp06bpsy03a0
Fp6nx 0.1mpa Range-1-5bar Max15bar
Fp4kx
Fb54p
Fp6nx 5kpa Range0-250mbar Max2bar
P96pxutox1
0fp06bssx05h0
0fp06bssx0300
199041196