

Goetze

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Goetze Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Goetze Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
06-892600-20	
618tGFO-20-f/f-20/20 - PTFE	Series 618 Gunmetal pressure relief valve overflow control valve (only with tGFO) not component tested Gas-tight version of the spring cap for gaseous and liquid media without ventilation Valve size DN20 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN20 - 3/4" Outlet size: DN20 - 3/4" Seal PTFE Pressure range from 0.20 bar to 0.80 bar
Pressure regulator Regulator DN50 PN25 - DI	Standart:EN 1988
DN50 10 BAR	
810sGK-15-m/-15/ - FKM	Series 810 Brass safety valve TV CE component tested free blowing cylindrical design not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: male thread BSP-P Inlet size: DN15 - 1/2" Gasket FKM Pressure 5 bar fixed. Component code 1 19-2055.11.D/G.0.8. 1000000000484
412sGK-15-m/-15/ - PTFE	Series 412 Stainless steel safety valve TV CE component tested free blowing cylindrical design not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: male thread BSP-P Inlet size: DN15 - 1/2" Seal

	PTFE Pressure 6 bar fixed. Component code 1 20-2003.14.D/G.0.76. 1000000376889
851bGK-15-f/f-15/25 - FKM	Series 851 Gunmetal safety valve in corner shape TÜV CE component tested with bellows for gaseous media with rotary lift Valve size DN15 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN15 - 1/2" Outlet size: DN25 - 1" Gasket FKM Pressure 10 bar fixed Component code 1 22-666.15.8.D/G-F/K/S.0.33. 1000000493882
851sGK-15-f/f-15/25 S4 PTFE	Gunmetal safety valve in corner shape Series 851 TÜV CE component tested not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN15 - 1/2" Outlet size: DN25 - 1" Spring bonnet without relief hole Seal PTFE Pressure 2.2 bar fixed. Customs Tariff No. 84814090 Component code 1 22-666.15.8.D/G.0.33. 1000000614473
15 450870 00	
628sGFL-15-f/f-15/15 PTFE 7,5 bar	
617tGFO-25-f/f-25/25 FE PTFE	
482mGFO-SP-50-FL/FL-50/50 GOX FKM BAM	Stainless steel pressure reducing valve in passage form with elastomer membrane for gaseous and liquid media without ventilation Back pressure 1-8 bar Valve size DN50 Entry: DIN cast flange connection Outlet: DIN cast flange connection Nominal inlet width: DN50 - 2" Nominal outlet width: DN50 - 2" BAM (CTE) tested materials for gaseous oxygen free of oil and grease Seal FKM BAM Pressure range from 1 bar to 8 bar
683mGO-15-f/f-15/15 - NBR	Pressure reducing valve made of gunmetal in straight-through form with elastomer membrane for gaseous media without lifting valve size DN15 inlet: internal thread BSP-P outlet: internal thread BSP-P inlet nominal width: DN15 - 1/2" outlet nominal width: DN15 - 1/2" seal NBR pressure range from 1.5 bar to 10 bar
Pressure gauge axial	Ø50 mm 0-10 bar, brass G1/4, class 1.6
683mGO-15-f/f-15/15 - NBR	683 Pressure reducing valve made of gunmetal in straight-through form with elastomer membrane for gaseous media without lifting valve size DN15 inlet: internal thread BSP-P outlet: internal thread BSP-P inlet nominal width: DN15 - 1/2" outlet nominal width: DN15 - 1/2" seal NBR pressure range from 1.5 bar to 10 bar
1/2 " stainless vacuum crusher	
618tGFO-25-f/f-25/25 - PTFE	pressure relief valve made of gunmetal overflow control valve (only for tGFO) not component tested gas-tight design of the spring cap for gaseous and liquid media without ventilation valve size DN25 Inlet: Internal thread BSP-P Outlet: internal thread BSP-P Inlet nominal diameter: DN25 - 1" Outlet nominal diameter: DN25 - 1" PTFE seal pressure range from 0.5 bar to 2.5 bar
	pressure relief valve made of gunmetal overflow control valve

618tGFO-25-f/f-25/25 - LA PTFE	(only for tGFO) not component tested gas-tight design of the spring cap for gaseous and liquid media without ventilation valve size DN25 Inlet: Internal thread BSP-P Outlet: internal thread BSP-P Inlet nominal diameter: DN25 - 1" Outlet nominal diameter: DN25 - 1" pressure range from 2 bar to 12 bar 1000000537709
618tGFO-15-f/f-15/15 EAC PTFE	706-VSL pressure relief valve made of gunmetal overflow control valve (only for tGFO) not component tested gas-tight design of the spring cap for gaseous and liquid media without ventilation valve size DN15 Inlet: Internal thread BSP-P Outlet: internal thread BSP-P Inlet nominal diameter: DN15 - 1/2" Nominal outlet width: DN15 - 1/2" with EAC marking PTFE seal pressure range from 2 bar to 12 bar
618tGFO-15-f/f-15/15 - PTFE	pressure relief valve made of gunmetal overflow control valve (only for tGFO) not component tested gas-tight design of the spring cap for gaseous and liquid media without ventilation valve size DN15 Inlet: Internal thread BSP-P Outlet: internal thread BSP-P Inlet nominal diameter: DN15 - 1/2" Nominal outlet width: DN15 - 1/2" pressure range from 12 bar to 20 bar 1000000368172
76.90 \ H-41 \ NB60	
851t	
Lwd Nb60 76.90 H-76	
852tgfl-50-FI/FI-50/80 Epdm	
77000044	
1160483	
C1.990.288 ~ Sealed Safety Valve 417 Bs+	
618tgfo-40-F/F-40/40 Ptfе	
Goe Daaе012961	
813mgk-25-M/-25/ Nbr	
618tgfo-25-F/F-25/25 Ptfе Baureihe 618	
76.97 H23	
352tgl-50-FI/FI-50/80 Ptfе	
Goe Top C95 Groove1	
Goe Top C86 Groove2	
76.90 ?-89	
810sgk-25-M/-25/ Fkm	
652sgk-40-F/F-40/40 Nbr	

851sgk-15-F/F-15/25-Ptfe-8bar
1160490
851tgf0-25-FI/FI-25/40 Epdm 10 Bar
104207, Drg No 412365c
810sgk-20-M/-20/ Fkm
14021970 Obsolete
1160643
76.90 H-81 Si60 Bg 1100059030
5035005200
76.53-1700k Nb6022 67-341038-99
1384679 Hn60plz 7690 H-89 11-000776-10
701 157 00
76.90 H-75a3 Hn60 Cf S
Nb 60 H05
76.21-3000 10-000043-10
1368535
76.90 Hel 127 A2 Hn60 Cf S
618tgfo-15-F/F-15/15 Ptfe Baureihe 618
76.90 H-75 Fp70
852tgfl-40-FI/FI-40/65 Epdm
76.90 H30 Nb60
7697h23nb60
76.90 H-01 Nb60
851sgk-20-F/F-20/32 Ptfe
851sgk-15-F/F-15/25 Ptfe
76.90-4201
618 Dn 15 G1/2 0-8
Nb 60 H08
77000117
76.90 Hel 127 A2 Hn60 Cf S (Ab 26 St.)

[810sgk-15-M/-15/ Fkm](#)

[77000090](#)

[76.62-5000k Nb6022 67-341295-99 \(Ex
60-341295-70\)](#)

[Hn60plz 7690 H-89 11-000776-10](#)