



## Gossen Metrawatt

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Gossen Metrawatt** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Gossen Metrawatt T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Sineax U553</a>	AC voltage transducer, RMS, with power supply
<a href="#">02074</a>	
<a href="#">Messbereich 0-10V</a>	Betriebsspannung 300 V 600 V 600 V Pr¼fspannung 3,5 kV 5,8 kV 5,8 kV Bei Messeingang > 15 A und ≤ 40 A Schraube M6 Ber¼hrungsschutz Shunt-Anschluss Leistungsaufnahme ca. 7 mA ± 10 % Leitungswiderstand 0,06 Ω (kalibriert) ± 10 % 1A ... 60A Spannungsabfall ca. 60 mV ± 10 % ≥ 1 V ca. 1000Ω/V ±10%
<a href="#">SINEAX U539</a>	147000
<a href="#">rs232</a>	
<a href="#">485</a>	
<a href="#">R6000-V001</a>	

<a href="#">R6000-V002</a>	8 channel controller in a DIN rail housing, Self-optimization, configurable inputs thermocouple / Pt100, Data logger, alarm history, power limitation, hot runner functions, Auxiliary voltage 24 V DC, configuration tool R6Konfig, A0 (16 binary inputs / outputs) D0 (screw terminal blocks) F3 (RS485 Modbus interface) Total net weight: Approx.1.842kg
<a href="#">DM5S-SINEAX DM5S</a>	Multi-transducer with analog output, MODBUS/RTU (optional), programmable With the following configuration: NLB version: Not according to NLB 01.Construction Without display, for DIN rail mounting 02.Application universal version. all applications 3U/3I 03.Rated frequency 45..50/60..65 Hz 04. Auxiliary power rated voltage 24..230V DC, 100..230V AC 05.Bus connection without 06.Outputs 2 analogue outputs, bipolar ±20mA 07. Test report report English (basic programming) 08.Programming Basic programming Country of origin: Switzerland Statistical goods number: 85437090
<a href="#">172081</a>	USB CABLE type A to type B, length 1.8m for SINEAX DM5S
<a href="#">AC-Hochspannungsprüfsystem</a>	The test system should be able to output at 50Hz frequency and have a power of 60kV 1A 50-60 KVA. The test system must be PD-Free to allow partial discharge measurement. The test system should contain 50kV-60kV 1nF coupling capacitor for partial discharge measurement. The test system should contain a 50kV-60kV 100pF SF6 isolated reference capacitor for tandelta measurement. The test system must have a PLC control unit with a touch panel. The test system should have a security system that will give an audible and light warning during the test. The test system should have 99 programmable interfaces and memories for different test parameters. The test system should have a resolution of 0.01kV. Test system Vmax. It should have a voltage rise rate of 2.06 kV/s. The test system should be able to work at a temperature of -10 +35 degrees. The test system should have an emergency stop button to cut off the power in an emergency.
<a href="#">DC Hi-Pot</a>	0-80 kV dc voltage 2.5% voltage fluctuation at 50 Hz at full load. 3-stage kV panel 4-stage current panel Adjustable tension application switch High voltage discharge resistor. Input-output protection fuses. 10 mA application for 15 minutes
<a href="#">SIRAX BT5100</a>	Programmable transmitter for Tension 01. With LCD display, for DIN rail mounting 02. Input range: AC 1P voltage unifunctional 03. Frequency range: 45...65 Hz 04. Measuring input current via current: Without 05. Measuring input current over voltage: Without 06. Measuring input voltage: 57...500 V LL 07. HE: 60...300 V AC/DC 08. Bus connection: RS485 (RTU) 09. Standard protocol: Modbus 10. Output: 0...20 mA / 4...20 mA or 0...10 V 11. Measurements: Standard 12. Test report: English ***Successor to U553 ***
<a href="#">194985</a>	SIRAX BT5100 AC voltage transducer 01. With LCD display DIN rail mounting 02. Input range: AC 1P voltage unifunctional 03. Frequency range: 45...65 Hz 04. Measuring input current via current: Without 05. Measuring input current over voltage: Without 06. Measuring input voltage: 57#500 V

	LL 07. HE: 24#60 V AC/DC 08. Bus connection: RS485 (RTU) 09. Standard protocol: Modbus 10. Output: 0...20 mA / 4...20 mA or 0...10 V 11. Measurements: Standard 12. Test report: English ***Nachfolger zu U553 ***
<a href="#">195617</a>	programming cable PRKAB5000 to SIRAX Basic transmitter
<a href="#">M246a</a>	Multimeter for testing copper cable installation, battery
<a href="#">M227a</a>	Milliohm- and Multimeter incl. KS17S, GH18 und ISO17025 Cal
<a href="#">M227s</a>	Tester Hybrid & E-CAR Set, tester, charger NA HIT27
<a href="#">M500x</a>	Universal tester M520P, Z500A, Z503F, PRO-AB, PRO-RLO-II
<a href="#">Z201b</a>	30 A DC, 100 mV / A DC AC
<a href="#">Z202b</a>	300 A DC, 10 mV
<a href="#">M113a</a>	Analog-multimeter including lead set and carrying strip
<a href="#">M242d</a>	HC20, MetraHit pro, WZ12A
<a href="#">M210a</a>	Exi-digital multimeter, CAT IV 1000 V
<a href="#">Metrahit27i</a>	(PRICE/EA) INSULATION DIGITAL MULTIMETER AND DATA LOGGER, AUTO/MANUAL RANGING WITH TEMPERATURE
<a href="#">M520n</a>	PROFITEST MBASE+, add.Selective Earth resistance test
<a href="#">Z211c</a>	Calibrator software for F5500A / F5520A
<a href="#">Z211e</a>	Update for METRAWin 90-2
<a href="#">M234d</a>	USB interface, lead set KS 17
<a href="#">M520s</a>	Universal tester for Testing protective devices ac. DIN VDE
<a href="#">Z821b</a>	3000A
<a href="#">Gtm5101000r0001</a>	Simulating model for Testing protective devices in power
<a href="#">M512r</a>	Adapter for testing of PRCD-K and PRCD-S
<a href="#">M244b</a>	Set METRAHIT CAL and METRAHIT X-TRA in HC30, incl. KS,
<a href="#">M521d</a>	PROFITEST C operator guidance in English
<a href="#">M244a</a>	Calibrator for Voltage, Resistance, Current, temperature
<a href="#">Z502f</a>	Barcode reader, RS232 (Laser Sensor)
<a href="#">M240a</a>	MetraHit X-tra, TRMS-multimeter
<a href="#">Z591b</a>	Generator clamp: 1000 A / 1 A, 0.2 mA to1200A, 0.2 mA to 1.2 A
<a href="#">K850a</a>	DC Electronic Load, 150W Input Power
<a href="#">M227f</a>	Milliohmmeter for EX, incl. Kelvin Sonde, Kelvin Clip

<a href="#">M227t</a>	Tester Hybrid & E-CARs, METRAHIT tester, charger
<a href="#">M630a</a>	Low Ohm Tester according to DIN VDE 0413, battery powered
<a href="#">M227o</a>	Tester Hybrid &E-CAR incl. Case HC30, METRAHIT tester, charger
<a href="#">M501f</a>	PROFITEST MTECH+ (M520R), Z613A , Z500A, Z503F, Z503A, Z501P
<a href="#">M500v</a>	Universal tester M520P, Z500A, Z503F, case Z503D, Z503E, Z502H
<a href="#">M520p</a>	PROFITEST MTECH, add. Selective Earth resistance test
<a href="#">M227c</a>	Test Kit including data acquisition-system with M227B
<a href="#">M251a</a>	Current measurement withcurrent sensors with voltage output
<a href="#">M248a</a>	TRMS multimeter digital triple display, 310000 Digit,
<a href="#">M523a</a>	Unit for testing the DC- component, tripping current
<a href="#">M252a</a>	Special multimeter without fuse Measurement w/CurrentClamps
<a href="#">Z225a</a>	0.2%)
<a href="#">M227g</a>	Set consisting of milliohmmeter for explosive atmospheres
<a href="#">M693d</a>	Hi Voltage Current Leakage Tester for Medical Devices
<a href="#">M501a</a>	PROFITEST MBASE+ (M520S), Z500A , Z503F, Z700D, Z502H, Z502R
<a href="#">Z246a</a>	Avionic Service case (without DMM), 68 parts, special test
<a href="#">M7010-V013</a>	Universal Electrical Safety Tester for portable equipment
<a href="#">M521a</a>	Tester for fault-current operated protective devices
<a href="#">M250a</a>	ETECH plus data storage (8MBit) and connector for power pack
<a href="#">M227b</a>	Milliohm- Insulation- and Multimeter including NA4/500
<a href="#">M687a</a>	TRMS multimeter: 4 1/2, Data Storage, GH, KS17-2, batter
<a href="#">M246s</a>	Multimeter like METRAHIT T-COM and insolation testing 10V
<a href="#">M253a</a>	ESPECIAL plus capacity measurement current measurement
<a href="#">M520r</a>	PROFITEST MBASE+, add.trip test for RCDs &loop resistance test
<a href="#">M501d</a>	PROFITEST MTECH+ (M520R), Z500A , Z503F, Z502M, Z502H, Z502R
<a href="#">M7050-V003</a>	Universal Electrical Safety Tester for devices

<a href="#">M227u</a>	Tester Hybrid & E-CARs METRAHIT tester, charger
<a href="#">M246n</a>	Avionic Service case including METRAHIT ISO Aero
<a href="#">M230b</a>	Precision-Digital-Multimeter including lead set KS
<a href="#">M7050-V001</a>	Universal Electrical Safety Tester for devices
<a href="#">Metrahitx-Tra</a>	(PRICE/EA) DIGITAL MULTIMETER, TRUE RMS, 12000 COUNT, AUTO/MANUAL RANGING WITH INFRARED INTERFACE, ROHS COMPLIANT: NA
<a href="#">M246b</a>	Insulation tester TRMS-Multimeter, KS17-2, battery
<a href="#">K851a</a>	DC Electronic Load, 300W Input Power
<a href="#">M210b</a>	Exi-digital multimeter, CAT IV 1000 V, lithium battery
<a href="#">M243e</a>	MetraHit TECH, TRMS-Multimeter, no Interface, rubber holster
<a href="#">M692b</a>	Electrical Safety Tester for Medical Devices
<a href="#">Z211f</a>	Calibrator- and adjustment software
<a href="#">536-</a>	G 536 phase angle With the following configuration: NLB version: Not according to NLB 01.Form 4 SINEAX in housing P13, rail-mounted. 02.Message 2 power factor (prop.cosPhi) 03.Application 2 3-od.4L-Drehstr.U: L1-L2 / I: L1 04. input nominal frequency 1 rated frequency: 50 Hz 05. input rated voltage 9 inputs. Un [V]: Rated voltage [V] 110.00 06. Input rated current 1 input current In: 1 A 07.Measurement 2 MB: 0.5..cap..1..ind..0.5 08. Output signal 2 Output: 4 ... 20mA 09.Auxiliary energy 2 Uh: 24..60V DC / AC 10.Setting time 1 4 periods of input freq. 11. Test Protocol 0 without test protocol
<a href="#">M245a</a>	Multimeter /calibrator for voltage, current, resistance
<a href="#">M501b</a>	PROFITEST MTECH+ (M520R), Z500A , Z503F, Z503D, Z503E, Z502H
<a href="#">Z211a</a>	Calibrator software
<a href="#">Z227t</a>	ADK Automotive diagnostics test case kit
<a href="#">M248b</a>	METRAHIT ULTRA, with Bluetooth interface, Android App
<a href="#">M500w</a>	Universal tester M520P, Z500A, Z503F, PRO-W, PRO-RLO-II
<a href="#">M246m</a>	Special edition for avionic maintenance, TRMS-multimeter
<a href="#">M520u</a>	PROFITEST MBASE+, add.Trip test for RCDs and loop resistance
<a href="#">Z751g</a>	RFID-reader / RFID scanner for RS232- (13.56 MHz)
<a href="#">M693b</a>	Current Leakage Tester for Medical Devices
<a href="#">Z721d</a>	Barcode- and label printer incl Software for USB interface

<a href="#">M246c</a>	TRMS-Multimeter, insulation (50V...1000V)
<a href="#">M240o</a>	MetraHit X-TRA, plus waterproof multimeter
<a href="#">M500y</a>	Universal tester M520P, Z500A, Z503F, PRO-W, E-clip 2, Z3512A