



Gossen Metrawatt

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Gossen Metrawatt Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Gossen Metrawatt T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Sineax U553	AC voltage transducer, RMS, with power supply
02074	
Messbereich 0-10V	Betriebsspannung 300 V 600 V 600 V Pr¼fspannung 3,5 kV 5,8 kV 5,8 kV Bei Messeingang > 15 A und ≤ 40 A Schraube M6 Ber¼hrungsschutz Shunt-Anschluss Leistungsaufnahme ca. 7 mA ± 10 % Leitungswiderstand 0,06 Ω (kalibriert) ± 10 % 1A ... 60A Spannungsabfall ca. 60 mV ± 10 % ≥ 1 V ca. 1000Ω/V ±10%
SINEAX U539	147000
rs232	
485	
R6000-V001	

R6000-V002	8 channel controller in a DIN rail housing, Self-optimization, configurable inputs thermocouple / Pt100, Data logger, alarm history, power limitation, hot runner functions, Auxiliary voltage 24 V DC, configuration tool R6Konfig, A0 (16 binary inputs / outputs) D0 (screw terminal blocks) F3 (RS485 Modbus interface) Total net weight: Approx.1.842kg
DM5S-SINEAX DM5S	Multi-transducer with analog output, MODBUS/RTU (optional), programmable With the following configuration: NLB version: Not according to NLB 01.Construction Without display, for DIN rail mounting 02.Application universal version. all applications 3U/3I 03.Rated frequency 45..50/60..65 Hz 04. Auxiliary power rated voltage 24..230V DC, 100..230V AC 05.Bus connection without 06.Outputs 2 analogue outputs, bipolar ±20mA 07. Test report report English (basic programming) 08.Programming Basic programming Country of origin: Switzerland Statistical goods number: 85437090
172081	USB CABLE type A to type B, length 1.8m for SINEAX DM5S
AC-Hochspannungsprüfsystem	The test system should be able to output at 50Hz frequency and have a power of 60kV 1A 50-60 KVA. The test system must be PD-Free to allow partial discharge measurement. The test system should contain 50kV-60kV 1nF coupling capacitor for partial discharge measurement. The test system should contain a 50kV-60kV 100pF SF6 isolated reference capacitor for tandelta measurement. The test system must have a PLC control unit with a touch panel. The test system should have a security system that will give an audible and light warning during the test. The test system should have 99 programmable interfaces and memories for different test parameters. The test system should have a resolution of 0.01kV. Test system Vmax. It should have a voltage rise rate of 2.06 kV/s. The test system should be able to work at a temperature of -10 +35 degrees. The test system should have an emergency stop button to cut off the power in an emergency.
DC Hi-Pot	0-80 kV dc voltage 2.5% voltage fluctuation at 50 Hz at full load. 3-stage kV panel 4-stage current panel Adjustable tension application switch High voltage discharge resistor. Input-output protection fuses. 10 mA application for 15 minutes
M246a	Multimeter for testing copper cable installation, battery
M227a	Milliohm- and Multimeter incl. KS17S, GH18 und ISO17025 Cal
M227s	Tester Hybrid & E-CAR Set, tester, charger NA HIT27
M500x	Universal tester M520P, Z500A, Z503F, PRO-AB, PRO-RLO-II
Z201b	30 A DC, 100 mV / A DC AC
Z202b	300 A DC, 10 mV
M113a	Analog-multimeter including lead set and carrying strip
M242d	HC20, MetraHit pro, WZ12A

M210a	Exi-digital multimeter, CAT IV 1000 V
Metrahit27i	(PRICE/EA) INSULATION DIGITAL MULTIMETER AND DATA LOGGER, AUTO/MANUAL RANGING WITH TEMPERATURE
M520n	PROFITEST MBASE+, add.Selective Earth resistance test
Z211c	Calibrator software for F5500A / F5520A
Z211e	Update for METRAWin 90-2
M234d	USB interface, lead set KS 17
M520s	Universal tester for Testing protective devices ac. DIN VDE
Z821b	3000A
Gtm5101000r0001	Simulating model for Testing protective devices in power
M512r	Adapter for testing of PRCD-K and PRCD-S
M244b	Set METRAHIT CAL and METRAHIT X-TRA in HC30, incl. KS,
M521d	PROFITEST C operator guidance in English
M244a	Calibrator for Voltage, Resistance, Current, temperature
Z502f	Barcode reader, RS232 (Laser Sensor)
M240a	MetraHit X-tra, TRMS-multimeter
Z591b	Generator clamp: 1000 A / 1 A, 0.2 mA to1200A, 0.2 mA to 1.2 A
K850a	DC Electronic Load, 150W Input Power
M227f	Milliohmmeter for EX, incl. Kelvin Sonde, Kelvin Clip
M227t	Tester Hybrid & E-CARs, METRAHIT tester, charger
M630a	Low Ohm Tester according to DIN VDE 0413, battery powered
M227o	Tester Hybrid &E-CAR incl. Case HC30, METRAHIT tester, charger
M501f	PROFITEST MTECH+ (M520R), Z613A , Z500A, Z503F, Z503A, Z501P
M500v	Universal tester M520P, Z500A, Z503F, case Z503D, Z503E, Z502H
M520p	PROFITEST MTECH, add. Selective Earth resistance test
M227c	Test Kit including data acquisition-system with M227B
M251a	Current measurement withcurrent sensors with voltage output
M248a	TRMS multimeter digital triple display, 310000 Digit,

M523a	Unit for testing the DC- component, tripping current
M252a	Special multimeter without fuse Measurement w/CurrentClamps
Z225a	0.2%)
M227g	Set consisting of milliohmmeter for explosive atmospheres
M693d	Hi Voltage Current Leakage Tester for Medical Devices
M501a	PROFITEST MBASE+ (M520S), Z500A , Z503F, Z700D, Z502H, Z502R
Z246a	Avionic Service case (without DMM), 68 parts, special test
M7010-V013	Universal Electrical Safety Tester for portable equipment
M521a	Tester for fault-current operated protective devices
M250a	ETECH plus data storage (8MBit) and connector for power pack
M227b	Milliohm- Insulation- and Multimeter including NA4/500
M687a	TRMS multimeter: 4 1/2, Data Storage, GH, KS17-2, batter
M246s	Multimeter like METRAHIT T-COM and insolation testing 10V
M253a	ESPECIAL plus capacity measurement current measurement
M520r	PROFITEST MBASE+, add.trip test for RCDs &loop resistance test
M501d	PROFITEST MTECH+ (M520R), Z500A , Z503F, Z502M, Z502H, Z502R
M7050-V003	Universal Electrical Safety Tester for devices
M227u	Tester Hybrid & E-CARS METRAHIT tester, charger
M246n	Avionic Service case including METRAHIT ISO Aero
M230b	Precision-Digital-Multimeter including lead set KS
M7050-V001	Universal Electrical Safety Tester for devices
Metrahitx-Tra	(PRICE/EA) DIGITAL MULTIMETER, TRUE RMS, 12000 COUNT, AUTO/MANUAL RANGING WITH INFRARED INTERFACE, ROHS COMPLIANT: NA
M246b	Insulation tester TRMS-Multimeter, KS17-2, battery
K851a	DC Electronic Load, 300W Input Power
M210b	Exi-digital multimeter, CAT IV 1000 V, lithium battery
M243e	MetraHit TECH, TRMS-Multimeter, no Interface, rubber holster
M692b	Electrical Safety Tester for Medical Devices

Z211f	Calibrator- and adjustment software
536-	G 536 phase angle With the following configuration: NLB version: Not according to NLB 01.Form 4 SINEAX in housing P13, rail-mounted. 02.Message 2 power factor (prop.cosPhi) 03.Application 2 3-od.4L-Drehstr.U: L1-L2 / I: L1 04. input nominal frequency 1 rated frequency: 50 Hz 05. input rated voltage 9 inputs. Un [V]: Rated voltage [V] 110.00 06. Input rated current 1 input current In: 1 A 07.Measurement 2 MB: 0.5..cap..1..ind..0.5 08. Output signal 2 Output: 4 ... 20mA 09.Auxiliary energy 2 Uh: 24..60V DC / AC 10.Setting time 1 4 periods of input freq. 11. Test Protocol 0 without test protocol
M245a	Multimeter /calibrator for voltage, current, resistance
M501b	PROFITEST MTECH+ (M520R), Z500A , Z503F, Z503D, Z503E, Z502H
Z211a	Calibrator software
Z227t	ADK Automotive diagnostics test case kit
M248b	METRAHIT ULTRA, with Bluetooth interface, Android App
M500w	Universal tester M520P, Z500A, Z503F, PRO-W, PRO-RLO-II
M246m	Special edition for avionic maintenance, TRMS-multimeter
M520u	PROFITEST MBASE+, add.Trip test for RCDs and loop resistance
Z751g	RFID-reader / RFID scanner for RS232- (13.56 MHz)
M693b	Current Leakage Tester for Medical Devices
Z721d	Barcode- and label printer incl Software for USB interface
M246c	TRMS-Multimeter, insulation (50V...1000V)
M240o	MetraHit X-TRA, plus waterproof multimeter
M500y	Universal tester M520P, Z500A, Z503F, PRO-W, E-clip 2, Z3512A