

Gruner



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Gruner Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Gruner Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Typ 236r3-230-04-054	230VAC, 2,5W 4NM, 30s/90 50%ED, IP54
360-024-20-S2	
3 way valves	haben sie es in dieser Ausfhrung: Dn50,dn40 12dc gibt es auch 220V wenn ja knnen sie mir fr die beiden einen Angebot schicken
720d-r1a-b032-005 12v 100a/250vac	
ul-722d-r1a-b105-031	Relay
235R3-230-04-058	
235R3 230-04-054	
235R3-230-04-054	
UL-722Q-R1A-B025	
19793	
227C-024-05	
227C-024-15	
227CMX-024T-15 MI	
227S-230-05-073	
30456	

33163	
33368	
361-024-10	
38250	
721G-R1A-B032	
850BH-R1A-D014	
93000	
PSE60-600-70	
HC-1011644	
HC-1015876	
225-230T-05/NI	
721D-R1A B032	
363-230-20G-S2-P5	GRUNER 363-230-20G-S2-P5 230V 2-/3-point damper drive 20Nm
T 31878	
363-230-20G-S2-P5	GRUNER 363-230-20G-S2-P5 230V 2-/3-point damper drive 20Nm
00.9109024.01	Type 235R3-230-04-054
236R3-230-04-064	230 VAC, 2,5 W, 4 NM, IP54
328CS-024-15B	47867 Rotary drive without spring return 24 VAC/DC, continuous control (0)2-10 V 15Nm, 3-5s/90° Connection cable 1000 mm Specification YSP 328 000
233D3-230-100-S1-007	230VAC . 50/60Hz 2,5W 100N 30s/40mm (IP54)
19119 721D-R1A-B032/ 12VDC	
721D-R1A-B032	
227csz-024-05-077 24vac/Dc	50/60hz 3,5w(5,5va) 5nm 20?35s-90? Y,U=2?10vdc 7/49
720D-R1A-B032-055	
UL-722D-R1A-B105-023	Relay
235R3-230-04-05	
363-024-20-S2	10177 Rotary drive without spring return 24 VAC/DC, 2/3 point Torque 20 Nm Running time 150 s/90° Connection with 1m cable Feedback signal: 2x additional switches Shaft drive: Ø 9-26 mm, square 9-18 mm Mounting with mounting strip + screws

227S-230-08	Rotary drive without spring return 120...230 VAC/DC, 2/3 point Torque 8 Nm Running time 20 s/90° Connection with 1m cable Feedback signal: - Shaft drive: O 8-20 mm, square 8-15 mm Mounting with mounting strip + screws
V2FA.40_25	Gruner 2-way control ball valve CCV hp 1600 kPa Internal thread: 1 1/2", 40, kvs 25.0 m3/h Housing: pressed brass Closing body:Stainless steel SS316L Spindle: stainless steel SS316L Seal: PTFE+Graphite / EPDM O-ring Medium temperature: 5...95°C Characteristic curve: A-AB equal percentage Leak rate: A-AB air bubble tight PN20
V2FA.40_40	Gruner 2-way control ball valve CCV hp 1600 kPa Internal thread: 1 1/2", DN40, kvs 40.0 m3/h Housing: pressed brass Closing body: SS316L stainless steel Spindle: stainless steel SS316L Seal: PTFE+Graphite / EPDM O-ring Medium temperature: 5...95°C Characteristic curve: A-AB equal percentage Leak rate: A-AB air bubble tight PN20
721D-R1A-B032	12VDC Q20 32R/32R 100A/25KVA 20085 TDWC4
235R3-230-04-054	
UL-722D-R1A-B105-031	
363-230-20G-S2-P5	Rotary drive without spring return 120...230 VAC/DC, 2/3 point Torque 20 Nm Running time 60 s/90° Connection with 1m cable Feedback signal: 2x additional switches, Potentiometers Shaft drive: O 9-26 mm, square 9-18 mm Mounting with mounting strip + screws
704L-R1A-H050	12V Latch relay - Polarized latching relay with manual override, 1 NO, up to 20 A/250 VAC lamp loads
363-230-20G-S2-P5	Rotary drive without spring return 120...230 VAC/DC, 2/3 point Torque 20 Nm Running time 60 s/90° Connection with 1m cable Feedback signal: 2x additional switches, Potentiometer Shaft drive: O 9-26 mm, square 9-18 mm Mounting with mounting strip + screws Feedback signal potentiometer 5 kΩ
232d3-230-06-059	
UI740a-R2a-B024-021-200a	
UI-721e-R1a-H032	
232-024-15-S2 - By 227-024-15-S1	
Fpc212	
227-230-15	
721d-R1a-B032	
227csz-024-05-077 24v 5nm	
235r3-230-04-064	
232d3-115-06-57	

227csz-024-05-077	
227-230-08	
722d-R1a-B105	
704-Ria-H050	
722d-R1a-B025	
00.9109024.01	
UI-722d-R1a-B105-031	
38251	
235-024-04	
37585	
740a-R2a-B024	
238-230-15	
232d3-230-06-011 Obsolete/Replaced By 363-230-20g-S2-P5	
UI-722q-R1a-B025	
227-230d-05	
227s-231-05-090	
323-024-15-S2 - Does Not Exist, Correct Code 232-024-15-S2 - , By 227-024-15- S1	
00 9109024 01 235r3 230 04 054	
227v-024	
UI-722f-R1a-B105	
227-024-05-S1-094	
237d-230-26-009	
227cs-024-05	
237D-230-26	ARt. Nr. 16968 Rotary drive, 26Ncm spring return 230VAC, 10s/90°, cable 1m 2-point control
740a R2a B 6r0 Not Availible	
UI-740-A-R2a-B024-014	
22808 Damper Motor 24vdc C/ W P	
Part Å720d-R1a-B032, 12vdc, 32r/32r, 100a/250vac, Q9 07153	

38252
720d-R1a-B032
33369
750h-R1a-B010-003
37585 361-230-20
227csz-024-05-077 24vac/Dc 50/60hz 3,5w(5,5va) 5nm 20?35s-90? Y,U=2? 10vdc 7/49
720d-R1a-B032 (12v Dc Gruner Relay)
723i-R1a-B430 120a, 250vac
227-230-05 Elektroantrieb 5 Nm
227-S-230-05-090
Bofbj206k3b+225-024t-05
227-230-15-S1
363-024-30-S2
Type 227 - Gr0246219-
235d3-024-Va20-009
235f-024-04 (Obsolete Replaced By 363-230-20g-S2-P5)
227-024-05-056
227csz 024 05 077
707l-R1r-H100
S235d B04 Obsolete
740g-R2a-B024 Oem
Type 733
227-024-15-S1
237d 230 26 009 -
Us-Pat.6046661
740a-R2a-C048-012
UI704lr1ah050019
733d-R3a-B9r0

235r 3-230 04-04 054	
238-024-15s2 , By 361-024-10-S2 Or 361-024-20-S2	
36450, 227cz-024-05/8e8	
721d R1a B500 019	
00.9109024.01, 235r3-230-04-054.	
E553-008	
720d-R1a-B032-005	
T 16230 UI-704I-R1a-H050-005- !!!	
235r3 ? 04 ? 54 220 Volt	
341-230-05	
235r-230-04-054 (- By 363-230-20g-S2-P5)	
232d3-115-06-057/232d3-115-06-066	
16230 UI-704I-R1a-H050-005 - Unknow Part.No.	
722f-R1a-B105	
750h-R1a-B010	
UI-704I-R1a-H050-005 Produkt	
235r3-230-04-064 230 Vac	
9066 24vdc 2polos	
225-230t-08 , Is 225-230t-05	
Us.Pat.6046661/740a-R2a-C048-012	
Gr-227-230-05,Alternative For 227 S-230-05	
9059 Bv.28 700-6500 - Not Available	
235r3-230-04-054	Rotary drive, 4 Nm 230VAC, 30s / 90 ° 1 additional switch, reversible 3-point control Customs tariff number: 85011010
227cs-024-15	
Rel.9059 Bv.28 700-6500	
23tr3-230-04-054	
235-R3-230-04-054	
Lr 24 A With Motor Body	

UI-704s-R1a-H050
233c-024t-400
720d-R1a-B032 - Product
704v-R1a-H050
722f-1r1a-B105 24vdc 105r/105r 120a/250v 23293
227-230 D-05-?5
00.9109024.01 Type 235r3-230-04-054
281d-E2u-G880
235r3/00.9109024.01
34421
Stellantrieb 232 D3 230-06-059mit Poti 1000 Ohm
00 9109024 01 Type 235r3 230 04 054
771a -E3u -W2k0
363-024-20-S2
361-024-20-S2
22808
227cs-024-08
227csz-024-05-077 24vac/Dc
361-230-10 Elektroantrieb (230v, 50/60hz, 1,5 W, 10nm)
361-230-20
235-R3-230-04-050-!! By Quot;235r3- 230-04-054quot;
231-024-30-S2 24vac/Dc 50/60hz 4.5w 0.8va (Obsolete Replaced By 363-024- 30-S2)
UI-740a-R2a-B024-021
361-024-10-S2
225-230t-05
722e-R1a-B430-013
227 230 15 S1

721g-R1a-B125	
15191	
232e3-230-15-S2	
UI-722q-R1a-Bo25	
228-230-05	
235R3-230-04-054	Rotary drive, 4 Nm 230VAC, 30s / 90 ° 1 additional switch, reversible 3-point control
771a -E3u- G500	
227c-024-15 Motor Controller	
225s-230t-05-S2	
0399361703	
Ascusol Pu 92 26kg	
232d3-115-06-066 L	
225-230t-05-S2	
225-230-08+bofb50xd, 2 Way Valve	
Type 725	
UI-721e-R1a-H032-047	
Tyr 235r3-230-04-058 - Oem	
227 S-230-05	
Iec60947-4-1	
237D-230-26-008	Rotary drive, 26Ncm Spring return, 230VAC 0...85°C, 20%ED 2-point control Customs tariff number: 85011010
22808 Damper	
363-230-20g-S2-P5	
Relay 750	
722f-R1a-B105 Relay	