

Hatlapa

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Hatlapa Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Hatlapa Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Ersatzteile / Spare Parts | |
| Part number : 84.05 | Brake lining. Lower Part Drawing No.: 1.72068 Pos 84.05 |
| Part number : 84.02 | Drawing No.: 1.72068 Pos. 84.02. |
| Part number: 69-42-** | Machine screw cross recessed, brass, countersunk head, M8, Length --- 100pcs. 40mm with nuts |
| See list / Spare parts | |
| Air Compressor HATLAPA Type L 80II | Double compressor control TD 200 |
| COMB SUCTION AND PRESS V/V 1ST STAGE | 20.20.10 |
| COMB SUCTION AND PRESS V/V 2ND STAGE | 20.20.20 |
| PISTON RING 20.30.10.40 | |
| SCRAPER RING 20.30.10.50 | |
| DOUBLE BEVELLED OIL CONTROL RING | 20.30.10.60 |
| SCRAPER RING | 20.30.20.40 |
| FACED COMPRESSION RING | 20.30.20.50 |
| GASKET 20.10.20 | |
| GASKET 20.20.50 | |
| GASKET 20.20.60 | |
| PACKING RING 20.20.30 | |

| | |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PACKING RING 20.20.40 | |
| SPARES FOR GEAR BOX | DRAWING NUMBER 320112 PINION SHAFT 318609 1pcs CYLINDER ROLLER BEARING 085676 2pcs |
| 758160 | |
| 1.1. Cylinder head 1st stage | (code 03.3) 20.10.30 in catalogue |
| 1.2. Cylinder head 2nd stage | (code 03.6) 20.10.60 in catalogue |
| 113327 Partno :11 | |
| Laying .07, 01.34 HATLAPA L 80 II | |
| Oil pumps .07, 07.1 HATLAPA L 80 II | |
| AIR PISTON COMPRESSOR HATLAPA L-20 | , ser #:18.5805-ON (19,5M3/H // 40 bar // 1450 RPM // 5,5 kW) |
| 20.20.20 | COMB. SUCTION A PRESS. VALVE 2 STAGE |
| 180619 | |
| 10.20.10.10 | crankshaft Kurbelwelle for serial-no.: 04.4081-0 suitable for: compressor L35 |
| Main Starting Air Compressor: L14 | Duty: Main Starting Air Compressor Type: 1 x L14 Description: 2 stage, 2 cylinder air cooled, single acting compressor Capacity: 14 m3/h FAD (+/- 5%) Customer FAD required: As above Working Pressure: 30 bar G Speed: 1450 rpm Shaft Power: 3.5 kW Control Voltage: 220 / 230 V Lubrication: Splash Heat to be dissipated: 2.8 kJ/sec Cooling air flow rate: 17.2 m3/min Inspection: DNV GL on compressor portion only Standard Compressor Features: · Flywheel and flexible coupling: Fitted · Mounting Arrangement: Flexible (AV Mounts) · Air intake filter with silencer · Inter and after cooler · Air Pressure gauges on all stages: Supplied fitted, glycerine filled · Condensate unloading - Manual & Automatic (Auto 2nd stage only) · Safety valves on all stages · Pipe connection for compressed air outlet · Crankcase breather · Oil level inspection glass · Fusible plug Additional features: · Flexible Air Hose: Supplied loose with tube connection · Air temperature measurement: T |
| 028674 | |
| 20.30.10.50 | napier ring Nasenring for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 161181 | |
| 002055 | |
| 10.30.10 | cover for oil pump Ölpumpendeckel for serial-no.: 04.4081-0 suitable for: compressor L35 |
| Parts List For Attached List | |
| 62mmk3/120 | |

| | |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.30.40 | gear wheel for oil pump Ölpumpenzahnrad for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 10.30.70 | sealing ring Dichtscheibe for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 20.20.50 | PACKING RING |
| 20.40.20.20 | con. rod bearing shell / 2 pcs.= 1 set Pleuellagerschale / 2 Stk. = 1 Satz for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 314716-44065 | Drawing SINGLE CONTROL COLUMN 3-0-3 Blatt1,2 pos.S1 |
| 30.20.10 | separator Abscheider for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 135725 | |
| Coupling Tire | From L35 compressor Please look at the attachement |
| 161179 | |
| 20.20.30 | PACKING RING |
| 20.20.40 | PACKING RING |
| 10.10.10.10 | crank case L for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 10.30.50 | gear wheel of oil pump Ölpumpenzahnrad for serial-no.: 04.4081-0 suitable for: compressor L35 |
| L35 With Motor | Main Starting Air Compressor Technical Specification - 1143518R.1 Duty: Main Starting Air Compressor Type: 1 x L35 Description: 2 stage, 2 cylinder air cooled, single acting compressor Capacity: 19,5 m ³ /h FAD (+/- 5%) Customer FAD required: 19.5 m ³ /h Working Pressure: 30 bar G Speed: 950 rpm Shaft Power: 4 kW Control Voltage: 220 / 230 V Lubrication: Force fed by pump Heat to be dissipated: 3.3 kJ/sec Cooling air flow rate: 19,5 m ³ /min Inspection: Works test on compressor portion only |
| 20.20.10 | COMB. SUCTION A. PRESS. VALVE 1 STAGE |
| 10.30.20 | radial packing ring Wellendichtring for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 10.10.20.20 | crankshaft bearing Kurbelwellenlager for serial-no.: 04.4081-0 suitable for: compressor L35 |
| 10.10.70 | o-ring O-Ring for serial-no.: 04.4081-0 suitable for: compressor L35 |
| V105 | hatlapa V105 compressor pressure valve / Verdichterdruckventil |
| 20.40.10.20 | con. rod bearing shell / 2 pcs.= 1 set Pleuellagerschale / 2 Stk. = 1 Satz for serial-no.: 04.4081-0 suitable for: |

| | |
|----------------------------------------|-------------------------------------------------------------------------|
| compressor L35 | |
| 002058 | |
| 10.30.30 | o-ring O-Ring for serial-no.: 04.4081-0 suitable for: compressor L35 |
| Serial No. 07.7714.3.1 | |
| 20.20.60 | PACKING RING |
| 020346 | |
| 008792 | |