

## Hauber

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Hauber** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Hauber T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">HE100.00.32.00.00.00.000</a>	Vibration monitoring Typ Artikelnr.10943 According to DIN ISO 10816 Measuring range: 0 ... 32 mm / s Frequency range: 10 ... 1000 Hz Temperature range: -40 ° C ... + 125 ° C Analog output: 4 ... 20 mA Supply voltage: 24V DC Housing: V2A stainless steel 1.4305 Fastening: M8 threaded pin Connection: plug-M12 Protection class: IP 66/67 Customs tariff number: 90318020 Country of origin: Germany
<a href="#">Cable - 4-pole - 5m - shielded (optional)</a>	Item number 10521 M12 socket straight Sheath: PUR / PVC Degree of protection: IP67
<a href="#">HE rubber protective sleeve for type HE100</a>	(Optional) Item number 10986 Can be used for the following type series: HE100, HE101, HE102, HE103 Corrosion protection and protection against external environmental influences Material: silicone Color: Black Cable passage: 4.5 ... 6.0 mm Total length: 130 mm Temperature range: -40 ° C ... + 125 ° C with HAUBER logo
<a href="#">ATEX Typ 663.32.102.0</a>	Vibration monitoring Article no. 10315 According to DIN ISO 10816 ATEX version: Zone 1 and 21 Classification: SIL2 / PL-d Frequency range: 10...1000 Hz Measuring range: 0...32 mm/s Analogue output: 4...20 mA Switching output: pre-

	alarm and main alarm Supply voltage: 24V DC Housing: V2A stainless steel 1.4305 Fastening: M8 screw Connection: 5 m cable integrated Protection class: IP 67 including 2 seals
<a href="#">Typ 640.16.000.0</a>	Article no. 10034 According to DIN ISO 10816 Measuring range: 0...16 mm/s Frequency range: 10...1000 Hz Temperature range: -40°C...+85°C Analogue output: 4...20 mA Supply voltage: 24V DC Housing: V2A stainless steel 1.4305 Fastening: M8 grub screw Connection: M12 plug Protection class: IP 67
<a href="#">10059 / 656.A Auswertgert</a>	
<a href="#">He100.00.16.01.00.00.000-S</a>	
<a href="#">10172</a>	
<a href="#">Typ 663 (Bestellcode: 663.32.010.0)</a>	
<a href="#">640.64.000.0</a>	
<a href="#">He100.00.16.00.00.00.000</a>	
<a href="#">664.16.000.0-S Vib Sensor</a>	
<a href="#">(Optional) 10480</a>	Cable - 8-pin - 5m - shielded M12 socket Sheath: PUR / PVC Protection class: IP67
<a href="#">664.16.000.0-S 10565</a>	
<a href="#">Vibration Monitoring Type He103.01.32.01.00.00.050</a>	Artikelnr.9999 According to DIN ISO 10816 ATEX application area: Zone 1/2/21/22 ATEX marking: Ex II 2 G Ex d IIC T4 Gb Ex II 2 D Ex tb IIIC T120 ° C Db Frequency range: 1 ... 1000 Hz Measuring range: 0 ... 32 mm / s RMS averaging time: 60 seconds Temperature range: -40 ° C ... + 125 ° C Analog output: 4 ... 20 mA Supply voltage: 24V DC Housing: V2A stainless steel 1.4305 Mounting: M8 threaded pin Connection: 5m shielded cable - integrated Protection class: IP 66/67
<a href="#">Kalibrierung</a>	
<a href="#">640 10 2007</a>	
<a href="#">10521 5 M Kabel Geschirmt</a>	
<a href="#">Art.Nr.10059 / Typ 656.A</a>	
<a href="#">10034 / 640 Schwingungsberwachung</a>	
<a href="#">Kabel - 4-Polig - 2m - Geschirmt</a>	
<a href="#">T0180-05-05-03-05-02</a>	
<a href="#">10059 / 656.A</a>	
<a href="#">663.64.103.0 10752</a>	
<a href="#">He100</a>	

<a href="#">664.10.200.26</a>	
<a href="#">T0180-05-05-03-05-02 Vib Sensor</a>	
<a href="#">Evaluation Electronics Type 656.A</a>	Artikelnr.10059 Evaluation of 1 sensor with a threshold and a line monitoring Customs tariff number: 90318020 Country of origin: Germany
<a href="#">Typ:640.16.000.0 F-Nr:60316</a> <a href="#">Obsolete,Replaced By</a> <a href="#">He100.00.16.00.00.00.000</a>	
<a href="#">10091</a>	
<a href="#">10520</a>	
<a href="#">10105 Schwingungsüberwachung Atex</a> <a href="#">Typ 664.8.200.0 Replaced By Typ He100</a> <a href="#">(Bestellcode:</a> <a href="#">He100.01.16.01.00.00.050)</a>	
<a href="#">10480</a>	
<a href="#">He100 Schwingungsüberwachung</a>	
<a href="#">Evaluation Electronics Type 652.3400</a>	Artikelnr.10225 - Evaluation of 2 pcs. vibration monitoring Type HE100 - Free adjustment of pre- and main alarm per vibration monitoring - Display language German - Supply voltage 24V DC - One analog output 4 ... 20 mA per vibration monitoring
<a href="#">10106</a>	
<a href="#">10034 / 640</a>	
<a href="#">Vibration Monitoring Type</a> <a href="#">He100.01.32.01.00.00.050</a>	Artikelnr.11001 According to DIN ISO 10816 ATEX application area: Zone 1/2/21/22 ATEX marking: Ex II 2 G Ex d IIC T4 Gb Ex II 2 D Ex tb IIIC T120 ° C Db Frequency range: 1 ... 1000 Hz Measuring range: 0 ... 32 mm / s Temperature range: -40 ° C ... + 125 ° C Analog output: 4 ... 20 mA Supply voltage: 24V DC Housing: V2A (1.4305) stainless steel Mounting: M8 threaded pin Connection: 5m shielded cable - integrated Protection class: IP 66/67 Customs tariff number: 90318020 Country of origin: Germany
<a href="#">640.16.000.0</a> <a href="#">He100.00.16.00.00.00.000</a>	
<a href="#">664.16.000.0 16 Mm/S Obsolete,</a> <a href="#">Replaced By He100</a>	
<a href="#">Type 640</a>	
<a href="#">663.12.200.2 (10499)</a>	
<a href="#">640.32.200.4</a>	
<a href="#">Typ 640.10.200.7</a>	
<a href="#">Typ He100</a>	

[10458 Kabel - 4-Polig - 10m - Geschirmt](#)

[664.16.000.0-S 10565 -Obsolete,  
Replaced By He100.00.16.01.00.00.000-S](#)

[Kabel Fuer He100.00.16.00.00.00.000](#)

[663.12.200.2](#)

[663.64.000.0](#)

Vibration monitoring type 663.64.000.0 ArtikelNr.10298  
According to DIN ISO 10816 Classification: SIL2 / PL-d  
Frequency range: 10 ... 1000 Hz Measuring range: 0 ... 64  
mm / s Analog output: 4 ... 20 mA Switching output: pre- and  
main alarm Supply voltage: 24 V DC Housing: V2A stainless  
steel 1.4305 Mounting: M8 screw Connection: M12 plug  
Protection class: IP 67 including 2 seals Customs tariff  
number: 90318020 Country of origin: Germany Weight / pcs.  
0,50 kg

[Type 664](#)

[10105 Schwingungsüberwachung Atex  
Typ 664.8.200.0](#)

[Typ He100 \(Bestellcode:  
He100.01.16.01.00.00.050\)](#)

[664.16.000.0-S - Obsolete, Replaced By  
He100.00.16.01.00.00.000-S](#)

[10106 Schwingungsüberwachung Atex  
Typ 664.16.200.0](#)