



Hegwein

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Hegwein** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Hegwein T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Zap - 160 M	
Z 859 K 2	
Z 341 K2	
Z551k230e2	
Z 1040 Z 160	
Z 837 K2	
Z 837 K1	
Z 834 F 3009	
Z 863 F1- Gasket	
A 5 Z1 -Plug	
VPM-HAD 2H5	Art nr : 279785
VPM-HAD 2H1	Art nr 279715
TYPE : SMV 4 P1	TWO WAY SOLENOID VALVE 220V 50HZ CONN.R1/2"FEM..PN16
Z 341 K2	Flame monitor part for intermittent operation, EU-type approved, built into an aluminum housing, connection voltage 230 V AC, 50/60 Hz with 10-pin connection for plug (on-site) 2010515

Type: ZDA0-1515P/283104	230V/50Hz With Ionization Flame Monitor
AD 2 H 1/00CBB00	
VPM-HAD 2H5	279785
VPM-HAD 2H1	279715
AD2H1	
2000023	A285 K2.3 Flame relay 90-110VDC with 2 potential-free changeover contacts max. 250VAC /1A ohms EU type tested For safety-related Incorporation into a higher level burn control for mounting on 35mm Hat profile support rail according to DIN EU 60715 Ambient temperature -20 to +60 degrees housing IP40 Terminal block IP20
ZT0-192M	2033213 Gas pilot burner with integrated ignition transformer and built-in ionization electrode for connection to an external flame monitor or burner control Voltage: 230V 500/60Hz Degree of protection: IP 54 El. Connection: 10-pin connector Tube length: 1920 mm Tube diameter: 48mm Gas connection: Rp 1/2 Air connection: Rp 1 Thermal power: max. 120 kW Gasar: natural gas req. Gas pressure: 50-150 mbar req. Air flow pressure: at least 29mbar Maximum air volume: 50 m3/h, the remainder must be available from the combustion chamber Adjustment of the pushers according to the description.
AVS-1-T1 -- 220V 50Hz 50 Mbar	
A 5 Z1	2000043 Combination H-A 10 THV 2XM20 with 2X screw connection Metal + H-A 10 BS + plastic plug for cable gland
A 285 K2.3	2000023 Flame relay 90-110VDC with potential-free changeover contacts max. 250VAC/1A(ohm.) EU type tested For safety-related Integration into a higher-level burner control for mounting on a 35mm top-hat rail according to DIN EU 60715 Ambient temperature: -20 to +60 Housing IP 40 Terminal block IP20
Z944K143	2016339 Z 944 K 143 Intermediate support ring in stainless steel complete with ceramic insulators for for burners BG1, BT1, B(D)A1, ZXB(T)1, ZXB(D)A1, ZAVEXB for burners BG2, BT2, B(D)A2, ZXB(T)2, ZXB(D)A2, ZAVEX2B for burners BG3, BT3, B(D)A3, ZXB(T)3, ZXB(D)A3, ZAVEX3B
Z726K2	2014327 Z 726 K2 Burner control integrated in Gas/oil pilot burners and gas burners Series: BR..., ZR... Operating mode: Intermittent Electrical connection: 10-pin plug connection Connection voltage: 230 V 50/60 Hz Protection class: IP 54 Temperature: -30°C to +85°C Configuration: First safety time: 3 s Flame failure time: 1 s Pre-ventilation time: 0 s no air pressure check, no restart **The IP protection class is only achieved when properly installed**
Z547K230E1	4023793 Z547K230E1 Replacement ignition transformer with 4 pole. connector for replacement of 1 pc. Z546K... suitable for the pilot burner and burner series ZA1..., ZDA1..., ZT1... and PA1..., PDA1..., PT1... and gas burner size BAP..., BDAP..., BTP..., BAO..., BDAO..., BTO... BA1..., BDA1..., BT1... BA2..., BDA2..., BT2... BA3..., BDA3..., BT3... Technical data: Primary voltage: 230 V AC, 50/60Hz Secondary voltage: 1 x 5 kV to ground Operating mode: continuous operation / 100% ED Secondary connection: wood screw thread Ambient temperature to: -30 to +80
ZAVEX0-95M	
SET-ZAVEXP/ZAVEX0	
Varied Detector GAS LEAK DETECTOR,[AD 2 H5	0.5BAR,115/230V
ad1h1	
Ad2h1 (Ex Ad00h1-001)	

Ad2h1	
Flame Rod For Zxda/1-72m/Nok50	
Avs1 T1	
2016577 Final Electrcode Support Ring	
Fd6ko	
Ad2 H 5	
Z545k8	
Flame Relay For Ignitin Spdt Contact For Zxda/1-72m/Nok50	
Ad1h1 Din-Dvgw	
A 285 K 2 3	
8978	
Z379f1	
Zaos -335 P 50	
2022920	
Z917k132	
Z473-K1	
Fd 8 Ko	
Zt1-80s/290033 (2033637)	
Zda 0-105 P/0000m	
Ad 2 H 5	
Zzkd16p3-2	
Avs1.T1 Obsolete, No Replacement	
4006184 Zg0 - 24 H / Heg00986	
Fd 2 Ko	
566 4763 081 Clamp	
Fd2 K0	
06 T Avs 1 T 1 Obsolete Pilot Control Unit	
Ad1h1 Gastester (Rotasy)	PR¼FGERÄT REG NR .: 94.01F036 PMAX:0,1 BAR 115-230V 50/60 HZ 5 VA IP:54
Fd 8 K0/0w0 Replaced By Fd 8 K0	
Ad 2 H1	
2000023 A 285 K2 3	
174m50/13z83	
Smu 4 P1/00k	
Hose For Fd 2 K0	

A0515z3000
Zda0-930m/S00, RI930mm
2001285 / Aal 75 P0d
K-09525-02
Zavex/0
Zda 0-170 M/00k50
2001303
Smu 4 H 5
Model: (Za2 / Zda2),Heat Release: Max. 600 Kw, Flame Length: Max. 2000 Mm, Tag Nos.: 5a21-Bsl- 02
Za0s 335 P 50
Smas65h1001
70469
Ad 2 H 5 (2001374) Obsolete
Za1-55m/0a0 + Z215z33
Ad 00 H1á;Á;Á;Á; 04 L - Obsolete
Z 1056 Z 273
Asd 75 P0d
Z707f3
Zavex/0b-201m/301184
Zrkn16-M2
C11,1 Bar ,Valve Size 1/2quot;
Z209-K1
2000023, A 285 K2.3
Z944k1
1 Way,Dn G 1/2quot;,110/115 Vac,50/60 Hz
Ztu120m/0000f (2034186)
Ad 00 H1 04 L
Zxa0-220 M/00ka0
A 10 Z 2 Diode
Zavex/0s-835m50/23201
Se8mi
Smu-4-P1-006
D-Lx100 UI-P With Cable - Old Code, New Code - D-Lx 100 UI-G1/M2/0000/Pp2
Zakd 145 M/ 0000m

2010327 Gas Nozzle
Z470-K1
Z 545 F11
Model: Zavex/0s-835m50/232017
Fd2 1-7-5-70mbr
Z550k230e2
Asd 75 P0i
Z215f33
Z 1050 Z 76
Ad 00 H1 Neuer Typ: Ad 2 H 1
Z214-K1
Fd 2 K 1-7
Zavex/0s - 201s/Heg14xxx
2034622 Zx420 K8k50
P/Nāzael113050
2001374 Valve Proving System
Z960k113
174 M 50/ 13 Z 83 Ignitor
St 6 H1
Smu 4 P1 By Fv - 285 - Rp 1/2 - 230 V
2016329 Z 944 K 109
Smu 4 P1/001
Asd820 K2 Gt;Gt;Gt; Discontinued
Zdanp-66m/0000c (2029620)
93.01f036 Obsolete, Replaced By Ad 2 H 5
2016575 Intermediate Support Ring
Earth Rod For Zxda/1-72m/Nok50
Z 1056 Z 305
Aau 230 L8
A 10 Z 2
Zakd 145 M30/00m , By Zakd 145 M/ 0000m
1 Way,Dn G 1/2",110/115 Vac,50/60 Hz
2001374 Ad 2 H 5
Znue-1p5-0
Ad2h5
2016572 Z960 K63

[Z675f700](#)

[Br1-24m/000ic0](#)

[A285k2.1 \(Obsolete Replaced By A 285 K2.3\)](#)

[Fv - 285 - Rp 1/2 - 230 V](#)

[Z384z16-30](#)