



Helmke

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Helmke** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Helmke T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Typ: Dor112m12-043	MOT. IMB5 IP56 11000061134 EN60034 D/Y 230/400V 2.1/1.2A 5Nm Th.Cl. : H 0-500 1/min 50 Hz UT= max 60°C NOT: MOTOR mit Bremse
E.-Magnetspule : 103 Vdc, 0,23a	Bremsmoment: 10Nm AnschluŐspannung: 230 VAC Luftspalt: 0,3 mm, IP: 56 HINWEIS: BREMSEN MIT GLEICHRICHTERDIODEN VON 230 VAC BIS 103 VDC.
Soft Compact	Soft Compact 5.5 kW, 400 V + 10-15%, 12 A Electronic soft start module for Three-phase squirrel cage motors (two-phase phase control) previous product name: KIMODUL 5DMA-14 CE
06-8473/D05979 3 faz motor	
DOR250M-02-2G, 55kw 2965rpm	
DOR355L3-02-2G, 400kw 2985rpm	
DOR355L3-02-2G-159	
Three-phase squirrel cage motor DKK-500-04	
Drehstrom-Kurzschlussl¼ufer-Motor CDDOR400-04	
DOR280M-06-3G-196	Three-phase squirrel cage motor Type: DOR280M-06-3G-196 Power: 55.00 kW Voltage: 400.00 V D / 690.00 V Y Frequency: 50.00 Hz Number of poles: 6 -pole Speed: 990.00 1 / min Design: IM B3 Size: 280 Protection class: IP 55 Terminal box: above Thermal class: F Efficiency class: IE3 Weight approx: 550.00 kg

160M2-2-145	
2FX280SG-02/F	
5DMA-14	
Anla#widerstand	
DOR100L-02-3A-171	
DOR100L2-04-3A	
DOR112M-04-3G-196	
DOR132M-04-2A-186	
DOR132M2-06-2A-186	
DOR132S1-02-3A-186	
DOR160L2-056	
DOR160M1-02-2A-157	
DOR160M1-02-3A-186	
DOR200L-08-1G-196	
DOR200L1-02-2G-196	
DOR200L2-02-3G	
DOR355M2-06-3G	
DOR560-06	
DOR560-06-159	
F361.B4	
GMV-1N 355 KS7	
GNRFZE132L/2	
NSFU-V-44-0340-CB-06-098	
V418/04S5A	
DOR132M-04-3A-186	Power : 7,50 kW Voltage : 400,00 V D / 690,00 V Y Frequency : 50,00 Hz Pole : 4 -pole Rpm : 1.450,00 Mounting : IM B3 Frame Size : 132 Protection : IP 55 Terminal Box : on top Insulation class : F/B RAL : 7030 Efficiency : IE3 Weight approx. : 53,30 kg Half-key blance Aluminium-housing 3 thermistors 1:1 interchangeable with motor DOR132M-04-2A-186,
Type: DSA55-400 / Control Panel	
DSA75-400 Control Panel	
DSA45-400 / Control Panel	
DSA160-400 Control Panel	
Brush holder Helmke DSKK560-06-036	
ARR3 14-4	107402883
TYPE: DOR63F-2	
DOR315-04-6600YV	

DOR315MB2-075	Power: 145.00 kW Operating mode: S1 Speed: 2,970.00 rpm Number of poles: 2-pole Direction of rotation: Both Voltage: 230.00 VD / 400.00 VY Frequency: 50.00 Hz Type: IM B3 Protection class: IP 55 Cooling type: IC 411 Thermal class: F B Ambient temperature: -20 to +48 ° Celsius Installation altitude (max.): 1000 m Main terminal box: Right Balancing type: half wedge Bearings: rolling bearings Standard: EN 60034-1 3 PTC thermistors for shutdown standstill heating 220 - 240 V Engine interchangeable with previous delivery from 2016, Serial No. 12000010222
DOR160M-04-3A	Power: 11.00 KW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 4-pole Speed: 1,500.00 rpm Type: IM B3 Size: 160 Protection class: IP 55 Thermal class: F Weight approx.: 99.00 kg
DOR180L-08-3G	Power: 11.00 kW Voltage: 400.00 VD / 600.00 VY Frequency: 50.00 Hz Number of poles: 8-pole Speed: 730.00 rpm Type: IM B3 Size: 180 Protection class: IP 55 Thermal class: F
DOR225M-04-3G	Power: 45.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 4-pole Speed: 1,483.00 rpm Type: IM B3 Size: 225 Protection class: IP 55 Thermal class: F Weight approx.: 347.00 kg
NDOR250M-08-049	Three-phase squirrel-cage motor Ex ec IIC T3 Gc Power: 30.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 8-pole Speed: 732.00 rpm Type: IM B3 Size: 250 Protection class: IP 55 Ex protection: Ex ec IIC T3 Gc Thermal class: F Weight approx.: 370.00 kg
DOR200L-02-3G	three-phase squirrel-cage motor Power: 37.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 2-pole Speed: 2,960.00 rpm Type: IM B3 Size: 200 Protection class: IP 56 Thermal class: F Weight approx.: 251.00 kg
DOR160L-04-3G	three-phase squirrel-cage motor Power: 15.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 4-pole Speed: 1,476.00 rpm Type: IM B3 Size: 160 Protection class: IP 55 Terminal box: Right Thermal class: F Weight approx.: 149.00 kg
DOR180L-04-3G	three-phase squirrel-cage motor Power: 22.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 4-pole Speed: 1,478.00 rpm Type: IM B3 Protection class: IP 55 Thermal class: F Weight approx.: 200.00 kg
DOR280M-02-4G	three-phase squirrel-cage motor Power: 90.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 2-pole Speed: 2,975.00 rpm Type: IM V1 Size: 280 Protection class: IP 55 Thermal class: F Weight approx.: 653.00 kg
d-GNRegFZE 1718/3	DC motor Ex de IIC T4 Gb Make: Winkelmann Type: d-GNRegFZE 1718/3 Ex protection: Ex de IIC T4 Gb Power: 7.50 kW U - anchor: 120.00 V Armature current: 73.20 A Speed: 1,750.00 rpm Field voltage: 120.00 V field current: 0.90 A Type: V1 Protection class: IP 55 Cooling type: IC 411 insulation class - warming : H Ambient temperature: -20 to +65 ° Celsius Installation altitude (max.): 1000 m Bearing type: rolling bearing Design: Foot (B3) As per serial no. 82820
DOR280S-04-4G	three-phase squirrel-cage motor Power: 75.00 kW Voltage: 400.00 VD Frequency: 50.00 Hz Number of poles: 4-pole Speed: 1,490.00 rpm Type: IM B3 Size: 280 Protection class: IP 55 Terminal box: Top Thermal class: F Weight approx.: 619.00 kg
Dkk-500-04 Three-Phase Squirrel Cage Motor	
E20	
Y2-355 L4	
Dor355m2-06-3g With Ptc Temperature Sensor	
Ecdor200-04	

Doh800/12 Cooler Filter Fan
S/N Ar109025-46374
Dor160l-4a
Type Dor560-06-159
Type: Dao1800-1820
160m2-2-145
E55
160m1-2-157 Motore Elettrico H-Plus Dor
Cddor400-04
Dkk-500-04
010102-Mhg02503hz555l Dor355-04
180m-4-157 Motori Elettrici Z-Plus 3 Mot Dor (Potenza 18,5 Kw)
Dor100l2-4a-157
160l-4-157 Z-Plus 3 Mot Dor
16x18x98 Mm.* For 700 Kw-1000 D/D
Nsfu-V-44-0340-Cb-06-098 By Nsfu-V-69-0370- Cb-06
805030
E80
328a8670p001
Dor160m2-02-3g-196
Cddor400-04, 340,00 Kw Drehstrom- Kurzschlussläufer-Motor
Dor 132m-4a-157-66tf-O Motor
328a8670p001 Emergency Lube Oil Pump Motor
E110
Dor160m1-02-3g
Dor112m-02-3a
Mc5201/70001
Dor160m1-2a-157
Type: 2fx280sg-02/F Obsolete
11000021754
Dkk560-04 Three-Phase Squirrel Cage Motor
160m2-2-145 Motore Elettrico H-Plus Dor
Fan For Electrical Motor Dor 315 L2-06-2g-159
Fan For Dor 315s-4-157

59915-00/42103 Control Unit
Dor90l-04-2a-186
Dor160m1-02-3g-196
160m2-2-145 Motor
Gmv-1n450ks6
Cddor400-04, 340,00 Kw
V418/04s5a - And
Doh800/12
59915-00/42103
Dor355-02
Gmv-1n 355ks7
Dor160m-04-2g
12041500133
Gmv160m
E235
Dkk560-04
Type:Gmv-1n 355 Ks7
Dor315s-4-157
Dor112m-02-3a Elektromotor
Dor280m-02-2g-035 Drehstrom- Kurzschlussläufer-Motor
Dor355-02 Drehstrom-Kurzschlussläufer-Motor
Dor500-04
97-3442/K4118
Dor280m-02-2g-035
3674/02-6378 - Old Ref., New Ref: - Type: Dao1800-1820
Dor200l1-02-2g (30,00 Kw)
K1000-230-635-2
Dfa270/258
Dor200l2-02-2g (37,00 Kw)
Dor400-04
Dor 132m-4a-157-66tf-0
Dor180m-04-3g-196
315l2-035
Ama 500l6a Bafh 1500 Kw
16x18x98 Mm.* For Helmke 700 Kw-1000 D/D

Dgh400/12
Dor160I-04-3g-196
Cddor400-04 Drehstrom-Kurzschlussläufer-Motor
Road Transmitter, Z Upper Contact
Dor 132s1-2a-157 Elektromotor
6 X 62 X 78 Mm.* R=75 Mm.
E28
1100032b92 Terminal Block For 1100032b92
Doh1000/12 Kiln Main Drive
Dor71g4-035
Orbis/84.540-10 ,Type:Dscor400I-8
Dor355m2-06-3g With Pt 100 Temperature Sensor
6 X 62 X 78 Mm.* R=75 Mm.*
Gmv 315k ? 0811mb3
Dor200I-04-3g-196
Dor180m-02-2g (22,00 Kw)
11000032892
Nsfu-V-69-0370-Cb-06
Doh1000/12
Dskk560-6-036